

HOWTO — AIStudio User Guide

Practical answers for day-to-day AIStudio use. Not a getting-started guide (see [QUICKSTART.md](#)) — reach for this when you need to do something specific or something isn't working as expected.

Version: Beta | Updated: 2026-05-21

Contents

- [Shell & Terminal](#)
 - [Using AIStudio](#)
 - [Corpus Management](#)
 - [Installing and Managing LLMs](#)
 - [Query Settings](#)
 - [Understanding Citations](#)
 - [Benchmark & Corpus Testing](#)
-

Shell & Terminal

What is the shell? The shell (Terminal) is a text-based interface for running commands on your Mac. AIStudio setup and management uses the shell for tasks the UI doesn't cover — like installing models or ingesting a new corpus. New to the shell? See [Apple's Terminal User Guide](#).

How do I open the Terminal? Press `Cmd+Space`, type `Terminal`, press Enter. Or open Finder → Applications → Utilities → Terminal.

Why does my terminal say "command not found" when I paste commands? Two common causes: - You pasted a `#` comment line — zsh tries to execute it. Paste only the commands, not the comment lines. - Your AIStudio aliases aren't loaded yet. Run:

```
source ~/.zshrc
```

Then try the command again on its own line. Do not chain: `source ~/.zshrc && ais_start` will fail. Run `source ~/.zshrc` first, then `ais_start`.

Using AIStudio

After running `./ais_install` from the repo root (see QUICKSTART.md), these commands are available from any terminal. If a command is not found, run `source ~/.zshrc` first.

Command	What it does
<code>ais_install [cmd]</code>	Install AIStudio user commands — <code>ais_install ais_log</code> adds a single command, <code>ais_install --verify</code> checks all aliases
<code>ais_start</code>	Start all services and open the UI in your browser
<code>ais_stop</code>	Stop all services
<code>ais_bench</code>	Run a benchmark on the demo corpus
<code>ais_log</code>	Tail live AIStudio backend log — run in a separate tab after <code>ais_start</code>
<code>ais_download_sec_10k</code>	Download SEC 10-K filings from EDGAR to <code>~/Downloads/sec_10k/</code> (~2 GB)
<code>ais_ingest_sec_10k</code>	Ingest SEC 10-K corpus into AIStudio (~30 min, backend must be running)
<code>ais_download_esef</code>	Download ESEF iXBRL corpus from <code>filings.xbrl.org</code> (~10 European banks)
<code>ais_ingest_esef</code>	Ingest ESEF iXBRL corpus into AIStudio (~20 min, backend must be running)
<code>ais_help</code>	Print this command reference

Every command supports `--help`:

```
ais_start --help
ais_bench --help
```

Upgrading AIStudio

How do I upgrade AIStudio when a new version is released?

Pull the latest code from GitHub:

```
cd ~/Developer/AIStudio && git pull
```

Then update Python dependencies in case new packages were added:

```
source .venv/bin/activate && pip install -r requirements.txt
```

Then restart:

```
ais_start
```

Does upgrading delete my corpus data? No. Your corpus data lives in `~/qdrant_storage/` on disk — completely separate from the AIStudio codebase. It persists across upgrades, restarts, and reboots. You never need to re-ingest after a routine upgrade.

When would I need to re-ingest after an upgrade? Only if the release notes say the chunk format changed. This is rare and always announced. When it happens, run:

```
AI STUDIO VECTORSTORE=qdrant PYTHONPATH=src python3 -m local_llm_bot.app.ingest --corpus <name> --force
```

The `--force` flag wipes and rebuilds the corpus cleanly.

The demo corpus re-ingests automatically on first `ais_start` after an upgrade if needed.

Corpus Management

How do I ingest a new corpus? Use the UI — open AIStudio, create a new corpus using the **New** button, then upload your files using the **Add** button. AIStudio handles ingestion automatically and shows progress in the chat area.

How do I re-ingest a corpus from scratch? Delete the corpus using the **Delete Corpus** button in the UI (type YES to confirm — it moves to Trash, recoverable). Then create a new corpus with the same name and re-upload your files via **Add**. AIStudio ingests everything in one pass.

What happens when I delete a file from a corpus — is it gone forever? No. Deleted files move to `data/corpora/<name>/uploads/trash/` — not permanently deleted.

How do I recover a file I accidentally deleted from a corpus?

```
# See what's in trash
ls ~/Developer/AIStudio/data/corpora/<name>/uploads/trash/

# Move it back
mv ~/Developer/AIStudio/data/corpora/<name>/uploads/trash/<filename> \
    ~/Developer/AIStudio/data/corpora/<name>/uploads/

# Re-ingest to restore it
AISTUDIO_VECTORSTORE=qdrant PYTHONPATH=src python3 -m local_llm_bot.app.ingest \
    --corpus <name> --root data/corpora/<name>/uploads --force
```

What happens when I delete an entire corpus — is it gone forever? No. The corpus folder moves to `~/Trash/`. The folder is renamed to avoid conflicts with previous deletions — it will be named `AISTudio_<name>` or `AISTudio_<name>_<timestamp>` if a folder with that name already exists in Trash.

How do I recover a corpus I accidentally deleted? First find the folder in Trash — it may have a timestamp suffix:

```
ls ~/.Trash/ | grep AISTudio_<name>
```

Then move it back and re-ingest:

```
mv ~/.Trash/AISTudio_<name> ~/Developer/AIStudio/data/corpora/<name>
# Or if it has a timestamp suffix:
mv ~/.Trash/AISTudio_<name>_<timestamp> ~/Developer/AIStudio/data/corpora/<name>
# Then re-ingest
```

Then re-upload the files via the UI (Add button) to restore the corpus in Qdrant.

How do I ingest the SEC 10-K corpus?

The SEC 10-K corpus is a special case. AIStudio provides `ais_download_sec_10k` because the SEC EDGAR filing system uses a specific access protocol — this automates what would otherwise be a complex multi-step download. But the ingest step that follows is **identical to ingesting any corpus you bring yourself**. The download step is what's special.

This is one of the few places in AIStudio where you'll run terminal commands directly. We expose it deliberately — understanding how large corpora are built is part of what makes AIStudio a learning tool, not just a product.

Step 1 — Download the filings to `~/Downloads/sec_10k/` (~5 min, ~2 GB):

```
ais_download_sec_10k
```

Step 2 — Ingest using the AIStudio UI:

Open AIStudio, create a new corpus named `sec_10k`, then upload the files from `~/Downloads/sec_10k/` using the **Upload** button. This is the same process as ingesting any corpus you build yourself — the download step is what's special.

Allow ~34 minutes for ingestion to complete.

Why ~/Downloads? You own the downloaded files — ~2 GB of SEC filings you may want to reuse, inspect, or build a different subset from. They stay in `~/Downloads/sec_10k/` until you decide what to do with them.

Installing and Managing LLMs

How do I see what models are installed?

```
ollama list
```

How do I install a new LLM?

```
ollama pull llama3.1:8b      # ~5GB — recommended default, fast
ollama pull llama3.1:70b    # ~42GB — best quality, requires ~64GB RAM
ollama pull mistral:7b      # ~4.4GB — alternative option
```

Once pulled, the model appears automatically in the **Model** dropdown in the UI. No restart required.

Which model should I choose? On Apple Silicon, `llama3.1:70b` and `llama3.1:8b` have identical query latency (~6–7s) once warm. Choose based on available RAM: - `llama3.1:8b` — 8GB RAM minimum, recommended for most users - `llama3.1:70b` — 64GB+ RAM, best answer quality - `mistral:7b` — good alternative on constrained hardware

How do I remove a model I no longer need?

```
ollama rm mistral:7b
```

See the [Ollama model library](#) for all available models.

Query Settings

The **Query Settings** panel in the sidebar controls how AIStudio retrieves and generates answers. These settings apply to every query until you change them.

Top K — *How many document chunks to retrieve* The number of passages retrieved from your corpus before generating an answer. Higher values give the model more context but increase latency slightly. - Default: 5 — good for most queries - Try 10 for complex questions spanning multiple documents - Try 3 for faster responses on focused questions

Choosing Top K by query type:

Query type	Recommended Top K	Example
Point-in-time, single firm	5	"What was Goldman's CET1 ratio in 2024?"
Trend across multiple years	10–15	"How has JPMorgan's capital ratio changed 2022–2025?"
Cross-firm comparison	10	"Compare risk disclosures at JPMorgan, Goldman, and Citi"
General question	5	"What is the company's AI strategy?"

If an answer seems incomplete or missing years/firms you expected — increase Top K first before rephrasing the question.

Adjust using the **Top K** input field in the sidebar.

Temperature — *How creative vs. precise the answer is* Controls randomness in the model's output. - 0.1–0.3 — precise, factual, stays close to the source documents. Best for financial data, specific numbers, compliance questions. - 0.5–0.7 — more varied, synthesizes across sources. Better for summaries. - Default: 0.3 — recommended starting point Adjust using the **Temperature** input field in the sidebar.

Keywords (optional) — *Boost retrieval for specific entities or terms* Enter comma-separated terms to give extra weight to chunks containing those keywords. Useful when your corpus spans multiple entities and semantic similarity alone pulls in the wrong results.

Examples: - JPMorgan, Bank of America, Wells Fargo — focus on specific firms - CET1, capital ratio, regulatory capital — focus on a specific topic - 2024, 2025 — focus on recent filings

Leave blank for full corpus retrieval. Use keywords when you know the specific entity or term you need.

Understanding Citations

Every answer includes numbered citations — [1], [2], [3] — in the text. These refer to the source passages listed in the **References** panel on the right side of the screen.

What citations tell you: - Which document the information came from - Which page in that document

What to do when an answer seems wrong: Check the citations first. If the referenced chunks don't actually contain the claim — the model may be reasoning beyond its sources. Try increasing Top K, adding Keywords for the specific entity, or rephrasing to be more specific.

Uncited claims: if a sentence has no citation marker, the model is drawing on general context rather than a specific retrieved passage. Treat uncited claims with more caution, especially for specific numbers or facts.

Opening the source: click the citation chip in the References panel to see the full chunk text and open the source document.

Benchmark & Corpus Testing

The benchmark harness serves two purposes: - **Performance** — measures query latency per question - **Veracity** — validates answer quality against a questions file

How do I run a benchmark on the demo corpus?

```
ais_bench
```

How do I benchmark a different corpus?

```
ais_bench --corpus help
ais_bench --corpus sec_10k --top-k 10
```

How do I test with a specific model or settings?

```
ais_bench --corpus demo --model llama3.1:70b --top-k 10 --temperature 0.1
```

How do I write my own test questions for a corpus? Create `benchmarks/<corpus_name>/<corpus_name>_questions.yaml`:

```
- topic: Getting Started
  questions:
```

```
- id: start_aistudio
  question: How do I start AIStudio?
  notes: Should reference ais_start command
```

Run `ais_bench --corpus <n>` — the questions file is auto-detected by corpus name.

Where do reports go? `benchmarks/<corpus>/reports/` — timestamped `.md` and `.json` pairs. The `.md` shows pass/fail per question with latency and citations.

For full benchmark documentation see [HARNESSESS.pdf](#).

Troubleshooting

UI shows "Error loading corpora" or "Ollama not running" on startup

The browser opened before the backend finished starting. Hard-refresh (`Cmd+Shift+R`). If that doesn't fix it, check the terminal for a Qdrant WAL error (see below).

Ollama version mismatch warning — "client version is X.X.X"

After a Homebrew update, Ollama's CLI binary may update while the background service still runs the old version. You'll see:

```
ollama version is 0.18.0
Warning: client version is 0.22.0
```

Fix:

```
brew services restart ollama
ais_stop
ais_start
```

Qdrant WAL lock — "Can't init WAL: Resource temporarily unavailable"

What it is: A corpus collection's write-ahead log was left locked from an unclean shutdown — force-quit terminal, power loss, or crash mid-write. Qdrant panics on the affected collection at startup. Other collections are unaffected.

How you'll know: Terminal shows the WAL error on `ais_start`, naming the specific collection. UI shows "Error loading corpora." Ingestion immediately fails.

Fix:


```
ais_stop
# Delete only the collection named in the panic message — e.g. aistudio_help
rm -rf ~/qdrant_storage/collections/aistudio_help
ais_start
```

Then re-ingest the corpus via the UI (Add button).

⚠ Delete only the specific collection named in the error — not the entire `~/qdrant_storage/` folder. That would destroy all your corpora.

Prevention: Always stop with `ais_stop`. Never force-quit or close the terminal while AIStudio is running.

Ingestion summary shows wrong file or chunk count

Delete the corpus via the UI and re-ingest. The Qdrant collection may be out of sync with the uploads folder.

How do I rename a corpus? Use the **Rename** button in the corpus header in the UI. AIStudio renames the directory, updates the corpus metadata, and triggers a background re-index. You'll see a progress estimate for large corpora. Do not rename corpus folders manually on disk — use the UI only.

How do I rename a file inside a corpus? AIStudio records file names at ingest time. Renaming a file after ingestion breaks citation lookup — queries will still return results but the "Open ↗" link will fail to resolve.

Safe approach: delete the file from the corpus using the **Delete** button in the Inspect view, then re-upload it with the correct filename via **Add**. AIStudio will re-ingest only the changed file.

For architecture context, see [docs/architecture_decisions.pdf](#). For getting started, see [QUICKSTART.md](#).