

The `homework` class and style*

Matt Bauman
mbauman@gmail.com

March 4, 2011

Abstract

This package contains a both a class and a style designed to simplify the authoring of schoolwork, homework and assignments. They may be used independently of each other; the class provides some slight modifications to the `article` class, while the style adds commonly used packages and functionalities.

Contents

1	Introduction	1
2	The <code>homework</code> class	2
2.1	Arbitrary section numbering	2
2.2	Class options	2
2.3	Implementation	2
2.3.1	Setup	2
2.3.2	Class option handling	3
2.3.3	Arbitrary section numbering	3
2.3.4	Document titling	4
3	The <code>homework</code> style	4
3.1	Font and encoding setup	4
3.2	Maths	6

1 Introduction

The `homework` package aims to put together a thorough and modern solution for the authoring of schoolwork, homework and assignments. I (Matt Bauman) am by no means a \LaTeX expert. I have, however, made my best effort in creating a package that uses the current best-practices in \LaTeX authoring. This means that `homework` relies on some relatively new packages (like $\epsilon\text{-TeX}$) that may not be available on older systems and some web-based compilers.

*This document corresponds to `homework` v0.1, dated 2011/02/13.

2 The homework class

The `homework` class provides minor enhancements and modifications to the `article` base class. Only alterations which cannot be reliably achieved across a variety of document classes are implemented here.

2.1 Arbitrary section numbering

Most notably, the `homework` class allows for the user to define arbitrary section numbers. As homework assignments are very closely tied to the *number* of the problem, relying on automatic sequential numbering can be problematic. Additionally, problem numbers are not always sequential or even sensible. Thus, the `homework` class augments the standard `\section`, `\subsection`, etc, syntax to optionally specify its number. For simplicity, I will describe everything in terms of `\section`, but this modification applies to all sectioning commands.

The optional argument of the original syntax `\section[toc-name]{sec-name}` is changed to allow a prefix `[number|toc-name]`. Recall that the `toc-name` is how the section will be reported to the table of contents and headers, and that when omitted, it is the same as `sec-name`. This addition attempts to be as compatible as possible with the original syntax. If a `|` character appears within the optional argument, then everything before it is considered the ‘number’ and everything after is the section name for the table of contents. Note that a `|` character may be ‘hidden’ by enclosing it within a double `{ }` group (Todo: is it possible to achieve this with just one group?), in which case it is no longer considered the separator.

Note that ‘empty’ parts of the optional argument are handled differently, depending upon which part was omitted. If the `toc-name` is omitted, e.g., `\section[number|]{sec-name}`, then the section name is used as the name for the table of contents. If, however, the `number` is omitted and the `|` remains, e.g., `\section[|toc-name]{sec-name}` then the section number is set to be empty.

2.2 Class options

In addition to the standard options provided by `article`, the `homework` class adds a `screen/print` option pair. These mutually exclusive options do not have very much functionality in the class currently. They do, however, change the default sidedness of the `article` class (`screen` defaults to `oneside` and `print` defaults to `twoside`). In addition, the `homework` style uses this switch to configure some options for the `hyperref` package.

2.3 Implementation

1 `*class`

2.3.1 Setup

The `etoolbox` package is required for some of the operations within this class file, including `\newtoggle`, `\ifcsundef` and `\ifstrempy`.

```
2 \RequirePackage{etoolbox}
```

2.3.2 Class option handling

```
3 \newcommand{\hw@sidedness}[1]{\def\hw@side{#1side}}
4 \newtoggle{hw@print}
5
6 \DeclareOption{print}{\toggletrue{hw@print} \hw@sidedness{two}}
7 \DeclareOption{screen}{\togglefalse{hw@print} \hw@sidedness{one}}
8 \DeclareOption{oneside}{\hw@sidedness{one}}
9 \DeclareOption{twoside}{\hw@sidedness{two}}
10
11 \DeclareOption*{\PassOptionsToClass{\CurrentOption}{article}}
12
13 \ExecuteOptions{11pt,screen}
14 \ProcessOptions\relax
15
16 \LoadClass[\hw@side]{article}
```

2.3.3 Arbitrary section numbering

To implement this, first, save the kernel `\@sect` command as `\@@sect`.

```
17 \let\@@sect\@sect
```

Then, redefine `\@sect` to call the function that will handle the parsing and implementation of the new syntax. Add two `|` at the end of the optional argument to ensure that there will *always* be at least three parts separated by `|`.

```
18 \def\@sect#1#2#3#4#5#6[#7]#8{ %
19   \hw@sectsplit{#1}{#2}{#3}{#4}{#5}{#6}{#7||}{#8}
20 }
```

The `\hw@sectsplit` macro is the meat of the implementation of arbitrary numbering. It parses the optional argument into three parts, `#3`, `#4`, and `#5`.

```
21 \def\hw@sectsplit#1#2[#3|#4|#5]#6{ %
```

As the `\thesection` (or `\thesubsection`, etc, but for simplicity, I will describe this in terms of `\section`) macro is overwritten whenever a custom number is used, we need to ensure that the original value is saved. The first time a sectioning command is called, we save this value into `\hw@theorigsection`. Note that this has the side-effect that the user may not redefine `\thesection` in the middle of the document.

```
22 \ifcsundef{hw@theorig#1}
23   {\expandafter\edef\csname hw@theorig#1\endcsname %
24     {\expandafter\expandonce\csname the#1\endcsname}}
25   {\relax}
```

Now we must parse the optional argument. Argument `#5` simply absorbs any extra `|`s. If it is empty, then that means that there were no `|`s in the input, and only a `toc-name` was specified. In this case, simply ensure that `\thesection` is

defined as its original definition and call the kernel's `\@sect` using the defined `toc-name`.

```

26 \ifstrempy{#4#5}
27 {
28   \expandafter\edef\csname the#1\endcsname %
29   {\expandafter\noexpand\csname hw@theorig#1\endcsname}
30   \@sect{#1}#2[#{#3}]{#6}
31 }

```

If, however, argument #5 was not empty, then the user is calling the new custom syntax. We define the `\thesection` as argument #3 and then call the kernel's `\@sect` command. If argument #4 is empty, use the default `toc-name`. Otherwise, use the input provided by the user in argument #4.

```

32 {
33   \expandafter\edef\csname the#1\endcsname{#3}
34   \ifstrempy{#4}
35     {\@sect{#1}#2[#{#6}]{#6}}
36     {\@sect{#1}#2[#{#4}]{#6}}
37   }
38 }

```

2.3.4 Document titling

I find the amount of whitespace above the title excessive in most cases. This attempts to patch the kernel's `\@maketitle` command to omit the initial `\vskip`.

```

39 \patchcmd{\@maketitle}{\null\vskip 2em}{\null}{}{}

```

Define more convenient synonyms for the small font sizes

```

40 \let\Small\footnotesize
41 \let\SMALL\scriptsize
42 </class>

```

3 The homework style

As the homework style is mostly composed of other packages, the implementation serves nicely as its only documentation section.

```

43 <*package>

```

Load fixes to L^AT_EX 2_ε right away.

```

44 \usepackage{fixltx2e}

```

3.1 Font and encoding setup

Fonts are convoluted and tricky, and they have changed a lot since T_EX and M_ET_A-F_{ONT} first appeared. A lot of information online is outdated. One major change is that fonts used to be bitmaps, and now they are almost all vectorized – font sizing

shifted from discrete to continuous. In addition, the world has gotten much better at supporting non-English languages through different font and text encodings. L^AT_EX still defaults to using bitmap fonts and the old encoding schemes.

There are three major advantages for an English language writer to switch to the newer font encoding T1.

1. Accented characters in the output may be selected, copied and searched. Contrast Gödel with Gödel. (This only simulates its rendering, but I believe it should be accurate. Try it!)
2. Words with accented characters are properly hyphenated. See: Süpercálifrag-
ilísticëxpialidoçious.
3. The characters <>| in the text source appear properly as <>| in the output, instead of ꞤꞤ—. (They have always worked properly in math mode.)

I highly recommend it.

This does, however, have an impact on the available fonts; they must match the encoding. Not all fonts are available in all encodings. Generally, if you wish to use a font other than Knuth's **Computer Modern**, you may have greater success using X_YL^AT_EX to typeset your document. It vastly simplifies font selection, and enables system fonts to be used in the document.

As I understand it, there are three major descendants of Knuth's original **Computer Modern** font:

Blue Sky Computer Modern A private company, Blue Sky, took Knuth's original source and spent many hours hand-tuning the hinting, and were selling it. AMS found the improvements very worthwhile and bought the rights to the font, allowing them to freely distribute it in their package. This is the default font in most (all?) modern L^AT_EX distributions, but it is unfortunately not encoded in T1.

CM-Super was the first effort in converting **Computer Modern** to the T1 encoding. It is based on the EC, or European, variant, with many many more available symbols. This is the default font when using a T1 encoding.

Latin Modern is derived from both **cm** and **cm-super**. It is generally regarded as superior to **cm-super**, as its vectorization was done by hand and it includes some much needed fixes to the font metrics. It has many more available glyphs and has continued development. See "[An exploration of the Latin Modern fonts](#)" by Will Robertson (pdf) for many more details.

When using **cm** or **cm-super**, you should load the **fix-cm** package *before* you call the document class. This enables continuous scaling of the fonts and applies some other fixes. But **homework** shall default to **Latin Modern** and T1 for the reasons listed above (when not using X_YL^AT_EX).

```
45 \usepackage{ifxetex}
46 \ifxetex
```

```

47 \usepackage{amssymb} % Load this first due to an incompatibility
48 \usepackage{xltextra}
49 \else
50 \usepackage{lmodern}
51 \usepackage[T1]{fontenc}

```

Just as font encodings have changed in the last 20 years, so has the encoding of text files. \TeX assumes an ASCII source file. However, most every plain text document today is unicode. While the new encoding is backwards compatible and is generally readable as ASCII, explicitly telling \LaTeX that the document is unicode allows for more complicated characters in the source. For example, it enables the writing of accents directly: `\verb|âéîöüñ|`. Even crazier characters may be easily typeset (provided you know how to input them): `\verb|ıŁŁŠŒ•ªºœ´®ßµ|`. $\text{X}\text{\TeX}$ supports this with the `xltextra` package loaded above.

```

52 \usepackage[utf8]{inputenc}

```

As a final modification to \TeX 's font handling, load the `microtype` package. In order to justify the text, \TeX adjusts the spacing between words to make the right column properly aligned. `Microtype` applies a few minor adjustments. The option `stretch=10` means that \TeX will stretch the font itself, up to 10% (the default is 20%, but I find that a bit excessive). This is barely noticeable, and often results in smaller (and more acceptable) inter-word spacing. The `protrusion=true` option allows punctuation to slightly hang over the right column. This makes text appear to align *better* along the right margin. This package is currently under development for full $\text{X}\text{\TeX}$ compatibility.

```

53 \usepackage[stretch=10,protrusion=true]{microtype}
54 \fi

```

The `textcomp` package allows easy access to some nice glyphs, such as `\textmu` (μ), bullets (\bullet \dagger $*$), arrows (\downarrow \rightarrow), currency symbols and other symbols that are traditionally mathmode-only. See the venerable `symbols-a4.pdf` for a full listing.

```

55 \usepackage{textcomp}

```

3.2 Maths

The canonical way of doing Mathematics in \LaTeX is with `amsmath` and its associated packages. That said, there are a few bugs that they are unable to fix; `mathtools` provides these fixes as well as a few much-needed enhancements.

```

56 \usepackage{amsmath,amsthm,amssymb}
57 \usepackage{mathtools}

```

Redefine the equation environment to be the same as `gather` for compatibility with `hyperref`:

```

58 \let\equation\gather
59 \let\endequation\endgather

```

The `dsfont` package is my preferred choice for typesetting the standard number sets: `\mathds{R...}` \mathbb{R} , \mathbb{C} , \mathbb{Z} , \mathbb{Q} , \mathbb{N} .

```

60 \usepackage{dsfont}

```

Additionally, I find the default script fonts lacking. I find Ralph Smith's Formal Script font, `rsfs` much more appealing in some cases. Compare `\mathcal` with `\mathscr`: \mathcal{F} , \mathcal{L} , \mathcal{F} , \mathcal{L} . Unfortunately, the `mathrsfs` package does not load the font for variable sizing, even though it supports it. See <http://tex.stackexchange.com/q/10698> for details; thanks to user [Leo Liu](#) for this solution. (This could potentially be split off into a simple `fix-rsfs` package, mirroring `fix-cm`.)

```
61 \DeclareFontFamily{U}{rsfs}{\skewchar\font127 }
62 \DeclareFontShape{U}{rsfs}{m}{n}{ % Allow continuous sizing
63   <-6> rsfs5
64   <6-8> rsfs7
65   <8-> rsfs10
66 }{}
67 \usepackage{mathrsfs}
```

The `xfrac` package provides very high quality slanted fractions, provided through the `\sfrac` command: $\frac{1}{2}$. It is the generally accepted replacement to `nicefrac`. There are lots of configuration options, but the defaults work very well.

```
68 \usepackage{xfrac}

69 \usepackage{empheq}
70 \newcommand{\sch@swap}[2]{\let\sch@tmp#1 \let#1#2 \let#2\sch@tmp}
71 \sch@swap{\theta}{\vartheta}
72 \sch@swap{\phi}{\varphi}
73 \sch@swap{\epsilon}{\varepsilon}
74
75 % Graphics and colors
76 \usepackage{svgnames}{xcolor}
77 \usepackage{graphicx}
78
79 % amazing unit rendering with si{\micro{}}A/cm^2, SI{3}{\meters\per\second}
80 \usepackage{siunitx}
81 \sisetup{per-mode = symbol} % use units in 'm/s' format
82 % And good chemical formula rendering
83 \usepackage[version=3]{mhchem}
84
85 % Figure handling
86 \usepackage{float} % Allow "unfloating" with the H placement specifier
87 \usepackage{wrapfig}
88 % \floatstyle{boxed}
89 % \restylefloat{figure}
90 \usepackage[small,labelfont=bf]{caption}
91 % \DeclareCaptionFont{singlespacing}{\setstretch{1}}
92 % \captionsetup{font=singlespacing}
93
94 \usepackage{placeins} % Allow \FloatBarrier
95
96 % Package for including code in the document
97 \usepackage{listings}
98 % For faster processing, load Matlab syntax for listings
```

```

99 \lstloadlanguages{Matlab}
100 \newcommand*{\matlabuserfunctions}[1]{
101   \lstset{language=Matlab, morekeywords=[3]{#1}} }
102 \lstset{language=Matlab,
103   frame=single,
104   basicstyle=\footnotesize\ttfamily,
105   keywordstyle=[1]\color{Blue}\bfseries,
106   keywordstyle=[2]\color{Purple},
107   keywordstyle=[3]\color{Blue}\underbar,
108   identifierstyle=,
109   commentstyle=\footnotesize\ttfamily\itshape\color{Green},
110   stringstyle=\color{Purple},
111   showstringspaces=false,
112   tabsize=5,
113   % Put standard MATLAB functions not included in the default
114   % language here
115   morekeywords={xlim,ylim,var,alpha,factorial,poissrnd,normpdf,normcdf},
116   % Put MATLAB function parameters here
117   morekeywords=[2]{on, off, interp},
118   % Put user defined functions here
119   % morekeywords=[3]{},
120   morecomment=[1][\color{Blue}]{...},
121   numbers=left,
122   firstnumber=1,
123   numberstyle=\footnotesize\color{Blue},
124   stepnumber=5
125 }
126 \newcommand*{\matlabscript}[2]
127 { \begin{itemize}\item[] \lstinputlisting[caption={\texttt{#1.m}. #2},label={lst:#1}]{#1.m}\end{itemize} }
128
129 \usepackage[marginpar]{todo}
130
131 % \iftoggle{hw@print}
132 %   {\usepackage{hyperref}}
133 \usepackage[colorlinks,linkcolor=blue]{hyperref}
134 \newcommand*{\magicref}[2]{\hyperref[#2]{#1 \ref{#2}}}
135
136 \newcommand*{\hwClass}[1]{\def\@hwClass{#1}}
137 \newcommand*{\hwTitle}[1]{\def\@hwTitle{#1}}
138 \title{\textbf{\@hwClass:} \@hwTitle}
139
140 \usepackage{tikz}
141 \usepackage{pgfplots}
142 \pgfplotsset{compat=1.4}
143 \end{package}

```