

# Automatic diagnosis and feedback for lexical stress errors in non-native speech: Towards a CAPT system for French learners of German

Anjana Sofia Vakil



UNIVERSITÄT  
DES  
SAARLANDES

Department of Computational Linguistics and Phonetics  
University of Saarland, Saarbrücken, Germany

Master's Thesis Colloquium  
16 April 2015

Some syllable(s) in a word more accentuated/prominent<sup>1</sup>

um·FAHR·en	vs.	UM·fahr·en
<i>to run over</i>		<i>to drive around</i>

- ▶ German: variable stress placement, contrastive stress<sup>1</sup>
- ▶ French: no word-level stress, final syllable lengthening<sup>2</sup>

Goal: Computer-Assisted Pronunciation Training (CAPT) for lexical stress errors for French learners of German

---

<sup>1</sup>A. Cutler. "Lexical Stress". In: *The Handbook of Speech Perception*. Ed. by D. B. Pisoni and R. E. Remez. 2005, pp. 264–289.

<sup>2</sup>M.-C. Michaux and J. Caspers. "The production of Dutch word stress by Francophone learners". In: *Proc. of the Prosody-Discourse Interface Conference (IDP)*. 2013, pp. 89–94.

## Motivation

### Lexical stress errors by French learners of German

- Annotation of a learner speech corpus

- Inter-annotator agreement

- Frequency & distribution of errors

## Diagnosis

- Word prosody analysis

- Diagnosis by comparison

- Diagnosis by classification

## Feedback

- Implicit

- Explicit

- Self-assessment

## The de-stress CAPT tool

Figure: Criteria for selecting errors to target in a CAPT system.



Lexical stress errors seem to be:

- ▶ Frequently produced by French learners of variable-stress languages<sup>1,2</sup>
- ▶ More important for intelligibility in L2 German than other types of errors<sup>3</sup>
- ▶ Possible to identify automatically by comparison<sup>1</sup> or classification<sup>4</sup>

---

<sup>1</sup>A. Bonneau and V. Colotte. “Automatic Feedback for L2 Prosody Learning”. In: *Speech and Language Technologies*. Ed. by I. Ipsic. InTech, 2011.

<sup>2</sup>M.-C. Michaux. “Exploring the production and perception of word stress by French-speaking learners of Dutch”. In: *Workshop on Crosslinguistic Influence in Non-Native Language Acquisition*. 2012.

<sup>3</sup>U. Hirschfeld. *Untersuchungen zur phonetischen Verständlichkeit Deutschlernender*. Vol. 57. Forum Phonetikum. 1994.

<sup>4</sup>Y.-J. Kim and M. C. Beutnagel. “Automatic assessment of American English lexical stress using machine learning algorithms”. In: *SLaTE*. 2011, pp. 93–96.

- ▶ How reliably can human annotators identify errors in learner utterances?
- ▶ How frequently are errors actually produced by French learners of German?

Data: IFCASL corpus of French-German L1/L2 speech<sup>1</sup>

- ▶ German utterances by French and German speakers
  - Adults (>18) and children (15-16)
  - Levels A2, B1, B2, C1 (children all A2/B1)
- ▶ Word- and phone-level segmentations  
(syllable level added automatically)
- ▶ Selected 12 word types (bisyllabic, initial stress)

Dataset for annotation:

668 word utterances by 55-56 L1 French speakers

---

<sup>1</sup>C. Fauth et al. “Designing a Bilingual Speech Corpus for French and German Language Learners: a Two-Step Process”. In: *9th Language Resources and Evaluation Conference (LREC)*. Reykjavik, Iceland, 2014, pp. 1477–1482.

15 Annotators, varying by: **[TODO make this a matrix?]**

- ▶ Native language (L1):
  - 12 German
  - 2 English (US)
  - 1 Hebrew
- ▶ Phonetics/phonology expertise:
  - 2 Experts
  - 10 Intermediates
  - 3 Novices

**[TODO 5 labels, remove the below]**

Each annotated 3 word types in one ~15 min. session  
(1 annotator did 6 word types in 2 sessions)



Figure: Praat annotation tool

tragen  
526

play word

play sentence

stress is on CORRECT syllable

stress is on INCORRECT syllable

no clear stress / I can't tell

wrong number of syllables

problem with audio

Figure: Praat annotation tool

tragen  
526

play word

play sentence

[correct]	stress is on CORRECT syllable
[incorrect]	stress is on INCORRECT syllable
[none]	no clear stress / I can't tell
[bad_nsylls]	wrong number of syllables
[bad_audio]	problem with audio

*How reliably can human annotators identify errors in learner utterances?*

- ▶ Agreement calculated for each overlapping pair
- ▶ Quantified by:
  - Percentage agreement:  $N_{\text{agreed}}/N_{\text{both annotated}}$
  - Cohen's Kappa<sup>1</sup> ( $\kappa$ ): accounts for chance agreement
- ▶ **[TODO remove?]** Overall agreement represented by mean, minimum, median, and maximum of all pairwise values

---

<sup>1</sup>J. Cohen. "A Coefficient of Agreement for Nominal Scales". In: *Educational and Psychological Measurement* 20.1 (Apr. 1960), pp. 37–46.

**Table:** Overall pairwise agreement between annotators

	% Agreement	Cohen's $\kappa$
Mean	54.92%	0.23
Maximum	83.93%	0.61
Median	55.36%	0.26
Minimum	23.21%	-0.01

- ▶ Rather low agreement (“fair”<sup>1</sup> mean  $\kappa$ )
- ▶ Large variability between annotators
- ▶ Not explained by L1/expertise groups

---


<sup>1</sup>J. R. Landis and G. G. Koch. “The measurement of observer agreement for categorical data.” In: *Biometrics* 33.1 (1977), pp. 159–174.

## [TODO Find more graphical way to portray this? Remove?]

Need a single label for each utterance to analyze error frequency & evaluate automatic diagnosis

- ▶ 268 utterances: no disagreement
- ▶ 265 utterances: majority vote
- ▶ remaining 135 utterances decided by rules, e.g.:
  - favor Expert judgments
  - favor certainty ([correct],[incorrect]) over [none]
  - be generous to learners if [correct] vs. [incorrect]

*How frequently are errors actually produced by French learners of German?*



- ▶ Large variability across word types
- ▶ Beginners made more errors (vs. advanced)
- ▶ Children made more errors (vs. adult beginners)

Requires word, syllable, and phone segmentations

- ▶ Automatically produced via forced alignment<sup>1</sup>
- ▶ This work uses existing IFCASL segmentations
- ▶ Syllable segmentations derived from words & phones

**[TODO segmentation screenshot]**

---

<sup>1</sup>L. Mesbahi et al. "Reliability of non-native speech automatic segmentation for prosodic feedback." In: *SLaTE*. 2011.

## Duration (DUR)

- ▶ Perceptual correlate: length/timing
- ▶ Best indicator of German stress<sup>1</sup>
- ▶ Simple to extract from segmentations
- ▶ Features: Relative syllable & nucleus (vowel) lengths

---

<sup>1</sup>G. Dogil and B. Williams. “The phonetic manifestation of word stress”. In: *Word Prosodic Systems in the Languages of Europe*. Ed. by H. van der Hulst. Berlin: Walter de Gruyter, 1999. Chap. 5, pp. 273–334.



## Fundamental frequency (F0)

- ▶ Perceptual correlate: pitch
- ▶ 2nd best indicator of stress after duration<sup>1</sup>
- ▶ Pitch contours computed using JSnoori<sup>2,3</sup>
- ▶ Features: relative syllable & nucleus:
  - Mean F0 (in voiced segments)
  - Maximum F0
  - Minimum F0
  - F0 range (max–min)

---

<sup>1</sup>G. Dogil and B. Williams. “The phonetic manifestation of word stress”. In: *Word Prosodic Systems in the Languages of Europe*. Ed. by H. van der Hulst. Berlin: Walter de Gruyter, 1999. Chap. 5, pp. 273–334.

<sup>2</sup>[jsnoori.loria.fr](http://jsnoori.loria.fr)

<sup>3</sup>J. Di Martino and Y. Laprie. “An efficient F0 determination algorithm based on the implicit calculation of the autocorrelation of the temporal excitation signal”. In: *EUROSPEECH*. Budapest, Hungary, 1999, p. 4.

## Intensity (INT)

- ▶ Perceptual correlate: loudness
- ▶ Worse predictor than DUR or F0, but still may have effect on stress perception<sup>1</sup>
- ▶ Energy contours computed using Jsnoori
- ▶ Features: relative syllable & nucleus:
  - Mean energy (over 60dB “silence threshold”)
  - Maximum energy

---

<sup>1</sup>A. Cutler. “Lexical Stress”. In: *The Handbook of Speech Perception*. Ed. by D. B. Pisoni and R. E. Remez. 2005, pp. 264–289.

**[TODO Slide previewing comparison vs. classification?]**

## Comparison to a single reference utterance




- ▶ Simplest approach, common in CAPT
- ▶ JSnoori (and predecessors) use this method<sup>1</sup>
  - Assigns 3 scores (DUR, F0, INT)
    - ▶ Same syllable stressed?
    - ▶ Difference between stressed/unstressed syllables similar enough?
  - Overall score = weighted average of 3 scores
- ▶ Problem: extremely utterance-dependent!

---

<sup>1</sup>A. Bonneau and V. Colotte. "Automatic Feedback for L2 Prosody Learning". In: *Speech and Language Technologies*. Ed. by I. Ipsic. InTech, 2011.

## Comparison to multiple reference utterances



- ▶ Less common in CAPT systems
- ▶ Less utterance-dependent than single comparison
- ▶ Overall score = average of one-on-one scores

## Options for selecting reference speaker(s)

- ▶ Manually
  - Learner's choice
  - Teacher/researcher's choice
- ▶ Automatically
  - May be more effective to choose reference speaker most closely resembling the learner<sup>1</sup>
  - Selected by comparing speakers' F0 mean and range (using all available recordings)

---

<sup>1</sup>K. Probst et al. "Enhancing foreign language tutors - In search of the golden speaker". In: *Speech Communication* 37.3-4 (July 2002), pp. 161–173.

- ▶ More abstract representation of L1 pronunciation
- ▶ Not yet explored for German CAPT

Research questions:

- ▶ *How well can lexical stress errors be classified?*
- ▶ *How does that compare with human agreement?*
- ▶ *Which features are most useful for classification?*

## Experiments:

- ▶ Trained CART classifiers using WEKA toolkit<sup>1</sup>
- ▶ Used annotated L2 dataset for training/test data (gold-standard labels)
- ▶ Used L1 utterances of the same words as training data (all automatically labeled [correct])

## Evaluated in terms of:

- ▶ Agreement ( $\%$ ,  $\kappa$ ) with gold-standard labels
- ▶ Precision, Recall,  $F_1$  and  $F_2$  for [correct] class **[TODO explain and/or put on handout]**

---


<sup>1</sup>[www.cs.waikato.ac.nz/ml/weka](http://www.cs.waikato.ac.nz/ml/weka)




*Which features are most useful for classification?*

Feature set	Description
DUR	Duration features
F0	Fundamental frequency features
INT	Intensity features
WD	Uttered word (e.g. <i>Tatort</i> )
LV	Speaker's L2 German skill level (A2 B1 B2 C1)
AG	Speaker's age/gender (Girl Boy Woman Man)

*How well can lexical stress errors be classified?*




*How well can lexical stress errors be classified?*




Best performance using only prosodic features: DUR+F0

- ▶ % Accuracy: 69.77%
- ▶  $\kappa$ : 0.29


*How well can lexical stress errors be classified?*



*How well can lexical stress errors be classified?*



*How well can lexical stress errors be classified?*



Best performance overall: WD+LV+DUR+F0+INT

- ▶ % Accuracy: 71.87%
- ▶  $\kappa$ : 0.34


*How does classification accuracy compare with human agreement?*

	% agreement	$\kappa$
Best classifier vs. gold standard	71.87%	0.34
Mean human vs. human	54.92%	0.23

- ▶ Results are encouraging in this context
- ▶ Still want better performance for real-world use

Allows learner to notice features of their utterance/reference utterance, without explicitly evaluating their pronunciation

- Often offered via signal visualization (e.g. in JSnoori)




- May be difficult for learners to interpret
- Simpler alternatives needed



## Graphical abstractions of prosody

Im Frühling **fliegen** Pollen durch die Luft.

Your utterance:




2SR23\_FGWB1\_536\_fliegen

0:04

[Download](#)

Reference utterance 1:




2SR23\_GGWA2\_018\_fliegen

0:03

[Download](#)

Reference utterance 2:



2SR23\_GGMC1\_034\_fliegen

0:03

[Download](#)

## Text stylization

Im Frühling **fliegen** Pollen durch die Luft.

Your  
utterance:

flie gen

2SR23\_FGBA2\_546\_fliegen



[Download](#)

Reference  
utterance 1:

flie<sub>gen</sub>

2SR23\_GGBA2\_007\_fliegen



[Download](#)

**[TODO ]**

**[TODO ]**

- ▶ Create Exercise
- ▶ Create DM
- ▶ Create Scorer?
- ▶ Create FM
- ▶ Show FB output