AI Value

Digital & AI Transformation

MEASURABLE • GOVERNED • SUSTAINABLE

INSTALLATION GUIDE — MINIFIED RUNTIME — EDITOR SIDE — LINUX AND WINDOWS

CortexSkills

Signing workstation, scenario a (private cloud / on-premises, Linux server), scenario b (localhost on Windows), without Docker, reference data and licence management (create, read, update, revoke, delete)

Version 1.15.1 · 2026-10-16

Internal — AI Value

Table of Contents

1. Overview 3
1.1 The reference data 4
2. Prerequisites and preparation 6
2.1 Machines 6
2.2 Install Node.js 22 6
2.3 Check and extract the package 7
3. The signing workstation (once) 8
4. Scenario a — Private cloud or on-premises (Linux server) 9
4.1 Node.js, copy and extraction on the server 9
4.2 Settings 9
4.3 Service and HTTPS 10
4.4 Operate 10
5. Scenario b — Localhost on Windows 12
5.1 Automatic start (optional) 12
5.2 Console, backup and restore on Windows 13
5.3 The reference organizations 13
6. Licence management 15
6.1 Create 15
6.2 Read 16
6.3 Update and renew 16
6.4 Revoke and remove 16
6.5 Delete 17
6.6 A customer who installs on their own premises 17
7. New version or key change 18
8. Plans and add-ons 19
9. Troubleshooting 20
10. Command reference 21

1. Overview

Everything the editor needs fits in a single file, Runtime_Editor_Linux_Windows_CortexSkills_1.15.1.zip; the customer runtime, Runtime_Customer_Linux_CortexSkills_1.15.1.tar.xz, is sent as is to customers. Both are minified production runtimes, ready to run with Node.js 22: no Docker, no npm, no build. This guide describes two scenarios: a — private cloud or on-premises, on a Linux server (systemd service and HTTPS); b — localhost, on a Windows 10 / 11 workstation. Both installations are production versions: reference data of every vertical and SMEs, no demonstration account.

In the editor package	Content	Where to use it
cortexskills · cortexskills.cmd	The launcher on Linux and Windows: start, admin (console), secrets, backup, restore, version.	Scenarios a and b.
cslic · cslic.cmd · cslic-sauvegarder	The licence manager (import, create, list, show, update, renew, revoke, delete, verify) and the encrypted backup of the workstation (Linux).	Your workstation only: the signing workstation.
app/	CortexSkills, editor edition (prices shown), and the licence manager, minified.	Scenarios a and b.
installer-service.sh · config/	Hardened systemd service and Nginx example (HTTPS).	Scenario a.
poste-signature/	Your signing key pair (vendor-private.pem, vendor-public.pem), created for you when the packages were prepared; the packages contain the matching public key.	To import once (cslic import), then delete from the package.
LISEZMOI.txt · README.txt	Reminder of the essential commands, in French and English.	Your workstation.
Runtime_Customer_Linux_CortexSkills_1.15.1.tar.xz (separate file)	The customer runtime (Linux): with no price and no commercial content.	Sent as is to customers with its .sha256, the customer installation guide and the customer user guide.

What the package contains — and what it does not

The production runtime: the minified server (file by file, without comments, internal names shortened), the compiled and minified web client (split per page, pre-compressed with Brotli and gzip, without source maps) and the libraries needed at run time.

The vendor public key: it verifies the licence, it cannot create one.

No readable source code, no test, no source map, no signing tool, no private key (except the poste-signature/ folder, chapter 3).

Node.js is not included: it is a prerequisite of the machine (Node.js 22 LTS, 22.13 or newer;

validated version: 22.22.2). This keeps the package to a single compressed file.

Run-time optimisations: only the screens opened are loaded (the first display loads about 370 KB of JavaScript instead of 2.2 MB), static files are served pre-compressed and cached by the browser for a year (their name changes with each version), and Node.js keeps the compiled code between two starts (data/.node-compile-cache).

1.1 The reference data

At first start, the installation loads 61 reference organizations: 32 large companies and 29 SMEs, in every vertical (29 sectors and a universal case). Each has two complete projects (Digital and AI focus) with its processes, tasks, steps, questionnaires, plans, documents and indicators: they are examples to look at, in English, French and Arabic.

No demonstration account

The sign-in page names no account; no demonstration password exists in this production version.

The people of the reference organizations cannot sign in: their accounts are disabled and their password, drawn at random at installation, is known to nobody.

Only the platform administrator (ADMIN_EMAIL) signs in at first; they look at the reference organizations read-only (Portfolio › Groups and organizations). Your customer organizations are created with the console (chapter 6).

They have no licence: they do not count in the number of users of your licence. For an empty database, set REFERENCE_DATA=non in .env before the first start.

How the application is protected

Minified code: each server file is compacted (no comments, internal names shortened, formatting removed); the web client is compiled and minified; no source map, no test, no signing tool. The package build checks that no application file is readable before producing the file.

Ed25519-signed licence: the plan, the number of users, the add-ons and the end date come only from the .lic file; a modified file is refused; the customer can change neither the plan nor the add-ons, neither on screen nor through the console.

Fixed mode: the package enforces the on-premises mode (licence required) and, on the customer side, the absence of commercial information, whatever the settings of .env.

Public key at a fixed place in app/; no setting can point to another one. The application refuses to start if a private key is in its folder.

Customer edition without commercial content: no price, no quotation, no Pricing screen; the prices are removed down to the database.

> Unprivileged Linux service, read-only except data/, local port only.

Limit to know: minified code remains executable, hence readable with effort by a determined administrator with full rights on the server; it is less protected than the Docker package, where the code is not reachable without extracting the image. Technical protection is completed by the contract (licence of use, ban on reverse engineering, audit right, number of users, end date).

2. Prerequisites and preparation

2.1 Machines

Machine	Need
Server (scenario a)	Linux 64-bit x86-64 with glibc 2.28+ (Ubuntu 22.04 / 24.04, Debian 12, RHEL / Rocky / AlmaLinux 9), 2 vCPU, 4 GB RAM, 20 GB free disk (4 vCPU / 8 GB beyond 100 active users); Node.js 22 LTS; systemd; Nginx; a DNS name; ports 80/443.
Windows workstation (signing and scenario b)	Windows 10 22H2 or Windows 11, 64-bit (x64), 8 GB RAM recommended, 20 GB free disk; Node.js 22 LTS. No WSL, no Docker.
Signing workstation on Linux (alternative)	Linux 64-bit x86-64 with Node.js 22; unzip, sha256sum, openssl (for cslic-sauvegarder).
Internet	Not needed to install CortexSkills once Node.js is installed (isolated servers and workstations possible).

2.2 Install Node.js 22

Windows. On https://nodejs.org/en/download, choose version 22 (LTS), “Windows Installer (.msi)”, x64; install with the default options (added to the PATH). Open a new command prompt: node -v shows v22.x (22.13 or newer; validated version: 22.22.2).

Linux (scenario a server, or signing workstation).

Node.js 22 LTS (22.13 or newer) must be installed on the server. Two methods; then check with node -v.

Method 1 — official archive (also works without Internet on the server). Download node-v22.22.2-linux-x64.tar.xz and SHASUMS256.txt from https://nodejs.org/dist/v22.22.2/ (on a connected workstation, then copy them to the server):

```
grep " node-v22.22.2-linux-x64.tar.xz$" SHASUMS256.txt | sha256sum -c -
sudo tar -xJf node-v22.22.2-linux-x64.tar.xz -C /usr/local --strip-components=1
node -v          # v22.22.2
```

Method 2 — NodeSource repository (server connected to the Internet).

```
# Ubuntu, Debian
curl -fsSL https://deb.nodesource.com/setup_22.x | sudo -E bash - && sudo apt-get install -y nodejs
# RHEL, Rocky, AlmaLinux
curl -fsSL https://rpm.nodesource.com/setup_22.x | sudo bash - && sudo dnf install -y nodejs
node -v          # v22.x (22.13 or newer)
```

The nodejs package of the standard Ubuntu or Debian repositories is too old (18 or 20): do not use “apt install nodejs” without NodeSource. If Node.js is installed elsewhere, give its path in the CORTEXSKILLS_NODE variable (for example /opt/node22/bin/node).

2.3 Check and extract the package

On Windows, in PowerShell (the C:\CortexSkills folder is an example; avoid “Program Files”, which is write-protected):

```
cd $env:USERPROFILE\Downloads
(Get-FileHash Runtime_Editor_Linux_Windows_CortexSkills_1.15.1.zip -Algorithm SHA256).Hash.ToLower()     # same as the content of the .sha256
Unblock-File Runtime_Editor_Linux_Windows_CortexSkills_1.15.1.zip
Expand-Archive Runtime_Editor_Linux_Windows_CortexSkills_1.15.1.zip -DestinationPath C:\CortexSkills
cd C:\CortexSkills\Runtime_Editor_Linux_Windows_CortexSkills_1.15.1
.\cortexskills.cmd version
```

Unblock-File removes the “downloaded from the Internet” mark: without it, Windows SmartScreen asks for a confirmation at each launch of a .cmd.

On Linux:

```
sha256sum -c Runtime_Editor_Linux_Windows_CortexSkills_1.15.1.zip.sha256 && unzip -q Runtime_Editor_Linux_Windows_CortexSkills_1.15.1.zip -d ~/cortexskills && cd ~/cortexskills/Runtime_Editor_Linux_Windows_CortexSkills_1.15.1
sha256sum -c --quiet SHA256SUMS.txt && echo "content intact"
./cortexskills version
```

3. The signing workstation (once)

The signing workstation is your own workstation, Windows or Linux. In the package folder:

Install your key pair and create the licence register, then delete the poste-signature folder:

```
# Windows (PowerShell, in C:\CortexSkills\
Runtime_Editor_Linux_Windows_CortexSkills_1.15.1)
.\cslic.cmd import poste-signature
icacls $env:USERPROFILE\.cortexskills-editeur /inheritance:r /grant:r "$
($env:USERNAME):(OI)(CI)F"
Remove-Item -Recurse poste-signature
# Linux
./cslic import poste-signature && rm -r poste-signature
```

cslic saves everything in %USERPROFILE%\.cortexskills-editeur (Windows) or ~/.cortexskills-editeur (Linux): cles/vendor-private.pem (secret), cles/vendor-public.pem, registre.json, licences/, archives/ and journal.log. The icacls command restricts this folder to your Windows account; on Linux, cslic creates it with rights 700. cslic shows the fingerprint of the public key: note it, your customers can compare it. The licence manager accepts English commands and options (import, create, --company, --users, --end…); its messages are in French.

Back up the signing workstation immediately, offline and encrypted:

```
# Linux: AES-256 encrypted archive (password asked)
./cslic-sauvegarder ~/vault            # → cortexskills-editeur-YYYY-MM-DD.tar.gz.enc
# restore: openssl enc -d -aes-256-cbc -pbkdf2 -in <file.enc> | tar -xz -C ~
# Windows: 7-Zip encrypted archive (AES-256), kept offline
& "C:\Program Files\7-Zip\7z.exe" a -p -mhe=on "$env:USERPROFILE\Documents\
cortexskills-editeur-$(Get-Date -f yyyy-MM-dd).7z" "$env:USERPROFILE\.cortexskills-
editeur"
```

Private key rules

It never leaves your workstation: not to a scenario a server, not to a customer, not by e-mail, not into a code repository.

If it is lost, you can no longer issue or renew a licence; if it is disclosed, anyone can issue one. In both cases, a new key pair and new packages and licences for every customer are needed.

On another workstation, restore the encrypted backup; do not create a new pair (cslic init), except for a deliberate key change (chapter 7).

This pair was created for you when the packages were prepared: it is kept nowhere else than in the editor package. After the import and the backup, also delete the zip file received.

To type just “cslic”: on Windows, add C:\CortexSkills\Runtime_Editor_Linux_Windows_CortexSkills_1.15.1 to your account’s PATH variable; on Linux, alias cslic="$HOME/cortexskills/Runtime_Editor_Linux_Windows_CortexSkills_1.15.1/cslic" in ~/.bashrc.

4. Scenario a — Private cloud or on-premises (Linux server)

On a Linux server you manage — private cloud, on-premises server or VPS — for a pilot or a demonstration in HTTPS. Same protections as at a customer; signing stays on your workstation: never copy poste-signature/ or the .cortexskills-editeur folder to the server.

4.1 Node.js, copy and extraction on the server

Install Node.js 22 on the server (2.2, Linux part), then:

```
scp Runtime_Editor_Linux_Windows_CortexSkills_1.15.1.zip
Runtime_Editor_Linux_Windows_CortexSkills_1.15.1.zip.sha256 user@server:~      # from
your workstation
# on the server
sudo apt -y install unzip nginx certbot python3-certbot-nginx
sha256sum -c Runtime_Editor_Linux_Windows_CortexSkills_1.15.1.zip.sha256
sudo unzip -q Runtime_Editor_Linux_Windows_CortexSkills_1.15.1.zip -d /opt && sudo
mv /opt/Runtime_Editor_Linux_Windows_CortexSkills_1.15.1 /opt/cortexskills
cd /opt/cortexskills && sudo rm -rf poste-signature *.cmd
sudo ufw allow OpenSSH && sudo ufw allow 80/tcp && sudo ufw allow 443/tcp && sudo ufw
enable
```

The poste-signature/ folder and the Windows launchers are removed from the server: they are not used there, and the private key must never be there (the application refuses to start if it finds one in its folder).

4.2 Settings

```
sudo cp env.example .env
./cortexskills secrets
sudo nano .env
```

Setting	Value	Example
PUBLIC_URL	The address users type, in HTTPS; it appears in the links sent by e-mail and WhatsApp.	https://skills.your-company.com
CORS_ORIGIN	The same address.	https://skills.your-company.com
HOST, PORT	Listening interface and port. 127.0.0.1: only the reverse proxy (or the local browser) reaches it.	127.0.0.1, 4000
JWT_SECRET	Random value of 32 characters or more (signs the sessions).	shown by “cortexskills secrets”

Setting	Value	Example
CHANNEL_SECRET_KEY	Another random value (encrypts the stored credentials).	shown by “cortexskills secrets”
ADMIN_EMAIL, ADMIN_NAME, ADMIN_PASSWORD	The platform administrator, created at first start. Password: 12 characters min., upper case, lower case, digit, symbol. Clear ADMIN_PASSWORD afterwards.	it.ops@your-company.com
REFERENCE_DATA	First start: “oui” loads the reference organizations; “non” creates an empty database.	oui
DATA_DIR	Optional: data folder. By default data/ in the package folder.	/var/lib/cortexskills
BACKUP_RETENTION_DAYS	Days the daily backups are kept (about 0.8 GB each).	7
SMTP_*	Your mail server for invitations, reminders and notifications.	smtp.your-company.com, 587
WHATSAPP_*	Optional: WhatsApp Business Cloud API.	—

The package enforces the on-premises mode (signed licence required), whatever the value of DEPLOYMENT_MODE or COMMERCIAL_INFO in .env: these settings are ignored.

4.3 Service and HTTPS

```
sudo ./installer-service.sh
journalctl -u cortexskills -f          # first start: 5 to 15 minutes, until “CortexSkills API is running”
sudo cp config/nginx-cortexskills.conf /etc/nginx/conf.d/cortexskills.conf && sudo nano /etc/nginx/conf.d/cortexskills.conf
sudo certbot certonly --nginx -d skills.mydomain.com
sudo nginx -t && sudo systemctl reload nginx
curl -s https://skills.mydomain.com/api/health
```

installer-service.sh checks Node.js, creates the cortexskills system user, makes app/ read-only, restricts data/ to the service and installs the hardened systemd service (read-only except data/, no privilege). Then clear ADMIN_PASSWORD from .env and run sudo systemctl restart cortexskills. Fill in the SMTP_* lines so that invitations and reminders really leave.

4.4 Operate

```
sudo systemctl status cortexskills · journalctl -u cortexskills -f
sudo -u cortexskills ./cortexskills backup
30 2 * * * rsync -a /opt/cortexskills/data/ backup@storage:/cortexskills/     # sudo crontab -e
```

- Restore: sudo systemctl stop cortexskills; sudo -u cortexskills ./cortexskills restore <file.db>; sudo systemctl start cortexskills.

- Update: backup, then replace app/, config/ and the scripts with those of the new version, and run sudo ./installer-service.sh again; .env, data/ and licence/ are kept, the database is migrated at start (same procedure as chapter 10.4 of the customer guide).
- Several customer organizations can be active on the same installation: one licence each.

5. Scenario b — Localhost on Windows

On your Windows workstation, to demonstrate, train or run a pilot with a customer, at the address http://localhost:4000, in the same on-premises production mode as at a customer, with the reference data. In PowerShell, folder C:\CortexSkills\Runtime_Editor_Linux_Windows_CortexSkills_1.15.1:

```
Copy-Item env.example .env
.\cortexskills.cmd secrets            # two secrets for .env
notepad .env
```

.env line	Value (localhost)
PUBLIC_URL, CORS_ORIGIN	http://localhost:4000
HOST, PORT	127.0.0.1, 4000
JWT_SECRET, CHANNEL_SECRET_KEY	the first two values shown by secrets
ADMIN_EMAIL, ADMIN_NAME, ADMIN_PASSWORD	your platform administrator
REFERENCE_DATA	oui (reference data) or non (empty database)

```
.\cortexskills.cmd start              # first start: 5 to 15 minutes, until "CortexSkills API is running"
```

Leave the window open and open http://localhost:4000 in the browser. Stop: Ctrl+C in the window. Then clear the value of ADMIN_PASSWORD in .env. The data is in data\ next to the launcher. At first launch, the Windows firewall may ask for permission for node.exe: refuse public network access, the application only listens on 127.0.0.1.

5.1 Automatic start (optional)

To start CortexSkills at sign-in, without a window, with the Task Scheduler (PowerShell):

```
$a = New-ScheduledTaskAction -Execute "C:\CortexSkills\Runtime_Editor_Linux_Windows_CortexSkills_1.15.1\cortexskills.cmd" -Argument "start" -WorkingDirectory "C:\CortexSkills\Runtime_Editor_Linux_Windows_CortexSkills_1.15.1"
$t = New-ScheduledTaskTrigger -AtLogOn -User $env:USERNAME
$s = New-ScheduledTaskSettingsSet -ExecutionTimeLimit 0 -AllowStartIfOnBatteries
Register-ScheduledTask -TaskName "CortexSkills" -Action $a -Trigger $t -Settings $s -Description "CortexSkills localhost"
Start-ScheduledTask CortexSkills · Stop-ScheduledTask CortexSkills · Unregister-ScheduledTask CortexSkills
```

5.2 Console, backup and restore on Windows

Action	Command (PowerShell, package folder)
Console help	.\cortexskills.cmd admin help
On-demand backup	.\cortexskills.cmd backup (in data\backups)
Restore (application stopped)	.\cortexskills.cmd restore · .\cortexskills.cmd restore <file.db>
Version	.\cortexskills.cmd version

5.3 The reference organizations

Sector	Large companies	SMEs
AEC & Construction (AEC)	Oasis Construction & Engineering	Souss BTP Solutions
Aerospace & Defense (AERO)	Aero Atlas Nouaceur	Precision Aero Composites
Automotive (AUTO)	Atlas Motors Kénitra	Tanger Auto Parts
Consumer Packaged Goods (CPG)	Sahel Consumer Brands	Savonnerie Beldi
Consumer Products Extended (CPEX)	Sahel Home & Living	Poterie Safi Design
Distribution (DIST)	Horizon Distribution	Distri Oriental
Electronics & High-Tech (ELEC)	Atlas Electronics Group	Circuitec Oujda
Energy & Utilities (ENUT)	Oasis Energy & Utilities	Solaris Maintenance Services
Fabrication & Assembly (FABA)	Atlas Steel Structures	Atelier Métal Berrechid
Food & Beverage (FNB)	Sahel Agro Industries	Coopérative Laitière Al Baraka
Footwear & Apparel (FTAP)	Atlas Textile & Footwear	Atelier Cuir Fès
Healthcare & Life Sciences (HLS)	Maghreb Life Sciences	BioLab Diagnostics Rabat
Healthcare Providers (HCPR)	Maghreb Hospitals Group ; Santéora Private Clinics Group ; Regional Hospital Centre	Clinique Al Amal
Industrial Machinery (MACH)	Maghreb Machines Industries	Fès Mécanique de Précision
Infrastructure (INFR)	Autoroutes & Ouvrages du Nord	Géo Inspect Maroc
Logistics (LOGI)	Horizon Logistics Tanger Med	Trans Atlas Express
Manufacturing (Generic) (MFGG)	Atlas Manufacturing Group	Plasti Meknès
Pharma (PHAR)	Maghreb Pharma Distribution	PharmaLog Services
Pharmaceutical & Process (PHPR)	Pharma Maghreb Process	Galénix Laboratoires
Private Education (PRED)	Horizon Private Universities	École Al Manar
Process / Packaged Goods (PKGD)	Sahel Packaging & Bottling	Emballages Kénitra
Process / Petrochemical (PETR)	Atlantique Petrochemicals	Chem Services Safi
Process Industries (PROC)	Phosphates & Minerals Atlas	Minerals Lab Khouribga

Sector	Large companies	SMEs
Public Education (PUED)	Académie Régionale Rabat-Salé	Lycée Pilote Ibn Sina
Retail (RETL)	Sahel Retail Stores	Marrakech Concept Store
Semiconductor & Electronics (SEMI)	Atlas Semiconductor Packaging	MicroTest Engineering
Shipbuilding (SHIP)	Chantiers Navals du Détroit	Marine Outfitting Agadir
Social & Solidarity Economy (SSE)	Fédération Nationale des Coopératives	Coopérative Argan Tiznit
Telecommunications (TELC)	Oasis Telecom	NetConnect Services
Universal (all sectors) (UNI)	Horizon Services Group	—

6. Licence management

A licence always follows the same cycle. Signing (create, update) is done on your workstation with cslic; installing and removing are done on the installation concerned with the console (cortexskills admin) — or by the customer themselves.

Stage	On the signing workstation (cslic)	On the installation (cortexskills admin …)
Request	—	org-create … then licence-request --org <domain> → Organization ID
Create (C)	cslic create …	licence-install --file <file.lic>
Read (R)	cslic list · cslic show L-0001 · cslic list --csv	licence-list · licence-show --org <domain> · Configuration and licence screen
Update (U)	cslic update L-0001 … · cslic renew L-0001 --end …	licence-install --file <new version>
Revoke	cslic revoke L-0001 --reason …	licence-remove --org <domain> --yes
Delete (D)	cslic delete L-0001 --yes	—

On the Linux server (scenario a), prefix the console with sudo -u cortexskills ./cortexskills admin; on Windows (scenario b), .\cortexskills.cmd admin. On Windows, cslic is written .\cslic.cmd.

6.1 Create

Create the organization on the installation:

```
cortexskills admin org-create --name "Example Clinic" --domain example-clinic.com \
  --admin-email admin@example-clinic.com --admin-name "Clinic Admin" --admin-password
'Str0ng#Passw0rd2026' --lang en
cortexskills admin licence-request --org example-clinic.com        # shows the
Organization ID
```

Sign on your workstation:

```
cslic create --company "Example Clinic" --org-id <Organization ID> --plan SME-GRO --
users 50 \
  --end 2027-12-31 --addons AD-11 --ref CONTRACT-2026-014
```

Option	Meaning	Rule
--company	Customer name written in the licence.	Required.
--org-id	Organization ID shown by the request.	Exact (UUID format); the licence is valid for this organization only.
--plan	Plan (chapter 8).	Sets the organization's modules.
--users	Maximum number of active users.	Creating a user beyond it is refused.
--end	End date (YYYY-MM-DD).	Warning 30 days before; read-only after.
--addons	Add-ons (chapter 8), separated by commas.	Optional; only these add-ons are active.

Option	Meaning	Rule
--features, --ref, --notes	Free mentions; contract reference; internal notes.	Optional.

cslic gives a number (L-0001, L-0002…), writes the file licences/L-0001_v1_Example_Clinic.lic in the signing workstation folder and records it in the register. A single active licence per organization: to change it, update it.

Install. Scenario a: first copy the file to the server. Scenario b: directly from your workstation.

```
# scenario a
scp ~/.cortexskills-editeur/licences/L-0001_v1_Example_Clinic.lic user@server:/tmp/
sudo cp /tmp/L-0001_v1_Example_Clinic.lic /opt/cortexskills/licence/ && sudo chmod 644 /opt/cortexskills/licence/*.lic
sudo -u cortexskills ./cortexskills admin licence-install --file licence/L-0001_v1_Example_Clinic.lic
# scenario b (PowerShell)
.\cortexskills.cmd admin licence-install --file $env:USERPROFILE\.cortexskills-editeur\licences\L-0001_v1_Example_Clinic.lic
```

6.2 Read

```
cslic list                      # active licences: number, company, plan, users, end, version, state
cslic list --all --csv register.csv   # the whole history, exported for a spreadsheet
cslic show L-0001            # detail and history (creation, updates, revocation)
cortexskills admin licence-list  # on the installation: installed licences and their state
cortexskills admin licence-show --org example-clinic.com
```

States (shown in French by cslic): ACTIVE, ACTIVE (n j) in the last 30 days, EXPIRÉE (expired), RÉVOQUÉE (revoked). The journal.log file of the workstation records each operation (date, user, licence).

6.3 Update and renew

```
cslic update L-0001 --users 80                  # more users
cslic update L-0001 --plan BND-02 --addons AD-02,AD-11   # other plan, other add-ons (--addons "" for none)
cslic renew L-0001 --end 2028-12-31                  # new end date
```

Each update signs a new version (L-0001_v2_…lic) and records it in the history. Install it like the first one (licence-install): it replaces the previous one, without restart.

6.4 Revoke and remove

```
cslic revoke L-0001 --reason "contract terminated"
cortexskills admin licence-remove --org example-clinic.com --yes     # on the installation: the users can no longer sign in
```

On your installations (scenarios a and b), removal is immediate. At a customer who installs themselves, a licence cannot be cancelled remotely: it stops at its end date. So prefer one-year terms, renewed, and enforce the contract. The organization's data stays in data/.

6.5 Delete

```
cslic delete L-0001 --yes            # revoked or expired licence; --force for a
licence still active
```

The record and all versions of the file are moved to archives/; the line disappears from the register. The log keeps a trace of the operation.

6.6 A customer who installs on their own premises

Send the customer: Runtime_Customer_Linux_CortexSkills_1.15.1.tar.xz and Runtime_Customer_Linux_CortexSkills_1.15.1.tar.xz.sha256, with the customer installation guide and the customer user guide (Word and PDF, in English or French). The package is the same for every customer: it contains your public key.

Receive the lines of their request (licence-request): company and Organization ID.

Sign with cslic create (6.1) and send them the .lic file by e-mail. They install it with licence-install, without any access from you to their server.

Renewals and changes: cslic update / renew, then send the new version.

7. New version or key change

- New version: you receive new files Runtime_Editor_Linux_Windows_CortexSkills_<version>.zip and Runtime_Customer_Linux_CortexSkills_<version>.tar.xz, built by the development team (the source code is not part of this delivery). On each installation: backup, then replace app/, config/ and the scripts; .env, data/ and licence/ are kept and the database is migrated at start. The reference data is not reloaded.
- On Windows (scenario b): stop the application, extract the new version into a new folder, copy .env and the data\ folder of the old one into it, then run .\cortexskills.cmd start; update the scheduled task if you use it.
- The new packages are built with your public key (vendor-public.pem, which you can export with cslic public-key): your licences remain valid.
- Key change (key lost or disclosed): create a new pair with cslic init in a new CSLIC_HOME, have the packages rebuilt with the new public key, then reissue and resend all licences; the old ones are no longer recognised by the new packages.

8. Plans and add-ons

Plan	Name	Contains
PK-01	Core training engineering offer	PK-01
PK-02	Delivery and learning experience offer	PK-02
PK-03	Evaluation, analytics and ROI offer	PK-03
PK-04	Compliance and certification offer	PK-04
PK-05	Talent and mobility offer	PK-05
PK-06	Extended enterprise offer	PK-06
PK-07	Consulting and diagnostic offer	PK-07
PK-08	Strategic workforce planning and governance offer	PK-08
BND-01	Starter Bundle	PK-01, PK-02
BND-02	Growth Bundle	PK-01 to PK-03
BND-03	Enterprise Bundle	PK-01 to PK-05
BND-04	Strategic Bundle	PK-01 to PK-06, PK-08
BND-05	Full Suite	PK-01 to PK-08
SME-ESS	SME Essentials Pack	PK-01
SME-GRO	SME Growth Pack	PK-01 to PK-03
SME-CMP	SME Complete Pack	PK-01 to PK-08

Add-on	Name
AD-01	Immersive learning (VR/AR/simulation)
AD-02	AI personalisation engine
AD-03	Predictive analytics
AD-04	Social and collaborative learning
AD-05	Gamification engine
AD-06	Content curation and aggregation
AD-07	Expert knowledge capture and transfer
AD-08	Multi-site / multi-entity deployment
AD-09	External validation of the training plan
AD-10	Managerial maturity
AD-11	Questionnaire library and multi-channel distribution

Prices remain visible in your installations (Administration › Pricing); they never appear at customers.

9. Troubleshooting

What you see	Cause	What to do
“Node.js 22 not found”	Node.js is not installed, or the window was opened before it was installed.	Install Node.js 22 (2.2) then open a new window; or CORTEXSKILLS_NODE=<path of node>.
“needs Node.js 22.13 or newer”	Node.js version too old.	Install Node.js 22 LTS (2.2).
cslic: “Poste de signature non initialisé” (not initialised)	Keys not imported on this workstation yet, or a different CSLIC_HOME.	cslic import poste-signature, or restore the encrypted backup.
cslic create: “déjà active pour cette organisation” (already active)	A single active licence per organization.	cslic update L-xxxx …
“The vendor PRIVATE key must never be on a customer server”	vendor-private.pem found in the application folder.	Remove it: it must exist only in the cles/ folder of the signing workstation.
licence-install: “signature is not valid” everywhere	Licences signed with a key other than the package’s.	Compare the fingerprints (cslic fingerprint); see chapter 7.
Long first start	Loading the reference data.	Normal (5 to 15 minutes). Do not interrupt it.
“Port 4000 is already in use”	CortexSkills already started (other window, scheduled task) or other software.	Close the other instance, or change PORT, PUBLIC_URL and CORS_ORIGIN in .env.
Windows: “Windows protected your PC” (SmartScreen)	Files marked “downloaded from the Internet”.	Unblock-File on the zip before extracting it (2.3), or Get-ChildItem -Recurse | Unblock-File in the folder.
Windows: “Access denied” when writing data\	Package extracted in Program Files.	Extract into C:\CortexSkills.
Linux: “EACCES” or “read-only file system”	Installation under /home or rights changed.	Install in /opt/cortexskills; run sudo ./installer-service.sh again.
Linux: “GLIBC_2.28 not found”	System too old, Alpine or arm64.	Recent Linux x86-64 (2.1), or the Docker package.
An account of a reference organization is refused	These accounts cannot sign in (1.1).	Platform administrator, or accounts of the organizations created with the console.

10. Command reference

Where	Command	Role
Workstation	cslic import poste-signature · cslic-sauvegarder <folder> · cslic fingerprint · cslic public-key	Keys and backup
Workstation	cslic create · list · show · update · renew · revoke · delete · verify	Licences (CRUD)
Installation	cortexskills start · version · secrets · backup · restore [file]	Start and operation
Installation	cortexskills admin org-create · org-list · licence-request · licence-install · licence-list · licence-show · licence-remove · password · help	Organizations, installed licences, accounts
Linux server	sudo ./installer-service.sh · systemctl status|restart cortexskills · journalctl -u cortexskills -f	Service (scenario a)
Windows workstation	.\cortexskills.cmd ... · .\cslic.cmd ... · Register-ScheduledTask (5.1)	Scenario b

Use of the application on the editor side (organizations, pricing, licences on screen, reference organizations): User_Guide_Editor_CortexSkills_EN.