

key-theorems package

version 0.0.2 α

github.com/mbertucci47/key-theorems

Matthew Bertucci

December 6, 2023

Abstract

An expl3-implementation of a key-value interface to `amsthm`, implementing most of the functionality provided by `thmtools`. Very much not a finished product. Don't use it for anything important!

1 Load-time Options

`overload` (initially unset)

Redefines `\newtheorem` to internally use the `key-theorems` machinery. The syntax remains the same.

`thmtools-compatible` (initially unset)

For compatibility with `thmtools` syntax. Currently defines the `\declaretheoremstyle`, `\declaretheorem`, and `\listoftheorems` commands and the `restatable` environment.

`store-all` (initially unset)

Tells `key-theorems` to grab the body of each theorem so it can later be printed with `\listofkeytheorems[print-body]`. Note that this means a theorem body *cannot* contain verbatim material.

2 Global Options

`\keytheoremset{<options>}`

`restate-counters={<comma-list of counters>}` (initially `{equation}`)

Additional counters whose values are preserved when a theorem is restated. This key does not reset the list, so you don't need to include `equation` in `<comma-list>`.

`continues-code=<code with #1>` (initially continuing from `p.\`, `\pageref{#1}`)

The code used to typeset the note produced by the `continues`^{P.2} key.

`qed-symbol=<symbol>` (initially `\openbox`)

Redefines `\qedsymbol` to be `<symbol>`.

3 Declaring Theorems

`\newkeytheorem{<env name>}[<options>]`

Defines a theorem environment `<env name>` which itself takes a few options (see subsection 3.1). You can also declare multiple theorems at once by replacing `<env name>` with a comma-list of names, e.g. `\newkeytheorem{theorem,lemma,proposition}[<options>]`.

By default, the theorem's printed name is a title-cased `<env name>`. This can be changed with the `name`^{P.3} key. All `<options>` are described in subsections 3.2 and 3.3.

```
% preamble
\newkeytheorem{theorem}

% document
\begin{theorem}
Some text
\end{theorem}
```

Theorem 1. *Some text*

3.1 Keys available to theorem environments

As in `amsthm`, theorems can take an optional argument that contains a note or heading.

```
\begin{theorem}[some heading]
Some text
\end{theorem}
```

Theorem 2 (some heading). *Some text*

Alternatively, the optional argument may contain any of the following keys.

`note=<text>` (initially unset)

Alias `name`. This is the key-value equivalent of the optional argument described above. This syntax, however, allows the argument to contain other keys.

```
\begin{theorem}[some heading]
Some text
\end{theorem}
\begin{theorem}[note=another heading]
Some more text
\end{theorem}
```

Theorem 3 (some heading). *Some text*

Theorem 4 (another heading). *Some more text*

`label=<label name>` (initially unset)

This is the key-value equivalent of `\begin{theorem} \label{<label name>}`.

```
\begin{theorem}[label=foo]
Some text
\end{theorem}
\ref{foo}
```

Theorem 5. *Some text*

5

`continues*=<label name>` (initially unset)

Pick up a theorem where you left off. The theorem number remains the same. The printed text can be customized with the `continues-code`^{P.1} option. The starred version also copies the theorem note, if it exists.

```
\begin{theorem}[continues=foo]
\dots and some more text.
\end{theorem}
```

Theorem 5 (continuing from p. 2). *... and some more text.*

`store=<cname>` (initially unset)

Alias `restate`. Defines a command `\<cname>` that can be used to restate the theorem, including the body text, later in the document. This is the local version of the `store-all`^{P.1} load-time option. A theorem given this key *cannot* contain verbatim material.

```
\begin{theorem}[store=blub]
A theorem worth restating.
\end{theorem}
More brilliant mathematics.
\blub
```

Theorem 6. *A theorem worth restating.*

More brilliant mathematics.

Theorem 6. *A theorem worth restating.*

3.2 Keys inherited from thmtools

These are the [*options*] passed to `\newkeytheorem`. For more description, see the `thmtools` package.

`name=<display name>` (initially title-cased *<env name>*)

Aliases `title` and `heading`.

<pre>% preamble \newkeytheorem{mythm}[name=Some Name] % document \begin{mythm} Some text \end{mythm}</pre>	<p>Some Name 1. <i>Some text</i></p>
---	---

`numbered=true|false` (default `true`, initially `true`)

For compatibility with `thmtools`, also accepts the values `yes` and `no`.

<pre>% preamble \newkeytheorem{theorem*}[name=Theorem, numbered=false] % document \begin{theorem*} An unnumbered theorem. \end{theorem*}</pre>	<p>Theorem. <i>An unnumbered theorem.</i></p>
---	--

`parent=<counter>` (initially unset)

Aliases `numberwithin` and `within`.

<pre>% preamble \newkeytheorem{conjecture}[parent=section] % document \begin{conjecture} The first number is the section. \end{conjecture}</pre>	<p>Conjecture 3.1. <i>The first number is the section.</i></p>
---	---

`sibling=<counter>` (initially unset)

Aliases `numberlike` and `sharenumber`.

<pre>% preamble \newkeytheorem{lemma}[sibling=theorem] % document \begin{lemma} This shares its counter with \texttt{theorem}. \end{lemma}</pre>	<p>Lemma 7. <i>This shares its counter with theorem.</i></p>
---	---

`style=<style name>` (initially unset)

Accepts any *<style name>* defined by `\newkeytheoremstyle`^{P.5}, as well as any of the predefined `amsthm` styles: `plain`, `definition`, and `remark`.

<pre> % preamble \newkeytheorem{remark}[style=remark] % document \begin{remark} Some text \end{remark} </pre>	<p><i>Remark 1. Some text</i></p>
--	-----------------------------------

`preheadhook`= $\langle code \rangle$ (initially unset)
`postheadhook`= $\langle code \rangle$ (initially unset)
`prefoothook`= $\langle code \rangle$ (initially unset)
`postfoothook`= $\langle code \rangle$ (initially unset)

Details in section 6.

<pre> % preamble \newkeytheorem{test}[preheadhook=PREHEAD, postheadhook=POSTHEAD, prefoothook=PREFOOT, postfoothook=POSTFOOT] % document \begin{test} Some text \end{test} </pre>	<p>PREHEAD</p> <p>Test 1. <i>POSTHEAD</i>Some text <i>PREFOOT</i></p> <p>POSTFOOT</p>
--	--

`refname`= $\langle ref\ name \rangle$ or $\{ \langle singular\ name \rangle, \langle plural\ name \rangle \}$ (initially $\langle display\ name \rangle$)

If a single string, then the name used by `hyperref`'s `\autoref` and `cleveref`'s `\cref`. If two strings separated by a comma, then the second string is the plural form used by `\cref`.

`Refname`= $\langle ref\ name \rangle$ or $\{ \langle singular\ name \rangle, \langle plural\ name \rangle \}$ (initially $\langle display\ name \rangle$)

Same as `refname` but for `\Autoref` (not yet implemented!) and `\Cref`.

<pre> % preamble \newkeytheorem{prop}[name=Proposition, refname={proposition,propositions}, Refname={Proposition,Propositions}] % document \begin{prop}[label=abc] Some text \end{prop} \begin{prop}[label=def] Some more text \end{prop} \begin{theorem} Consider \cref{abc,def}. \end{theorem} </pre>	<p>Proposition 1. <i>Some text</i></p> <p>Proposition 2. <i>Some more text</i></p> <p>Theorem 8. <i>Consider propositions 1 and 2.</i></p>
--	---

`qed`= $\langle symbol \rangle$ (default `\openbox`, initially unset)

Adds $\langle symbol \rangle$ to the end of the theorem body. If no value is given, the symbol \square is used.

```

% preamble
\newkeytheorem{example}[qed]
\newkeytheorem{solution}[qed=$\clubsuit$]

% document
\begin{example}
Some text
\end{example}
\begin{solution}
Some more text
\end{solution}

```

Example 1. *Some text*



Solution 1. *Some more text*



3.3 Keys added by key-theorems

`tcolorbox={\langle tcolorbox options \rangle}` (initially unset)

This key specifies that the theorem be placed inside a `tcolorbox` environment with `\langle options \rangle`.

```

% preamble
\tcbset{
  defstyle/.style={
    arc=0mm,
    colback=blue!5!white,
    colframe=blue!75!black
  },
}
\newkeytheorem{corollary}[tcolorbox]
\newkeytheorem{definition}[
  style=definition,
  tcolorbox={defstyle}
]

% document
\begin{corollary}
Some text
\end{corollary}
\begin{definition}
Some more text
\end{definition}

```

Corollary 1.

Some text

Definition 1.

Some more text

4 Theorem Styles

`\newkeytheoremstyle{\langle name \rangle}{\langle options \rangle}`

This is key-theorems' version of `thmtools'` `\declaretheoremstyle[\langle options \rangle]{\langle name \rangle}`. Since it makes little sense to define a style with no keys, we've made the `\langle options \rangle` argument mandatory.

4.1 Keys inherited from `thmtools`

The following keys have the same meaning and syntax as the corresponding `thmtools` keys.

`spaceabove=\langle length \rangle` (initially `\topsep`)

`spacebelow=\langle length \rangle` (initially `\topsep`)

`bodyfont=\langle font declarations \rangle` (initially `\itshape`)

`headindent=\langle length \rangle` (initially `0pt`)

`headfont=\langle font declarations \rangle` (initially `\bfseries`)

`ignore={⟨comma-list of env names⟩}` (initially unset)

`show={⟨comma-list of env names⟩}` (initially all theorems)

`onlynamed={⟨comma-list of env names⟩}` (initially unset)

`ignoreall` (initially unset)

<pre> \listofkeytheorems[ignoreall,show=theorem] \listofkeytheorems[ignoreall, show=conjecture, title=List of Conjectures] </pre>	<div> <div>List of Theorems</div> <div> 1 Theorem 1 2 Theorem (some heading) . . . 2 3 Theorem (some heading) . . . 2 4 Theorem (another heading) . 2 5 Theorem 2 5 Theorem (continuing from p. 2) 2 6 Theorem 2 8 Theorem 4 </div> </div> <div> <div>List of Conjectures</div> <div> 3.1 Conjecture 3 </div> </div>
---	--

`showall` (initially set)

`title=⟨text⟩` (initially List of Theorems)

`swapnumber=true|false` (initially false)

5.2 Keys added by key-theorems

`title-code=⟨code with #1⟩` (initially `\section*{#1}`)

If `\chapter` is defined, then initially this is instead `\chapter*{#1}`.

`no-title` (initially unset)

Suppresses the title of the list of theorems. Useful for custom ordering of the list.

<pre> \keytheoremset{ignoreall} \listofkeytheorems[show=example] \listofkeytheorems[show=solution,no-title] </pre>	<div> <div>List of Theorems</div> <div> 1 Example 4 1 Solution 4 </div> </div>
--	---


`print-body` (initially unset)

Instead of listing the theorem headings, the theorems are restated with their body text. Requires the `store-all`^{P. 1} load-time option to be useful.

6 Theorem Hooks

`\addtotheoremhook[⟨env name⟩]{⟨hook name⟩}{⟨code⟩}`

`⟨hook name⟩` can be `prehead`, `posthead`, `prefoot`, or `postfoot`. If no `⟨env name⟩` is given, the `⟨code⟩` is added to the “generic” hook, i.e. applied to all theorems. As in `thmtools`, the order of hooks is as follows:



In thmtools, the `prefoot` and `postfoot` hooks always prepend code, i.e. the code

```

\addtotheoremhook{A}
\addtotheoremhook{B}

```

results in BA after the theorem. With key-theorems, code is added in the order declared, meaning

```

\addtotheoremhook{postfoot}{A}
\addtotheoremhook{postfoot}{B}

```

results in AB after the theorem. This is the behavior of the \LaTeX kernel hooks that `key-theorems` uses under the hood.

Right now, code added using the hook keys `preheadhook`^{P. 4}, etc. is outermost, meaning executed first in `prehead` and `posthead` and last in `prefoot` and `postfoot`. This may change if I think of good reasons to do so...

Index

`\addtotheoremhook`, 7

bodyfont key, 5

break key, 6

Commands

- `\addtotheoremhook`, 7
- `\declaretheorem`, 1
- `\declaretheoremstyle`, 1
- `\keytheoremlistset`, 6
- `\keytheoremset`, 1
- `\listofkeytheorems`, 1
- `\listoftheorems`, 1
- `\NAME`, 6
- `\newkeytheorem`, 1
- `\newkeytheoremstyle`, 5
- `\NOTE`, 6
- `\NUMBER`, 6

continues key, 2

continues-code key, 1

`\declaretheorem`, 1

`\declaretheoremstyle`, 1

definition value, 3, 6

Environments

- restatable, 1

headfont key, 5

headindent key, 5

heading key, 3

headpunct key, 6

headstyle key, 6

ignore key, 7

ignoreall key, 7

inherit-style key, 6

Keys

- bodyfont, 5
- break, 6
- continues, 2
- continues-code, 1
- headfont, 5
- headindent, 5
- heading, 3
- headpunct, 6
- headstyle, 6
- ignore, 7
- ignoreall, 7
- inherit-style, 6
- label, 2
- name, 2, 3
- no-title, 7
- note, 2
- notebraces, 6
- notefont, 6
- numbered, 3
- numberlike, 3
- numberwithin, 3
- numwidth, 6

onlynamed, 7

overload, 1

parent, 3

postfoothook, 4

postheadhook, 4

postheadspace, 6

prefoothook, 4

preheadhook, 4

print-body, 7

qed, 4

qed-symbol, 1

Refname, 4

refname, 4

restate, 2

restate-counters, 1

sharenumber, 3

show, 7

showall, 7

sibling, 3

spaceabove, 5

spacebelow, 5

store, 2

store-all, 1

style, 3

swapnumber, 7

tcolorbox, 5

thmtools-compatible, 1

title, 3, 7

title-code, 7

within, 3

`\keytheoremlistset`, 6

`\keytheoremset`, 1

label key, 2

`\listofkeytheorems`, 6

`\listoftheorems`, 1

margin value, 6

`\NAME`, 6

name key, 2, 3

`\newkeytheorem`, 1

`\newkeytheoremstyle`, 5

no-title key, 7

`\NOTE`, 6

note key, 2

notebraces key, 6

notefont key, 6

`\NUMBER`, 6

numbered key, 3

numberlike key, 3

numberwithin key, 3

numwidth key, 6

onlynamed key, 7

overload key, 1

parent key, 3

plain value, 3, 6

postfoothook key, 4

postheadhook key, 4

- postheadspace key, 6
- prefoothook key, 4
- preheadhook key, 4
- print-body key, 7
- qed key, 4
- qed-symbol key, 1
- Refname key, 4
- refname key, 4
- remark value, 3, 6
- restatable environment, 1
- restate key, 2
- restate-counters key, 1
- sharenumber key, 3
- show key, 7
- showall key, 7
- sibling key, 3
- spaceabove key, 5
- spacebelow key, 5
- store key, 2
- store-all key, 1
- style key, 3
- swapnumber key, 7
- swapnumber value, 6
- tcolorbox key, 5
- thmtools-compat key, 1
- title key, 3, 7
- title-code key, 7
- Values
 - definition, 3, 6
 - margin, 6
 - plain, 3, 6
 - remark, 3, 6
 - swapnumber, 6
- within key, 3