

keytheorems package

version 0.1.6dev

github.com/mbertucci47/keytheorems

Matthew Bertucci

October 4, 2024

Abstract

An `expl3`-implementation of a key-value interface to `amsthm`, implementing most of the functionality provided by `thmtools`. Several issues encountered with `thmtools` are avoided (see the README for a list) and a few new features are added.

Contents

1	Dependencies	1
2	Global options	2
2.1	Compatibility options	2
2.2	Other global options	2
3	Defining theorems	3
3.1	Keys available to theorem environments	3
3.2	Keys also defined in <code>thmtools</code>	5
3.3	Keys added by <code>keytheorems</code>	7
4	Theorem styles	9
4.1	Keys also defined in <code>thmtools</code>	9
4.2	Keys added by <code>keytheorems</code>	10
5	Restating theorems	10
6	Listing theorems	11
6.1	Keys inherited from <code>thmtools</code>	11
6.2	Keys added by <code>keytheorems</code>	12
6.3	Adding code to list of theorems	13
7	Theorem hooks	13
8	Miscellaneous notes	14
8.1	<code>beamer</code> support	14
8.2	Public coding interfaces	14
9	Further examples	14
	Index	15

1 Dependencies

Without using the `tcolorbox`^{P.7} or `tcolorbox-no-titlebar`^{P.8} options, the package loads the `aliascnt`, `amsthm`, `refcount`, `translations`, and `unique` packages. A \LaTeX kernel no older than 2023-06-01 is required; if older than 2024-06-01, `nameref` is required.

2 Global options

`\keytheoremset{⟨options⟩}`

Every key in this section can be given as an option to `\usepackage` or in `\keytheoremset`, with the exception that `continues-code` can only be used in the latter.

2.1 Compatibility options

`overload` (initially unset)

Redefines `\newtheorem` to internally use the `keytheorems` machinery. The syntax remains the same. This is automatically set by `thmtools-compat`.

`thmtools-compat` (initially unset)

For compatibility with `thmtools` syntax. For most documents,

```
\usepackage[thmtools-compat]{keytheorems}
```

should be a drop-in replacement for `\usepackage{amsthm,thmtools}`. The option defines the commands in the left column below. The right column lists the corresponding `keytheorems` replacement that should be used in new documents.

thmtools command		keytheorems replacement
<code>\declaretheorem</code>	→	<code>\newkeytheorem^{→P.3}</code>
<code>\declaretheoremstyle</code>	→	<code>\newkeytheoremstyle^{→P.9}</code>
<code>\listoftheorems</code>	→	<code>\listofkeytheorems^{→P.11}</code>
<code>\listtheoremname</code>	→	<code>title^{→P.12} key</code>
<code>\addtotheoremheadhook</code>		
<code>\addtotheoremheadhook</code>	→	<code>\addtotheoremhook^{→P.13}</code>
<code>\addtotheoremheadhook</code>		
<code>\addtotheoremheadhook</code>		
<code>restatable</code> environment	→	<code>store^{→P.4} key</code>
<code>restatable*</code> environment	→	<code>store*^{→P.4} key</code>

Also defined are the `shaded` and `thmbox` keys, implemented internally with `tcolorbox` rather than the `shadethm` and `thmbox` packages, respectively.

2.2 Other global options

`auto-translate=true|false` (default `true`, initially `true`)

If `false`, `keytheorems` does not automatically translate the title text for `\listofkeytheorems→P.11` and the note produced by the `continues→P.4` key. These texts can be manually customized with the `title→P.12` and `continues-code` keys, respectively.

`continues-code=⟨code with #1⟩` (initially `\GetTranslation{keythms_continues}\pageref{#1}`)

The code used to typeset the note produced by the `continues→P.4` key. If English or an unknown language is used, defaults to `continuing from p.\, \pageref{#1}`. Currently (likely inaccurate!) translations exist for French, German, Italian, Portuguese, and Spanish.

`qed-symbol=⟨symbol⟩` (initially `\openbox`)

Redefines `\qedsymbol` to be `⟨symbol⟩`.

`restate-counters={⟨comma-list of counters⟩}` (initially `{equation}`)

Additional counters whose values are preserved when a theorem is restated. This key does not reset the list, so you don't need to include `equation` in `⟨comma-list⟩`.

`store-all` (initially unset)

Tells `keytheorems` to grab the body of each theorem so it can later be printed with the `print-body→P.13` option of `\listofkeytheorems→P.11`. Note that this means a theorem body *cannot* contain verbatim material.

`store-sets-label` (initially unset)
 Defines the `store`^{P.4} key to also set `label`^{P.3}, i.e. it makes `store=<tag>` equivalent to `store=<tag>,label=<tag>`. Similarly for `store*`^{P.4}.

3 Defining theorems

`\newkeytheorem{<env name>}[<options>]`

Defines a theorem environment `<env name>` which itself takes a few options (see subsection 3.1). You can also declare multiple theorems at once by replacing `<env name>` with a comma-list of names, e.g. `\newkeytheorem{theorem,lemma,proposition}[<options>]`.

By default, the theorem's printed name is a title-cased `<env name>`. This can be changed with the `name`^{P.5} key. All `<options>` are described in subsections 3.2 and 3.3.

```
% preamble
\newkeytheorem{theorem}

% document
\begin{theorem}
Some text
\end{theorem}
```

Theorem 1. *Some text*

`\renewkeytheorem{<env name>}[<options>]`
`\providekeytheorem{<env name>}[<options>]`
`\declarekeytheorem{<env name>}[<options>]`

Sometimes a package or class defines theorems that need to be overwritten by the user. For this case, `keytheorems` provides `\renewkeytheorem` which redefines `<env name>` or errors if it is not defined. For completeness, also provided are `\providekeytheorem` and `\declarekeytheorem`. The former only defines `<env name>` if it is not already defined; the latter always overwrites `<env name>`.

3.1 Keys available to theorem environments

As in `amsthm`, theorems can take an optional argument that contains a note or heading.

```
\begin{theorem}[some heading]
Some text
\end{theorem}
```

Theorem 2 (some heading). *Some text*

Alternatively, the optional argument may contain any of the following keys.

`note=<text>` (initially unset)

Alias `name`. This is the key-value equivalent of the optional argument described above. This syntax, however, allows the argument to contain other keys.

```
\begin{theorem}[some heading]
Some text
\end{theorem}
\begin{theorem}[note=another heading]
Some more text
\end{theorem}
```

Theorem 3 (some heading). *Some text*

Theorem 4 (another heading). *Some more text*

`short-note=<text>` (initially unset)

Alias `short-name`. This replaces the value of `note` when displayed in `\listofkeytheorems`^{P.11}.

`label=<label name>` (initially unset)

This is the key-value equivalent of `\begin{theorem} \label{<label name>}`.

```
\begin{theorem}[label=foo]
Some text
\end{theorem}
\ref{foo}
```

Theorem 5. *Some text*

5

continues*= $\langle label\ name \rangle$ (initially unset)

Pick up a theorem where you left off. The theorem number remains the same. The printed text can be customized with the `continues-code`^{P.2} option. The starred version also copies the theorem note, if it exists.

```
\begin{theorem}[continues=foo]
\dots and some more text.
\end{theorem}
```

Theorem 5 (continuing from p.4). *...and some more text.*

store*= $\langle tag \rangle$ (initially unset)

Alias `restate*`. Stores the the theorem to be restated at any point in the document with `\getkeytheorem`^{P.10}. With the starred version, counters and labels are taken from the copy called with `\getkeytheorem`, so in this case can only be restated once. This allows you, for example, to write all theorems and proofs in the appendix and call `\getkeytheorem` at the appropriate time mid-document. For the numbering to be correct, the unstarred key will need at most two runs and the starred key at most three runs.

```
\begin{theorem}[store=blub]
A theorem worth restating.
\end{theorem}
More brilliant mathematics.
\getkeytheorem{blub}
```

Theorem 6. *A theorem worth restating.*

More brilliant mathematics.

Theorem 6. *A theorem worth restating.*

A theorem given this key *cannot* contain verbatim material or other unexpected catcodes, such as a `tikz-cd` diagram. The latter issue can be averted with the `ampersand-replacement` key.

```
% preamble
\usepackage{tikz}
\usetikzlibrary{cd}

% document
\begin{lemma}[store=diagram]
Some commutative diagram:
\[\begin{tikzcd}[ampersand
\& replacement=\&]
X\times_S Y \ar[r] \ar[d] \& X \ar[d]
Y \ar[r] \& S
\end{tikzcd}\]
\end{lemma}
\dots
\getkeytheorem{diagram}
```

Lemma 7. *Some commutative diagram:*

$$\begin{array}{ccc} X \times_S Y & \longrightarrow & X \\ \downarrow & & \downarrow \\ Y & \longrightarrow & S \end{array}$$

...

Lemma 7. *Some commutative diagram:*

$$\begin{array}{ccc} X \times_S Y & \longrightarrow & X \\ \downarrow & & \downarrow \\ Y & \longrightarrow & S \end{array}$$

restate-keys= $\{\langle list\ of\ keys \rangle\}$ (initially unset)

Allows passing different keys to the restated theorem. At the moment this is only useful with the `note`^{P.3} key.

```

\begin{theorem}[
  store=rktest,
  note=ORIGINAL,
  restate-keys={note=RESTATED}]
Wow, yet another theorem.
\end{theorem}
\getkeytheorem{rktest}

```

Theorem 8 (ORIGINAL). *Wow, yet another theorem.*

Theorem 8 (RESTATED). *Wow, yet another theorem.*

`listhack=true|false`

(initially false)

Meant only to be used with the `break→P.9` style key for a theorem starting with a list. Compare:

```

% preamble
\newkeytheoremstyle{breaksty}{break}
\newkeytheorem{observation}[style=breaksty]

% document
\begin{observation}
\begin{enumerate}
\item First item
\end{enumerate}
\end{observation}

\begin{observation}[listhack=true]
\begin{enumerate}
\item First item
\end{enumerate}
\end{observation}

```

Observation 1. *1. First item*

Observation 2.

1. First item

Note that the value `true` must be explicitly set so that `listhack` is not interpreted as the note text.

`seq=<name>`

(initially unset)

Adds the theorem to a custom sequence `<name>` that can then be listed with `\listofkeytheorems[seq=<name>]`. See `seq→P.13` for more details.

3.2 Keys also defined in thmtools

These are the [`<options>`] available to `\newkeytheorem`. Except for `name` and `style→P.6`, each key below can also be used in `\newkeytheoremstyle→P.9`. For more description, see the `thmtools` package.

`name=<display name>`

(initially title-cased `<env name>`)

Aliases `heading` and `title`.

```

% preamble
\newkeytheorem{mythm}[name=Some Name]

% document
\begin{mythm}
Some text
\end{mythm}

```

Some Name 1. *Some text*

`numbered=true|false|unless-unique`

(default `true`, initially `true`)

For compatibility with `thmtools`, also accepts the values `yes`, `no`, and `unless unique`.

```
% preamble
\newkeytheorem{theorem}[
  name=Theorem, numbered=false
]

% document
\begin{theorem*}
An unnumbered theorem.
\end{theorem*}
```

Theorem. *An unnumbered theorem.*

parent= $\langle counter \rangle$ (initially unset)

Aliases **numberwithin** and **within**.

```
% preamble
\newkeytheorem{conjecture}[parent=section]

% document
\begin{conjecture}
The first number is the section.
\end{conjecture}
```

Conjecture 3.1. *The first number is the section.*

sibling= $\langle counter \rangle$ (initially unset)

Aliases **numberlike** and **sharenumber**.

```
% preamble
\newkeytheorem{lemma}[sibling=theorem]

% document
\begin{lemma}
This shares its counter with
\texttt{theorem}.
\end{lemma}
```

Lemma 9. *This shares its counter with theorem.*

style= $\langle style name \rangle$ (initially unset)

Accepts any $\langle style name \rangle$ defined by `\newkeytheoremstyleP.9`, as well as any of the predefined amsthm styles: **plain**, **definition**, and **remark**.

```
% preamble
\newkeytheorem{remark}[style=remark]

% document
\begin{remark}
Some text
\end{remark}
```

Remark 1. Some text

preheadhook= $\langle code \rangle$ (initially unset)

postheadhook= $\langle code \rangle$ (initially unset)

prefoothook= $\langle code \rangle$ (initially unset)

postfoothook= $\langle code \rangle$ (initially unset)

Details in [section 7](#).

```

% preamble
\newkeytheorem{test}[
  preheadhook=PREHEAD,
  postheadhook=POSTHEAD,
  prefoothook=PREFOOT,
  postfoothook=POSTFOOT
]

% document
\begin{test}
Some text
\end{test}

```

PREHEAD

Test 1. *POSTHEAD*Some text *PREFOOT*

POSTFOOT

`qed=<symbol>`

(default `\openbox`, initially unset)

Adds `<symbol>` to the end of the theorem body. If no value is given, the symbol \square is used.

```

% preamble
\newkeytheorem{example}[qed]
\newkeytheorem{solution}[qed=${\clubsuit}]

% document
\begin{example}
Some text
\end{example}
\begin{solution}
Some more text
\end{solution}

```

Example 1. *Some text*

\square

Solution 1. *Some more text*

\clubsuit

`refname=<ref name> or {<singular name>,<plural name>}`

(initially `<display name>`)

If a single string, then the name used by `\autoref` and `\cleveref`'s `\cref`. If two strings separated by a comma, then the second string is the plural form used by `\cref`.

`Refname=<ref name> or {<singular name>,<plural name>}`

(initially `<display name>`)

Same as `refname` but for `\Autoref` and `\Cref`. Note that `\Autoref` is defined by `keytheorems`, but requires `hyperref` to work. As with `\autoref`, there is also a starred version `\Autoref*` that suppresses the hyperlink.

```

% preamble
\newkeytheorem{prop}[
  name=Proposition,
  refname={proposition,propositions},
  Refname={Proposition,Propositions}
]

% document
\begin{prop}[label=abc]
Some text
\end{prop}
\begin{prop}[label=def]
Some more text
\end{prop}
\begin{theorem}
Consider \cref{abc,def}.
\Autoref{abc} \dots
\end{theorem}

```

Proposition 1. *Some text*

Proposition 2. *Some more text*

Theorem 10. Consider *propositions 1 and 2. Proposition 1 ...*

3.3 Keys added by `keytheorems`


`tcolorbox={<tcolorbox options>}`

(initially unset)

This key specifies that the theorem be placed inside a tcolorbox environment with `<options>`. The theorem head is typeset as a tcolorbox title; to avoid this see `tcolorbox-no-titlebar`^{P.8}.

```
% preamble
\tcbset{
  defstyle/.style={
    arc=0mm,
    colback=blue!5!white,
    colframe=blue!75!black
  },
}
\newkeytheorem{corollary}[tcolorbox]
\newkeytheorem{definition}[
  style=definition,
  tcolorbox={defstyle}
]

% document
\begin{corollary}
Some text
\end{corollary}
\begin{definition}[A nice definition]
Some more text
\end{definition}
```



`tcolorbox-no-titlebar={<tcolorbox options>}` (initially unset)

Same usage as `tcolorbox`^{P.7} but the theorem head is typeset as usual, not as a tcolorbox title.

```
% preamble
\newkeytheorem{boxcor}[
  tcolorbox-no-titlebar={
    colback=red!10
  },
  name=Corollary,sibling=corollary
]

% document
\begin{boxcor}
Some text
\end{boxcor}
```



tcolorbox offers its own comprehensive `theorems` library. If all of your theorems are to be tcolorboxes, I highly recommend using it instead of this package! However, if only some of your theorems will use a tcolorbox, you may want to replicate the styles of `\NewTcbTheorem`. Here is an example that emulates tcolorbox's standard theorem style.


```

% preamble
\tcbset{
  thmstyle/.style={
    colback=green!5,
    colframe=green!35!black},
  }
\newkeytheoremstyle{tcb-standard}{
  tcolorbox=thmstyle,
  headpunct={},
  notebraces={}{},
  noteseparator={: },
  notefont=\bfseries,
  bodyfont=\normalfont,
  }
\newkeytheorem{mytheo}[
  name=My Theorem,
  style=tcb-standard]

% document
\begin{mytheo}[This is my title]
Some theorem text
\end{mytheo}

```

My Theorem 1: This is my title

Some theorem text

4 Theorem styles

`\newkeytheoremstyle{<name>}{<options>}`

This is `keytheorems'` version of `thmtools'` `\declaretheoremstyle[<options>]{<name>}`. Since it makes little sense to define a style with no keys, we've made the `<options>` argument mandatory. Note that unlike `amsthm's` `\newtheoremstyle`, this command will error if a style has already been defined. To overwrite an existing style, there is the analogous `\renewkeytheoremstyle`. For completeness, there are also `\providekeytheoremstyle` and `\declarekeytheoremstyle`.

The defined style can be used with either the `style`^{P.6} key or the traditional `\theoremstyle`.



For the AMS classes `amsart`, `amsbook`, and `amspoc`, as well as the `amsart`-based `acmart`, the initial key values are slightly different than what's below in order to match those class's defaults.

4.1 Keys also defined in `thmtools`

The following keys have the same meaning and syntax as the corresponding `thmtools` keys. In addition to the list below, most of the keys available to `\newkeytheorem`^{P.3} can be used in `\newkeytheoremstyle`.

`bodyfont`=`` (initially `\itshape`)

`break` (initially unset)

Do not use this with the `postheadspace`^{P.10} key.

`headfont`=`` (initially `\bfseries`)

`headformat`=`margin|swapnumber|<code using \NAME, \NUMBER, and \NOTE>`

Alias `headstyle`. Within `<code>`, the commands `\NAME`, `\NUMBER`, and `\NOTE` correspond to the formatted parts of the theorem head.



In `headformat`, you may also use the traditional `amsthm` commands `\thmname`, `\thmnumber`, and `\thmnote`, where #1 is the theorem name, #2 the number, and #3 the note. `keytheorems` expands the head spec inside `\text_expand:n` so for these commands to work properly, the package adds them to `\l_text_expand_exclude_tl`. Note also that if you use these lower-level commands, the style keys `notebraces`^{P.10}, `notefont`^{P.10}, `noteseparator`^{P.10}, and `numberfont`^{P.10} will have no effect (of course, you can manually control these things inside the commands' arguments).

headindent= $\langle length \rangle$ (initially 0pt)

headpunct= $\langle code \rangle$ (initially {.})

notebraces= $\{\langle left\ brace \rangle\}\{\langle right\ brace \rangle\}$ (initially {\{ }})

notefont= $\langle font\ declarations \rangle$ (initially \fontseries\mddefault\upshape)

postheadspace= $\langle length \rangle$ (initially 5pt plus 1pt minus 1pt)

Do not use this with the **break**^{P.9} key.

spaceabove= $\langle length \rangle$ (initially \topsep)

spacebelow= $\langle length \rangle$ (initially \topsep)

4.2 Keys added by keytheorems

inherit-style= $\langle style\ name \rangle$ (initially unset)

Inherit the keys of any style declared with **\newkeytheoremstyle**^{P.9}. Additionally, the three styles predefined by amsthm are possible values: **plain**, **definition**, and **remark**.

noteseparator= $\langle code \rangle$ (initially \square)

The code inserted before the note, and printed only if there is a note. This is executed *before* the font commands set by **notefont** take effect.

numberfont= $\langle font\ declarations \rangle$ (initially)

For almost all theorem styles, it is recommended that you *do not* change this setting.

5 Restating theorems

When a theorem is given the **store**^{P.4} key, the contents of the theorem are saved and written to a .thlist file. At the start of the next run, this file is input at the beginning of the document and allows you to retrieve the stored theorems at any point, before or after the original theorem.

\getkeytheorem $[\langle property \rangle]\{\langle tag \rangle\}$

Retrieves the theorem given the key **store**= $\langle tag \rangle$ or **store***= $\langle tag \rangle$. An optional $\langle property \rangle$ can be given to retrieve only the corresponding part of the theorem. Currently only the property **body** is implemented, which retrieves the (unformatted) body of the theorem.

```
\getkeytheorem{mytag}
```

```
\begin{example}[store=mytag]
```

```
Fascinating example.
```

```
\end{example}
```

```
\getkeytheorem[body]{mytag}
```

Example 2. *Fascinating example.* \square

Example 2. *Fascinating example.* \square

Fascinating example.

\IfRestatingTF $\{\langle true\ code \rangle\}\{\langle false\ code \rangle\}$

\IfRestatingT $\{\langle true\ code \rangle\}$

\IfRestatingF $\{\langle false\ code \rangle\}$

Executes $\langle true\ code \rangle$ if being retrieved with **\getkeytheorem** and $\langle false\ code \rangle$ if in the original theorem. This is reversed if **store*** is used.

```

\begin{example}[store=hmm]
I am the
\IfRestatingTF{restated}{original}
example!
\end{example}

\getkeytheorem{hmm}

```

Example 3. *I am the original example!* ☐

Example 3. *I am the restated example!* ☐

6 Listing theorems

`\listofkeytheorems[<options>]`

Similar to `\listoffigures` or `\listoftables` but for theorems. For memoir and the AMS classes, keytheorems tries to copy the formatting of these commands as defined by the class. For other classes, manual adjustments to `numwidth`^{→P. 12} and `indent`^{→P. 12} may be necessary.

`\keytheoremset{<options>}`

`\listofkeytheorems`

List of Theorems

1	Theorem	3
2	Theorem (some heading)	3
3	Theorem (some heading)	3
4	Theorem (another heading) . .	3
5	Theorem	3
5	Theorem (continuing from p. 4)	4
6	Theorem	4
7	Lemma	4
8	Theorem (ORIGINAL)	4
1	Observation	5
2	Observation	5
1	Some Name	5
	Theorem	5
3.1	Conjecture	6
9	Lemma	6
1	Remark	6
1	Test	6
1	Example	7
1	Solution	7
1	Proposition	7
2	Proposition	7
10	Theorem	7
1	Corollary	7
1	Definition (A nice definition) .	7
2	Corollary	8
1	My Theorem (This is my title)	8
2	Example	10
3	Example	10

6.1 Keys inherited from thmtools

`ignore={<comma-list of env names>}` (initially unset)

`ignoreall` (initially unset)

```

\listofkeytheorems[ignoreall,show=theorem]
\listofkeytheorems[
  ignoreall, show=conjecture,
  title=List of Conjectures
]

```

List of Theorems

1	Theorem	3
2	Theorem (some heading) . . .	3
3	Theorem (some heading) . . .	3
4	Theorem (another heading) .	3
5	Theorem	3
5	Theorem (continuing from p. 4)	4
6	Theorem	4
8	Theorem (ORIGINAL)	4
10	Theorem	7

List of Conjectures

3.1	Conjecture	6
-----	----------------------	---

numwidth= $\langle length \rangle$ (initially 2.3em)

For the AMS classes, this is initially 1.5pc.

onlynamed= $\{\langle comma-list of env names \rangle\}$ (initially unset)

show= $\{\langle comma-list of env names \rangle\}$ (initially all theorems)

showall (initially set)

swapnumber=true|false (initially false)

title= $\langle text \rangle$ (initially `\GetTranslation{keythms_listof_title}`)

Defaults to “List of Theorems” if English or an unknown language is used. Currently French, German, Italian, Portuguese, and Spanish have (likely inaccurate!) translations. A translation can be added with a GitHub pull request or manually with

`\DeclareTranslation{ $\langle lang \rangle$ }{keythms_listof_title}{ $\langle text \rangle$ }.`

6.2 Keys added by keytheorems

format-code= $\langle code with \#1, \#2, and \#3 \rangle$ (initially `\numberline{#2}#1#3`)

Allows full control over the format for list entries. The theorem name is #1, the number is #2, and the (formatted) note is #3. The note formatting is still controlled by `note-code`^{P.13}.

indent= $\langle length \rangle$ (initially 1.5em)

Sets the left indent of items in the list of theorems. For memoir and the AMS classes, the indent is initially 0pt. It is not recommended to change this unless your class has different defaults not already covered.

no-chapter-skip=true|false (initially false)

By default a small vertical space is inserted between each chapter’s chunk of theorems. Setting this key to true removes this space.

chapter-skip-length= $\langle dimension \rangle$ (initially 10pt)

Controls the amount of space inserted between chunks.

no-continues=true|false (initially false)

Suppresses the printing of theorems given the `continues`^{P.4} key in the list of theorems.

`no-title=true|false` (initially false)

Suppresses the title of the list of theorems. Useful for custom ordering of the list.

```
\keytheoremset{ignoreall}
\listofkeytheorems[show=example]
\listofkeytheorems[show=solution,no-title]
```

List of Theorems

1	Example	7
2	Example	10
3	Example	10
1	Solution	7

`no-toc=true|false` (initially false)

With the standard classes, lists of figures/tables are not added to the table of contents by default. The same is true for `\listofkeytheorems`, and with those classes this key does nothing. However some classes, notably `memoir` and the AMS classes, do add lists to the table of contents. With these classes, this key suppresses the addition of the list of theorems to the table of contents.

`note-code=<code with #1>` (initially { (#1)})

Formats the optional note in the list of theorems.

`onlynumbered={<comma-list of env names>}` (initially unset)

Similar to `onlynamed`^{P.12}, but lists only those theorems which are numbered. This is useful if you'd like to exclude things like unnumbered definitions and remarks from the list of theorems.

`print-body` (initially unset)

Instead of listing the theorem headings, the theorems are restated with their body text. Not very useful without the `store-all`^{P.2} load-time option.

`seq=<name>` (initially unset)

Used to list only the theorems added to the custom sequence `<name>` with the `seq`^{P.5} theorem key. This is the only way to fully customize which theorems appear in the list of theorems. Unlike with `show`^{P.12}, you do not need to use `ignoreall`^{P.11} to prevent theorems not in `<name>` from being printed.

`title-code=<code with #1>` (initially `\section*{#1}`)

If `\chapter` is defined, then initially this is instead `\chapter*{#1}`. This key has no effect if used with an AMS class because these classes hard-code the section heading into `\@starttoc`.

6.3 Adding code to list of theorems

There are analogous commands to `\addcontentsline` and `\addtocontents` for adding entries or arbitrary code to the list of theorems.



You *must* use these commands rather than the aforementioned because the `.thlist` file is also used to define restated theorems and cannot contain unexpected code.


`\addtheoremcontentsline{<level>}{<text>}`

`\addtotheoremcontents{<code>}`

7 Theorem hooks

`\addtotheoremhook[<env name>]{<hook name>}{<code>}`

`<hook name>` can be `prehead`, `posthead`, `prefoot`, `postfoot`, or `restated`. If no `<env name>` is given, the `<code>` is added to the “generic” hook, i.e. applied to all theorems. As in `thmtools`, the order of hooks is as follows:



The `restated` hook is applied at the start of theorems retrieved with `\getkeytheorem`, before the `prehead` hook. This can be useful for disabling commands such as `\footnote` in the restated theorems, e.g.

```
\addtotheoremhook{restated}{\renewcommand\footnote[2] [] {}}
```

By default, `keytheorems` disables the `\label` and `\RecordProperties` commands in restated theorems.

In `thmtools`, the `prefoot` and `postfoot` hooks always prepend code, i.e. the code

```
\addtotheoremhook{postfoot}{A}
\addtotheoremhook{postfoot}{B}
```

results in BA after the theorem. With `keytheorems`, code is added in the order declared, meaning

```
\addtotheoremhook{postfoot}{A}
\addtotheoremhook{postfoot}{B}
```

results in AB after the theorem. This is the behavior of the \LaTeX kernel hooks that `keytheorems` uses under the hood.

Code added using the hook keys `preheadhook`^{P.6}, etc. is outermost, meaning executed first in `prehead` and `posthead` and last in `prefoot` and `postfoot`.

8 Miscellaneous notes

8.1 beamer support

The package contains some *highly experimental* code to support theorems with `beamer`, including overlays. Most style keys are disabled by the default `beamer` theorem template. More become functional by setting

```
\setbeamertheoremstyle{theorems}[ams style]
```

in the preamble. Alternatively, you have full control of theorems by setting the class option `noamsthm`.

Note that by default `beamer` defines a set of theorems when the class is loaded. These can be overwritten with `\renewkeytheorem`^{P.3} or disabled entirely with the `notheorems` class option.

Due to complications with overlays, writing contents of theorems to the `thlist` file is disabled. This means theorems can only be restated *after* their original statement. Furthermore, `\listofkeytheorems`^{P.11} is disabled and a warning issued if used.

User feedback is necessary to make this code fully compatible. Please report issues on the [Github page](#)!

8.2 Public coding interfaces

- `\l_keythms_thmuse_envname_tl`

Inside theorem environments, as well as in all of the theorem hooks, you have access to the theorem's environment and counter name in this token list variable.

9 Further examples

More examples will be added soon – rather, eventually... For now, you can find a `keytheorems` adaptation of `amsthm`'s classic file `thmtest.tex` in the Github `tests` folder: `keytheorems-amsthmtest.tex`.

Index

`\addtheoremcontentsline`, 13
`\addtotheoremcontents`, 13
`\addtotheoremhook`, 13
auto-translate key, 2
`\Autoref`, 7
`\Autoref*`, 7

bodyfont key, 9
break key, 9

chapter-skip-length key, 12
Commands
 `\addtheoremcontentsline`, 13
 `\addtotheoremcontents`, 13
 `\addtotheoremhook`, 13
 `\Autoref`, 7
 `\Autoref*`, 7
 `\declarekeytheorem`, 3
 `\declarekeytheoremstyle`, 9
 `\getkeytheorem`, 10
 `\IfRestatingF`, 10
 `\IfRestatingT`, 10
 `\IfRestatingTF`, 10
 `\keytheoremset`, 11
 `\keytheoremset`, 2
 `\listofkeytheorems`, 11
 `\NAME`, 9
 `\newkeytheorem`, 3
 `\newkeytheoremstyle`, 9
 `\NOTE`, 9
 `\NUMBER`, 9
 `\providekeytheorem`, 3
 `\providekeytheoremstyle`, 9
 `\renewkeytheorem`, 3
 `\renewkeytheoremstyle`, 9
continues key, 4
continues-code key, 2

`\declarekeytheorem`, 3
`\declarekeytheoremstyle`, 9
definition value, 6, 10

format-code key, 12

`\getkeytheorem`, 10

headfont key, 9
headformat key, 9
headindent key, 10
heading key, 5
headpunct key, 10
headstyle key, 9

`\IfRestatingF`, 10
`\IfRestatingT`, 10
`\IfRestatingTF`, 10
ignore key, 11
ignoreall key, 11
indent key, 12
inherit-style key, 10

Keys

auto-translate, 2
bodyfont, 9
break, 9
chapter-skip-length, 12
continues, 4
continues-code, 2
format-code, 12
headfont, 9
headformat, 9
headindent, 10
heading, 5
headpunct, 10
headstyle, 9
ignore, 11
ignoreall, 11
indent, 12
inherit-style, 10
label, 3
listhack, 5
name, 3, 5
no-chapter-skip, 12
no-continues, 12
no-title, 13
no-toc, 13
note, 3
note-code, 13
notebraces, 10
notefont, 10
noteseparator, 10
numbered, 5
numberfont, 10
numberlike, 6
numberwithin, 6
numwidth, 12
onlynamed, 12
onlynumbered, 13
overload, 2
parent, 6
postfoothook, 6
postheadhook, 6
postheadspace, 10
prefoothook, 6
preheadhook, 6
print-body, 13
qed, 7
qed-symbol, 2
Refname, 7
refname, 7
restate, 4
restate-counters, 2
restate-keys, 4
seq, 5, 13
sharenumber, 6
short-name, 3
short-note, 3
show, 12
showall, 12
sibling, 6
spaceabove, 10

- spacebelow, 10
- store, 4
- store-all, 2
- store-sets-label, 3
- style, 6
- swapnumber, 12
- tcolorbox, 7
- tcolorbox-no-titlebar, 8
- thmtools-compat, 2
- title, 5, 12
- title-code, 13
- within, 6
- \keytheoremset, 11
- \keytheoremset, 2
- label key, 3
- listhack key, 5
- \listofkeytheorems, 11
- margin value, 9
- \NAME, 9
- name key, 3, 5
- \newkeytheorem, 3
- \newkeytheoremstyle, 9
- no-chapter-skip key, 12
- no-continues key, 12
- no-title key, 13
- no-toc key, 13
- \NOTE, 9
- note key, 3
- note-code key, 13
- notebraces key, 10
- notefont key, 10
- noteseparator key, 10
- \NUMBER, 9
- numbered key, 5
- numberfont key, 10
- numberlike key, 6
- numberwithin key, 6
- numwidth key, 12
- onlynamed key, 12
- onlynumbered key, 13
- overload key, 2
- parent key, 6
- plain value, 6, 10
- postfoothook key, 6
- postheadhook key, 6
- postheadspace key, 10
- prefoothook key, 6
- preheadhook key, 6
- print-body key, 13
- \providekeytheorem, 3
- \providekeytheoremstyle, 9
- qed key, 7
- qed-symbol key, 2
- Refname key, 7
- refname key, 7
- remark value, 6, 10
- \renewkeytheorem, 3
- \renewkeytheoremstyle, 9
- restate key, 4
- restate-counters key, 2
- restate-keys key, 4
- seq key, 5, 13
- sharenumber key, 6
- short-name key, 3
- short-note key, 3
- show key, 12
- showall key, 12
- sibling key, 6
- spaceabove key, 10
- spacebelow key, 10
- store key, 4
- store-all key, 2
- store-sets-label key, 3
- style key, 6
- swapnumber key, 12
- swapnumber value, 9
- tcolorbox key, 7
- tcolorbox-no-titlebar key, 8
- thmtools-compat key, 2
- title key, 5, 12
- title-code key, 13
- unless-unique value, 5
- Values
 - definition, 6, 10
 - margin, 9
 - plain, 6, 10
 - remark, 6, 10
 - swapnumber, 9
 - unless-unique, 5
- within key, 6