

Vibe Coding & Secure Swarm Prototyping


The architectural blueprint for agentic software development, multi-agent orchestration, and autonomous vulnerability remediation.






Character-by-character
syntax generation.

Build a
secure auth
middleware...



Developer shifts to describing intent,
reviewing output, and conversational iteration.

Instead of writing code character by character, you converse with an AI to produce working software. — Andrej Karpathy (2025)


Natural Language First
Translate plain English specs into complex code.
Intent Over Syntax
Focus shifts from how to write it to what it should do and why.
Human as Architect
AI as Pair Programmer
Always-available partner with vast, cross-stack recall.
Conversational Iteration
Prompt → Generate → Review → Refine
Vibe coding amplifies expertise. The best vibe coders know exactly what to ask for, how to evaluate the output, and when to intervene.

Full Autopilot (Very High Risk)



- Throwaway prototypes, hackathons, scripts
- Maximum speed, maximum risk
- Generates hidden technical debt

Collaborative Mode (Moderate Risk)

- Feature development, startup MVPs
- Human reviews every block and steers architecture

Human-Led + AI Assist (Low Risk)




- Production systems, security-critical code
- Regulated industries

Karpathy's Warning: Vibe coding in its purest form is not for production systems without strict sandboxes and verification gates.

1. Describe

Natural-language prompt defining features constraints.



2. Generate

AI produces architecture and core components.



3. Review

Human reads, tests, and evaluates the diff.




4. Refine

Follow-up prompts to fix edge cases and refactor.



5. Ship

Integrate, run security gates, document, deploy.




Vibe Coding




Scale & Orchestrate

Swarm Prototyping




Swarm Prototyping is A/B testing during development. Spawn multiple agents to build competing architectures in parallel, evaluate objectively, and select the winner.

Parallel Execution	Diverge-then-Converge	Agent Specialization	Disposable Outputs


Orchestrator Agent
Decomposes tasks, provisions isolated workspaces, and assigns work.
Worker Agents
Specialized execution across decoupled micro-domains.
UI Builder
API Implementer
PyTest Author
Critic / Evaluator Agent
Reviews outputs, runs security/unit suites, scores quality, ranks variants.
Merger Agent
Integrates winning branches into a cohesive, conflict-free codebase.

Fan-Out / Fan-In




Map-reduce for code. Split large tasks, merge results.

Tournament




N agents compete on the exact same spec.
Critic picks the deterministic winner.

Pipeline



Sequential quality stages
(Design → Implement → Test & Harden).

Specialization Grid



Decoupled micro-domains against a shared contract.

When to Swarm



- Exploring architectural approaches
- Building PoCs under time pressure
- Decoupled microservices
- Benchmarking algorithms

Condition: Requires an automated test/eval harness to score outputs.

When NOT to Swarm (Sequential Mode)




- Tightly coupled legacy systems
- Regulated / compliance-critical production code
- Projects requiring deep proprietary context


Condition: When merge and integration costs exceed generation savings.

Vibe Coding vs. Swarm Prototyping: A Comparison

Dimension	Vibe Coding	Swarm Prototyping
Agents	1 Human : 1 Agent	1 Human : N Agents
Workflow	Conversational, sequential	Parallel, diverge-then-converge
Speed	Fast for focused tasks	Faster for broad exploration
Setup Complexity	Low setup, immediate	Higher setup (worktrees, orchestration)
Token Cost	Low (single session)	~4x–15x multiplier across N workers
Best For	Features, bug fixes, refactors	Architecture tournaments, parallel microservices


Line 1: Vibe Coding Surfaces
Google Antigravity
Claude Code
Gemini Code Assist
High-performing teams combine Swarm Prototyping for ambiguous design sprints and Vibe Coding for day-to-day feature delivery.
OpenAI Swarm
LangGraph
CrewAI
Line 3: Managed Enterprise Platforms
Vertex AI Agent Builder
Amazon Bedrock Agents
Amazon Bedrock Agents
Cursor
Line2: Multi-Agent Frameworks
OpenAI Swarm
Google ADK
Claude Agent SDK
GitHub Copilot

The Dark Side of AI Coding



The "It Works" Trap

Code demos cleanly locally but hides race conditions or injection flaws.

Cargo Cult Coding

Accepting AI output without understanding the underlying logic.

Slopsquatting & Hallucinations

AI invents fake SDK methods; attackers register them on PyPI/npm.

Context Rot

Dumping massive repositories into one chat degrades LLM attention, causing contradictory edits.

Hidden Tech Debt


Duplicated, imperative glue code that silently erodes modularity.

Security Blind Spots

Unchecked SQL injection, SSRF, and hardcoded credentials.

Production Readiness Guardrails

- [✓] Review: Every line of AI-generated code is read and understood by a human.
- [✓] Test First: Unit and integration tests cover critical paths alongside specifications.
- [✓] Scan: SAST and secret detection passes with zero injection vectors.
- [✓] Dependencies: All imported packages exist at approved, vulnerability-free versions.
- [✓] Architecture: Intent documented via ADR so engineers can maintain the service.
- [✓] Performance: Load-tested under p95/p99 concurrency (AI optimizes for plausibility, not latency).
- [✓] Provenance: Intellectual property and copyleft policies rigorously verified.



Workspace='branch' (Isolated Git Worktrees)



Configuration

`Antigravity:`	`invoke_subagent(Workspace='branch')`
`Claude Code:`	`claude -w <name>`


Never run a swarm in a single working directory. Always isolate workers in Git worktrees to prevent state corruption without duplicating disk space.

Cloud Workstations & VPC-SC

VPC Service Controls (VPC-SC) Perimeter. Blocks data exfiltration.

Google Cloud Workstation
(Private Cluster)

constraints/compute.vmExternalIpAccess
(Zero Public IP)




Problem: Standard 2-hour idle timeouts kill active 3-hour background agent builds.

Solution: Configure `idleAction=SUSPEND` and deploy `/google/scripts/keep_alive.sh` to detect active agent PIDs. VM hibernates to disk only when truly idle, preserving RAM state.

Agent Sandbox on GKE



Summary Matrix: Enterprise Sandboxing



The Bottleneck Funnel



Google AI Threat Defense Lifecycle

Prepare
SAIF policies, locked registries, VPC-SC.

Scan & Prioritize
SCC + Wiz Security Graph correlating vulnerabilities to real cloud runtime exposure.

Remediate
Dispatch CodeMender for PoC-verified autonomous patches.

Monitor
Model Armor & Cloud Audit Logs (is_agentic=true).

Inside CodeMender - Hybrid Architecture



Developer



CI runner

Local CLI Client (`cm`)

- Explicit file scoping (`scan.extensions.include`)
- Local compiler toolchain integration
- Local process sandbox execution
- Supports C/C++, Java, Go, JS/TS, Python, Rust





Hosted Multi-Agent Reasoning Service


- Gemini reasoning agents hypothesize root causes
- Designs precise exploit payloads
- Runs LLM-as-judge patch critiques

The CodeMender Workflow



Mandatory Sandbox Execution: `cm verify` and `cm fix` execute live exploit payloads. Always run inside an isolated CI container or **gVisor** sandbox.

The Complete Agentic Architecture



Architectural Axioms Manifesto

1. **Scale Exploration, Not Just Typing:** Use Swarm Prototyping to benchmark architectures rapidly, isolating Git worktrees.

2. **Assume It's Broken Until Proven Secure:** Defeat the 'It Works' trap through mandatory testing and CodeMender exploit verification.

3. **Defense-in-Depth Sandboxing is Non-Negotiable:** Untrusted execution demands nested isolation (terminal -> GKE gVisor).

4. **Pause, Don't Purge:** Protect long-horizon agent builds with idleAction=SUSPEND.

5. **The Human is the Ultimate Architect:** As AI writes syntax, human engineers rigorously enforce boundaries and production quality gates.