AgentOps: Evals, Observability & Cost by Michaël Bettan

Definition: AgentOps (AI Evaluation, Observability, Runtime Engineering, and Production FinOps) is the operational control plane that transforms a probabilistic language model and multi-step tool loop into a reliable, auditable, and economically viable production service. Because generative agents sample tokens stochastically, branch dynamically across external APIs, and mutate state over multi-turn trajectories, classical software verification (binary unit tests and HTTP `200 OK` uptime checks) cannot detect silent quality regressions, "right answer, wrong trajectory" policy violations, or heavy-tail cost explosions.

Why production AI systems fail without an AgentOps control plane:

- **Silent quality & trajectory regressions:** A prompt edit, retrieval tweak, or unpinned model alias can degrade factual faithfulness by 20%—or skip a mandatory identity-verification tool—while every HTTP call still returns `200 OK`.
- **Compounding multi-step unreliability:** A single-step accuracy of 90% collapses to **59.0%** across a 5-step sequential agent workflow (0.90^5).
- **Integration seam failures:** Individual prompts and tools pass isolated tests at >95%, yet the end-to-end pipeline fails because Component A's output format, truncation limit, or error handling violates Component B's input assumptions.
- **Runtime & state mismatches:** Deploying a stateful orchestrator to an ephemeral scale-to-zero container without externalized session storage wipes in-flight memory, while attempting to host standalone MCP servers or custom GPUs on opinionated agent runtimes hits hard platform boundaries.
- **Unbounded heavy-tail economics:** Sizing budgets on median (`p50`) token usage leads to 4×–15× cost overruns when multi-agent fan-out, `thinking_level=HIGH` reasoning loops, tool retries, and mandatory human-review labor hit production scale.

> MENTAL MODEL
>
> Prompts and model weights are **probabilistic components**; your evaluation harness, simulation sandbox, OpenTelemetry trace pipeline, runtime boundary, resilience stack, and FinOps ledger form the **deterministic containment vessel** around them. You cannot eliminate variance inside the model, so you bound, measure, optimize, and price it at every boundary.

The 5-Pillar AgentOps Operational Loop:

1. **Specify, Simulate & Grade (Offline Evals):** Curate a stratified golden dataset, climb the 3-tier grading ladder (Deterministic Code → Calibrated Autoraters / Adaptive Rubrics → Human Experts), and stress-test multi-turn paths with **2-Step Agent Simulation** and **Environment Simulation**.
2. **Verify Seams & Consistency (`pass^k` & Test Pyramid):** Gate releases on worst-case consistency (`pass^k`), trajectory invariants (`trajectory_in_order_match`), and coupled Level 3 integration seam tests.
3. **Observe, Cluster & Optimize (Telemetry & Flywheel):** Instrument PII-safe **OpenTelemetry** `gen_ai.*` spans and dual-attribution audit logs (`is_agentic=true`), monitor live traffic via **Online Evaluation Monitors**, group regressions with **Failure Cluster Analysis**, and close the loop with **Agent Optimizer / Prompt Optimizer**.
4. **Select Runtimes & Isolate Faults (Scale & Resilience):** Match workloads to **Agent Runtime**, **Cloud Run**, or **GKE** (`Agent Substrate` / `Agent Sandbox`), and wrap every model/tool hop in full-jitter backoff, idempotency keys, circuit breakers, and validated fallbacks.
5. **Roll Out Safely & Price the Tail (Shadow/A/B & FinOps):** Promote changes through read-only **Shadow Mode** and **4-Element A/B Tests**, model budgets on `p95` / `p99` heavy tails, and subtract the **Step 4 Human-Review Tax** to verify net enterprise ROI.

1. Evaluation Strategy & The 3-Tier Grading Hierarchy

Why "Vibe Checks" Fail in Production

Eyeballing 5 to 10 interactive examples ("vibe checking") is useful for initial prototyping, but it breaks down immediately as an engineering release gate:

- **Zero statistical power:** On a sample of 10 inputs, a 15% regression is indistinguishable from sampling noise.
- **Confirmation bias:** Developers naturally test happy-path phrasing and subconsciously avoid adversarial inputs, malformed documents, or ambiguous multi-intent queries.
- **Unseen trade-offs:** Tightening a prompt to stop false positives on one edge case frequently induces false refusals or format regressions on twenty others that nobody re-tested.


Eval-Driven Development (EDD) Lifecycle:

1. **Define "done" quantitatively first:** Specify target task completion rate, trajectory compliance, acceptable refusal rate, `p95` latency ceiling, and maximum cost per resolved task *before* iterating on prompts or switching models.
2. **Curate a stratified golden dataset:** Combine happy-path production queries (50%), boundary/edge cases such as empty retrieval, multi-intent prompts, and truncated inputs (30%), and adversarial/safety-probing inputs (20%).
3. **Version everything:** Pin the golden dataset version, autorater rubric version, system prompt template, tool schemas, Agent Registry snapshot, and exact model ID so every eval run is a single-variable experiment.
4. **Inspect per-case diffs, not just aggregate means:** Two prompts that both score 86% overall may fail on completely different slices; always inspect regressions by failure cluster and severity.

The 3-Tier Grading Ladder

Always climb the grading ladder from the cheapest, fastest, most deterministic check to the most expensive semantic review. Never pay an LLM judge or human annotator to verify a property that a 5-line function can check deterministically.

Tier	Grader Type	What It Evaluates	Speed & Cost	Reproducibility	Rule of Thumb
Tier 1	**Deterministic Code Graders**	Exact enum/label match, regex/forbidden strings, JSON Schema & Pydantic validation, AST/compile checks, SQL/code execution unit tests, tool-call sequence & argument bounds	Milliseconds · **$0**	**100% deterministic**	**Always run first.** Gate every CI/CD commit on Tier 1 properties.
Tier 2	**Calibrated Autoraters (LLM-as-Judge)**	Open-ended semantic quality: factual faithfulness to retrieved context, adaptive rubric satisfaction, tool-selection rationale, tone, policy compliance	Seconds · **Token cost per run**	High (when anchored + calibrated)	Use only for semantic qualities code cannot parse; calibrate against Tier 3.
Tier 3	**Human Domain Calibration**	Ambiguous domain edge cases, high-stakes medical/legal/financial accuracy, novel failure discovery, golden-set labeling, autorater calibration	Hours to days · **Highest ($50–$200+/hr)**	Subject to inter-rater variance	Use to build the golden set, audit slices, and measure Tier 2 agreement.



LLM-as-Judge Biases & Engineering Mitigations

Using an uncalibrated LLM as a grader introduces systematic measurement errors that can steer prompt engineering in the wrong direction.

Judge Bias	Mechanism & Symptom	Production Mitigation
Verbosity (Length) Bias	Judges consistently award higher scores to longer, polite, multi-paragraph responses even when they contain fluff, repetition, or subtle hallucinations.	Explicitly penalize unnecessary verbosity in the rubric; grade atomic factual claims (precision/recall) rather than holistic impression; normalize or cap length where appropriate.
Positional (Order) Bias	In pairwise A/B comparisons, judges systematically favor whichever response appears in slot A (primacy bias) or slot B (recency bias).	Run **every pairwise comparison twice** with swapped order `(A, B)` and `(B, A)`. Count a win only if the same candidate wins both passes; mark split decisions as a tie.
Self-Preference Bias	A model family or checkpoint favors outputs matching its own stylistic distribution and blind spots, overlooking reasoning errors it would make itself.	Grade with a **different model family or higher capability tier** than the generator, and always run the judge in a **fresh, isolated context window** containing only the rubric, source ground truth, and candidate output.
Score Inflation & Scale Drift	Asking an LLM to "rate quality from 1 to 100" or "1 to 10" yields arbitrary clusterings around 7–9 with low run-to-run consistency.	Use **binary (`Pass` / `Fail`) checks** decomposed per criterion (adaptive rubrics), or low-granularity **1–3 or 1–5 anchored scales** where every integer has an explicit behavioral definition.
Post-Hoc Rationalization	If the judge outputs a numeric score *first* and its explanation *second*, attention locks onto justifying the emitted token rather than evaluating the evidence.	Enforce structured output where the `reasoning` / `critique` **field precedes the** `score` **field** (Chain-of-Thought *before* judgment).

Calibrating the Autorater Against Human Ground Truth

Because a model-based autorater acts as a learned classifier, benchmark its reliability before trusting its scores:

1. **Build a human-labeled calibration set:** Have 2–3 domain experts independently grade 100–300 stratified examples using the exact same rubric. Measure **inter-annotator agreement** first (if humans disagree with each other, e.g., $\kappa < 0.40$, the rubric itself is ambiguous and must be rewritten before touching the LLM judge).
2. **Measure Autorater–Human Alignment:**
   - **Cohen's Kappa (κ):** Measures agreement on binary or categorical classifications while correcting for chance agreement ($\kappa = (p_o - p_e) / (1 - p_e)$). Target **$\kappa \geq 0.75$** before automating release gates.
   - **Spearman's Rank Correlation (ρ) / Kendall's τ:** Measures monotonic ranking alignment on ordinal 1–5 rubrics.
   - **Confusion Matrix (FPR / FNR):** Track false-pass rate (judge says Pass, human says Fail) separately from false-fail rate; in safety or compliance gates, tune the rubric to minimize false passes.

```python
from pydantic import BaseModel, Field

class FaithfulnessGrade(BaseModel):
    extracted_claims: list[str] = Field(
        description="Atomic factual claims made in the candidate response."
    )
    unsupported_claims: list[str] = Field(
        description="Claims from extracted_claims not directly supported by the source context."
    )
    critique: str = Field(
        description="Step-by-step verification comparing each claim against the source text."
    )
    score: int = Field(
        ge=1, le=3,
        description="1 = Any hallucinated/unsupported claim; 2 = Faithful but omits key context; 3 = Fully faithful and complete."
    )
```

COMMON TRAP

Never ask the same model context that generated an answer to critique and score its own output in the next conversational turn ("self-grading in-thread"). Because prior reasoning tokens and assumptions remain in `messages[]`, the model exhibits severe self-confirmation bias. Always invoke autoraters in a **clean, independent request**.

2. Managed Evaluation Frameworks, Autoraters & Simulation

In enterprise Google Cloud and multi-framework architectures (PAA Section 4.1), teams must choose the right evaluation tool for each stage of the developer inner loop, CI/CD pipeline, pre-release stress test, and live production monitor—rather than forcing a single tool to do everything.

Choosing the Right Evaluation Tooling Tier

Evaluation Tier & Tooling	Primary Mechanism	Speed & Variance	Best Fit & Architectural Boundary
1. Deterministic Harness Replay (`adk conformance test --mode=replay`)	Replays recorded LLM responses from `adk conformance record` baselines against live agent code, callbacks, and state transitions.	**< 5 seconds · $0 · Zero variance**	Every git commit / pre-commit hook verifying that callback guardrails, `state_delta` logic, and routing code did not regress.
2. In-Repo CI Gate (`adk eval`, `Agent Evaluator.evaluate`, `agents-cli eval run`)	Runs `*.test.json` and `*.evalset.json` suites against live models, grading `tool_trajectory_avg_score` (`EXACT`, `IN_ORDER`, `ANY_ORDER`), rubrics, and `custom_metrics`.	**1–5 minutes · Low cost**	Pull-request blocking gates inside GitHub Actions or Cloud Build for code-first ADK repositories (`tests/eval/`).
3. Cloud-Scale Managed Evaluation (**Agent Platform Gen AI Evaluation Service** — `client.evals`)	Framework-agnostic managed service (`EvalTask` / `client.evals.evaluate`) providing **Adaptive Rubrics**, **Custom Autoraters**, **2-Step Agent Simulation**, **Environment Simulation**, and **Online Evaluation Monitors**.	**Minutes to continuous · Managed scale**	Cross-language/cross-framework agents (ADK, LangGraph, Managed Agents, Cloud Run), model migrations (e.g., to `gemini-4-argon`), synthetic stress-testing, and live production trace scoring.

Gen AI Evaluation Service: Autorater & Metric Taxonomy

The **Gen AI Evaluation Service** evaluates both **reference-based** benchmarks (where a golden ground-truth answer or expected tool trajectory exists) and **reference-free** traces (essential for scoring unlabeled live production conversations):


Metric Family	Reference Needed?	How It Works	Canonical Built-In Metrics & Use Cases
Adaptive Rubrics *(Recommended Default)*	**No** (Reference-free)	Dynamically generates a **tailored set of pass/fail unit-test rubrics** unique to *each individual prompt* in the dataset, then scores the candidate response against each generated check.	`GENERAL_QUALITY`, multi-turn instruction adherence across diverse, open-ended user prompts where a static checklist would be too vague or brittle.
Static Rubrics	**No**	Applies an identical, organization-wide pass/fail rubric across every prompt in the suite.	Mandatory regulatory disclaimers, brand voice rules, PII refusal formatting, policy invariants.
Agent Outcome & Grounding Autoraters	**No** (Context-grounded)	Specialized LLM-as-judge autoraters inspecting full conversation traces and retrieved/tool context.	`FINAL_RESPONSE_QUALITY`, `HALLUCINATION` (faithfulness to tool/RAG observations), `TOOL_USE_QUALITY`, `SAFETY`.
Trajectory Metrics	**Yes** (Golden tool trace)	Deterministic comparison between the agent's executed tool sequence/arguments and a reference trajectory.	`trajectory_exact_match` (strict compliance sequences), `trajectory_in_order_match` (required milestones in order, extra read-only calls allowed), `trajectory_any_order_match` (parallel fan-out), `trajectory_precision`, `trajectory_recall`.
Computation & Custom Code Metrics	**Yes / Optional**	Deterministic algorithms or custom Python functions (`custom_metrics`) executing at $0 judge token cost.	`EXACT_MATCH`, `ROUGE`, `BLEU`, JSON Schema validation, SQL AST checks, hard tool-call count or token-budget gates.
Custom Autoraters	**Configurable**	User-defined judge prompt templates, structured critique-before-score schemas, and domain rubrics registered in `client.evals` and calibrated against human raters.	Proprietary clinical, legal, underwriting, or financial grading rules that generic prebuilt autoraters do not encode.

THE "RIGHT ANSWER, WRONG PATH" COMPLIANCE TRAP

Grading a customer-refund or healthcare agent solely with `FINAL_RESPONSE_QUALITY` or `multi_turn_task_success_v1` will pass an agent that guessed or issued a refund *without* calling `verify_customer_identity` or `check_return_eligibility` first. Whenever policy mandates verification steps, **always pair outcome autoraters with `trajectory_in_order_match` or `trajectory_exact_match`** (plus a forbidden-tool custom check).

Pre-Launch Stress Testing: 2-Step Agent Simulation & Environment Simulation

Hand-written golden sets rarely exceed 50–200 single-turn prompts and miss multi-turn clarification loops or third-party API brownouts. Before launching—even when zero historical production logs exist—combine Agent Platform's two simulation engines:



1. **2-Step Agent Simulation:** Requires an immutable **Agent Registry** snapshot so every benchmark is reproducible. In **Step 1**, the simulator reads the agent's system instructions and tool declarations to synthesize realistic `Starting Prompts` paired with hidden `Conversation Plans` (e.g., an impatient traveler who only reveals their booking code when explicitly asked). In **Step 2**, a simulated user model conducts the multi-turn session and records full traces.
2. **Environment Simulation:** Wraps tool boundaries during evaluation to inject deterministic faults (`HTTP 503 Service Unavailable` , `429 RESOURCE_EXHAUSTED` , 12-second latency spikes, empty results) and mocked responses—proving your retry, fallback, and escalation guardrails work **without risking real side effects on production payment or ERP APIs**.

3. Non-Deterministic Metrics: `pass@k` vs. `pass^k`

Because LLM generation is stochastic, running the exact same prompt and tool sequence k times can produce different trajectories and outcomes. Picking the wrong multi-trial metric can make a brittle system look production-ready on paper while failing constantly for real users.

Mathematical & Operational Contrast

Let $p \in [0, 1]$ be the single-trial probability that an agent or model completes a task correctly on one independent run, and let k be the number of independent trials.

$$\text{pass@k} = 1 - (1 - p)^k \quad \text{vs.} \quad \text{pass}^k = p^k$$

Metric	Formula (for single-run success p)	Meaning	Curve as k Increases	When to Use	When It Is Dangerous
`pass@k` *(At-Least-One Success)*	$1 - (1 - p)^k$ *(unbiased estimator over $n \geq k$ samples)*	Chance of seeing **one or more successes** across k independent runs.	**Rises toward 100%** (masks underlying flakiness)	Code generation with a compiler/unit-test verifier; swarm tournament prototyping where a deterministic filter picks the single working output.	**Customer-facing chat or autonomous agents:** users only see 1 run, and side-effecting tools cannot be casually run 5 times hoping one works.
`pass^k` *(Every-Run Consistency)*	p^k	Chance that **every single run across k trials** succeeds without failure.	**Decays exponentially toward 0%** (exposes variance)	**Customer-facing agents**, unattended background automation, regulated workflows, and mutating tool pipelines where every invocation must be reliable.	Over-optimizing `pass^k` on purely creative brainstorming tasks where diversity across samples is desirable.

The Exponential Decay of Consistency (`pass^k` Table)

Notice how a single-run accuracy of p = 0.90 looks impressive on `pass@5` (99.999%) while collapsing to 59.0% on `pass^5` and 34.9% on `pass^10` :

Single-Run Accuracy (p)	`pass@1` / `pass^1`	`pass@5` ($1 - (1 - p)^5$)	`pass^5` (p^5)	`pass^10` (p^{10})	Operational Interpretation
0.70 (70%)	70.0%	99.8%	**16.8%**	**2.8%**	Usable for 5-sample code synthesis with unit tests; **unusable** for live automation.
0.85 (85%)	85.0%	99.99%	**44.4%**	**19.7%**	Fails more than half the time over 5 consecutive runs.
0.90 (90%)	90.0%	99.999%	**59.0%**	**34.9%**	Still fails **41% of 5-run consistency suites**.
0.95 (95%)	95.0%	>99.999%	**77.4%**	**59.9%**	Minimum baseline before adding deterministic guardrails.
0.99 (99%)	99.0%	>99.999%	**95.1%**	**90.4%**	Production-grade step reliability (achieved via code gates + schema constraints).

Compounding Multi-Step Accuracy Across Sequential Agent Steps

The exact same multiplicative law governs a single execution of a **multi-step sequential workflow**. If an agent must complete M sequential steps (e.g., Classify Intent → Formulate Query → Select Tool → Parse Payload → Synthesize Final Answer) and each step has independent success probability p_i, end-to-end workflow success is the product of every step:


$$P(\text{Workflow Success}) = \prod_{i=1}^{M} p_i \quad (\text{or } p^M \text{ if each step has accuracy } p)$$

- **Example:** A 6-step autonomous workflow where every individual step scores **92%** in isolation (p = 0.92) has an end-to-end first-pass success rate of $0.92^6 \approx$ **60.6%**—meaning nearly **4 out of 10 production runs fail**.
- **Architectural remedies to beat compounding decay:**
  1. **Replace probabilistic steps with deterministic workflow nodes:** If steps 2 and 4 can be written as standard code, ADK workflow edges, or strict schema validators (p = 1.00), a 6-step pipeline shrinks to 3 probabilistic hops ($0.92^3 \approx 77.9\%$).
  2. **Insert programmatic verification gates between steps:** Catch and auto-correct malformed tool arguments or schema errors at step i before passing corrupt state to step i+1.
  3. **Bound step count:** Keep autonomous loops shallow and route predefined sequences through deterministic workflow orchestrators (`SequentialAgent`) rather than LLM routers.

> **EXAM & PRODUCTION RULE**
> Whenever a scenario involves an unattended workflow, customer-facing support agent, or financial/database tool execution, evaluate readiness using **`pass^k`** (every trial succeeds) and **end-to-end trajectory completion**, never `pass@k` . Use `pass@k` only when a downstream deterministic verifier (such as a test suite or compiler) can automatically filter k candidates before side effects occur.

4. The 4-Level Agent Test Pyramid & Integration Seams

Testing an agentic system exclusively through end-to-end live conversations is slow, expensive, and non-diagnostic; testing it exclusively through isolated unit tests misses catastrophic multi-step handoff failures. Production teams structure verification as a **4-Level Agent Test Pyramid**.



The 4 Levels in Detail

Level	Scope & Target	What Is Mocked vs. Live	Execution Cadence & Cost	What It Catches
Level 1: Deterministic Unit & Replay Tests	Tool JSON schemas, Pydantic validators, prompt template rendering, PII scrubbers, retry state machines, `adk conformance test --mode=replay`	**LLM is 100% mocked / replayed** from recorded fixtures. Pure code execution.	Every save / pre-commit hook · **Milliseconds to <5s · $0**	Broken schema definitions, template `KeyError` bugs, callback regressions, broken `state_delta` routing.
Level 2: Single-Step Component Evals	A single LLM call in isolation: intent router, entity extractor, query rewriter, or RAG answer generator	**Live LLM call** against a frozen, curated golden input + fixed context snapshot.	Every PR touching prompts/models · **Seconds to minutes · Low cost**	Prompt regressions, classification drift, hallucination on specific golden slices, schema compliance drops.
Level 3: Trajectory & Seam Integration Tests	Multi-turn agent loop across 2–8 steps: tool selection, argument passing, error recovery, subagent handoffs	**Live LLM + Environment Simulation / sandboxed test doubles** (including injected `503`, `429`, and empty-result fixtures).	Pre-release gate / nightly build · **Minutes · Moderate cost**	**Integration seam failures**, infinite tool loops, silent error swallowing, oversized tool payloads, state loss during compaction.
Level 4: Live Canary & Online Monitors	Real production traffic across the full deployed stack	**100% live** (canary slice, shadow pipeline, or 1–5% sampled **Online Evaluation Monitors**).	Continuous in production · **Budgeted % of prod spend**	Input/data drift, unpredicted user phrasing, latency spikes, real third-party API schema changes.

Why Integration Seams Hide Silent Bugs

An **integration seam** is the boundary where the output of Component A becomes the input of Component B (for example: *Query Rewriter* → *Hybrid Retriever*, *Tool Execution Output* → *Agent Context*, or *Planner Subagent* → *Executor Subagent*).

Compound Error Cascades across Multi-Step Pipelines: Every individual component can score **>95% in isolated component evaluations** while the end-to-end system fails on **>40% of real tasks** because independent step probabilities compound multiplicatively ($0.95^5 \approx 77\%$) and isolated evaluations feed idealized, clean inputs to each stage rather than handling noisy upstream artifacts.


Seam Failure Pattern	How Component A Behaves ("Passes L2")	How Component B Breaks Across the Seam	Architectural Fix
Format & Schema Drift	Extractor outputs dates as `"Oct 26, 2026"` or wraps JSON in ```` ```json ```` markdown fences (passes loose L2 check).	Downstream SQL/API tool expects strict ISO-8601 `2026-10-26` or raw JSON and throws a validation/parse error.	Enforce **strict structured outputs** (`output_schema` / JSON Schema) at the seam and validate with a Level 1/3 contract test.
Unbounded Tool Output & Silent Truncation	Search tool dumps a 40,000-token raw log into context (diluting model attention), or middleware naively slices the first 4,000 chars.	Either attention degrades across turns (**context rot**) or the stack trace at the bottom is cut off, causing a confident *"No errors found"*.	Truncate structurally (head + tail + error lines, or return pagination metadata `truncated: true, next_cursor: "..."`).
State Loss During Context Compaction	Sliding-window summarizer compresses 12 prior turns into a 3-sentence prose paragraph.	Summarizer drops an exact UUID, config flag, or constraint read in Turn 2 that Turn 14 needs to execute a tool safely.	Persist exact IDs, constraints, and slot values in structured **Session `state`** (`session.state`), never solely in summarized prose.
Swallowed Tool Failures (Empty vs. Error)	Tool wrapper catches a database timeout (`504`) and returns `[]` or `""` so the pipeline doesn't crash.	The model interprets `[]` as ground truth (*"You have zero open orders"*) instead of a transient system outage.	Never conflate empty results with failures; return explicit structured error flags (`is_error: true`, error code, retryability).
Distribution Shift Between Stages	Query rewriter expands short user queries into 80-word boolean strings that were never in the retriever's golden set.	Dense embedding model loses specificity on 80-word keyword-stuffed queries, dropping top-5 recall by 30%.	Evaluate *Query Rewriter + Retriever* together as a coupled pair in Level 3 seam tests using end-to-end Recall@K.

5. Observability, Distributed Tracing & Drift Detection

In a production agentic workflow, a single user message can fan out into Model Armor screening, hybrid vector retrieval, cross-encoder reranking, multi-turn `gemini-4-argon` or Claude reasoning calls, MCP tool executions, and A2A sub-agent delegations. Without standardized **distributed tracing**, diagnosing a 19-second stall, a reasoning loop, or a hallucination is guesswork.

OpenTelemetry `gen_ai.*` Semantic Conventions & Agent Observability

Instrument every workflow with **OpenTelemetry (OTel) Semantic Conventions for Generative AI** (`gen_ai.*` attributes across `invoke_agent` , `chat` , and `execute_tool` spans) so traces render uniformly across **Google Cloud Trace**, **Agent Registry Observability**, and vendor-neutral APMs:



Telemetry, Privacy & Dual-Attribution Governance on Google Cloud (PAA 4.2 & 5.1):

- **Metadata-First Default Telemetry:** On Agent Runtime, setting `GOOGLE_CLOUD_AGENT_ENGINE_ENABLE_TELEMETRY=true` (with `OTEL_SEMCONV_STABILITY_OPT_IN=gen_ai_latest_experimental`) exports full latency waterfalls, token/cache counts, tool latencies, and error codes **without** logging raw user prompts or model completions.
- **Opt-In PII-Scrubbed Payload Capture:** Raw message content capture (`OTEL_INSTRUMENTATION_GENAI_CAPTURE_MESSAGE_CONTENT=true`) must only be enabled in approved environments paired with **Sensitive Data Protection (SDP)** de-identification templates (redacting/tokenizing SSNs, payment cards, emails, and secrets) and RBAC-restricted Cloud Logging buckets (`roles/logging.privateLogViewer`).
- **Dual-Attribution Agentic Audit Logging (`is_agentic=true`):** When an agent acts on behalf of a human user, Cloud Audit Logs and execution logs tag events with `is_agentic=true` and record **both** (1) the cryptographic SPIFFE **Agent Identity** (`principal://...` / `spiffe://...`) and (2) the initiating **human user principal**—eliminating "confused deputy" forensic blind spots.

Troubleshooting Production Agent Issues via Telemetry Views

Agent Registry's Observability suite (Overview, Evaluation, Models, Tools, Usage, Logs, Traces, Topology) maps production symptoms directly to root causes:

Production Issue (PAA 4.2)	Diagnostic Signature in Cloud Trace / Agent Observability	Root Cause & Engineering Remediation
Agent Reasoning Loops	`Traces` waterfall shows 8–15 consecutive `gen_ai.chat` ↔ `execute_tool` spans calling the exact same tool with identical or oscillating arguments until `max_turns` aborts.	Ambiguous tool error message (e.g., returning `""` instead of actionable schema feedback) or missing loop cap. Return structured error hints (`ReflectAndRetryToolPlugin`), enforce `max_llm_calls` / `max_iterations` , and break cycles with deterministic state flags.
Tool Invocation Latency Spikes	End-to-end turn `p95` jumps to 14s while LLM `ttft_ms` and decode time stay <1.2s; `Tools` tab highlights a single MCP server `p95` at 11.5s or 5 serial tool spans.	Unpooled database connections, cross-region VPC hops, or sequential execution of independent reads. Co-locate runtimes with data, use `MCP Toolbox` connection pooling, and fan out independent reads concurrently (`ParallelAgent`).
Ignored Tools ("No-Tool Interactions")	`Tools` tab shows high **"no-tool interaction"** rate alongside elevated `HALLUCINATION` autorater flags on domain questions.	Vague or overlapping tool docstrings/schemas cause the model to guess from parametric memory instead of calling the tool. Sharpen tool descriptions and add `trajectory_in_order_match` CI gates.
Model Prefill / Thinking Bottlenecks	`Models` & `Traces` tabs show `thinking_tokens` dominating `total_generation_ms` on simple classification hops, or high `ttft_ms` with `cached_tokens = 0` .	`thinking_level="HIGH"` over-allocated to routine steps, or dynamic timestamps placed at line 1 busting prefix caching. Route simple steps to `gemini-3.5-flash-lite` (`minimal`) or `gemini-3.8-flash` (`low`), and move volatile state after `static_instruction` .

SLIs, SLOs & Two Distinct Forms of Production Drift


Production AI systems track **four SLI dimensions: Responsiveness** (`p95 TTFT` , `p95` turn latency), **Pipeline Reliability** (`429` / `5xx` rate, tool `is_error` rate, fallback rate, unexpected `max_tokens` / `refusal` stop reasons), **Economic Efficiency** (cache hit ratio >75%, cost per resolved task, `p95` turns/session), and **Semantic Quality** (sampled **Online Evaluation Monitor** pass rates ≥ 96% and human escalation rate).

Even with zero code deploys, quality degrades over time through two distinct drift mechanisms with opposite fixes:

Drift Type	Root Cause	Symptoms in Telemetry	Engineering Remediation
1. Input / Data Drift *(World Changes)*	Real user queries, new product SKUs, updated regulations, or changed third-party API payloads diverge from your static golden set and RAG corpus.	Model ID and prompt hash are unchanged and infra SLIs are green, yet **retrieval similarity scores drop**, out-of-domain queries rise, and Online Monitor faithfulness declines gradually.	**1.** Monitor query embedding distribution shift & retrieval score histograms. **2.** Refresh the RAG / Agent Search corpus. **3.** Feed SDP-scrubbed failing traces into the **LM Feedback Flywheel** to expand the golden evalset.
2. Model / Provider Drift *(System Changes)*	Calling a moving model alias (e.g., `-latest`), an unannounced provider routing update, or an unvalidated prompt/tool-schema edit.	Sudden step-change shift in output length, `refusal` rate, JSON parse errors, or tool-calling aggressiveness across all topics simultaneously.	**1. Pin exact immutable model snapshot IDs** and Agent Registry versions. **2.** Run automated Level 2/3 eval gates before any model cutover (using **Data-Driven Prompt Optimizer** when migrating model families). **3.** Maintain instant config rollback to the prior pinned ID.

6. LM Feedback Flywheel, Failure Clustering & Agent Optimizer

Drift detection tells you *that* quality moved; the **LM Feedback Flywheel** and **Agent Optimizer** ensure every production failure class is discovered automatically, grouped by root cause, fixed programmatically without "prompt whack-a-mole," and permanently guarded against in CI/CD.



Step-by-Step Closed-Loop Feedback Flywheel

1. **Capture Multi-Source Signals:** Collect explicit user feedback (thumbs-down, bug reports), implicit behavioral friction (immediate re-prompting, session abandonment, human escalation), and automated **Online Evaluation Monitors (`OnlineEvaluator`)** that continuously sample 1–5% of live Cloud Trace spans and score them asynchronously with reference-free autoraters (`HALLUCINATION` , `TOOL_USE_QUALITY` , `GENERAL_QUALITY`).
   - *IAM Governance Rule:* Online monitors execute under a platform service agent that reads trace payloads and spends judge tokens—restrict monitor creation/modification IAM permissions to authorized AgentOps engineers.
2. **Scrub Before Storage:** Export flagged `trace_id` records to BigQuery via Cloud Logging sinks after passing payloads through **Sensitive Data Protection (SDP)** de-identification templates so production fixtures never leak customer PII or credentials.
3. **Triage via Failure Cluster Analysis (Auto Loss Analysis):** Instead of playing whack-a-mole on isolated support tickets, run **Failure Cluster Analysis** over low-scoring online traces and failed simulation runs. An analyzer LLM clusters raw failures into actionable root-cause buckets (e.g., *"Cluster #1 (34% of failures): `book_flight` receives relative dates like 'next Friday' instead of ISO-8601", "Cluster #2 (19%): premature final answer before reading page 2 of search results"*) ranked by Frequency × Severity.
4. **Reproduce & Codify Outcomes (Not Brittle Transcripts):** Convert representative traces from top clusters into reproducible `evalset` cases with recorded tool fixtures. Assert **outcomes and required safety milestones** (`trajectory_in_order_match`) rather than exact word-for-word transcripts so valid alternative reasoning paths still pass.
5. **Protect Generalization with a Held-Out Split & Watch Saturation:** Keep a **held-out validation slice** of production failures invisible to both engineers and automated prompt optimizers during tuning (preventing prompt memorization/overfitting), and continuously refresh suites that saturate near 100%.

Programmatic Prompt Optimization (`Agent Optimizer` / Prompt Optimizer)

Manually rewriting a 4,000-token system prompt to fix Failure Cluster #1—or migrating prompts from an older model to `gemini-3.8-flash`, `gemini-4-argon`, or a smaller `Gemma 4` deployment—often introduces regressions on previously working behaviors. Agent Platform provides two automated optimization engines:

Optimizer Engine	Inputs Required	Optimization Modes & Mechanism	When to Choose
Zero-Shot Optimizer (`client.prompt_optimizer.optimize_prompt`)	**Only the raw prompt / system instruction** (zero labeled examples or eval dataset required).	`optimization_mode="zero_shot"` : Analyzes prompt structure against model best practices and immediately returns `suggested_prompt` plus `applicable_guidelines` (e.g., adding missing role boundaries, fixing ambiguous constraints, removing redundant instructions).	Cold-start prototyping, cleaning up ad-hoc developer prompts in seconds, or preparing an initial baseline before collecting golden data.
Data-Driven Optimizer & **`Agent Optimizer`** (Custom Optimization Job)	System instructions + prompt template + **labeled/scored sample dataset** + **Gen AI Evaluation metrics** + **target model ID**.	Runs an iterative closed-loop job (`evaluate → analyze failure clusters → mutate prompt/demos → re-evaluate on target model`) across three selectable modes: • **`instruction`** : Rewrites system instructions only. • **`demonstration`** : Selects optimal few-shot examples from candidates (or populates **Example Store**). • **`instruction_and_demo`** : Jointly optimizes instructions and few-shot demonstrations.	**1.** Fixing ranked **Failure Clusters** without regressing existing evals. **2. Model migrations** (adapting prompts to `gemini-4-argon` or distilling a frontier prompt down to `gemini-3.5-flash-lite` / `Gemma 4` for cost/latency savings).

7. Deployment Runtime Selection: Agent Runtime vs. Cloud Run vs. GKE

Selecting the wrong compute runtime in Google Cloud (PAA Section 4.2) creates immediate architectural friction—either starving a stateful agent of memory, breaking MCP server hosting, or saddling a small team with unnecessary Kubernetes node management. Apply **Rule 0 (Managed by Default)**: start at the most managed runtime that satisfies your language, protocol, accelerator, and isolation constraints.

Google Cloud Agentic Runtime Decision Matrix

Architectural Dimension	Agent Runtime *(formerly Agent Engine)*	Cloud Run *(Services & Jobs)*	Google Kubernetes Engine (GKE)	Managed Agents API *(Preview)*
Primary Workload Fit	Stateful Python/ADK, LangGraph, CrewAI, or A2A orchestrators (`reasoning Engines`) needing turnkey agent ops	**Custom Streamable HTTP MCP servers**, polyglot agents (TS, Java, Go, Python), webhook/Pub/Sub event-driven agents	**Self-hosted open-weight models** (**`Gemma 4`** , **`Llama`**) **on GPUs/TPUs**, dense multi-agent meshes, strict kernel-isolated multi-tenant sandboxes	Declarative autonomous coding, research, and file-processing agents (`Agents API` + `Interactions API`)
Operational Overhead	**Lowest** (fully managed agent container lifecycle)	**Low** (serverless container-to-URL, scales to zero)	**Highest** (cluster, node pools, networking, controller upgrades)	**Zero** (Google runs the loop and no-egress Linux container)
State & Memory Model	**Built-in:** Native **Agent Platform Sessions**, **Memory Bank**, **Example Store**, and **Code Execution** sandbox	**Stateless / Ephemeral RAM:** Local memory vanishes on scale-in; must attach external **Sessions** (`agentengine://`), **Memorystore**, **Firestore**, or **Cloud SQL**	StatefulSets, **Agent Substrate** (`<1s` auto-snapshot/restore of memory & files on GKE Standard), or external managed DBs	Server-side state chained via `previous_interaction_id` and `environment_id` (`global` endpoint)
Scaling & Duration	Managed autoscaling; `min_instances` for zero cold start; supports long-running / multi-day async workflows	Scales `0 → N` rapidly; HTTP timeout up to **60 minutes**; Cloud Run Jobs for batch backfills	Granular HPA/VPA, custom queue metrics, GPU time-slicing, Spot VMs, **Committed Use Discounts (CUDs)**	Synchronous streaming or `background=True` multi-hour async execution
Hosts Custom MCP Servers?	**No** (consumes MCP/A2A, does not host standalone MCP servers)	**Yes — Primary serverless choice** for Streamable HTTP `/mcp` servers	**Yes** — High-density, stateful, or private in-cluster MCP fleets	**No** (supports server-side tools only)
Custom GPUs / Self-Hosted Models?	**No** (calls managed model APIs)	**Limited** (serverless GPU inference for lightweight bursts)	**Yes — Primary choice** for vLLM/TGI serving of **Gemma 4** on GPUs/TPUs *(never proprietary Gemini weights!)*	**No**
Code Sandbox Isolation	Managed **Code Execution** micro-container (`<1s` startup, 100 MB I/O, up to 14-day TTL)	Call external Agent Platform Code Execution sandbox API	**Agent Sandbox on GKE** (`Sandbox Template` + `SandboxWarmPool` pre-warmed **gVisor** pods; blocks `hostNetwork` / `hostPath`)	Built-in isolated Linux container (outbound network disabled by default)

GKE Sub-Architecture Choice: Agent Substrate vs. Agent Sandbox

When requirements mandate GKE, distinguish its two specialized agent orchestration architectures:

- **Agent Substrate on GKE (Actor-Based, GKE Standard):** Best for high-density stateful agents that frequently go idle between user turns. Active agents multiplex over a shared pool of warm Pods; idle agents automatically checkpoint memory and filesystem state to storage and restore in **`< 1 second`** , maximizing node utilization.
- **Agent Sandbox on GKE (Pod-Based, GKE Autopilot or Standard):** Best when each agent or untrusted code execution requires a dedicated Kubernetes Pod (`Sandbox` / `SandboxClaim` CRDs, `SandboxWarmPool` for sub-second startup), full `PodSpec` sidecars, hardware accelerators (GPUs/TPUs), and mandatory **gVisor** kernel isolation enforced via Validating Admission Policy.

Runtime Capacity, Quota & Configuration Traps


1. ***"Region temporarily at capacity"*** **vs.** **`429 RESOURCE_EXHAUSTED`** :
   - Seeing **`"Region temporarily at capacity"`** when deploying an Agent Runtime instance means **physical regional compute pool exhaustion**, *not* an IAM error or project quota cap—filing a quota increase ticket will not resolve it. Deploy to an alternate supported region, right-size vCPU/memory, or retry off-peak.
   - Seeing **`429 RESOURCE_EXHAUSTED`** during Gemini API inference indicates shared Standard PayGo contention or TPM/RPM limits. Route stateless requests to the **`global`** **endpoint**, apply full-jitter backoff, enable **Priority PayGo** for bursty interactive paths, or purchase **Provisioned Throughput (GSUs)** for predictable baseline load. *(Remember: Provisioned Throughput does not cover Batch Prediction or internal calls made by other managed services like Agent Search, even when using the same model.)*

2. **Reserved Environment Variables on Agent Runtime:** Never override `GOOGLE_CLOUD_PROJECT` or `PORT`, and never define custom variables starting with the reserved `GOOGLE_CLOUD_AGENT_ENGINE*` prefix (except documented platform toggles like `GOOGLE_CLOUD_AGENT_ENGINE_ENABLE_TELEMETRY=true`).

3. **Agent Registry Auto-Registration Rules:** Agents on **Agent Runtime**, **Gemini Enterprise**, official Google MCP servers, annotated **GKE** workloads, and **Cloud Run** services deployed with `--functional-type=agent` + `--identity-type=agent-identity` auto-register in **Agent Registry**; unflagged Cloud Run services and external/on-prem MCP servers must be registered via the writable `Service` resource.

8. Production Resilience Stack & Fault Isolation

LLM APIs and external tools operate under tight token-per-minute (TPM) and request-per-minute (RPM) quotas, variable compute load, and occasional regional brownouts. Production resilience requires a **4-layer defense stack** where each control lives at a distinct architectural boundary.



Layer 1: Exponential Backoff with Full Jitter & Idempotency

When an upstream model endpoint returns `429 Too Many Requests` or `529 Overloaded`, naive fixed-interval retries synchronize across all concurrent workers—creating a **retry storm (thundering herd)** that guarantees the next wave fails too.

1. **Honor `Retry-After` first:** If the response includes a `retry-after` or `retry-after-ms` header, sleep for at least that server-specified duration.
2. **Use Exponential Backoff with Full Jitter** when no header is present:

$$t_{sleep} = \text{Uniform}(0, \min(T_{cap}, T_{base} \cdot 2^{attempt}))$$

Randomizing the wait across [0, cap] desynchronizes concurrent callers.


3. **Single Retry Owner:** Official SDKs (`google-genai`, `anthropic`) retry transient errors (`408`, `409`, `429`, `≥500`) **twice by default**. Never wrap an SDK call that has default retries enabled inside your own 4-attempt loop (multiplying to 3 × 4 = 12 hits per request). Either configure `HttpRetryOptions` / `max_retries` on the SDK client or set `max_retries=0` and manage retries in one wrapper.
4. **Never retry terminal errors or content decisions:** Fail fast on `400` (bad schema, invalid `thinking_level`), `401` / `403` (auth), `404` (bad model ID), `413` (payload too large), **workspace spend-cap `429` s** (which lack `retry-after`), and `HTTP 200` with `stop_reason: "refusal"` / safety block.
5. **Idempotency Keys on Mutating Tools:** Retrying a mutating tool (`charge_credit_card`, `issue_refund`, `create_jira_ticket`) after a `504 Gateway Timeout` risks duplicate execution if the first request committed server-side. Every mutating tool must pass a deterministic **`idempotency_key`** (`sha256(session_id + turn_index + tool_name + canonical_args)`) deduplicated in Memorystore/Redis or the downstream API.

Layers 2–4: Circuit Breakers, Validated Fallbacks & Context-Rich Escalation

- **Layer 2 — Circuit Breakers (`Closed → Open → Half-Open`):** Per-request retries during a 10-minute outage hold thousands of sockets open, starving web workers. A shared service-boundary circuit breaker trips **`Open`** once error rates breach threshold (failing fast in `<1 ms` into Layer 3), then probes recovery via **`Half-Open`** after a cooldown window.
- **Layer 3 — Orchestration Fallbacks:** Fail over first to the same model via the **`global`** **endpoint** or a secondary region; if falling back across model tiers/families (e.g., `gemini-4-argon` → `gemini-3.8-flash` or `Claude Opus` → `Sonnet`), maintain a **fallback-specific prompt/parameter configuration** (adjusted via **Data-Driven Prompt Optimizer** and validated on your Level 2/3 golden suite) so unsupported parameters (like `thinking_budget` vs. `thinking_level`) do not cause secondary `400` crashes.
- **Layer 4 — Structured Human Escalation:** When fallbacks exhaust or `max_turns` / policy boundaries trigger, hand off a structured bundle (`trace_id`, session history, verified customer entities, tools already invoked + outputs, and escalation reason) so the human specialist never asks the customer to repeat themselves.

9. Safe Rollouts: Shadow Mode vs. 4-Element A/B Testing

Passing an offline golden dataset and simulation suite (Levels 1–3) is necessary but never sufficient for high-volume production changes. Real user traffic contains live concurrency, cache warmth, and long-tail phrasing that static suites miss. Promote changes through a **4-Stage Progressive Delivery Pipeline**:



Shadow Mode (Dark Launch) vs. Canary vs. A/B Testing

Rollout Stage	Who Sees Candidate Output?	Side-Effecting Tools Allowed?	What It Validates Best	Blind Spots / Limitations
Offline & Simulation	Eval harness only	Mocked / **Environment Simulation**	Regressions on known golden cases, multi-turn persona stress tests, fault-injection handling	Cannot test real production concurrency, live cache hit ratios, or organic user reactions.
Shadow Mode *(Dark Launch)*	**Nobody** (logged async; user receives baseline response)	**Read-only tools only** (mutating tools MUST be stubbed/sandboxed!)	Real-world `p95` / `p99` latency, crash rates, token spend, cache hit rate, first-turn tool selection, and async autorater parity	**Cannot measure multi-turn user reaction** (user replies to baseline Turn 1, creating counterfactual divergence on Turn 2+) or business conversion.
Canary Release	**1%–5% of live traffic** (sticky by session)	Live tools (with circuit breakers & auto-rollback)	Production stability, quota saturation, and catastrophic UX failures under real closed-loop dialogue	Small slice lacks statistical power to prove subtle (2%–3%) resolution or conversion gains.
Controlled A/B Test	**Randomized split** (e.g., 50/50 or 80/20 sticky by user/account)	Full live stack	Causal impact on primary business/quality outcomes + non-inferiority against cost and latency guardrails	Requires pre-committed sample size N and business-cycle duration; exposes treatment cohort to candidate.

CRITICAL SHADOW MODE SAFETY RULE

In shadow mode, live requests are duplicated asynchronously to the candidate agent. If the candidate calls **mutating tools** (`refund_order`, `update_crm`, `send_email`), running unsandboxed shadow mode executes real side effects twice or corrupts production data! Enforce a **read-only tool sandbox** in shadow mode.

Rigorous Controlled Experimentation & A/B Testing

An A/B experiment must lock in **all four elements before launch**:

1. **Explicit Falsifiable Hypothesis & Sticky Randomization Unit:** Randomize at the **user, account, or session level** (`hash(user_id + experiment_salt) % 100`), **never per HTTP turn** (which mixes models mid-conversation, destroys prefix caching, and ruins causal attribution).
2. **Single-Variable Isolation:** Change **one variable per treatment arm** (e.g., prompt revision OR model tier, not prompt + model + retriever + UI simultaneously).
3. **Primary Outcome Metric + Guardrail Metrics (Non-Inferiority Bounds):** Pair one primary success metric (e.g., *Verified Resolution Rate without Escalation*) with strict guardrails that must not degrade: `p95` TTFT/turn latency, **token cost per resolved task**, unhelpful refusal rate, tool error rate, and `HALLUCINATION` monitor score.
4. **Pre-Committed Sample Size N & Statistical Stopping Rule:** Fix $\alpha = 0.05$, power $1 - \beta = 0.80$, MDE, and minimum full weekly cycle beforehand. **Never stop early the first day $p < 0.05$ ("peeking" / p-hacking)** unless using formal sequential testing boundaries (Always-Valid p-values / O'Brien-Fleming alpha-spending).

10. Token Economics, Heavy-Tail Sizing & 4-Step Enterprise ROI

More enterprise AI pilots fail at the FinOps gate than at the accuracy gate. A prototype that costs $0.02 per query on clean developer tests can easily cost $0.85 per resolved ticket in production once heavy-tail context growth, ~15× multi-agent fan-out, online judge sampling, and human review labor are included.

Heavy-Tail Token Distributions (`p95` / `p99` vs. `p50`)

LLM token consumption follows a **heavily right-skewed (log-normal / Pareto) distribution**:

- **Why `p50` (median) sizing fails:** While the median session might be 2 turns consuming 3,000 tokens ($0.01), the top 5%–10% (`p95` – `p99`) involve 15-turn debugging loops, 50-page PDFs, large MCP JSON payloads, `thinking_level="HIGH"` reasoning traces, and retries—consuming 150,000 to 500,000+ tokens per session.
- Without context compaction and prefix caching, resending history across N turns bills **quadratically** ($O(N^2)$):

$$\text{Cumulative Input Tokens across N turns} \approx N \cdot S_{\text{static}} + \sum_{t=1}^{N} (N - t + 1) \cdot \Delta_{\text{turn t}}$$

- **FinOps Sizing Rule:** Model TPM quotas and monthly budgets using the **distribution mean or `p95` / `p99`-weighted buckets**, never `p50 × volume`, and enforce hard caps (`max_turns`, `max_tokens`, observation pruning) to clip runaway tails.


High-Impact Cost-Bending Levers (Multi-Agent ~15× Multiplier)

Autonomous multi-agent systems consume **~15× more tokens** than single-turn chat (~4× more than single-agent tool loops) due to parallel subagent context initialization, multi-hop reasoning, and coordinator synthesis. Bend the cost curve with six architectural levers:

Cost-Optimization Lever	Mechanism	Typical Savings Impact	Critical Exam & Production Nuance
1. Tiered Semantic Model Routing	Route simple classification/guardrails to `gemini-3.5-flash-lite` (`Haiku`), workhorse tool loops to `gemini-3.8-flash` (`Sonnet`), and complex synthesis to `gemini-4-argon` (`Opus`).	**50% – 80%** token spend reduction	Validate each routed tier against your Level 2/3 golden set (and tune prompts with **Data-Driven Optimizer**).
2. Prefix-Aligned Context Caching	**Implicit caching** (automatic on `gemini-4-argon` at ≥ 4,096 tokens and `3.x` at ≥ 4,096 to 6,144 tokens, **zero storage fee**, ~90–95% read discount) vs. **Explicit caching** (`cachedContents` / `cache_control` with TTL storage/write cost where supported).	**Up to 80% – 95%** on repeated input prefixes + lower TTFT	Cache creation bills at standard input price on Gemini; **explicit `cachedContents` pays TTL storage fees while implicit caching has zero storage cost** (`gemini-4-argon` supports implicit only). Keep static instructions/tools at byte 0!
3. Thinking / Effort Right-Sizing	Use `thinking_level="minimal"` on `3.5-flash-lite` or `"low"` / `"medium"` on `3.8-flash` & `4-argon` (and `effort: "low"` on Claude) for routine hops, since thinking tokens bill at **output token rates**.	**30% – 60%** output token reduction	Reserve `thinking_level="high"` for ambiguous planning, root-cause analysis, or complex math/code synthesis.
4. Async Batch / Flex Inference	Run nightly 10,000-case offline evalsets, bulk backfills, and large autorater jobs via **Batch Prediction / Flex PayGo / Message Batches API** (≤ 24h SLA).	**~50% price reduction** on input & output tokens	**Provisioned Throughput (GSUs) does NOT cover batch prediction**—use Batch/Flex for offline workloads and GSUs for steady real-time traffic.
5. Observation Masking & Session Compaction	Prune verbose MCP JSON/HTML fields after extraction (`after_tool_callback`), run tabular filtering inside the **Code Execution sandbox**, and compact older session turns.	**40% – 70%** reduction in multi-turn $O(N^2)$ growth	Store critical IDs/constraints in structured `session.state` before compacting prose to prevent **state erasure**.
6. Idle Infra Hygiene	Tune `min_instances`, suspend idle Cloud Workstations (`idleAction=SUSPEND`), and undeploy unused **Vector Search 1.0** index endpoints.	Eliminates 24/7 fixed hourly burn at zero QPS	Deployed Vector Search 1.0 endpoints bill continuously per node-hour even when serving zero queries.

Total Cost of Ownership & Enterprise ROI Framework

Calculate **Net Monthly Benefit** across all four steps—ignoring **Step 4 (Human-Review & Exception Tax)** is the #1 cause of negative-ROI production launches:



- **Worked Sanity Check:** On 50,000 claims/month at $12/claim baseline ($600k), 80% automation yields **$480k Gross Savings** (Step 2) against **$30k AI OpEx** (Step 3). If compliance requires a 6-minute ($6) audit on all 40,000 automated claims ($240k) plus 20-minute ($30) specialist rework on 2,500 subtle errors ($75k), **Step 4 Review Tax = $315k**, cutting Net Benefit from $450k down to **$135k/month**. If audit time approaches baseline manual time (e.g., 14 min vs. 12 min), Net ROI turns **negative**—fixable only by raising `pass^k` precision, adding $0 Tier 1 deterministic gates, and calibrating confidence routing so humans audit only genuinely uncertain slices.

Architectural Readiness & Feasibility Triage

Verdict	Criteria	Canonical Example	Architectural Action
1. Feasible as Scoped	Accuracy, `p95` latency, unit economics, and governance bounds all fit current models and data.	Internal IT helpdesk agent grounded on Agent Search with 4s streaming TTFT and ticket fallback.	Proceed to Level 1–3 eval harness + MVP build.
2. Feasible with Constraints *(Re-Scope)*	Core task works, but synchronous latency or unreviewed autonomy conflicts with physics/risk.	50-page contract redlining requested in `< 1s` with 100% autonomous legal sign-off.	Re-scope to **async background execution** (`background=True`, 30–60s) + **mandatory human approval gate (HITL)**.
3. Not Feasible *(Hard Stop)*	Requires 100.00% zero-defect determinism without review, `< 5 ms` control loops, or 10× negative unit economics.	High-frequency `< 5 ms` trading execution or unreviewed autonomous clinical dosing from raw handwriting.	**Reject LLM on critical path**; use deterministic rules/classical ML, or re-scope to assistive drafting with HITL.

11. Production Failure Modes & Glossary

Production Failure Mode Diagnostic Matrix

Observed Production Symptom	Root Cause	Correct Engineering Remediation	Trap / Wrong Fix to Avoid
Compliance agent scores 97% on `FINAL_RESPONSE_QUALITY` yet issues refunds without checking eligibility	**"Right answer, wrong path"** blind spot in outcome-only grading	Pair outcome autoraters with **`trajectory_in_order_match`** / **`trajectory_exact_match`** and a forbidden-tool check	Raising the `FINAL_RESPONSE_QUALITY` threshold from 0.90 to 0.99
Team has zero historical chat logs and cannot test multi-turn edge cases or `503` tool outages safely	Relying solely on static single-turn prompts or live prod backends	Run **2-Step Agent Simulation** (from an **Agent Registry** snapshot) + **Environment Simulation** fault injection	Running load/fault tests directly against live production payment APIs
Manual prompt edits to fix one bug cluster keep breaking three unrelated instructions	Manual "prompt whack-a-mole" without closed-loop optimization	Cluster traces via **Failure Cluster Analysis**, expand the golden set (with a **held-out split**), and run **Data-Driven Prompt Optimizer / Agent Optimizer**	Appending contradictory ALL-CAPS warnings to the bottom of the system prompt
Deploying a custom Streamable HTTP MCP server onto Agent Runtime fails	**Agent Runtime** hosts stateful agent orchestrators (`reasoningEngines`), not standalone MCP servers	Host custom Streamable HTTP MCP servers on **Cloud Run** (or **GKE**) and register them in **Agent Registry**	Embedding external MCP server daemons inside `session.state`
Users lose conversation context randomly on a TypeScript/Python agent hosted on Cloud Run	Storing session history in **ephemeral Cloud Run container RAM** across scale-to-zero recycles	Externalize state to **Agent Platform Sessions** (`agentengine://`), **Memorystore for Redis**, **Firestore**, or **Cloud SQL**	Increasing Cloud Run request timeout to 60 minutes without external state
Architect proposes self-hosting `gemini-4-argon` on GKE GPUs for VPC isolation	**Proprietary Gemini weights cannot be self-hosted** on customer clusters	Call managed Gemini endpoints inside **VPC Service Controls** (+ Provisioned Throughput if needed), or self-host open-weight **Gemma 4** on GKE	Creating a GKE GPU node pool to pull `gemini-4-argon` container weights
Agent Runtime deployment fails with `"Region temporarily at capacity"`	**Physical regional compute pool exhaustion** (not a project quota limit)	Deploy to an alternate supported region, reduce per-instance vCPU/RAM, or retry off-peak	Filing an IAM or project quota-increase support ticket and waiting
Every component passes isolated Level 2 evals at >95%, but end-to-end tasks fail 45% of the time	**Integration seam failure** (schema mismatch, oversized tool payloads, or state loss during compaction)	Add **Level 3 Trajectory & Seam Integration Tests**, strict JSON schemas, and structured `session.state` preservation	Tuning isolated Level 2 prompts further in single-step harnesses
Shadow mode rollout accidentally sends duplicate cancellation emails to real customers	Shadow pipeline executed **live mutating tools** instead of a read-only sandbox	Intercept/mock all state-mutating tools in shadow mode; allow only read-only retrieval	Running unsandboxed shadow mode on a smaller 5% traffic slice
AI saves 80% of drafting time, yet total department labor cost rises by 12%	**Step 4 Human-Review & Exception Tax** exceeds Step 2 Gross Savings	Add $0 Tier 1 code validators and calibrate confidence routing so humans audit only uncertain/high-risk slices	Ignoring human audit time in the FinOps ROI spreadsheet

Glossary

Term	Definition
3-Tier Grading Hierarchy	Evaluation ladder ordering checks from **Tier 1** (deterministic code/schema assertions, $0) → **Tier 2** (calibrated LLM autoraters) → **Tier 3** (human domain experts).
Adaptive Rubrics	Gen AI Evaluation Service capability (`GENERAL_QUALITY`) that dynamically generates prompt-specific pass/fail testable rubrics per input rather than using one static checklist.
2-Step Agent Simulation	Multi-turn synthetic stress-testing from an **Agent Registry** snapshot: Step 1 synthesizes `Starting Prompts` + `Conversation Plans` ; Step 2 executes simulated user dialogues.
Environment Simulation	Evaluation harness layer that intercepts outbound tool calls to inject deterministic faults (`HTTP 503` , `429` , timeouts, mocked rows) without touching live backends.
Online Evaluation Monitors	Continuous production evaluators (`OnlineEvaluator`) that asynchronously sample live Cloud Trace spans and score them with reference-free autoraters (`HALLUCINATION` , `TOOL_USE_QUALITY`).
Failure Cluster Analysis	Automated LLM grouping of failed simulation and low-scoring production traces into ranked root-cause buckets (Frequency × Severity).

Term	Definition
Zero-Shot vs. Data-Driven Optimizer	Agent Platform prompt optimization engines: **Zero-Shot** rewrites a raw prompt immediately using structural guidelines (no data); **Data-Driven / Agent Optimizer** iteratively optimizes `instruction` , `demonstration` , or `instruction_and_demo` against labeled data and eval metrics for a target model.
Dual-Attribution Audit Log	Cloud Logging / Audit Log record (`is_agentic=true`) capturing both the cryptographic SPIFFE **Agent Identity** (`principal://...`) and the initiating human user principal.
Agent Runtime vs. Cloud Run vs. GKE	Google Cloud runtime triad: **Agent Runtime** for turnkey stateful Python/ADK/A2A agents; **Cloud Run** for scale-to-zero polyglot containers and Streamable HTTP MCP servers; **GKE** (`Agent Substrate` / `Agent Sandbox`) for self-hosted **Gemma 4** on GPUs/TPUs and gVisor kernel isolation.
`pass@k` vs. `pass^k`	At-least-one success $(1 - (1 - p)^k$, valid only with a deterministic verifier) vs. every-run consistency (p^k, mandatory for live customer agents and unattended workflows).
Tool Payload Bloat & State Loss	Multi-turn failure modes where huge unpruned tool payloads dilute model attention or aggressive prose summarization drops a critical earlier UUID or parameter.
Human-Review Tax (Step 4 ROI)	Mandatory labor cost of human auditors reviewing flagged AI outputs and specialists fixing false positives—subtracted in Step 4 of enterprise ROI.