3/4/26

Test-2

1) What is DOM in JavaScript?

DOM (Document Object Model) is a tree-like structure of your HTML page.

JS uses DOM to access and modify HTML elements

Example:

```
document.getElementById("title").textContent = "Hello";
```

2) How do you select an element using JS?

Methods:

```
document.getElementById("id")
document.querySelector(".class")
document.querySelectorAll("p")
document.getElementsByClassName("class")
```

3) What is style.display property?

It controls visibility of an element

```
element.style.display = "none";
element.style.display = "block";
```

4) How do you hide an element?

```
document.getElementById("box").style.display = "none";
```

5) How do you show an element?

```
document.getElementById("box").style.display = "block";
```

6) Toggle function using if condition:

```
function toggleBox () {
    let el = document.getElementById("box");
    if (el.style.display === "none") {
        el.style.display = "block";
    } else {
        el.style.display = "none";
    }
}
```

7) Default value if display is not set

It returns:

" "

(empty string)

8) display: none vs visibility: hidden

* display: none — Element removed (no space)

* visibility: hidden — Element hidden but space remains

9) Toggle using ternary operator:

```
function toggleBox () {
    let el = document.getElementById ("box");
    el.style.display = el.style.display == "none" ?
                        "block" : "none";
}
```

10) Inline JavaScript vs Event listener (with example)

Inline JS

```
<button onclick = " toggleBox () " > click Me </button>
```

Problems:

* Messy HTML
* Hard to maintain
* Not reusable

Event listener

HTML:

```
<button id = "btn"> click Me </button>
<div id = "box" > hello </div>
```

JS:

```
function toggleBox () {
    let el = document.getElementById ("box");
        el.style.display =
            el.style.display === "none" ? "block" : "none";
}
document.getElementById ("btn")
    .addEventListener ("click", toggleBox);
```