Test

28/2/26

1) Difference b/w tag and an element

Tag : The keyword inside angle brackets

Element : The complete structure (opening tag + content + closing tag).

Example : Hello

2) What are block-level elements? Give three examples and explain their behavior.

Block level elements always start on new line, automatically the browsers add some space before and after the element.

Example : , < div >

Behavior :

* Always start on a new line.
* Take full width.
* Can contain inline & block elements

3) What are inline elements? How are they different from block-level elements.

Inline elements are does not starts at new line. It only takes up as much width as necessary. Example :

Block-level elements supports full width & Always starts with a new line but inline support limited width & it does not start on a new line.

4) If you apply width & height to an inline element, what happens? why?

When applying width & height it doesn't takes because in the inline element width & height are ignores

inline element follows the elements only takes up as much as necessary when we use with inline-block they respect the width & height.

inline element only occupy space based on their content and do not follow the box model.

5) Explain the D/B semantic & non semantic elements with examples.

Semantic	Non-semantic
-> Describes the purpose of the content to browsers & developers	-> does not describe content meaning
	-> They are only used for layout and styling
Example:	Example:
< header >	< div >
< article >	< span >
< footer >	

6) Why is <header> better than for page structure?

Both can contain content

header → Semantic

* Describes the meaning
* Helps search engines
* Accessibility

div → non semantic

No meaning

no help

Not clear

7) What is the d/B <b> and ?

<b> → used for bold text

 → The text has very important content.

8) What is the d/B <i> and ?

<i> → Used to style text in italic

→ Does not add importance

→ Purely for appearance.

 → Used to emphasize text

→ Adds importance

→ screen readers stress the word.

9) When should we use <mark> and <small>? Give real-time examples.

<mark> → used to highlight that is relevant or important to the user

<small> → Used for side notes, disclaimers, copyright, or less important text

appearance smaller text.

Example:

<p> Search result : Learn <mark> HTML </mark>

<p> <small> © 2026 My website. All rights reserved.
</ small ></ /p>

10) What is the purpose of the <a> tag?

<a> tag is used to create hyperlinks that allow users to navigate from one page to another

11) Mandatory in the <a> tag? What happens if is not given?

The mandatory attribute is : href

href stands for Hypertext Reference

<a href = "https: // example . com" > Visit website</a>

happens if is not given:

* Text appears normal
* Not clickable
* No navigation happens

12) D/B target = "_blank" and target "= _self"

The target attribute in the <a> tag specifies where the linked page will open.

<a href = "https: // example.com" target = "_blank">
open in new tab </ a>

< target = "_self" → opens the link in same tab

Example:

<a href = "https://example.com" target = "_self">
Open in same tab </a>

13) Can an <a> tag wrap a block-level element? Explain your answer.

HTML 4: <a> was an inline element and could not contain block-level elements like or <p>.

HTML 5: <a> can wrap block elements. This allows entire sections to become clickable

14) What happens if we place a block-level element inside an inline element? Is it valid in HTML5?

Placing a block-level element inside an inline element may still render in HTML5, but it is not recommended because inline element are meant to contain text or inline elements only. It can cause layout issues and is considered poor HTML structure.

15) Write a small [illegible] that includes

```
<html>
<head>
    <title> My website </title>
</head>
<body>
    <div>
        welcome to my page
    </div>
    <p> This is <strong> Important </strong>
Information <p>
</body>
</html>
```