

Proceedings Track

Truth Has a Boundary. A Machine-Verified Topological Constraint on Models That Separate Truth from Falsehood

Editors: List of editors' names

Abstract

Probing studies read truth off a language model's activations, treating truth as a continuous decodable field over representation space. We ask what the shape of that space requires of any model answering over it. Our central result is a coupling theorem. If a continuous model on a connected representation space ever answers truly and ever answers falsely, and its confidence separates true answers from false ones, then some query must carry confidence exactly at the threshold while its answer sits exactly on the truth boundary. The theorem mentions no safety guarantee, so it does not depend on how a guarantee treats its own threshold. A guarantee including its threshold is impossible, and one excluding it survives but is silent at the coupled query. Under Lipschitz regularity the coupled point sits inside an ambiguity tube of computable width, any feasible system must carry strictly positive truth-side slack, and for nonzero linear probes the truth boundary is an affine hyperplane of codimension one. A symmetry version needs no coverage assumption, a discrete analysis prices the removal of topology, and multi-turn and stochastic extensions follow, with the stochastic dichotomy deriving falsehood. We machine-verify every theorem in Lean 4 against Mathlib with no sorry placeholders, and the main results reduce to the three standard kernel axioms. Experiments observe the predicted coupling in five small language models, with the model's own confidence signal and against null baselines, and an adversarial attempt to train away the slack plateaus strictly above zero.

Keywords: representational geometry, topology, uncertainty, calibration, intermediate value theorem, Borsuk-Ulam, formal verification, Lean

1. Introduction

Truth is geometrically simple inside language models. Linear probes separate true from false statements in activation space, unsupervised methods find latent knowledge, and steering along learned directions makes models more truthful (Marks and Tegmark, 2024; Azaria and Mitchell, 2023; Burns et al., 2023; Li et al., 2023; Zou et al., 2023). All of this work treats truth as a continuous, decodable field over representation space.

We take that picture seriously as geometry. Suppose truth is a continuous scalar field on a connected representation space, and the model's answers and confidences are continuous fields on the same space, assumptions mentioning no architecture, training, or scale, applying to any model whose fields are defined and continuous on the stated domain. What they yield is a coupling theorem. If the model ever answers truly and ever answers falsely, and its confidence separates true answers from false ones, then some query carries confidence exactly at the threshold while its answer sits exactly on the truth boundary (Figure 1).

The proof is short, and the theorem's value lies in what it does not mention, no safety guarantee and no threshold convention, so every policy question becomes a corollary. An inclusive guarantee is impossible, an exclusive one survives but says nothing at the point topology guarantees, slack buys safety, and for the nonzero linear probes used in practice the truth boundary is an affine hyperplane.




Figure 1: The coupling theorem in one picture. Along any true-to-false path, separation forces confidence above τ on the strictly true side and below on the strictly false side, so both fields must cross, and the crossings coincide at the coupled point x_0 inside the ambiguity tube of Theorem 12.

Contributions. The boundary coupling theorem with its corollary taxonomy (Section 3); the geometry of the boundary, closed, crossed by every true-to-false path, a hyperplane for nonzero linear probes, with an ambiguity tube of strictly positive truth-side slack (Section 4); a symmetry version needing no coverage (Section 5); a discrete analysis with multi-turn and stochastic extensions (Section 6); and full machine verification (Section 6, Table 2).

The mathematics is elementary, and the contribution is not technical difficulty. It is a framing in which exact threshold uncertainty is a topological property of representation space, precision, since the theorems name every assumption in play, and verification, since we machine-check every statement, leaving the premises as the only thing to argue about. The theorems do not say models err often, and the coupled point is neither strictly true nor strictly false.

Related work. Statistical and computability arguments make hallucination inevitable in other senses (Kalai and Vempala, 2024; Kalai et al., 2025; Xu et al., 2024); ours is topological and yields uncertainty rather than confident falsehood. The probing literature models truth as a continuous decodable field (Marks and Tegmark, 2024; Burns et al., 2023; Azaria and Mitchell, 2023; Li et al., 2023; Zou et al., 2023; Park et al., 2024), exactly our hypothesis on δ , and our results give that program a frontier. Connected-domain modeling follows the manifold hypothesis (Fefferman et al., 2016; Cai et al., 2021), and the symmetry section is a scalar relative of Borsuk-Ulam (Borsuk, 1933; Matoušek, 2003). To our knowledge this is the first fully machine-verified impossibility-style result on model truthfulness at the level of representation geometry (de Moura and Ullrich, 2021; mathlib Community, 2020). Appendix A extends all four threads.

2. The setting

$\mathcal{X}$ is a topological space of queries as the model represents them, prompt embeddings or residual-stream states, $\mathcal{A}$ a topological space of answers, and our standing assumption is simple.

(T) $\mathcal{X}$ is connected and nonempty.

Proceedings Track

Standard practice models ambient embedding spaces as $\mathbb{R}^d$ or connected submanifolds, satisfying (T), though a token-driven model’s reachable set may be disconnected. When guarantees range over the ambient space, as they do whenever a probe or steering vector applies at arbitrary points, (T) holds. Continuity likewise idealizes trained networks, softmax and embeddings being continuous while argmax decoding is not, and Section 6 prices dropping either idealization.

Definition 1 (Model and truth fields) *A model is a map $F = (a, c)$ from $\mathcal{X}$ to $\mathcal{A} \times \mathbb{R}$, with answer $a(x)$ and scalar confidence $c(x)$, continuous if both components are. A truth field is a continuous δ from $\mathcal{X} \times \mathcal{A}$ to $\mathbb{R}$, a signed truth-distance, negative on strictly true answers, positive on strictly false ones, with the truth boundary as its zero set. The realized truth field is $\delta_F(x) = \delta(x, a(x))$.*

A linear probe $w^\top x - b$ on activations (Marks and Tegmark, 2024; Burns et al., 2023) is a candidate continuous δ_F , its zero set the probe’s classification boundary. Whether that coincides with semantic truth away from the fitted samples is an empirical premise, not a theorem, and our results hold under it.

Definition 2 (Truth-separating at threshold τ) *Fix a threshold τ , a truth slack $\varepsilon \geq 0$, and a confidence margin $\gamma \geq 0$. F is (ε, γ) -separating at τ if $\delta_F(x) < -\varepsilon$ implies $c(x) > \tau + \gamma$ and $\delta_F(x) > \varepsilon$ implies $c(x) < \tau - \gamma$. The slack is in units of δ_F and the margin in units of c , so the condition survives independent rescaling. Exactly separating means both are zero.*

Definition 3 (Covering) *F is ε -covering if some query has $\delta_F < -\varepsilon$ and some has $\delta_F > \varepsilon$, at $\varepsilon = 0$ somewhere strictly right and somewhere strictly wrong.*

Definition 4 (Guarantees) *A threshold-inclusive guarantee says that $c(x) \geq \tau$ implies $\delta_F(x) < 0$, and a threshold-exclusive one that $c(x) > \tau$ implies $\delta_F(x) < 0$.*

Any model ever right and ever wrong satisfies covering, separation idealizes a perfect truth probe used as confidence, the guarantees idealize mitigation, the coupling results hold at any threshold, and the biconditional variants sit at one half.

Remark 5 (This is not statistical calibration) *Separation is pointwise and much stronger than statistical calibration (Guo et al., 2017), and one-way by construction. The biconditional variant adds the converses, so the sign of δ_F and the side of the threshold determine each other. The symmetry and discrete results use it, and it implies the one-way pair, Lean `strictCalibrated_to_epsCalibrated_zero_half`.*

3. The boundary coupling theorem

Topology enters through one theorem needing no confidence.

Theorem 6 (Boundary existence) *Let $\mathcal{X}$ satisfy (T), the answer map and truth field be continuous, and F be 0-covering. Then some x_0 has $\delta_F(x_0) = 0$, since δ_F is continuous with both signs and the IVT applies on the connected space. Lean `model_truth_boundary_nonempty`, IVT step `IsPreconnected.intermediate_value2`.*

Proceedings Track

Theorem 7 (Boundary coupling) *Let $\mathcal{X}$ satisfy (T). Let c be continuous, and let F be 0-covering and exactly separating at τ . Then some x_0 satisfies both*

$$c(x_0) = \tau \quad \text{and} \quad \delta_F(x_0) = 0.$$

Proof Separation converts the coverage witnesses into confidence witnesses on both sides of τ , and the IVT gives x_0 with $c(x_0) = \tau$. Were $\delta_F(x_0)$ negative, separation would give $c(x_0) > \tau$, and positive, $c(x_0) < \tau$, so $\delta_F(x_0) = 0$. This is Lean theorem `boundary_coupling`. ■

The theorem mentions no guarantee, so no threshold convention affects it. We call such an x_0 a *coupled point* (Figure 1), and what it means for safety is policy, with each policy a corollary.

Corollary 8 (Policy taxonomy) *Adding a threshold-inclusive guarantee to Theorem 7’s hypotheses is jointly contradictory, the trilemma, since coverage, exact separation, and an inclusive guarantee cannot jointly hold. Adding a threshold-exclusive guarantee yields no contradiction, but the coupled point satisfies $c(x_0) = \tau$, its antecedent fails exactly there, and the system owns a boundary query about which its guarantee says nothing. Lean theorems `closed_guarantee_impossible`, `hallucination_trilemma`, and `open_guarantee_silent`.*

Defining the guarantee with a strict inequality therefore does not dissolve the impossibility. The coupling theorem is convention-free, the convention only selects which clause of the taxonomy applies, and the coupled point exists under either convention.

4. The geometry of the boundary

Theorem 9 (Closed, and crossed by every path) *For any topological $\mathcal{X}$ and $\mathcal{A}$, continuous δ and answer map, $\{x \mid \delta_F(x) = 0\}$ is closed in $\mathcal{X}$, and any continuous path from a query answered strictly truly to one answered strictly falsely contains a point exactly on the truth boundary. Lean theorems `model_truth_boundary_isClosed` and `path_crosses_truth_boundary`.*

Theorem 10 (Linear probes have hyperplane boundaries) *Let f be a nonzero linear probe on a d -dimensional real space with offset b . Then $\{x \mid f(x) = b\}$ is an affine translate of the kernel of f , of dimension exactly $d - 1$. Lean theorems `linear_probe_boundary_coset` and `linear_probe_boundary_dim`, by rank-nullity.*

Theorem 11 (Nonlinear boundaries are hyperplanes to first order) *Let f be differentiable at a boundary point x_0 of a d -dimensional real space, with nonzero derivative L . Then every neighborhood of x_0 contains strictly true and strictly false points, and for every $\varepsilon > 0$ some $\delta > 0$ has every boundary point x within δ satisfying $|L(x - x_0)| \leq \varepsilon \|x - x_0\|$, deviating sublinearly from the tangent hyperplane $x_0 + \ker L$ of dimension $d - 1$. Lean theorems `regular_point_is_crossing`, `nonlinear_boundary_tangent`, and `tangent_hyperplane_dim`.*

Proceedings Track

The hyperplane picture therefore survives nonlinearity to first order, every regular point a sign crossing generating local coverage for free against a codimension-one tangent hyperplane. Next we quantify what slack changes.

Theorem 12 (Corridor and tube) *Let c be L_c -Lipschitz and δ_F be L_δ -Lipschitz. For $\gamma > 0$, queries with $c \geq \tau + \gamma$ and with $c \leq \tau - \gamma$ are at distance at least $2\gamma/L_c$, and for a coupled point x_0 , every query within distance r of x_0 has truth margin at most $L_\delta r$ and confidence within $L_c r$ of the threshold. Lean theorems `confidence_gap_width`, `ambiguity_tube`, and `truth_margin_tube`.*

The coupled point therefore centers a tube of near-ambiguous queries, decisive regions no closer than the corridor width.

Theorem 13 (Approximate coupling, and slack must be positive) *Let $\mathcal{X}$ satisfy (T), let c be continuous, and let F be ε -covering, (ε, γ) -separating at τ , and carry a threshold-inclusive guarantee. Then some x_0 has $c(x_0) = \tau$ and $-\varepsilon \leq \delta_F(x_0) < 0$, and consequently the truth slack satisfies $\varepsilon > 0$ for every margin $\gamma \geq 0$, so zero truth slack is infeasible. These are Lean theorems `two_slack_approx_coupling`, `exact_from_approx`, and `truth_slack_must_be_positive`.*

Slack is therefore a geometric budget, positivity attaching to the truth side alone. We read the infimum of feasible truth slack as the system’s truth-boundary width, with the relative width of Section 7 as a dimensionless proxy, and under the guarantee no query with confidence between τ and $\tau + \gamma$ sits exactly on the boundary (Lean `no_boundary_in_upper_band_two_slack`).

5. Symmetry replaces coverage

Symmetry can replace coverage. Suppose semantic negation acts on $\mathcal{X}$ as a continuous involution σ with no fixed point and the realized truth field is odd under it, idealizing negation’s measured reflection of truth directions (Marks and Tegmark, 2024).

Theorem 14 (Odd fields vanish) *Let $\mathcal{X}$ satisfy (T) with such an action σ , and let g be continuous and odd under σ . Then g has a zero, by the IVT between any x and σx . This is Lean theorem `antipodal_odd_has_zero`.*

This is the scalar shadow of Borsuk-Ulam, needing no sphere. Two refinements make it robust and concrete.

Theorem 15 (Robust and concrete oddness) *Let $\mathcal{X}$ satisfy (T), σ map $\mathcal{X}$ to itself, and g be continuous with $|g(\sigma x) + g(x)| \leq \varepsilon$ for all x . Then some x has $|g(x)| \leq \varepsilon/2$. Moreover, on the unit sphere of $\mathbb{R}^d$, $d \geq 2$, with negation the antipodal map, every continuous odd field vanishes somewhere on the sphere. Lean theorems `approx_odd_near_zero` and `sphere_odd_has_zero`.*

The near-boundary point degrades linearly with the defect, and the sphere is, up to a learned affine map, where layer normalization places its states, negation the candidate antipode.

Proceedings Track

Theorem 16 (Antipodal coupling) *Let $\mathcal{X}$ satisfy (T) with a free continuous involution σ , F be continuous with biconditional separation at $\frac{1}{2}$, and δ_F be odd. Then some x has $c(x) = \frac{1}{2}$ and $\delta_F(x) = 0$. Lean `antipodal_hallucination_trilemma`.*

No coverage hypothesis appears, so a negation-closed family of questions meets the truth boundary by symmetry alone. Equivariance, usually a design virtue (Bronstein et al., 2021), is here the engine of the obstruction.

6. Leaving the continuum, adding turns and randomness

Token spaces are finite, and one may object that connectedness does illegitimate work. The discrete analysis prices the objection, since without topology we must assume the boundary witness rather than derive it.

Theorem 17 (Discrete impossibility) *Let $\mathcal{X}$ and $\mathcal{A}$ be arbitrary sets with arbitrary F and δ , with biconditional separation at $\frac{1}{2}$. If some query has $\delta_F = 0$, a threshold-inclusive guarantee fails, and such a guarantee is possible exactly when no boundary query exists. These are Lean theorems `boundary_question_impossible` and `faithful_iff_boundary_free`.*

The assumed witness is what connectedness derived free in Theorem 6, and without it a crossing survives.

Proposition 18 (Discrete sign change) *Let g map $\{0, \dots, n\}$ to $\mathbb{R}$ with $g(0) < 0 < g(n)$. Then some i has $g(i) < 0 \leq g(i+1)$. This is Lean theorem `discrete_sign_change`.*

Along any token path from true to false, δ_F crosses zero between adjacent steps, a straddling pair rather than a boundary state, hence no contradiction alone. The continuum upgrades the crossing into a witness. Interaction does not escape, since $\mathcal{X}^T$ is connected and the arguments transport verbatim (`multi_turn_history_dependent`). Nor does randomization. On the expected fields the coupling theorem yields expected confidence one half at expected truth-distance zero (`stochastic_coupling_expected`), and a dichotomy converts expectation into sampling behavior.

Theorem 19 (Stochastic dichotomy) *Let (Ω, μ) be a probability space and let c, d be real functions on Ω with d integrable and of mean zero. Suppose sample faithfulness holds almost everywhere, meaning $c \geq \frac{1}{2}$ implies $d < 0$, and suppose $\mu\{c \geq \frac{1}{2}\} > 0$. Then $\mu\{d > 0\} > 0$. This is Lean theorem `stochastic_dichotomy`.*

A model faithful on almost every sample and confident with positive probability at a coupled point must emit strictly false answers with positive probability. Randomization spreads the boundary across samples, and here alone the theory derives falsehood.

Machine verification. Every theorem and proposition corresponds to a named, sorry-free Lean 4 result (de Moura and Ullrich, 2021; mathlib Community, 2020). The artifact builds with zero errors, axiom audits reduce each main theorem to the three standard kernel axioms, Table 2 maps every result to its identifier, and the prose claims nothing beyond the formal statements.

TRUTH HAS A BOUNDARY

Proceedings Track

Table 1: Boundary coupling and null calibration in five small models. Probe and Head are held-out accuracies, Verbal the model’s own answer accuracy, Cross the mean confidence at the probe’s zero crossing, Gap the median crossing distance as a fraction of the path, Width the relative boundary width, Decisive the endpoint-decisive paths of the endogenous field, Endo its median gap on them, Perm and Rand the median null gaps over twenty seeds.

Model	Layer	Probe	Head	Verbal	Cross	Gap	Width	Decisive	Endo	Perm	Rand
GPT-2 (124M)	9/12	0.77	0.72	0.48	0.52	0.25	0.33	23/53	0.23	0.48	0.33
Pythia-410M	18/24	0.82	0.77	0.50	0.51	0.20	0.36	0/84	none	0.45	0.45
Qwen2.5-0.5B	12/24	0.96	0.96	0.71	0.49	0.10	0.20	128/137	0.13	0.43	0.40
Phi-1.5 (1.3B)	18/24	0.72	0.72	0.56	0.43	0.31	0.37	53/80	0.40	0.48	0.38
Qwen2.5-1.5B	14/28	1.00	1.00	0.96	0.54	0.05	0.11	146/147	0.08	0.45	0.45




Figure 2: Upper pair of rows, the truth probe (normalized, median and interquartile band) and the independently trained confidence along true-to-negation paths, the dotted line marking the mean probe zero crossing where confidence passes near one half. Lower pair, the same with the model’s own probability of answering true from patched final-block states, decisive paths where any exist. The Qwens sweep through one half at the boundary, Pythia-410M answers true everywhere so the premise fails, and GPT-2 and Phi-1.5 sit between.

7. Empirical illustration

We checked whether the idealized theory is visible in five open models, GPT-2 (124M), Pythia-410M, Qwen2.5-0.5B, Phi-1.5 (1.3B), and Qwen2.5-1.5B, on the 1496 matched city statements and negations of [Marks and Tegmark \(2024\)](#). We embed each statement at its final token, select the layer whose probe validates best, train the truth field δ_F as a linear logistic probe on one city split and the confidence field c as a second head on a disjoint split with a different seed, independently trained readouts of the same space, the canonical construction the theory models. We interpolate hidden states from each true statement to its negation, record both fields, and keep paths whose endpoints the probe classifies correctly, 83, 104, 137, 66, and 148 paths, holding test cities out of both splits.

Proceedings Track

Findings. Table 1 and Figure 2 summarize. Probes separate truth at 0.72 to 1.00 while only the Qwens verbalize it above chance, 0.71 and 0.96 against 0.48 to 0.56, the known represented-verbalized gap. Every kept path shows the predicted adjacent sign change, mean confidence at the probe’s zero crossing is 0.52, 0.51, 0.49, 0.43, and 0.54, and the gap between the two crossings tracks probe accuracy monotonically, from 0.31 for Phi-1.5, the weakest probe, to 0.05 for Qwen2.5-1.5B, the strongest. The ordering follows separation, not parameter count, since Phi-1.5 outweighs all but Qwen2.5-1.5B yet separates worst, a sweep of all its 24 layers topping out at 0.73 test accuracy, while the Qwen pair shows scale helping through separation, probe 0.96 to 1.00 and the gap halved. The relative boundary width, median $|\delta_F|$ where confidence is in $[0.4, 0.6]$ over endpoint scale, runs 0.37 to 0.11, and the kNN graph keeps true and false in one shared main component in all five models, though three show a second component, identified below.

The model’s own confidence. Both fields above target truth, so we repeat the experiment with a confidence field the model supplies itself, no trained head, read through unembedding weights fixed by pretraining. We capture the final block’s last-token state under a question template, interpolate as before, patch the state back in, and read the model’s own probability of answering true, the probe trained on a disjoint split of the same states, 53, 84, 137, 80, and 147 kept paths. A path satisfies the separation premise when this field sits on the correct side of one half at both endpoints. Table 1 and Figure 2 report the result. Qwen2.5-1.5B meets the premise on 146 of 147 paths at gap 0.08 and Qwen2.5-0.5B on 128 of 137 at 0.13, against nulls of 0.40 and above. Pythia-410M answers true regardless, so the premise fails everywhere and the theory predicts nothing. GPT-2 (23 of 53 decisive) and Phi-1.5 (53 of 80, verbal 0.56) have gaps at null, so endpoint decisiveness without verbal capability is not separation. Coupling with the model’s own uncertainty appears cleanly where the premise holds throughout, and never where it fails.

Null baselines. Permuted-label and random-direction heads, twenty seeds each on the same kept paths, calibrate the gaps (Table 1). The trained-head gaps of 0.25, 0.20, 0.10, 0.31, and 0.05 fall below every null median, and below the entire null range for Pythia-410M and both Qwens, while GPT-2 and Phi-1.5 sit inside the random-head range, weak evidence alone. Bootstrap 95 percent intervals over ten thousand path resamples are 0.175 to 0.325, 0.15 to 0.287, 0.10 to 0.125, 0.175 to 0.375, and 0.05 to 0.075, with 0.10 to 0.15 and 0.075 to 0.10 for the Qwens’ endogenous fields, every upper bound at or below its null median except endogenous GPT-2 and Phi-1.5.

A second dataset. The same pipeline on the 354 Spanish-English translation pairs from the same source replicates in both Qwens, probes 0.98 and 0.94 with gaps 0.05 and 0.10, while Pythia-410M and Phi-1.5 drop to probes 0.70 and 0.71 with gaps at null and GPT-2 is at chance with too few paths to score, so coupling again appears exactly where separation holds.

What the second component is. Where a second kNN component appears it splits exactly by surface form, positives in one and negations in the other, with true and false in equal measure inside each. Syntax separates activations, not truth, and the interpolation paths are ambient line segments, connected regardless of clustering.

Proceedings Track

Measuring the oddness defect. The matched pairs also measure the oddness premise of Section 5. The defect $|\delta_F(x) + \delta_F(\sigma x)|$ relative to endpoint scale has median 0.40, 0.43, 0.30, 0.53, and 0.17, smallest for the strongest model. Exact oddness fails, which is why Theorem 15 carries the approximate version, whose near-boundary point survives any defect. The width column of Table 1 likewise gives the slack diagnostic of Section 4 an empirical proxy, 0.11 to 0.37.

Nonlinear probes. A linear truth field crosses zero along a linear path by construction, so we replace both fields with one-hidden-layer MLPs on the same splits, removing that guarantee and the hyperplane boundary. The MLP probes reach 0.79, 0.87, 0.97, 0.80, and 1.00 with 124, 121, 144, 104, and 149 kept paths, every path still crosses zero, and at least 98 percent cross exactly once, each crossing the clean sign change Theorem 11 derives at regular points. The coupling tightens or holds, gaps 0.15, 0.20, 0.075, 0.175, and 0.05, confidence at the crossing 0.42, 0.50, 0.42, 0.38, and 0.49, so the coupling is not an artifact of linearity.

An adversarial falsification attempt. The strongest test of an impossibility result is a maximally empowered attempt to violate it. We freeze the truth field, train a confidence head on the forbidden objective, above one half where the field says true and below elsewhere, guarantee weighted five to one, on all non-test statements plus fresh interpolants each epoch, and evaluate on 21,000 to 30,000 held-out path points per model. Theorem 13 predicts a positive slack floor, boundary-localized failures, and a trade against guarantee violations, and all three appear. The slack plateaus between 0.22 and 0.91 of endpoint scale, exactly flat over Qwen2.5-0.5B’s final fifteen epochs, never zero; median failing depth shrinks from 0.40 or more to 0.04 to 0.11, concentrating in the boundary tube; and guarantee violations persist. The theorem forbids only exactly zero slack for a fixed head, Theorem 12 pricing the escape, so the plateau reflects this adversary’s regularity and sharpening only thins the tube around a boundary that does not go away.

What this does and does not show. The premises hold to varying degrees, disjoint splits rule out shared training data, the nonlinear replication removes the analytic sign-change guarantee, and the endogenous experiment addresses the shared-target concern where the model verbalizes truth. Code, data, and results are in the supplementary material.

8. Discussion

The theorem rests on connectedness, continuity, coverage, and separation, the trilemma adding an inclusive guarantee, and each hypothesis admits relaxation at a named price (Appendix A). Refusal training is connectedness surgery, restricting to reachable queries is the same move while probing and steering deploy over the ambient space, and dropping continuity keeps only the adjacent crossing. The recommended stance is band separation (Theorem 13), the infimum of feasible truth slack a measurable diagnostic. The results are existence statements, so nothing follows about error rates, Theorem 19 alone derives falsehood, and the truth field idealizes probe behavior, Theorem 15 pricing oddness. With Theorem 11 and the scalar Borsuk-Ulam analog verified, what remains is the full theorem for jointly odd axes (Engels et al., 2025).

Proceedings Track

References

- Amos Azaria and Tom Mitchell. The internal state of an LLM knows when it’s lying. In *Findings of the Association for Computational Linguistics: EMNLP*, 2023.
- Karol Borsuk. Drei Sätze über die n -dimensionale euklidische Sphäre. *Fundamenta Mathematicae*, 20:177–190, 1933.
- Michael M. Bronstein, Joan Bruna, Taco Cohen, and Petar Veličković. Geometric deep learning: Grids, groups, graphs, geodesics, and gauges. *arXiv preprint arXiv:2104.13478*, 2021.
- Collin Burns, Haotian Ye, Dan Klein, and Jacob Steinhardt. Discovering latent knowledge in language models without supervision. In *International Conference on Learning Representations (ICLR)*, 2023.
- Xingyu Cai, Jiaji Huang, Yuchen Bian, and Kenneth Church. Isotropy in the contextual embedding space: Clusters and manifolds. In *International Conference on Learning Representations (ICLR)*, 2021.
- Leonardo de Moura and Sebastian Ullrich. The Lean 4 theorem prover and programming language. In *Automated Deduction – CADE 28*, pages 625–635. Springer, 2021.
- Joshua Engels, Eric J. Michaud, Isaac Liao, Wes Gurnee, and Max Tegmark. Not all language model features are one-dimensionally linear. In *International Conference on Learning Representations (ICLR)*, 2025.
- Sebastian Farquhar, Jannik Kossen, Lorenz Kuhn, and Yarin Gal. Detecting hallucinations in large language models using semantic entropy. *Nature*, 630:625–630, 2024.
- Charles Fefferman, Sanjoy Mitter, and Hariharan Narayanan. Testing the manifold hypothesis. *Journal of the American Mathematical Society*, 29(4):983–1049, 2016.
- Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q. Weinberger. On calibration of modern neural networks. In *Proceedings of the 34th International Conference on Machine Learning (ICML)*, 2017.
- Felix Hensel, Michael Moor, and Bastian Rieck. A survey of topological machine learning methods. *Frontiers in Artificial Intelligence*, 4:681108, 2021.
- Saurav Kadavath, Tom Conerly, Amanda Askell, Tom Henighan, Dawn Drain, Ethan Perez, Nicholas Schiefer, Zac Hatfield-Dodds, Nova DasSarma, Eli Tran-Johnson, Scott Johnston, Sheer El-Showk, Andy Jones, Nelson Elhage, Tristan Hume, Anna Chen, Yuntao Bai, Sam Bowman, Stanislav Fort, Deep Ganguli, Danny Hernandez, Josh Jacobson, Jackson Kernion, Shauna Kravec, Liane Lovitt, Kamal Ndousse, Catherine Olsson, Sam Ringer, Dario Amodei, Tom Brown, Jack Clark, Nicholas Joseph, Ben Mann, Sam McCandlish, Chris Olah, and Jared Kaplan. Language models (mostly) know what they know. *arXiv preprint arXiv:2207.05221*, 2022.

Proceedings Track

Adam Tauman Kalai and Santosh S. Vempala. Calibrated language models must hallucinate. In *Proceedings of the 56th Annual ACM Symposium on Theory of Computing (STOC)*, 2024.

Adam Tauman Kalai, Ofir Nachum, Santosh S. Vempala, and Edwin Zhang. Why language models hallucinate. *arXiv preprint arXiv:2509.04664*, 2025.

Kenneth Li, Oam Patel, Fernanda Viégas, Hanspeter Pfister, and Martin Wattenberg. Inference-time intervention: Eliciting truthful answers from a language model. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2023.

Samuel Marks and Max Tegmark. The geometry of truth: Emergent linear structure in large language model representations of true/false datasets. In *First Conference on Language Modeling (COLM)*, 2024.

The mathlib Community. The Lean mathematical library. In *Proceedings of the 9th ACM SIGPLAN International Conference on Certified Programs and Proofs (CPP)*, pages 367–381, 2020.

Jiří Matoušek. *Using the Borsuk–Ulam Theorem: Lectures on Topological Methods in Combinatorics and Geometry*. Springer, 2003.

Gregory Naitzat, Andrey Zhitnikov, and Lek-Heng Lim. Topology of deep neural networks. *Journal of Machine Learning Research*, 21(184):1–40, 2020.

Kiho Park, Yo Joong Choe, and Victor Veitch. The linear representation hypothesis and the geometry of large language models. In *International Conference on Machine Learning (ICML)*, 2024.

Ziwei Xu, Sanjay Jain, and Mohan Kankanhalli. Hallucination is inevitable: An innate limitation of large language models. *arXiv preprint arXiv:2401.11817*, 2024.

Andy Zou, Long Phan, Sarah Chen, James Campbell, Phillip Guo, Richard Ren, Alexander Pan, Xuwang Yin, Mantas Mazeika, Ann-Kathrin Dombrowski, Shashwat Goel, Nathaniel Li, Michael J. Byun, Zifan Wang, Alex Mallen, Steven Basart, Sanmi Koyejo, Dawn Song, Matt Fredrikson, J. Zico Kolter, and Dan Hendrycks. Representation engineering: A top-down approach to AI transparency. *arXiv preprint arXiv:2310.01405*, 2023.

Appendix A. Extended discussion and related work

Hallucination inevitability. Kalai and Vempala (2024) show statistically that calibrated models must hallucinate on facts seen once in training, Kalai et al. (2025) extend this line, and Xu et al. (2024) give a computability-theoretic inevitability argument. Our mechanism is topological, lives in representation space, localizes the conclusion at the truth boundary, and is more modest, since the deterministic theorems yield uncertainty rather than confident falsehood.

Proceedings Track

Geometry of truth in representations. Linearly decodable truth (Marks and Tegmark, 2024), unsupervised latent-knowledge discovery (Burns et al., 2023), lie detection from internal states (Azaria and Mitchell, 2023), and causal steering along truth directions (Li et al., 2023; Zou et al., 2023) all model truth as a continuous decodable field on activation space, and the linear representation hypothesis formalizes concepts as directions in that space (Park et al., 2024), and the literature treats confidence signals (Farquhar et al., 2024; Kadavath et al., 2022) the same way. Topological analyses of networks (Naitzat et al., 2020; Hensel et al., 2021) and geometric deep learning (Bronstein et al., 2021) engineer or analyze such structure, and we derive constraints from it.

Disconnect the space. Abstention breaks the argument at the IVT step, since declining to answer on an open region deletes it from the domain and can disconnect the true region from the false region. Refusal training, on this reading, is connectedness surgery. Under the symmetry version the cut must separate every representation from its negation image, so piecemeal refusal is not enough.

Quantify only over reachable queries. The coupled point may be an ambient activation that no real prompt produces, and a guarantee quantified only over reachable representations is then untouched. The objection is fair, and it is the domain version of disconnecting the space. But probing and steering pipelines apply their readouts at interpolated and edited activations, which is deployment over the ambient space, and a guarantee over the uncertified reachable set inherits every unknown of that set. Restricting the domain is a coherent stance if stated as one.

Give up coverage or continuity. A model that never answers strictly falsely escapes. That is vacuous for general-purpose systems and meaningful for retrieval-grounded ones restricted to verified content. Dropping continuity also escapes, at the price computed in Section 6, where only the adjacent-crossing statement survives unconditionally.

Implications for probing and steering. Truth-probe pipelines posit a continuous δ_F , and steering moves representations relative to its zero set (Li et al., 2023; Zou et al., 2023). Completing such a pipeline over a connected domain with both truth values realized yields an exact-uncertainty point on the probe’s own boundary, a hyperplane for linear probes, and mitigation effort should go there.

Appendix B. Formal statement conventions

The Lean formalization states results over arbitrary topological spaces Q and A , with a `ConnectedSpace` instance on Q , a model M from Q to $A \times \mathbb{R}$, and a truth field `delta` on $Q \times A$ (rendered here in ASCII). The realized truth field is

```
fun q => delta (q, (M q).1)
```

and confidence is `(M q).2`. We name the main conditions as follows, and some identifiers retain historical names.

- `TwoSlackSeparating M delta c eps gamma` is separation at threshold c with truth slack eps and confidence margin gamma . The equal-slack case is `EpsCalibrated M delta c eps`, definitionally `(epsCalibrated_iff_twoSlack)`.

Proceedings Track

- Covering with slack ϵ is `EpsCovering M delta epsilon`.
- The biconditional variant at threshold one half is `StrictCalibrated M delta`.
- The threshold-inclusive guarantee at threshold one half is `TrilemmaFaithful M delta`.
The general threshold version appears inline in the theorems that use it.

The embedding-space instantiation uses `EuclideanSpace R (Fin d)`. The quantitative results use `PseudoMetricSpace` and explicit Lipschitz hypotheses, and the hyperplane results use `LinearMap` with rank-nullity.

Table 2: Every result in the paper and its machine-checked counterpart.

Result	Lean identifier
Thm. 6	<code>model.truth_boundary_nonempty</code>
Thm. 7	<code>boundary_coupling</code>
Cor. 8	<code>closed_guarantee_impossible, hallucination_trilemma, open_guarantee_silent</code>
Thm. 9	<code>model.truth_boundary_isClosed, path_crosses_truth_boundary</code>
Thm. 10	<code>linear_probe_boundary_coset, linear_probe_boundary_dim</code>
Thm. 11	<code>regular_point_is_crossing, nonlinear_boundary_tangent, tangent_hyperplane_dim</code>
Thm. 12	<code>confidence_gap_width, ambiguity_tube, truth_margin_tube</code>
Thm. 13	<code>two_slack_approx_coupling, exact_from_approx, truth_slack_must_be_positive</code>
Upper-band exclusion	<code>no_boundary_in_upper_band_two_slack</code>
Thm. 14	<code>antipodal_odd_has_zero</code>
Thm. 15	<code>approx_odd_near_zero, sphere_odd_has_zero</code>
Thm. 16	<code>antipodal_hallucination_trilemma</code>
Thm. 17	<code>boundary_question_impossible, faithful_iff_boundary_free</code>
Prop. 18	<code>discrete_sign_change</code>
Multi-turn	<code>multi_turn_history_dependent</code>
Stochastic expected-value coupling	<code>stochastic_coupling_expected</code>
Thm. 19	<code>stochastic_dichotomy</code>
Bundled master theorem	<code>hallucination_master_theorem</code>
Definitional bridges	<code>strictCalibrated.to_epsCalibrated_zero_half, epsCalibrated_iff_twoSlack</code>

Appendix C. Core proof term

The Lean proof of the coupling theorem, lightly annotated and rendered in ASCII.

```
theorem boundary_coupling
  {Q A : Type*} [TopologicalSpace Q] [ConnectedSpace Q]
  [TopologicalSpace A]
  (M : Q -> A x R) (delta : Q x A -> R) (c : R)
  (hconf : Continuous (fun q => (M q).2))
```

Proceedings Track

```
(hcov : EpsCovering M delta 0)
(hcal : EpsCalibrated M delta c 0) :
  exists q0, (M q0).2 = c /\ delta (q0, (M q0).1) = 0 := by
obtain <<qt, ht>, <qf, hf>> := hcov
-- separation turns coverage witnesses into confidence witnesses
have hct : (M qt).2 > c + 0 := hcal.1 qt ht
have hcf : (M qf).2 < c - 0 := hcal.2 qf hf
have hct' : (M qt).2 > c := by linarith
have hcf' : (M qf).2 < c := by linarith
-- IVT on the confidence field
obtain <q0, _, hq0> :=
  isPreconnected_univ.intermediate_value2
    (mem_univ qf) (mem_univ qt)
    hconf.continuousOn continuous_const.continuousOn
    (le_of_lt hcf') (le_of_lt hct')
refine <q0, hq0, ?_>
-- at conf = c, separation excludes both signs
by_contra hne
rcases lt_or_gt_of_ne hne with hlt | hgt
. have hd : delta (q0, (M q0).1) < -0 := by simpa using hlt
  have := hcal.1 q0 hd
  linarith
. have := hcal.2 q0 hgt
  linarith
```

Appendix D. Artifact checklist

The anonymized supplementary zip contains the complete Lean project and the experiment. The Lean part includes the build configuration, the toolchain pin for Lean v4.28.0, the manifest pin for Mathlib v4.28.0, and eighteen source files. To reproduce, run `lake build`. It completes with zero errors and no `sorry`. The final-verification file and the files numbered 13 through 15 print the axiom sets of the main theorems. The experiment part includes the scripts, the public datasets of [Marks and Tegmark \(2024\)](#), the numerical results, and the figures. The theorems themselves depend on no experiment.