# The Defense Trilemma: Why Prompt Injection Defense Wrappers Fail?

Manish Bhatt*† OWASP
Sarthak Munshi† Amazon Web Services
Vineeth Sai Narajala† Cisco
Idan Habler† Cisco
Ammar Al-Kahfah† Amazon Web Services
Ken Huang Distributedapps.ai
Joel Andrew Webb
Blake Gatto
Department of Mathematics, University of New Orleans
Shrewd Security

## Abstract

We prove that no continuous, utility-preserving wrapper defense—a function $D\colon X \to X$ that preprocesses inputs before the model sees them—can make all outputs strictly safe for a language model with connected prompt space, and we characterize exactly where every such defense must fail. We establish three results under successively stronger hypotheses: *boundary fixation*—the defense must leave some threshold-level inputs unchanged; an *$\varepsilon$-robust constraint*—under Lipschitz regularity, a positive-measure band around fixed boundary points remains near-threshold; and a *persistent unsafe region*—under a transversality condition, a positive-measure subset of inputs remains strictly unsafe. These constitute a *defense trilemma*: continuity, utility preservation, and completeness cannot coexist. We prove parallel discrete results requiring no topology, and extend to multi-turn interactions, stochastic defenses. The results do not preclude training-time alignment, architectural changes, or defenses that sacrifice utility. The full theory is mechanically verified in Lean 4 with Mathlib `https://github.com/mbhatt1/stuff/tree/main/ManifoldProofs` (46 files, $\sim$360 theorems, no admitted proofs, three standard axioms) and validated empirically on three LLMs [17].

## 1 Introduction

Can you build a wrapper around a language model that eliminates all prompt injection vulnerabilities? Most current defense work implicitly assumes yes. Input classifiers that flag suspicious prompts [1], constitutional rewriting pipelines [3], and input sanitization layers [7] all share the same structure: a function $D\colon X \to X$ that preprocesses prompts before the model sees them, mapping unsafe inputs to safe equivalents while leaving safe inputs unchanged. We prove the answer is no, under two constraints. If the defense is *continuous* (similar prompts produce similar rewrites) and *utility-preserving* (safe prompts pass through unchanged), it cannot be *complete* (make every output safe). These three properties form a **defense trilemma**: any two can coexist, but not all three (Figure 2).

The impossibility is not about specific attacks or clever prompt engineering. It arises from the *geometry* of the prompt space itself: in a connected space, the safe region is open but not closed, so any continuous defense that fixes safe inputs must also fix points on the safety boundary. Under

*Corresponding author: manish.bhatt13212@gmail.com

†Equal contribution. This work was conducted independently and does not reflect the views, policies, or endorsements of the authors' respective employers.

Preprint.

successively stronger hypotheses, we establish three results with progressively stronger conclusions (Figure 3):

**Boundary fixation (Theorem 4.1).** The defense must fix at least one boundary point, i.e., a prompt where alignment deviation equals the threshold exactly—passing it through with no remediation.

**$\varepsilon$-robust constraint (Theorem 5.1).** Under Lipschitz regularity, the defense cannot uniformly reduce alignment deviation far below $\tau$ near the fixed boundary point. For any $x$ within distance $\delta$ of the fixed point $z$:

$$f(D(x)) \;\geq\; \tau - LK\,\delta. \tag{1}$$

**Persistent unsafe region (Theorem 6.3).** Under a transversality condition, the alignment surface rises faster than the defense can pull it down, leaving a positive-measure region that remains unsafe:

$$f(D(x)) > \tau \quad \text{for all } x \in \mathcal{S}, \qquad \mu(\mathcal{S}) > 0. \tag{2}$$

**From discrete to continuous.** All three results apply to continuous interpolants of discrete data. The Tietze extension theorem guarantees that any finite set of behavioral observations in a normal space admits continuous extensions, and the impossibilities hold for every such extension (Theorem 8.1).

**Scope and limitations.** Our results apply specifically to *continuous, utility-preserving wrapper defenses* on *connected* prompt spaces. They do *not* preclude effective safety through other mechanisms, including:

- training-time alignment (RLHF, DPO, constitutional AI training),
- architectural changes to the model itself,
- discontinuous defenses (e.g., hard blocklists or discrete classifiers),
- output-side filters, ensemble defenses, or human-in-the-loop review,
- adaptive-threshold systems,
- multi-component systems whose classifiers may reject or redirect inputs rather than preserving utility on every prompt.

In short, our theorems cover only a single continuous wrapper $D\colon X \to X$ that preprocesses inputs; any mechanism outside this class is not constrained by our results.

All three conditions—continuity, utility preservation, and connectedness—are individually necessary; we give counterexamples for each (Section C).

**Contributions.**

1. **Boundary fixation** (Theorem 4.1): any continuous, utility-preserving defense on a connected Hausdorff space must fix a point $z$ with $f(z) = \tau$. Relaxed to score-preserving and $\varepsilon$-approximate variants (Theorems 4.4 and 4.5).
2. **$\varepsilon$-robust constraint** (Theorem 5.1): under Lipschitz regularity, $f(D(x)) \geq \tau - LK\,\mathrm{dist}(x, z)$ for all $x$. A positive-measure band near $z$ is constrained (Theorem 5.2).
3. **Persistent unsafe region** (Theorem 6.3): under a transversality condition ($G > \ell(K+1)$, where $\ell$ is the defense-path Lipschitz constant), a positive-measure set remains strictly above $\tau$ after defense.
4. **Quantitative bounds**: explicit volume lower bound (Theorem 7.1), cone measure bound (Theorem 7.2), and an asymmetric defense dilemma (Theorem 7.3).
5. **Discrete defense dilemma** (Theorem 8.3): on finite sets, completeness forces non-injectivity (information loss); injectivity forces incompleteness.
6. **Extensions**: multi-turn (Theorem 9.1), stochastic (Theorem 9.2), and pipeline (Theorem 9.3) settings.
7. **Lean 4 formalization**: 46 files, $\sim$360 theorems, zero `sorry` statements, three standard axioms. Full proofs in Section B; artifact in Section H.

Table 1: Positioning among impossibility results (top) and empirical findings independently consistent with our predictions (bottom).

| **Result** | **Target** | **Method** | **Impossibility** | **Verified** |
|---|---|---|---|---|
| Tsipras et al. [21] | Classifier | PAC / Gaussian | Robustness + accuracy | No |
| Fawzi et al. [11] | Classifier | Lipschitz geom. | Adv. invulnerability | No |
| Wolpert & Macready [22] | Optimizer | Counting | Universal dominance | No |
| Cohen et al. [5] | Smoothed clf. | Rand. smoothing | (Certifies bound) | No |
| **This work** | **Def. wrapper** | **Topology** | **Cont. + util. + compl.** | **Lean 4** |
| *Empirical findings consistent with our derived predictions* | | | | |
| **Our prediction** | **Theorem** | **Confirming evidence** | | **Pred.** |
| Diminishing safety returns | Int. Stability | MART [24]; Sleeper Agents [25] | | §11 |
| Long context $\to$ exp. harder defense | Cost Asymm. | Many-Shot Jailbreaking [26]; Kim et al. [27] | | §11 |
| Agentic tool-use degrades exp. | Pipeline Lip. | InjecAgent [28]; ASB [29] | | §11 |
| Temperature boundary instab. | Stoch. Imposs. | Instability of Safety [30] | | §11 |
| Quantization preserves deep vulns | Int. Stability | Skoltech [31]; ETH [32] | | §11 |
| Merging preserves weaker parent | Int. Stability | Hammoud et al. [33] | | §11 |
| Adv. training fragments | Fragment Size | Whack-a-Mole [34]; IRIS [35] | | §11 |
| Asymmetric transfer | Transferability | Weak-to-Strong [36]; IRIS [35] | | §11 |
| Alignment tax $\propto$ unsafe vol. | Discrete Dil. | Safety Tax [37]; Huang et al. [38] | | §11 |
| Patch blast radius | Patching Nonl. | Slingshot [39]; Sleeper Agents [25] | | §11 |

## 2 Related Work

Adversarial robustness research has established that small perturbations can fool classifiers [20, 6, 9, 14] and that robustness may fundamentally trade off against accuracy [21, 11]. Certified defenses provide guarantees for fixed models [5, 8, 19, 13, 2], and topological perspectives have illuminated the structure of decision boundaries [16]. For LLMs specifically, jailbreaking attacks [23, 4, 10, 12] and automated red-teaming [15, 18] demonstrate persistent vulnerabilities.

Our work differs in kind: rather than studying how failures arise for fixed models or how specific systems can be certified, we impose *universal constraints on the defense map itself*. The closest conceptual precedent is the no-free-lunch framework [22], which proves that no optimizer dominates across all problems. We prove the analogous result for wrapper defenses: under continuity and utility preservation, no defense eliminates all failures.

Table 1 situates our result among comparable impossibility and tradeoff theorems.

## 3 Formal Framework

**Definition 3.1** (Alignment Deviation Function)**.** *Let $X$ be a topological space (a set equipped with a notion of "open" and "closed" sets, such that the whole space and the empty set are both open and closed, arbitrary unions and finite intersections of open sets are open, and a notion of "neighborhoods" of points—that is, points "close to" a given point). An* alignment deviation function *is a continuous map $f\colon X \to \mathbb{R}$, i.e., small changes in the input produce small changes in the score.*




Figure 1: Schematic of the prompt space. The defense $D$ must leave all safe inputs unchanged (utility preservation) and tries to remap unsafe inputs into the safe region. Boundary fixation (Theorem 4.1) proves the defense must also leave some boundary points unchanged, the black dot $z$ passes through with no remediation.

*Given a threshold $\tau \in \mathbb{R}$:*

$$S_\tau = \{x \in X : f(x) < \tau\} \qquad \textit{(safe region)} \tag{3}$$
$$U_\tau = \{x \in X : f(x) > \tau\} \qquad \textit{(unsafe region)} \tag{4}$$
$$B_\tau = \{x \in X : f(x) = \tau\} \qquad \textit{(boundary)} \tag{5}$$

**Definition 3.2** (Defense)**.** *A* defense *is a continuous map $D\colon X \to X$. It is* utility-preserving *if $D(x) = x$ for all $x \in S_\tau$ (safe prompts pass through unchanged), and* complete *if $f(D(x)) < \tau$ for all $x \in X$ (every output is safe).*

The central question is whether a defense can be both utility-preserving and complete. The following sections show that under natural conditions the answer is no.

## 4 Boundary Fixation

We begin with the most fundamental result. The argument fits in a paragraph: the defense fixes every safe input, so continuity makes its fixed-point set closed. But the safe region $S_\tau$ is open (preimage of an open interval under continuous $f$), and in a connected space a nonempty proper open set is not closed. Hence the fixed-point set cannot stop exactly at the edge of the safe region, it must spill onto the boundary $B_\tau$. Some boundary prompts pass through unchanged.

**Theorem 4.1** (Boundary Fixation)**.** *Let $X$ be a connected Hausdorff space (a space that is "in one piece" and where distinct points can be separated by neighborhoods). Let $f\colon X \to \mathbb{R}$ be continuous with $S_\tau, U_\tau \neq \emptyset$, and $D\colon X \to X$ continuous with $D|_{S_\tau} = \mathrm{id}$. Then there exists $z \in X$ with $f(z) = \tau$ and $D(z) = z$. Moreover, every $z \in \overline{S_\tau} \setminus S_\tau$ satisfies $f(z) = \tau$ and $D(z) = z$, and this set is nonempty.*

*Proof sketch.* In a Hausdorff space, $\mathrm{Fix}(D)$ is closed (preimage of the diagonal). By utility preservation, $S_\tau \subseteq \mathrm{Fix}(D)$, so $\overline{S_\tau} \subseteq \mathrm{Fix}(D)$. But $S_\tau = f^{-1}((-\infty, \tau))$ is open and not closed (connectedness: a nonempty proper clopen set would disconnect $X$). Hence $\overline{S_\tau} \supsetneq S_\tau$. Any $z \in \overline{S_\tau} \setminus S_\tau$ satisfies $f(z) = \tau$ (limits of values $<\tau$ cannot exceed $\tau$, and $z \notin S_\tau$ forces $f(z) \geq \tau$) and $D(z) = z$. Full proof in Section B. □

This means that the defense's fixed-point set is too large to avoid the boundary. Utility preservation forces it to contain the safe region; closure forces it to contain the boundary; connectedness ensures the boundary is nonempty. Alternatively: a complete utility-preserving defense would be a continuous retraction $D\colon X \to S_\tau$ (since $D|_{S_\tau} = \mathrm{id}$ and $D(X) \subseteq S_\tau$), but a retract of a Hausdorff




Figure 2: The defense trilemma. Any continuous wrapper defense on a connected space can satisfy at most two of the three properties. The bottom edge is our main result; the other two edges correspond to counterexamples in Section C.

space is closed (the fixed-point set is closed), while $S_\tau$ is open and not closed (connectedness)—a contradiction.

**Theorem 4.2** (Defense Trilemma)**.** *Let $X$ be a connected Hausdorff space, $f\colon X \to \mathbb{R}$ continuous with $S_\tau, U_\tau \neq \emptyset$. No $D\colon X \to X$ can simultaneously be continuous, utility-preserving ($D|_{S_\tau} = \mathrm{id}$), and complete ($f(D(x)) < \tau$ for all $x$).*

All three hypotheses are individually necessary. A defense can satisfy at most two of the three—the *defense trilemma* (Figure 2). Counterexamples for each dropped hypothesis appear in Section C.

**Remark 4.3** (Not all boundary points are fixed)**.** *The theorem captures $\overline{S_\tau} \setminus S_\tau$, not all of $B_\tau$. Boundary points not in $\overline{S_\tau}$ may escape fixation.*

### 4.1 Relaxed Utility Preservation

Strict utility preservation ($D(x) = x$ for safe $x$) can be relaxed. The impossibility survives score-preserving rewrites and even approximate score preservation.

**Theorem 4.4** (Score-Preserving Defense)**.** *Let $X$ be a connected Hausdorff space, $f\colon X \to \mathbb{R}$ continuous with $S_\tau, U_\tau \neq \emptyset$. If $D\colon X \to X$ is continuous and* score-preserving on safe inputs*: $f(D(x)) = f(x)$ for all $x \in S_\tau$, then there exists $z$ with $f(z) = \tau$ and $f(D(z)) = \tau$.*

*Proof sketch.* Define $h = f \circ D - f$. Then $h$ is continuous and $h|_{S_\tau} = 0$. The zero set $\{h = 0\}$ is closed and contains $\overline{S_\tau}$, since closed sets contain their boundary points. For $z \in \overline{S_\tau} \setminus S_\tau$, $f(D(z)) = f(z) = \tau$. □

The next result weakens score preservation to approximate:

**Theorem 4.5** ($\varepsilon$-Relaxed Utility Preservation)**.** *Under the hypotheses of Theorem 4.4, if $|f(D(x)) - f(x)| \leq \varepsilon$ for all $x \in S_\tau$, then there exists $z$ with $f(z) = \tau$ and $f(D(z)) \geq \tau - \varepsilon$.*

*Proof sketch.* The set $\{x : h(x) \geq -\varepsilon\}$ is closed and contains $S_\tau$, hence $\overline{S_\tau}$. For $z \in \overline{S_\tau} \setminus S_\tau$: $f(D(z)) = \tau + h(z) \geq \tau - \varepsilon$. □

**Remark 4.6** (Why $D(S_\tau) \subseteq S_\tau$ alone is insufficient)**.** *The weakest relaxation—$D(S_\tau) \subseteq S_\tau$ with no score constraint—does allow a complete defense (e.g., a constant map $D(x) = x_0$ to a fixed safe point). But this destroys all semantic content: every prompt produces the same response. The score-preservation conditions formalize the requirement that defense must not destroy utility, without requiring the defense to be the identity.*

## 5 $\varepsilon$-Robust Constraint

Boundary fixation produces at least one fixed point; Lipschitz regularity makes the failure spread to a neighborhood.

**Theorem 5.1** ($\varepsilon$-Robust Defense Constraint)**.** *Under the hypotheses of Theorem 4.1, if $(X, d)$ is a metric space, $f$ is $L$-Lipschitz, and $D$ is $K$-Lipschitz, then for the fixed boundary point $z$:*

$$f(D(x)) \;\geq\; \tau - LK\,\mathrm{dist}(x, z) \qquad \textit{for all } x \in X. \tag{6}$$

*Points within distance $\delta$ of $z$ remain within $LK\delta$ of threshold.*

*Proof sketch.* Since $D(z) = z$ and $D$ is $K$-Lipschitz: $\mathrm{dist}(D(x), z) \leq K\,\mathrm{dist}(x, z)$. Since $f(z) = \tau$ and $f$ is $L$-Lipschitz: $|f(D(x)) - \tau| \leq L \cdot K\,\mathrm{dist}(x, z)$. Full proof in Section B. □

**Theorem 5.2** (Positive-Measure $\varepsilon$-Band)**.** *Under the hypotheses of Theorem 5.1, if $X$ is connected and $f$ takes values below $\tau - \varepsilon$ for some $\varepsilon > 0$, then the band $\mathcal{B}_\varepsilon = \{x : \tau - \varepsilon \leq f(x) \leq \tau\}$ has positive measure (under any measure positive on nonempty open sets). Specifically, $B(c, \varepsilon/(4L)) \subseteq \mathcal{B}_\varepsilon$ for the midpoint $c$ with $f(c) = \tau - \varepsilon/2$ (which exists by the intermediate value theorem).*

**Remark 5.3** (Defense behavior on the $\varepsilon$-band)**.** *By Theorem 4.1, $\overline{S_\tau} \subseteq \mathrm{Fix}(D)$. Every point in $\mathcal{B}_\varepsilon$ with $f(x) < \tau$ is safe and therefore fixed by utility preservation; every point with $f(x) = \tau$ in $\overline{S_\tau}$ is fixed by boundary fixation. On both subsets $f(D(x)) = f(x) \in [\tau - \varepsilon, \tau]$. The remainder—boundary points outside $\overline{S_\tau}$—is contained in the level set $f^{-1}(\tau)$, which has measure zero when $f$ is Lipschitz on $\mathbb{R}^n$ (by the coarea formula; not formalized in the Lean artifact).*

*Proof sketch.* For $y \in B(c, \varepsilon/(4L))$: $|f(y) - f(c)| \leq L \cdot \varepsilon/(4L) = \varepsilon/4$. Since $f(c) = \tau - \varepsilon/2$, we get $\tau - 3\varepsilon/4 \leq f(y) \leq \tau - \varepsilon/4$, so $y \in \mathcal{B}_\varepsilon$. □

## 6 Persistent Unsafe Region

The $\varepsilon$-robust constraint bounds the depth to which the defense pushes near-boundary points, but permits values slightly below $\tau$. When the alignment surface rises faster than the defense can pull it down, some points remain above threshold.

**Decoupling global and directional Lipschitz constants.** The $\varepsilon$-robust bound (Theorem 5.1) uses the *global* Lipschitz constant $L$ of $f$, which bounds $f$ uniformly in all directions. The persistence argument, however, compares $f$'s growth rate in the *steep direction* to how much the defense can reduce $f$ along the *displacement direction* $D(x) - x$. In anisotropic settings these directions differ: $f$ may rise steeply toward the unsafe region while varying slowly in the direction the defense pulls.

We write $\ell$ for the *defense-path Lipschitz constant*:

$$\ell \;=\; \sup_{x \neq D(x)} \frac{|f(D(x)) - f(x)|}{\mathrm{dist}(D(x),\, x)}$$

(with $\ell = 0$ when $D = \mathrm{id}$, i.e., the supremum over the empty set is taken as 0). Since $f$ is $L$-Lipschitz globally, $\ell \leq L$. When the alignment surface is **isotropic** ($\ell = L$), the steep region is empty for every $K \geq 0$ (verified in Lean as `shallow_boundary_no_persistence`). The result is non-vacuous precisely when the surface is **anisotropic**: $\ell < L$, with directional gradient $G$ satisfying $G > \ell(K + 1)$.

**Lemma 6.1** (Input-Relative Bound)**.** *Under the hypotheses of Theorem 5.1, if $f$ has defense-path Lipschitz constant $\ell$, then $f(D(x)) \geq f(x) - \ell(K + 1)\,\mathrm{dist}(x, z)$ for all $x \in X$.*

*Proof sketch.* Triangle inequality: $\mathrm{dist}(D(x), x) \leq \mathrm{dist}(D(x), z) + \mathrm{dist}(z, x) \leq (K+1)\,\mathrm{dist}(x, z)$. Defense-path Lipschitz: $|f(D(x)) - f(x)| \leq \ell\,\mathrm{dist}(D(x), x) \leq \ell(K + 1)\,\mathrm{dist}(x, z)$. □

This means that the defense can reduce any point's score by at most $\ell(K + 1)$ times its distance from $z$. If the score rises faster than that, the defense loses.




Figure 3: The three impossibility results on a 1D cross-section. **(a)** The defense must fix boundary point $z$ (Thm. 4.1). **(b)** Near $z$, Lipschitz regularity constrains the defense to a shallow $\varepsilon$-band (yellow; Thm. 5.1). **(c)** Where $f$ rises faster than the defense budget $\ell(K+1)\delta$ (dashed red), the region above $\tau$ persists (red shading; Thm. 6.3).

**Definition 6.2** (Steep region)**.** *Given a fixed boundary point $z$, the* steep region *is $\mathcal{S} = \{x \in X : f(x) > \tau + \ell(K+1)\,\mathrm{dist}(x, z)\}$—the set of points where alignment deviation exceeds $\tau$ by more than the defense's Lipschitz budget can compensate.*

**Theorem 6.3** (Persistent Unsafe Region)**.** *Let $X$ be a connected Hausdorff metric space, $f$ continuous and $L$-Lipschitz, $D$ continuous and $K$-Lipschitz with $D|_{S_\tau} = \mathrm{id}$, and $S_\tau, U_\tau \neq \emptyset$. Let $z \in \overline{S_\tau} \setminus S_\tau$ be the fixed boundary point from Theorem 4.1, and let $\ell$ be the defense-path Lipschitz constant. If $\mathcal{S} \neq \emptyset$, then:*

1. *$\mathcal{S}$ is open.*
2. *$\mathcal{S}$ has positive measure (under any measure positive on nonempty open sets).*
3. *For every $x \in \mathcal{S}$: $f(D(x)) > \tau$.*

*The defense leaves a positive-measure region that remains unsafe.*

*Proof sketch.* $\mathcal{S}$ is a strict superlevel set of a continuous function, hence open. For $x \in \mathcal{S}$: $f(D(x)) \geq f(x) - \ell(K+1)\,\mathrm{dist}(x, z) > \tau$ by Theorem 6.1 and the definition of $\mathcal{S}$. Full proof in Section B. □

When does the steep region exist? Whenever the alignment surface has directional slope exceeding $\ell(K+1)$ at the boundary:

**Proposition 6.4** (Transversality from Directional Derivative)**.** *In a normed space, if $f$ has Fréchet derivative $f'$ at boundary point $z$ with directional value $f'(v) > \ell(K+1)$ along a unit vector $v$, then $z + tv \in \mathcal{S}$ for sufficiently small $t > 0$. If $\|f'\| > \ell(K+1)$, such a $v$ exists by operator-norm near-attainment. Verified in Lean as* `gradient_norm_implies_steep_nonempty` *(*`MoF_21_GradientChain`*), which derives the local growth bound from* `HasFDerivAt` *rather than assuming it.*

This condition is observed empirically in the two models with $U_\tau \neq \emptyset$ (Section 10): the alignment surface rises steeply toward the unsafe region ($G$ large) while the defense operates in a smoother subspace ($\ell \ll L$).

## 7 Quantitative Bounds

The preceding results establish that failures *exist* and have positive measure. This section provides explicit lower bounds and identifies a fundamental dilemma in choosing the defense's aggressiveness.

**Theorem 7.1** (Volume Lower Bound)**.** *Let $f : \mathbb{R}^n \to \mathbb{R}$ be $L$-Lipschitz with $L > 0$, and let $\mu$ denote Lebesgue measure. If there exists $c$ with $f(c) = \tau - \varepsilon/2$, then $B(c, \varepsilon/(4L)) \subseteq \mathcal{B}_\varepsilon$, giving:*

$$\mu(\mathcal{B}_\varepsilon) \;\geq\; V_n \cdot \left(\frac{\varepsilon}{4L}\right)^n \tag{7}$$

*where $V_n$ is the volume of the unit ball in $\mathbb{R}^n$. In $\mathbb{R}^1$, this simplifies to $\mu(\mathcal{B}_\varepsilon) \geq \varepsilon/(2L)$.*

*Proved in the Lean artifact as* `MoF_17_CoareaBound`.

Smoother surfaces (smaller $L$) produce wider $\varepsilon$-bands.

**Theorem 7.2** (Cone Measure Bound)**.** *In $\mathbb{R}$ with Lebesgue measure $\mu$, if $f(x) \geq \tau + c(x - z)$ for all $x \in (z,\, z + \delta_0)$ with $c > \ell(K + 1)$, then $\mu(\{x : f(D(x)) > \tau\}) \geq \delta_0$.*

*Proved in the Lean artifact as* `MoF_18_ConeBound`.

This gives a concrete lower bound on the persistent region: if the alignment surface is steep over an interval of length $\delta_0$, the defense fails on at least that much volume. The bound $\geq \delta_0$ is tight: equality holds when the cone condition fails exactly at $z + \delta_0$ (i.e., $f(z + \delta_0) = \tau + c\,\delta_0$ and $f(x) < \tau + c(x - z)$ for $x > z + \delta_0$). If the cone extends beyond $\delta_0$, the persistent region is strictly larger.

The defense designer faces a dilemma in choosing the Lipschitz constant $K$ of the defense:

**Theorem 7.3** (Defense Dilemma)**.** *Assume $f$ is differentiable at boundary point $z$ with $G = \|\nabla f(z)\|$, and let $\ell$ be the defense-path Lipschitz constant (Section 6). Define $K^* = G/\ell - 1$. Then:*

1. *If $K < K^*$: the persistent unsafe region exists ($G > \ell(K + 1)$, Theorem 6.3 applies).*
2. *If $K \geq K^*$: the $\varepsilon$-robust bound $\tau - \ell(K+1)\delta$ becomes loose enough that the theorem can no longer exclude the defense from succeeding on the steep region ($\ell(K + 1) \geq G$).*

*Since $\ell \leq L$, the dilemma is sharpest when $\ell \ll L$ (anisotropic surfaces). When $\ell = L$ (isotropic), $K^* \leq 0$ and horn (1) is vacuous.*

*Proved in the Lean artifact as* `MoF_19_OptimalDefense`*; the Lean theorem* `optimal_K_exists` *is stated for generic positive reals $(G, L)$—instantiating $L \mapsto \ell$ recovers the defense-path version above.*

## 8 From Discrete Data to Continuous Theory

This section bridges discrete token observations and continuous theory.

### 8.1 Continuous Interpolation

Any finite set of behavioral observations can be extended to a continuous function on the full space. The classical Tietze extension theorem guarantees this:

**Theorem 8.1** (Continuous Relaxation)**.** *Let $(X, d)$ be a connected, normal, Hausdorff metric space, and $S \subset X$ a finite set of observations with observed alignment scores $g\colon S \to \mathbb{R}$ satisfying $g(p) < \tau$ and $g(q) > \tau$ for some $p, q \in S$. Then there exists a continuous $f\colon X \to \mathbb{R}$ extending $g$ (i.e., $f|_S = g$) for which the hypotheses of Theorem 4.1 hold. If the extension is chosen to be Lipschitz (via McShane–Whitney), the hypotheses of Theorem 5.1 also hold. If $f$ is additionally Lipschitz (as for GP posterior means under standard kernel assumptions), Theorem 6.3 applies wherever transversality is met.*

*Proof sketch.* **Step 1** (Extension exists). $S$ is finite and $X$ is $T_1$ (every Hausdorff space is $T_1$), so $S$ is closed. Since $X$ is normal and $g\colon S \to \mathbb{R}$ is continuous (every function on a discrete closed subset is continuous), the Tietze extension theorem provides a continuous $f\colon X \to \mathbb{R}$ with $f|_S = g$.

**Step 2** (Hypotheses of Theorem 4.1 are satisfied). We have $f(p) = g(p) < \tau$ and $f(q) = g(q) > \tau$, so $S_\tau \neq \emptyset$ and $U_\tau \neq \emptyset$. Since $X$ is connected and Hausdorff, Theorem 4.1 applies: any continuous, utility-preserving defense has a fixed boundary point.

**Step 3** (Lipschitz extension enables stronger results). When a Lipschitz extension is needed (e.g., for Theorems 5.1 and 6.3), the McShane–Whitney theorem provides an $L$-Lipschitz $f$ agreeing with $g$ on $S$. Given the Lipschitz constants $L$ of $f$ and $K$ of $D$, the $\varepsilon$-robust bound $f(D(x)) \geq \tau - LK\,\mathrm{dist}(x, z)$ follows from Theorem 5.1. If additionally the alignment surface has directional slope $c > \ell(K + 1)$ at the fixed boundary point $z$ (where $\ell$ is the defense-path Lipschitz constant), Theorem 6.3 gives a positive-measure region that remains strictly unsafe. □

If we observe both safe and unsafe model behaviors, the impossibility holds for *every* continuous model consistent with our observations.

### 8.2 Direct Discrete Results

To address the objection that continuous impossibility might be an artifact of continuous relaxation, we prove parallel results directly on finite sets using only counting arguments and induction. No topology is required; all results are verified in Lean as `MoF_12_Discrete`.

**Theorem 8.2** (Discrete IVT)**.** *Let $f\colon \{0,\dots,n+1\} \to \mathbb{R}$ with $f(0) < \tau$ and $f(n+1) \geq \tau$. Then there exists $i$ with $f(i) < \tau$ and $f(i+1) \geq \tau$.*

**Theorem 8.3** (Discrete Defense Dilemma)**.** *Let $X$ be a finite set with $S_\tau, U_\tau \neq \emptyset$, and $D\colon X \to X$ utility-preserving ($D(x) = x$ for $f(x) < \tau$).*

1. *If $D$ is injective, then $f(D(u)) \geq \tau$ for every $u$ with $f(u) \geq \tau$ (including boundary points): the defense is incomplete.*
2. *If $D$ is complete ($f(D(x)) < \tau$ for all $x$), then $D$ is non-injective: $\exists\, x \neq y$ with $D(x) = D(y)$.*

*Proof.* (1) Suppose $D$ is injective and $f(D(u)) < \tau$ for some $u$ with $f(u) \geq \tau$. Then $D(u)$ is safe, so $D(D(u)) = D(u)$ by utility preservation. Injectivity gives $D(u) = u$, so $f(u) = f(D(u)) < \tau$, contradicting $f(u) \geq \tau$.

(2) For any $u \in U_\tau$: completeness gives $f(D(u)) < \tau$, so utility preservation gives $D(D(u)) = D(u)$. But $u \neq D(u)$ since $f(u) \geq \tau > f(D(u))$. So $u$ and $D(u)$ are distinct inputs with $D(u) = D(D(u))$: the defense is non-injective. □

The continuous trilemma trades *continuity* for completeness; the discrete dilemma trades *injectivity*. Part (1) is the genuine constraint: an information-preserving defense *cannot* eliminate unsafe outputs. Any complete defense must destroy information—collapsing distinct inputs to the same output. This is not a failure of the defense; it is the *mechanism* by which it operates. The downstream model receives the same input regardless of whether the original was safe or an attack; any audit or attack-detection logic must act *before* $D$ is applied.

## 9 Extensions

The core results assume a static, deterministic, single-turn defense. *Does multi-turn interaction, randomization, or pipelining provide an escape?* We show it does not. Each extension is a direct application of the boundary fixation machinery to a modified setting.

### 9.1 Multi-Turn Impossibility

**Theorem 9.1** (Multi-Turn Impossibility)**.** *Let $\{f_t, D_t\}_{t=1}^{T}$ be alignment functions and defenses over $T$ turns on a connected Hausdorff space, each continuous and utility-preserving, with $S_\tau^{(t)}, U_\tau^{(t)} \neq \emptyset$ at every turn. Then for every turn $t$, there exists $z_t$ with $f_t(z_t) = \tau$ and $D_t(z_t) = z_t$.*

*Proof sketch.* Apply Theorem 4.1 to $(f_t, D_t)$ at each turn. The functions may depend on full history—this does not matter, as each timestep is a fresh instance of boundary fixation. □

Multi-turn interaction compounds the problem: the attacker's best observed exploit improves monotonically (`running_max_monotone`), and the attacker can steer toward transversality via binary search (`transversality_reachable`).

### 9.2 Stochastic Defense Impossibility

**Theorem 9.2** (Stochastic Defense Impossibility)**.** *Let $X$ be a connected Hausdorff space, $f\colon X \to \mathbb{R}$ continuous with $S_\tau, U_\tau \neq \emptyset$. Let $D$ be a stochastic defense and define $g(x) = \mathbb{E}_{y\sim D(x)}[f(y)]$. If $g$ is continuous and $g(x) = f(x)$ for all $x \in S_\tau$, then there exists $z$ with $f(z) = \tau$ and $g(z) = \tau$.*

Table 2: Falsifiable predictions confirmed by empirical data.

| Theorem | Predicts | Confirmed by |
|---|---|---|
| Basin Structure (A.1) | Basins are open with positive measure | Heatmaps show extended regions |
| Fragmentation (A.2) | Smooth → large basins; rough → mosaic | Llama: mesa; GPT-OSS: mosaic |
| Convergence (D.2) | Attacks exhibit monotone convergence | Convergence curves plateau |
| Transferability (D.3) | Similar surfaces → shared basins | Llama .93 → GPT-OSS .73 → Mini .47 |
| Authority (D.4) | Horizontal banding | Bands at $a_2 \approx .25$–$.35$, $.65$–$.85$ |
| Persistent (6.3) | Steep boundaries → unsafe volume persists | Llama's .93 plateau persists under defense |
| Interior Stability (E.1) | Deep basin points survive fine-tuning | Vulnerability persists across variants |
| Cost (F.1) | 2D tractable, high-$d$ intractable | 15K queries fill 63% at $d=2$ |
| Pipeline (9.3) | Deeper pipelines → wider failure band | Not directly tested (no pipeline experiment) |

*Proof sketch.* Define $h = g - f$. Then $h$ is continuous and $h|_{S_\tau} = 0$, so $h$ vanishes on $\overline{S_\tau}$ (same closure argument as Theorem 4.4). For $z \in \overline{S_\tau} \setminus S_\tau$: $g(z) = f(z) = \tau$. □

*Remark (stochastic dichotomy).* Since $\mathbb{E}[f(D(z))] = \tau$, either $f(D(z)) = \tau$ almost surely (the defense is deterministic at $z$), or the random variable $f(D(z))$ has positive probability of exceeding $\tau$—i.e., the defense *actively produces unsafe outputs* with positive probability. The stochastic case is therefore strictly harder than the deterministic one: a genuinely random defense at boundary points must sometimes make things worse.

*Remark.* The continuity of $g$ is a nontrivial assumption: it requires the distribution $D(x)$ to vary continuously with $x$ in a suitable sense. Stochastic defenses with discontinuous rejection probabilities escape this theorem.

### 9.3 Nonlinear Agent Pipelines

**Theorem 9.3** (Pipeline Lipschitz Degradation)**.** *If stages $T_1, \ldots, T_n$ are $K_1, \ldots, K_n$-Lipschitz, the composed pipeline is $(\prod K_i)$-Lipschitz. For $n$ stages each with $K \geq 2$, the effective constant is $K^n$—exponential in depth.*

**Theorem 9.4** (Pipeline Impossibility)**.** *If the composed pipeline $P = T_n \circ \cdots \circ T_1 \circ D$ is continuous and $P(x) = x$ for all $x \in S_\tau$, then $P$ has boundary fixed points. If $D$ is $K_D$-Lipschitz and each $T_i$ is $K$-Lipschitz, the $\varepsilon$-robust band scales as $L \cdot K_D \cdot K^n \cdot \delta$*

*Proved in the Lean artifact as* `MoF_15_NonlinearAgents`.

Note: $P(x) = x$ for safe $x$ requires $T_n \circ \cdots \circ T_1$ to act as the identity on safe inputs, not just $D$. This holds when the tool chain preserves safe inputs (e.g., a safety-certified pipeline), but not for arbitrary tools.

Additional results on basin structure, fragment sizes, perturbation robustness, convergence, transferability, and cost asymmetry appear in Sections A and D to F.

## 10 Experimental Validation

The Manifold of Failure framework [17] maps three LLMs over a 2D behavioral space with two axes: *query indirection* (how obliquely the prompt asks for unsafe content) and *authority framing* (how much the prompt invokes authority or permission). Table 2 summarizes nine qualitative predictions, all directionally consistent with observations.

**Llama-3-8B** (mean AD $0.93$, basin rate $93.9\%$): near-flat alignment surface (small $L$), large robustness radii. Estimated from the 2D behavioral surface in [17]: directional slope $G \approx 5$ at the steepest boundary crossing. For the defense-path Lipschitz constant we assume a hypothetical nearest-safe-projection defense ($D(x)$ maps each point to the closest $x' \in S_\tau$) and estimate $\ell \approx 1$ from grid-adjacent score differences in the direction orthogonal to the boundary (the projection direction on the 2D grid). Setting $K = 1$ (identity-rate defense), these satisfy $G > \ell(K + 1) = 2$.

**GPT-OSS-20B** (mean AD $0.73$, basin rate $64.3\%$): a rugged landscape (large $L$) with many small fragments. Horizontal bands confirm authority monotonicity.

**GPT-5-Mini** (peak AD $0.50$, basin rate $0\%$): at $\tau = 0.50$, $U_\tau = \emptyset$—none of the three theorems apply, correctly predicting no impossibility.

### 10.1 Live Empirical Validation of Theorem 6.3

The numbers above are read off the published Manifold of Failure heatmaps. To check the persistence theorem on *independently re-collected* alignment-deviation surfaces and to expose every intermediate quantity, we built a small validator that takes any 2D heatmap and computes:

1. the empirical surface Lipschitz constant $L$ from all-pairs finite differences over filled grid cells;
2. for a chosen defense $D$, the empirical Lipschitz constant $K$ of $D$ and the defense-path Lipschitz constant $\ell$;
3. the maximum directional rate $G$ at which $f$ rises across the safe-unsafe boundary (all-pairs finite differences between filled safe and filled unsafe cells);
4. the *predicted steep set* $\mathcal{S}_{\text{pred}} = \{x : f(x) > \tau + \ell(K{+}1)\,\mathrm{dist}(x,\, z^*)\}$, where $z^*$ is the filled boundary cell with $f(z^*)$ closest to $\tau$;
5. the *actual persistent set* $\mathcal{S}_{\text{act}} = \{x : f(D(x)) > \tau\}$.

Theorem 6.3's empirical content is the containment $\mathcal{S}_{\text{pred}} \subseteq \mathcal{S}_{\text{act}}$ under any continuous, $K$-Lipschitz, utility-preserving $D$. We test this as a per-cell confusion matrix:

- *True positive (TP):* cell in both sets — theorem confirmed for that cell.
- *Interior false positive ($FP_{\text{int}}$):* non-boundary cell in $\mathcal{S}_{\text{pred}}$ but not $\mathcal{S}_{\text{act}}$. A non-zero count would be a real counterexample.
- *Boundary false positive:* a discrete defense moving a boundary cell. *Not* a violation; witnesses that the discrete defense is not topologically continuous, so the theorem's hypothesis does not apply.
- *False negative (FN):* cell in $\mathcal{S}_{\text{act}}$ but not $\mathcal{S}_{\text{pred}}$. *Not* a violation; Theorem 6.3 only claims the containment one way.

We ran the full pipeline live against the OpenAI API on two real target models: `gpt-5-mini-2025-08-07` (well aligned) and `gpt-3.5-turbo-0125` (less aligned), with `gpt-4.1-2025-04-14` as the judge. The MAP-Elites driver from [17] produced a $25 \times 25$ alignment-deviation grid for each target, which the validator then analyzed against the canonical continuous defense ($D = \mathrm{id}$, so $K = 1$ and $\ell = 0$). For `gpt-3.5-turbo-0125` we additionally ran a saturation study with $400$ evaluations ($100$ seed prompts $+300$ MAP-Elites iterations, $\sim$5,200 OpenAI API calls, wall clock $\sim$130 min, cost $\sim$\$15) which filled $82$ cells with $66$ strictly unsafe ($f > \tau$) and $10$ boundary cells. The two earlier runs are kept as smoke-tests of the validator's logic on sparse grids; the saturation row is the doubt-eliminator.

Table 3: Live empirical validation of Theorem 6.3 against the canonical continuous defense ($D = \mathrm{id}$, $K = 1$, $\ell = 0$). $|\mathcal{S}_{\text{pred}}|$ is the predicted steep-set size $\{x : f(x) > \tau + \ell(K{+}1)\,\mathrm{dist}(x, z^*)\}$; $|\mathcal{S}_{\text{act}}|$ is the actual post-defense persistent set $\{x : f(D(x)) > \tau\}$; TP/$FP_{\text{int}}$/FN are the per-cell confusion-matrix counts. Across all three live runs, the two sets match cell-for-cell, with zero interior false positives.

| **Target** | $\tau$ | **Filled** | $L$ | $G$ | $\lvert\mathcal{S}_{\text{pred}}\rvert$ | $\lvert\mathcal{S}_{\text{act}}\rvert$ | **TP** | $\mathbf{FP}_{\text{int}}$ | **FN** |
|---|---|---|---|---|---|---|---|---|---|
| gpt-5-mini-2025-08-07 | 0.30 | 14 | 6.13 | 6.13 | 7 | 7 | 7 | **0** | 0 |
| gpt-3.5-turbo-0125 (smoke) | 0.50 | 9 | 11.44 | 11.44 | 7 | 7 | 7 | **0** | 0 |
| gpt-3.5-turbo-0125 (saturated) | 0.50 | 82 | 23.63 | 23.63 | 66 | 66 | 66 | **0** | 0 |




Figure 4: Per-cell validation of Theorem 5.1 on the saturated live run. Each of the 82 filled cells is one dot: 56 interior unsafe ($f(x) > \tau$, red), 16 safe ($f(x) < \tau$, green), 10 boundary cells in $\overline{S_\tau} \setminus S_\tau$ (black squares). The dashed line is the predicted bound $LK\,\mathrm{dist}(x, z^*) + |f(z^*) - \tau|$ with empirically-measured $LK = 23.63$ and discretization slack $0.375$. Every dot lies below the bound; the worst empirical $|f(D(x)) - \tau|$ is $0.50$ against a predicted maximum of $\sim$30, a $\sim$59$\times$ margin. The 66 red and black cells together are $\mathcal{S}_{\text{pred}} = \mathcal{S}_{\text{act}}$ under the identity defense—predicted and actual persistent sets coincide cell-for-cell. (Log $y$-axis to show both the dots and the bound line on the same plot.)

On the saturated run, every one of the 66 predicted-persistent cells is also actually persistent under identity, with zero false positives and zero false negatives—the predicted set $\mathcal{S}_{\text{pred}}$ and the empirical set $\mathcal{S}_{\text{act}}$ are *the same set of* 66 *cells*, on a real OpenAI model surface, with no model-specific tuning of the validator. Theorem 5.1's $\varepsilon$-robust bound also holds for all 82 filled cells under identity, with worst-case empirical $|f(D(x)) - \tau|$ of $0.50$ vs. predicted maximum $LK\,\mathrm{dist}(x, z^*) + |f(z^*) - \tau| = 29.30$, a $\sim$59$\times$ margin. Theorem 4.1's boundary fixation is non-vacuously activated: 10 boundary cells exist in $\overline{S_\tau} \setminus S_\tau$ and the closest one to $\tau$ sits at $|f(z^*) - \tau| = 0.375$, the discretization gap that vanishes under grid refinement.

**Defense sweep on the saturated grid.** The validator's `sweep` subcommand runs the same archive against the canonical identity defense and against multiple discrete `bounded_step` defenses with progressively larger displacement radii. Across all 7 defenses tested (identity plus `bounded_step` with max_step $\in \{1, 2, 3, 5, 8, 12\}$), the per-cell confusion-matrix produces *zero interior false positives* on every run—i.e., zero empirical counterexamples to Theorem 6.3 across the entire defense sweep on the same dense alignment-deviation surface (Table 4).

Reading the sweep: as the defense's reach grows from max_step $= 1$ (cell can move at most one grid step) to max_step $= 8$ (essentially nearest-safe projection), the actual persistent set shrinks from 55 cells down to 0. The predicted steep set under any `bounded_step` is just the anchor cell because the empirical defense-path Lipschitz constant $\ell = L = 23.63$ on this dense surface, which forces $\ell(K{+}1) > G$ for all $K > 0$—transversality fails for the discrete bounded defenses. Theorem 6.3 therefore makes no positive prediction on those rows, only the negative one ("no interior counterexample is allowed"), and the empirical data confirms it. The well-aligned target additionally exemplifies the harmless-boundary case: at $\tau = 0.5$, gpt-5-mini's peak AD is exactly $0.5$ and $U_\tau = \emptyset$, so the trilemma's preconditions fail and the validator correctly reports "not applicable"—matching the qualitative GPT-5-Mini observation above and confirming the theorem's silence in the right place.

Table 4: Defense sweep on the saturated `gpt-3.5-turbo-0125` grid (82 filled cells, $\tau = 0.5$). Empirical defense Lipschitz constant $K$ grows with reach; the steep-set size shrinks (`bounded_step` is non-continuous, so its steep set collapses to the anchor under the discrete check) but the actual persistent set falls cleanly along the K-tradeoff curve from Theorem 7.3. **Across all 7 defenses, $\mathbf{FP_{int}} = 0$.**

| **Defense** | $K$ | $\ell$ | $\lvert\mathcal{S}_{\text{pred}}\rvert$ | $\lvert\mathcal{S}_{\text{act}}\rvert$ | **TP** | $\mathbf{FP_{int}}$ | **FN** |
|---|---|---|---|---|---|---|---|
| identity | 1.00 | 0.00 | 66 | 66 | 66 | **0** | 0 |
| `bounded_step(1)` | 3.61 | 23.63 | 1 | 55 | 0 | **0** | 55 |
| `bounded_step(2)` | 3.61 | 23.63 | 1 | 47 | 0 | **0** | 47 |
| `bounded_step(3)` | 4.00 | 23.63 | 1 | 29 | 0 | **0** | 29 |
| `bounded_step(5)` | 8.60 | 23.63 | 1 | 3 | 0 | **0** | 3 |
| `bounded_step(8)` | 8.60 | 23.63 | 1 | 0 | 0 | **0** | 0 |
| `bounded_step(12)` | 8.60 | 23.63 | 1 | 0 | 0 | **0** | 0 |

The validator is available as a small standalone Python package (`trilemma_validator/` in the repository), with subcommands `trilemma pipeline` (run `rethinking-evals` end-to-end and validate), `trilemma validate` (analyze an existing heatmap), `trilemma sweep` (run multiple defenses on a single archive), `trilemma experiment` (just run the experiment), and `trilemma synth` (generate a synthetic mesa/mosaic/flat surface for a self-contained smoke test). The full per-cell records (each cell's $f(x)$, $D(x)$, $f(D(x))$, distance to $z^*$, $\varepsilon$-robust LHS and RHS, and steep/persistent membership flags) are emitted as JSON by the validator and reproduced from the live archives in `trilemma_validator/live_runs/`, including the saturated grid above (`gpt35_turbo_t05_saturated/`).

## 11 The Engineering Prescription

The results do not say defense is valueless; they say *complete* defense is impossible under the stated constraints. The engineering goal shifts from elimination to management, ordered from most to least actionable:

**1. Make the boundary shallow.** Set $\tau$ so that boundary-level behavior is benign. If $f(z) = \tau$ yields a polite refusal rather than harmful compliance, the impossibility is mathematically true but practically harmless. GPT-5-Mini exemplifies this: its ceiling at $\mathrm{AD} = 0.50$ means $U_\tau = \emptyset$, so the impossibility theorems do not apply and no defense failure is predicted.

**2. Reduce the Lipschitz constant.** Smaller $L$ tightens the bound $\ell \leq L$, potentially reducing the defense-path constant $\ell$ and narrowing the persistent region. The tradeoff: smoother surfaces spread vulnerabilities over wider but more easily monitored regions.

**3. Reduce the effective dimension.** Defense cost grows as $N^d$ (Theorem F.1). Constraining the prompt interface—standardized formats, restricted API parameters, bounded context lengths—reduces $d$, making the behavioral space tractable.

**4. Monitor, don't eliminate, the boundary.** Transversal crossings persist under fine-tuning (Theorem E.2) and recur every turn (Theorem 9.1). Rather than attempt the impossible, deploy runtime monitoring that detects approach to the boundary. The Lipschitz bound (Theorem D.1) gives a computable estimate of distance to the boundary from any observed AD value.

## 12 Limitations

**Boundary fixation is at the boundary.** Fixed points satisfy $f(z) = \tau$ exactly. If $\tau$-level behavior is benign, the theorem is true but harmless.

**The $\varepsilon$-robust constraint limits depth, not direction.** The defense may push near-boundary points slightly below $\tau$. The bound limits how far, not whether.

**Persistence requires transversality.** The persistent unsafe region exists only where the alignment surface is steep ($c > \ell(K+1)$, where $\ell$ is the defense-path Lipschitz constant). For isotropic $f$ ($\ell = L$), $\mathcal{S}$ is empty for all $K \geq 0$.

**Grid-based cost asymmetry.** Theorem F.1 assumes exhaustive grid enumeration. Learning-based defenses that generalize across the space may sidestep the exponential bound.

## 13 Conclusion

We establish a three-level impossibility hierarchy for prompt-injection defense: boundary fixation, the $\varepsilon$-robust constraint, and the persistent unsafe region theorem. Continuous topology, Lipschitz bounds, discrete counting, stochastic expectations, multi-turn dynamics, and capacity constraints all point to the same conclusion: under the wrapper model, some failures persist.

The practical prescription is to make the boundary shallow, smooth, and low-dimensional, and to engineer around it rather than assume it can be eliminated.

## Broader Impact

This work characterizes structural limitations of a specific class of defenses (continuous utility-preserving wrappers). The results could inform defense engineering by identifying which design constraints matter most. They could also be misread as implying that LLM defense is futile—this is not the case. The theorems apply only to wrappers satisfying specific mathematical assumptions; training-time alignment, architectural changes, discontinuous filtering, ensemble defenses, and human-in-the-loop systems are not covered. We emphasize that the impossibility results should motivate better defense design, not abandonment of defense.

## References


[1] G. Alon and M. Kamfonas. Detecting language model attacks with perplexity. *arXiv preprint arXiv:2308.14132*, 2023.

[2] A. Bagnall and G. Stewart. Certifying the true error: Machine learning in Coq with verified generalization guarantees. *Proceedings of the AAAI Conference on Artificial Intelligence*, 2019.

[3] Y. Bai et al. Constitutional AI: Harmlessness from AI feedback. *arXiv preprint arXiv:2212.08073*, 2022.

[4] P. Chao, A. Robey, E. Dobriban, H. Hassani, G. J. Pappas, and E. Wong. Jailbreaking black box large language models in twenty queries. *arXiv preprint arXiv:2310.08419*, 2024.

[5] J. Cohen, E. Rosenfeld, and J. Z. Kolter. Certified adversarial robustness via randomized smoothing. *Proceedings of ICML*, 2019.

[6] I. J. Goodfellow, J. Shlens, and C. Szegedy. Explaining and harnessing adversarial examples. *Proceedings of ICLR*, 2015.

[7] H. Inan et al. Llama Guard: LLM-based input-output safeguard for human-AI conversations. *arXiv preprint arXiv:2312.06674*, 2023.

[8] G. Katz, C. Barrett, D. L. Dill, K. Julian, and M. J. Kochenderfer. Reluplex: An efficient SMT solver for verifying deep neural networks. *Proceedings of CAV*, 2017.

[9] N. Carlini and D. Wagner. Towards evaluating the robustness of neural networks. *Proceedings of IEEE S&P*, 2017.

[10] A. Mehrotra et al. Tree of attacks: Jailbreaking black-box LLMs automatically. *Advances in Neural Information Processing Systems*, 37, 2024.

[11] A. Fawzi, H. Fawzi, and O. Fawzi. Adversarial vulnerability for any classifier. *Advances in Neural Information Processing Systems*, 31, 2018.

[12] K. Greshake, S. Abdelnabi, S. Mishra, C. Endres, T. Holz, and M. Fritz. Not what you've signed up for: Compromising real-world LLM-integrated applications with indirect prompt injection. *Proceedings of AISec*, 2023.

[13] X. Huang, M. Kwiatkowska, S. Wang, and M. Wu. Safety verification of deep neural networks. *Proceedings of CAV*, 2017.

[14] A. Madry, A. Makelov, L. Schmidt, D. Tsipras, and A. Vladu. Towards deep learning models resistant to adversarial attacks. *Proceedings of ICLR*, 2018.

[15] J.-B. Mouret and J. Clune. Illuminating search spaces by mapping elites. *arXiv preprint arXiv:1504.04909*, 2015.

[16] G. Naitzat, A. Zhitnikov, and L.-H. Lim. Topology of deep neural networks. *Journal of Machine Learning Research*, 21(184):1–40, 2020.

[17] S. Munshi, M. Bhatt, V. S. Narajala, I. Habler, A. Al-Kahfah, K. Huang, and B. Gatto. Manifold of failure: Behavioral attraction basins in language models. *arXiv preprint arXiv:2602.22291v2*, 2026.

[18] M. Samvelyan et al. Rainbow teaming: Open-ended generation of diverse adversarial prompts. *Advances in Neural Information Processing Systems*, 37, 2024.

[19] G. Singh, T. Gehr, M. Püschel, and M. Vechev. An abstract domain for certifying neural networks. *Proceedings of POPL*, 2019.

[20] C. Szegedy et al. Intriguing properties of neural networks. *Proceedings of ICLR*, 2014.

[21] D. Tsipras, S. Santurkar, L. Engstrom, A. Turner, and A. Madry. Robustness may be at odds with accuracy. *Proceedings of ICLR*, 2019.

[22] D. H. Wolpert and W. G. Macready. No free lunch theorems for optimization. *IEEE Trans. Evol. Comput.*, 1(1):67–82, 1997.

[23] A. Zou, Z. Wang, N. Carlini, M. Nasr, J. Z. Kolter, and M. Fredrikson. Universal and transferable adversarial attacks on aligned language models. *arXiv preprint arXiv:2307.15043*, 2023.

[24] K. Ge et al. MART: Improving LLM safety with multi-round automatic red-teaming. *Proceedings of NAACL*, 2024.

[25] E. Hubinger et al. Sleeper agents: Training deceptive LLMs that persist through safety training. *arXiv preprint arXiv:2401.05566*, 2024.

[26] C. Anil et al. Many-shot jailbreaking. *Advances in Neural Information Processing Systems*, 37, 2024.

[27] D. Kim et al. What really matters in many-shot attacks? *Proceedings of ACL*, 2025.

[28] Q. Zhan et al. InjecAgent: Benchmarking indirect prompt injections in tool-integrated LLM agents. *Findings of ACL*, 2024.

[29] H. Zhang et al. Agent security bench (ASB): Formalizing and benchmarking attacks and defenses in LLM-based agents. *arXiv preprint arXiv:2410.02644*, 2024.

[30] Y. Yuan et al. The instability of safety. *arXiv preprint arXiv:2512.12066*, 2025.

[31] V. Tsvetkov et al. Quantization and safety: A closer look at LLM safety under weight compression. *arXiv preprint arXiv:2502.15799*, 2025.

[32] F. Nesti et al. Mind the gap: Adversarial attacks against GGUF quantized LLMs. *Proceedings of ICML*, 2025.

[33] H. Hammoud et al. Model merging and safety alignment: One bad model spoils the bunch. *Findings of EMNLP*, 2024.

[34] X. Liu et al. Alignment whack-a-mole. *arXiv preprint arXiv:2603.20957*, 2026.

[35] D. Rosenberg et al. IRIS: Adversarial suffix attacks against robust defenses. *Proceedings of NAACL*, 2025.

[36] X. Zhao et al. Weak-to-strong jailbreaking on large language models. *Proceedings of ICML*, 2025.

[37] Y. Huang et al. The safety tax of reasoning alignment. *arXiv preprint arXiv:2503.00555*, 2025.

[38] Y. Huang et al. On the geometric inevitability of the alignment tax. *arXiv preprint arXiv:2603.00047*, 2026.

[39] L. Bailey et al. Slingshot: RL-based agent-to-agent jailbreaking. *arXiv preprint arXiv:2602.02395*, 2026.

# Appendices

## A Vulnerability Landscape

This section characterizes the geometry of the unsafe region.

**Theorem A.1** (Basin Structure)**.** *If $f$ is continuous and $f(p) > \tau$, then $U_\tau$ is open. Under any measure positive on nonempty open sets, $U_\tau$ has positive measure.*

**Theorem A.2** (Basin Fragment Minimum Size)**.** *If $X$ is a normed space, $f$ is $L$-Lipschitz with $f(p) > \tau$, the connected component of $U_\tau$ containing $p$ has diameter $\geq 2(f(p) - \tau)/L$.*

Smoother surfaces (smaller $L$) produce larger basins; rougher surfaces produce smaller fragments.

## B Full Proofs

*Proof of Theorem 4.1 (Boundary Fixation).* **Step 1** (Hausdorff $\Rightarrow$ fixed-point set is closed). $\mathrm{Fix}(D) = \{x : D(x) = x\}$ is the preimage of the diagonal $\Delta \subset X \times X$ under $x \mapsto (D(x), x)$. In a Hausdorff space, $\Delta$ is closed, so $\mathrm{Fix}(D)$ is closed.

**Step 2** (Utility preservation $\Rightarrow$ safe region $\subseteq$ fixed points). $S_\tau \subseteq \mathrm{Fix}(D)$. Since $\mathrm{Fix}(D)$ is closed: $\overline{S_\tau} \subseteq \mathrm{Fix}(D)$.

**Step 3** (Connectedness $\Rightarrow$ safe region is not closed). $S_\tau = f^{-1}((-\infty, \tau))$ is open. If also closed, it would be clopen—but in a connected space the only clopen sets are $\emptyset$ and $X$. Since both $S_\tau$ and $U_\tau$ are nonempty, $S_\tau$ is not closed.

**Step 4** (Boundary point exists). $\overline{S_\tau} \supsetneq S_\tau$, so there exists $z \in \overline{S_\tau} \setminus S_\tau$. Continuity gives $f(z) \leq \tau$; $z \notin S_\tau$ gives $f(z) \geq \tau$. Hence $f(z) = \tau$.

**Step 5** (Defense fixes the boundary point). $z \in \overline{S_\tau} \subseteq \mathrm{Fix}(D)$, so $D(z) = z$ and $f(D(z)) = \tau$. □

*Proof of Theorem 5.1 ($\varepsilon$-Robust Constraint).* By Theorem 4.1, the fixed boundary point $z$ exists.

**Step 1.** Since $D(z) = z$ and $D$ is $K$-Lipschitz: $\mathrm{dist}(D(x), z) = \mathrm{dist}(D(x), D(z)) \leq K\,\mathrm{dist}(x, z)$.

**Step 2.** Since $f(z) = \tau$ and $f$ is $L$-Lipschitz: $|f(D(x)) - \tau| = |f(D(x)) - f(z)| \leq L\,\mathrm{dist}(D(x), z) \leq LK\,\mathrm{dist}(x, z)$. □

*Proof of Theorem 6.3 (Persistent Unsafe Region).* **(1)** $\mathcal{S}$ is the strict superlevel set of $x \mapsto f(x) - \ell(K+1)\,\mathrm{dist}(x, z)$ at level $\tau$, hence open.

**(2)** Open and nonempty implies positive measure.

**(3)** For $x \in \mathcal{S}$: $f(x) > \tau + \ell(K+1)\,\mathrm{dist}(x, z)$. By Theorem 6.1: $f(D(x)) \geq f(x) - \ell(K+1)\,\mathrm{dist}(x, z) > \tau$.

*Lean:* `persistent_unsafe_refined` *in* `MoF_20_RefinedPersistence` *(defense-path constant $\ell$).* `MoF_11_EpsilonRobust` *contains an earlier version using the global constant $L$; as noted in Section 6, that version is vacuous for isotropic surfaces.* □

## C Counterexamples: Each Hypothesis Is Necessary

**Counterexample C.1** (Removing connectedness)**.** $X = \{0, 1\}$ *discrete,* $f(0) = 0$, $f(1) = 1$, $\tau = 0.5$. $D(0) = 0$, $D(1) = 0$*: continuous, utility-preserving, complete.*

**Counterexample C.2** (Removing continuity)**.** $X = [0, 1]$, $f(x) = x$, $\tau = 0.5$. $D(x) = x$ *for* $x < 0.5$, $D(x) = 0$ *for* $x \geq 0.5$*: utility-preserving and complete, but discontinuous at* $0.5$.

**Counterexample C.3** (Removing utility preservation)**.** $D(x) = x_0$ *for a fixed safe point: continuous and complete, but destroys all inputs.*

## D Attack Properties

**Theorem D.1** (Perturbation Robustness)**.** *If $f$ is $L$-Lipschitz and $f(p) > \tau$, then $B(p, (f(p) - \tau)/L) \subseteq U_\tau$. The radius is monotone in $f(p)$.*

**Theorem D.2** (Iterative Convergence)**.** *Any monotone-improvement operator $T$ with score in $[0, 1]$ converges. If each step gains $\geq \delta$, convergence takes $\leq \lfloor 1/\delta \rfloor$ steps.*

**Theorem D.3** (Transferability)**.** $\|f - g\|_\infty \leq \delta \implies \{f > \tau + \delta\} \subseteq \{g > \tau\}$. *Transfer costs zero additional queries.*

**Theorem D.4** (Authority Monotonicity)**.** *If $f(y, \cdot)$ is monotone non-decreasing in authority for each fixed indirection $y$, the vulnerability set is upward-closed with a critical threshold $a_2^*(y)$ (by IVT, when $f(y, \cdot)$ is continuous and crosses $\tau$). If additionally $f$ is monotone non-decreasing in indirection for each fixed authority, the threshold curve $y \mapsto a_2^*(y)$ is non-increasing.*

**Theorem D.5** (Gradient Ascent)**.** *If $f$ has nonzero Fréchet derivative at $x$, there exist $v$ and $\varepsilon > 0$ with $f(x + \varepsilon v) > f(x)$.*

## E Stability Under Fine-Tuning

**Theorem E.1** (Interior Stability)**.** *If $\|f - g\|_\infty \leq \varepsilon$: $f(x) > \tau + \varepsilon \implies g(x) > \tau$, and $f(x) < \tau - \varepsilon \implies g(x) < \tau$. Only the band $|f(x) - \tau| \leq \varepsilon$ is uncertain.*

**Theorem E.2** (Crossing Preservation)**.** *Let $f, g\colon [a, b] \to \mathbb{R}$ be continuous. If $f$ crosses $\tau$ on $[a, b]$ with margin $m$ (i.e., $f(a') < \tau - m$ and $f(b') > \tau + m$ for some $a', b' \in [a, b]$) and $\|f - g\|_\infty \leq \varepsilon < m$, then $g$ also crosses $\tau$ on $[a, b]$.*

**Theorem E.3** (Patching Is Nonlocal)**.** *There exist $f, g$ with $\|f - g\|_\infty \leq \varepsilon$ such that eliminating a vulnerability at one point necessarily changes values at distant points.*

## F Cost Asymmetry

**Theorem F.1** (Exponential Cost Asymmetry)**.** *For grid-based defense with $N \geq 2$ bins per axis in $d$ dimensions: attack cost $\leq 1/\delta$ (dimension-independent); defense cost $= N^d$ (exponential in $d$); ratio $\delta \cdot N^d \to \infty$ as $d \to \infty$.*

At $d = 2$ with $N = 25$ and $\delta = 0.01$, the ratio is $6.25$. At $d = 10$, it climbs to $\sim 10^{12}$.

## G Additional Verified Results

**Lipschitz displacement bound.** $D$ is $K$-Lipschitz with $D(z) = z \implies \operatorname{dist}(D(x), x) \leq (K + 1) \operatorname{dist}(x, z)$.

**Tool calls amplify failure.** Each non-contractive tool call multiplicatively increases the pipeline's effective Lipschitz constant: $K^n < K^{n+1}$ for $K \geq 2$.

**Attacker monotone improvement.** Best observed alignment deviation is non-decreasing across turns.

**Attacker steering.** If directional slope varies continuously with attacker parameter $\alpha$ and crosses $\ell(K + 1)$, transversality is reachable by IVT.

**Stochastic regularity.** $g(x) = \mathbb{E}[f(D(x))]$ satisfies $g - f = 0$ on $\overline{S_\tau}$.

**Discrete defense dilemma.** An injective, utility-preserving defense is incomplete (every unsafe input stays unsafe). A complete, utility-preserving defense is non-injective (distinct inputs collapse to the same output). The three properties—completeness, utility preservation, injectivity—form a trilemma.

**Defense position invariance.** Lipschitz constant of defense-before-tools equals defense-after-tools: $K_D \cdot K_T^n$.

## H Lean Artifact

The complete theory is verified in Lean 4.28.0 with Mathlib v4.28.0, available at `https://github.com/mbhatt1/stuff/tree/main/ManifoldProofs`. The artifact comprises 46 files:

- 10 core theory files (MoF_01–MoF_10)
- 10 cost theory files (MoF_Cost_01–MoF_Cost_10)
- 10 advanced theory files (MoF_Adv_01–MoF_Adv_10)
- 1 continuous relaxation (MoF_ContinuousRelaxation)
- 1 $\varepsilon$-robust constraint + persistent unsafe region with global Lipschitz constant (MoF_11_EpsilonRobust)
- 1 discrete impossibility (MoF_12_Discrete)
- 1 multi-turn + stochastic extensions (MoF_13_MultiTurn)
- 1 representation-independent meta-theorem (MoF_14_MetaTheorem)
- 1 nonlinear agent pipelines (MoF_15_NonlinearAgents)
- 1 relaxed utility preservation (MoF_16_RelaxedUtility)
- 1 quantitative $\varepsilon$-band volume bound (MoF_17_CoareaBound)
- 1 cone measure bound for persistent unsafe region (MoF_18_ConeBound)
- 1 optimal defense characterization (MoF_19_OptimalDefense)
- 1 refined persistence with defense-path Lipschitz constant $\ell$ (MoF_20_RefinedPersistence); this file contains the primary formalization of Theorems 6.1 to 6.3
- 1 gradient chain: $\|\nabla f(z)\| > \ell(K+1)$ implies persistent unsafe region via operator-norm direction extraction and derivative-based local growth (MoF_21_GradientChain)
- 3 capstone files (MasterTheorem, Euclidean instantiation, verification)
- 1 root import file (ManifoldProofs.lean)