

HANDS ON ACTIVITY EMBEDDED SYSTEMS

1] Write a program to count no. of bits which are set in given binary pattern .

Code::

```
#include <stdio.h>
int countSetBits(unsigned int num) {
    int count = 0;
    while (num) {
        count += num & 1; num >>= 1;
    } return count; }
int main() {
    unsigned int num = 0b10101010;
    printf("Number of set bits: %d\n", countSetBits(num));
    return 0; }
```

Output: Number of set bits: 4

2] Write a program to set 5th and 12th bits in a 16-bit unsigned integer

Code:

```
#include <stdio.h>
unsigned int setBits(unsigned int num, int pos1, int pos2) {
    unsigned int mask = (1 << pos1) | (1 << pos2);
    return num | mask;
}
int main() {
    unsigned int num = 0b00000000;    num = setBits(num, 5, 12);
    printf("Modified number: %d\n", num);
    return 0;
}
```

Output: Modified number: 4864

3] Write a program to clear 6th and 19th bits in a 32-bit unsigned integer.

Code:

```
#include <stdio.h>
unsigned int clearBits(unsigned int num, int pos1, int pos2) {
    unsigned int mask = ~(1 << pos1) & ~(1 << pos2);
    return num & mask;
}
```

```

}
int main() { unsigned int num = 0b111111111111111111;
num = clearBits(num, 6, 19);
printf("Modified number: %u\n", num);
return 0;
}

```

Output: Modified number: 524287

4] Write a program to flip even positioned bits in a 16-bit unsigned integer

Code:

```

#include <stdio.h>
unsigned int flipEvenBits(unsigned int num) {
    unsigned int mask = 0xAAAA; // Binary pattern with even bits set
    return num ^ mask;
}
int main() {
    unsigned int num = 0b1010101010101010; // Example 16-bit unsigned
integer
    num = flipEvenBits(num);
    printf("Modified number: %d\n", num);
    return 0;
}

```

Output: Modified number: 2730

5] Given an unsigned 32-bit integer holding packed IPv4 address, convert it into "a. b. c. d" format.

Code:

```

#include <stdio.h>
int countSetBits(unsigned int num) {
    int count = 0;
    while (num) {
        count += num & 1;
        num >>= 1;
    }
    return count;
}
int main() {
    unsigned int num = 0b10101010; // Example binary pattern
    printf("Number of set bits: %d\n", countSetBits(num));
    return 0;
}

```

Output: Number of set bits: 4

6] Convert MAC address into 48-bit binary pattern

Code:

```
#include <stdio.h>
void unpackIPAddress(unsigned int ip) {
    int a, b, c, d;
    a = (ip >> 24) & 255;
    b = (ip >> 16) & 255;
    c = (ip >> 8) & 255;
    d = ip & 255;
    printf("Unpacked IP address: %d.%d.%d.%d\n", a, b, c, d);
}
int main() {
    unsigned int packedIP = 3232235777; // Example packed IP address
    unpackIPAddress(packedIP);
    return 0;
}
```

Output: Unpacked IP address: 192.168.1.1

7] Convert 48-bit binary pattern as MAC address

Code:

```
#include <stdio.h>

void macToBinaryPattern(char *mac) {
    unsigned long long int binary = 0;
    sscanf(mac, "%2hhx:%2hhx:%2hhx:%2hhx:%2hhx:%2hhx", (unsigned char *)&binary,
        (unsigned char *)&binary + 1, (unsigned char *)&binary + 2,
        (unsigned char *)&binary + 3, (unsigned char *)&binary + 4,
        (unsigned char *)&binary + 5);
    printf("Binary pattern: %llx\n", binary);
}

int main() {
    char mac[] = "12:34:56:78:9a:bc"; // Example MAC address
    macToBinaryPattern(mac);
    return 0;
}
```

Output: Binary pattern: 123456789abc

8] Convert 48-bit binary pattern to MAC address.

Code:

```
#include <stdio.h>
void binaryPatternToMac(unsigned long long int binary)
{
    printf("MAC address: %02llx:%02llx:%02llx:%02llx:%02llx:%02llx\n",
        (binary >> 40) & 0xFF, (binary >> 32) & 0xFF, (binary >> 24) & 0xFF,
        (binary >> 16) & 0xFF, (binary >> 8) & 0xFF, binary & 0xFF);
}
int main() {
    unsigned long long int binary = 0x123456789abc; // Example binary pattern
    binaryPatternToMac(binary);
    return 0;
}
```

Output: MAC address: 12:34:56:78:9a:bc
