

Part I

Introduction

1 An Overview (week 1)

1.1 Information Systems

1. Functions in models
 - ☐ Are always computable
 - ☐ Can always be represented as data
 - ☐ Can be constrained by axioms
2. Interpretation relationships
 - ☐ Are always computable
 - ☐ Relate constants to real-world entities
 - ☐ Are uniquely defined

1.2 Data Management

1. What is not specified in the data definition language ?
 - ☐ The structure of a relational table
 - ☐ The query of user
 - ☐ A constraint on a relational table
2. Logical data independence means
 - ☐ An abstract data type is implemented using different data structures
 - ☐ A new view is computed without changing an existing database schema
 - ☐ A model can be represented in different data modelling formalisms

1.3 Data Management Tasks

1. Which is wrong ? An index structure
 - ☐ Is created as part of physical database design
 - ☐ Is selected during query optimization
 - ☐ Accelerates search queries
 - ☐ Accelerates tuple insertion
2. Persistence means that
 - ☐ A change of a transaction on a database is never lost after it is completed
 - ☐ The state of a database is independent of the lifetime of a program
 - ☐ The same logical database can be stored in different ways on a storage medium

1.4 Information Management

1. Grouping Twitter users according to their interest by analyzing the content of their tweets is
 - ☐ A retrieval task
 - ☐ A data mining task
 - ☐ An evaluation task
 - ☐ A monitoring task

1.5 Distributed Information Systems

1. Creating a web portal for comparing product prices is (primarily) a problem of
 - ☐ Distributed data management
 - ☐ Heterogeneous data integration
 - ☐ Collaboration among autonomous systems

1.6 Distributed Data Management

1. When you open a Web page with an embedded Twitter stream, the communication model used by Twitter is
 - ☐ Push, unicast and conditional
 - ☐ Pull, multicast and ad-hoc
 - ☐ Push, multicast and ad-hoc
 - ☐ Pull, unicast and conditional

1.7 Heterogeneity

1. Creating a web portal for comparing product prices requires to address
 - ☐ Syntactic heterogeneity
 - ☐ Semantic heterogeneity
 - ☐ Both
2. An ontology is a
 - ☐ Sdatabase
 - ☐ database schema
 - ☐ data model
 - ☐ data modeling formalism
 - ☐ model

1.8 Autonomy

1. Trust is
 - ☐ A quality of information
 - ☐ A quality of a user
 - ☐ A quality of the relationship among user and information
 - ☐ A quality of the relationship among users

Part II

Storage

2 Distributed Data Management

2.1 Schema Fragmentation

2.1.1 Relational Databases

1. At which phase of the database lifecycle is fragmentation performed ?
 - ☐ At database design time

- ☐ During distributed query processing
- ☐ During updates to a distributed database

2. The reconstruction property expresses that


- ☐ In case of a node failure the data can be recovered from a fragment from another node
- ☐ The original data can be fully recovered from the fragments
- ☐ Every data value of the original data can be found in at least one fragment

2.1.2 Primary Horizontal Fragmentation (week 2)

1. Example: application A1 accesses


1. Fragment F1: with frequency 3
2. Fragment F2: with frequency 1

A1 accesses the whole relation with frequency



- ☐ 13/7
- ☐ 4/7
- ☐ 14/7

2. Consider the access frequencies below: How many horizontal fragments would a minimal and complete fragmentation have?



- ☐ 3
- ☐ 4
- ☐ 6

3. Which of the following sets of simple predicates is complete?



- ☐ Location = "Munich", Budget > 200000
- ☐ Location = "Munich", Location = "Bangalore"
- ☐ Location = "Paris", Budget ≤ 200000
- ☐ None of those

4. Which is true for MinFrag algorithm?

- ☐ The output is independent of the order of the input
- ☐ It produces a monotonically increasing set of predicates
- ☐ It always terminates
- ☐ All of the above statements are true

5. When deriving a horizontal fragmentation for relation S from a horizontally fragmented relation R

- ☐ Some primary key attribute in R must be a foreign key in S
- ☐ Some primary key attribute in S must be a foreign key in R
- ☐ Both are required

2.2 Graph Databases (week 3)

2.2.1 Semi-structured Data

1. Semi-structured data

- ☐ Is always schema-less
- ☐ Always embeds schema information into the data
- ☐ Must always be hierarchically structured
- ☐ Can never be indexed

2. Why is XML a document model?

- ☐ It supports application-specific markup
- ☐ It supports domain-specific schemas
- ☐ It has a serialized representation
- ☐ It uses HTML tags

2.2.2 Graph Data Model

1. In a graph database

- ☐ There is a unique root node
- ☐ Each node has a unique identifier
- ☐ Data values in leaf nodes are unique
- ☐ The labels of edges leaving a node are different
- ☐ There is a unique path from the root to each leaf

2. The simulation relationship is a relation

- ☐ Among nodes in the data and schema graph
- ☐ Among edges in the data and schema graph
- ☐ Among sets of nodes in the data and schema graph
- ☐ Among sets of edges in the data and schema graph

3. Which is true?

- ☐ For each labelled edge in S a corresponding edge in D can be identified
- ☐ For each root node in S a corresponding root node D can be identified
- ☐ For each leaf node in D a corresponding typed node in S can be identified

- ☐ For each node in S a unique path reaching it from a root node can be identified
- 4. If there exists a uniquely defined simulation relationship among a graph database D and a schema graph S
 - ☐ The data and schema graph are simulation equivalent
 - ☐ Ambiguous classification cannot occur
 - ☐ Multiple classification cannot occur
- 5. If schema graph S_1 subsumes S_2
 - ☐ Every graph database corresponding to S_1 corresponds also to S_2
 - ☐ S_2 simulates S_1
 - ☐ S_1 has fewer nodes than S_2

2.2.3 Schema Extraction

1. Which is wrong? In a dataguide
 - ☐ Every path in the data graph occurs only once
 - ☐ Every node in the data graph occurs only in one data guide node
 - ☐ Every data guide node has a unique set of nodes
 - ☐ A leaf node in the data graph corresponds always to a leaf node in the data guide
2. In a non-deterministic schema graph
 - ☐ Every node of the data graph occurs exactly once
 - ☐ Every path of the data graph occurs at most once
 - ☐ Every label of an outgoing edge of a node in the schema graph is unique

Part III Search

3 Information Retrieval and Data Mining

3.1 Information Retrieval (week 4)

3.1.1 Information Retrieval

1. A retrieval model attempts to model
 - ☐ The interface by which a user is accessing information
 - ☐ The importance a user gives to a piece of information
 - ☐ The formal correctness of a query formulation by user
 - ☐ All of the above
2. If the top 100 documents contain 50 relevant documents
 - ☐ The precision of the system at 50 is 0.5
 - ☐ The precision of the system at 100 is 0.5
 - ☐ The recall of the system is 0.5
 - ☐ None of the above
3. If retrieval system A has a higher precision than system B
 - ☐ The top k documents of A will have higher similarity values than the top k documents of B

- ☐ The top k documents of A will contain more relevant documents than the top k documents of B
- ☐ A will recall more documents above a given similarity threshold than B
- ☐ Relevant documents in A will have higher similarity values than in B

3.1.2 Text-based Information Retrieval

1. Full-text retrieval means that
 - ☐ The document text is grammatically deeply analyzed for indexing
 - ☐ The complete vocabulary of a language is used to extract index terms
 - ☐ All words of a text are considered as potential index terms
 - ☐ All grammatical variations of a word are indexed
2. The term-document matrix indicates
 - ☐ How many relevant terms a document contains
 - ☐ How relevant a term is for a given document
 - ☐ How often a relevant term occurs in a document collection
 - ☐ Which relevant terms are occurring in a document collection
3. Let the query be represented by the following vectors: (1, 0, -1) (0, -1, 1); the document by the vector (1, 0, 1)
 - ☐ Matches the query because it matches the first query vector
 - ☐ Matches the query because it matches the second query vector
 - ☐ Does not match the query because it does not match the first query vector
 - ☐ Does not match the query because it does not match the second query vector
4. Which is right? The term frequency is normalized
 - ☐ By the maximal frequency of a term in the document
 - ☐ By the maximal frequency of a term in the document collection
 - ☐ By the maximal frequency of a term in the vocabulary
 - ☐ By the maximal term frequency of any document in the collection
5. The inverse document frequency of a term can increase
 - ☐ By adding the term to a document that contains the term
 - ☐ By adding a document to a document collection that does not contain the term
 - ☐ By removing a document from the document collection that does not contain the term
 - ☐ By adding a document to a document collection that contains the term

3.2 Advanced Retrieval Models (week 5)

3.2.1 Latent Semantic Indexing


1. In vector space retrieval each row of the matrix M^T corresponds to
 - ☐ A document
 - ☐ A concept
 - ☐ A query
 - ☐ A query result
2. Applying SVD to a term-document matrix \mathbf{M} . Each concept is represented
 - ☐ As a singular value
 - ☐ As a linear combination of terms of the vocabulary
 - ☐ As a linear combination of documents in the document collection
 - ☐ As a least square approximation of the matrix \mathbf{M}
3. The number of term vectors in the SVD for LSI
 - ☐ Is smaller than the number of rows in the matrix \mathbf{M}
 - ☐ Is the same as the number of rows in the matrix \mathbf{M}
 - ☐ Is larger than the number of rows in the matrix \mathbf{M}
4. A query transformed into the concept space for LSI has
 - ☐ s components (number of singular values)
 - ☐ m components (size of vocabulary)
 - ☐ n components (number of documents)

3.2.2 User Relevance Feedback

1. Can documents which do not contain any keywords of the original query receive a positive similarity coefficient after relevance feedback ?
 - ☐ No
 - ☐ Yes, independent of the values β and γ
 - ☐ Yes, but only if $\beta > 0$
 - ☐ Yes, but only if $\gamma > 0$

3.2.3 Link-based Ranking

2. A positive random jump value for exactly one node implies that
 - ☐ a random walker can leave the node even without outgoing edges
 - ☐ a random walker can reach the node multiple times even without outgoing edges
 - ☐ a random walker can reach the node even without incoming edges
 - ☐ none of the above
3. Given the graph below and an initial hub vector of $(1, 1, 1)$. The hub-authority ranking will result in the following



- ☐ authority vector $(0, 0, 1)$; hub vector $(1, 1, 0)$
- ☐ authority vector $(0, 0, 2)$; hub vector $(2, 2, 0)$
- ☐ authority vector $(0, 0, 1)$; hub vector $(\frac{1}{2}, \frac{1}{2}, 0)$
- ☐ authority vector $(0, 0, 2)$; hub vector $(1, 1, 0)$

3.2.4 Inverted Files (week 6)

1. A posting indicates
 - ☐ The frequency of a term in the vocabulary
 - ☐ The frequency of a term in a document
 - ☐ The occurrence of a term in a document
 - ☐ The list of terms occurring in a document
2. When indexing a document collection using an inverted file, the main space requirement is implied by
 - ☐ The access structure
 - ☐ The vocabulary
 - ☐ The index file
 - ☐ The postings file
3. Using a trie in index construction
 - ☐ Helps to quickly find words that have been seen before
 - ☐ Helps to quickly decide whether a word has not seen before
 - ☐ Helps to maintain the lexicographic order of words seen in the documents
 - ☐ All of the above
4. Maintaining the order of document identifiers when partitioning the document collection is important
 - ☐ In the index merging approach for single node machines
 - ☐ In the map-reduce approach for parallel clusters
 - ☐ In both
 - ☐ In neither of the two

3.2.5 Distributed Retrieval

1. When applying Fagin's algorithm for a query with three different terms for finding the k top documents, the algorithm will scan
 - ☐ 2 different lists
 - ☐ 3 different lists
 - ☐ k different lists
 - ☐ it depends how many rounds are taken
2. Once k documents have been identified that occur in all of the lists

- ☐ These are the top- k documents
- ☐ The top- k documents are among the documents seen so far
- ☐ The search has to continue in round-robin till the top- k documents are identified
- ☐ Other documents have to be searched to complete the top- k list

- ☐ Frequent items
- ☐ Rare items
- ☐ Does not matter

5. With the square root rule for replica allocation : given two items that are accessed with probabilities $p_1 > p_2$ that are replicated r_1 and r_2 times. Which is always true ?

- ☐ $r_1 < r_2$
- ☐ $r_1^{1/p_1} < r_2^{1/p_2}$
- ☐ $r_1 - p_1 < r_2 - p_2$

4 Peer-2-Peer Search

4.1 Peer-2-Peer Systems

4.1.1 P2P Systems and Resource Location

1. Which resource is in Napster not shared in a P2P approach ?
 - ☐ File storage
 - ☐ File metadata storage
 - ☐ Network bandwidth
 - ☐ Content rights
2. "Churn" refers to the fact that in a peer-to-peer system :
 - ☐ Peers constantly join and leave the network
 - ☐ Peers constantly add and remove resources
 - ☐ Peers constantly search for resources
3. An "overlay network" supports :
 - ☐ Efficient routing to a given IP address
 - ☐ Efficient routing to the location of a resource identifier
 - ☐ Efficient exchange of large files
 - ☐ Efficient messaging in centralized social network

4.1.2 Unstructured P2P Overlay Networks

1. In an unstructured overlay network (such as Gnutella) a peer receiving a "peer discovery" message (ping)
 - ☐ Responds by sending a message to the originator of the message
 - ☐ Responds by replying to the last forwarder of the message
 - ☐ Responds by sending a message to all its neighbors
2. If the largest city in the world has 16 Mio inhabitants, the second largest 11.3 Mio inhabitants, the third largest 9.2 Mio, the fourth largest 8.0 Mio, and so on, then this is
 - ☐ A Powerlaw distribution
 - ☐ A Zipf distribution
 - ☐ None of the two
3. Assume that in a country the size of cities follows a powerlaw distribution with exponent 2. A city of 16 Mio inhabitants has probability of $1/256$ to occur. Then a city of 8 Mio inhabitants is
 - ☐ Twice as probable
 - ☐ Four times as probable
 - ☐ Eight times as probable
4. Expanding ring search is particularly suitable to locate

4.1.3 Hierarchical P2P Overlay Networks

Credits

Quiz questions were taken from the lecture notes of Prof. Karl Aberer.