

Part I

Introduction

1 An Overview (week 1)

1.1 Information Systems

1. Functions in models
 - ☐ Are always computable
 - ☐ Can always be represented as data
 - ☐ Can be constrained by axioms
2. Interpretation relationships
 - ☐ Are always computable
 - ☐ Relate constants to real-world entities
 - ☐ Are uniquely defined

1.2 Data Management

1. What is not specified in the data definition language ?
 - ☐ The structure of a relational table
 - ☐ The query of user
 - ☐ A constraint on a relational table
2. Logical data independence means
 - ☐ An abstract data type is implemented using different data structures
 - ☐ A new view is computed without changing an existing database schema
 - ☐ A model can be represented in different data modelling formalisms

1.3 Data Management Tasks

1. Which is wrong ? An index structure
 - ☐ Is created as part of physical database design
 - ☐ Is selected during query optimization
 - ☐ Accelerates search queries
 - ☐ Accelerates tuple insertion
2. Persistence means that
 - ☐ A change of a transaction on a database is never lost after it is completed
 - ☐ The state of a database is independent of the lifetime of a program
 - ☐ The same logical database can be stored in different ways on a storage medium

1.4 Information Management

1. Grouping Twitter users according to their interest by analyzing the content of their tweets is
 - ☐ A retrieval task
 - ☐ A data mining task
 - ☐ An evaluation task
 - ☐ A monitoring task

1.5 Distributed Information Systems

1. Creating a web portal for comparing product prices is (primarily) a problem of
 - ☐ Distributed data management
 - ☐ Heterogeneous data integration
 - ☐ Collaboration among autonomous systems

1.6 Distributed Data Management

1. When you open a Web page with an embedded Twitter stream, the communication model used by Twitter is
 - ☐ Push, unicast and conditional
 - ☐ Pull, multicast and ad-hoc
 - ☐ Push, multicast and ad-hoc
 - ☐ Pull, unicast and conditional

1.7 Heterogeneity

1. Creating a web portal for comparing product prices requires to address
 - ☐ Syntactic heterogeneity
 - ☐ Semantic heterogeneity
 - ☐ Both
2. An ontology is a
 - ☐ Sdatabase
 - ☐ database schema
 - ☐ data model
 - ☐ data modeling formalism
 - ☐ model

1.8 Autonomy

1. Trust is
 - ☐ A quality of information
 - ☐ A quality of a user
 - ☐ A quality of the relationship among user and information
 - ☐ A quality of the relationship among users

Part II

Storage

2 Distributed Data Management

2.1 Schema Fragmentation

2.1.1 Relational Databases

1. At which phase of the database lifecycle is fragmentation performed ?
 - ☐ At database design time

- ☐ During distributed query processing
- ☐ During updates to a distributed database

2. The reconstruction property expresses that


- ☐ In case of a node failure the data can be recovered from a fragment from another node
- ☐ The original data can be fully recovered from the fragments
- ☐ Every data value of the original data can be found in at least one fragment

2.1.2 Primary Horizontal Fragmentation (week 2)

1. Example: application A1 accesses


1. Fragment F1: with frequency 3
2. Fragment F2: with frequency 1

A1 accesses the whole relation with frequency



- ☐ 13/7
- ☐ 4/7
- ☐ 14/7

2. Consider the access frequencies below: How many horizontal fragments would a minimal and complete fragmentation have?



- ☐ 3
- ☐ 4
- ☐ 6

3. Which of the following sets of simple predicates is complete?



- ☐ Location = "Munich", Budget > 200000
- ☐ Location = "Munich", Location = "Bangalore"
- ☐ Location = "Paris", Budget ≤ 200000
- ☐ None of those

4. Which is true for MinFrag algorithm?

- ☐ The output is independent of the order of the input
- ☐ It produces a monotonically increasing set of predicates
- ☐ It always terminates
- ☐ All of the above statements are true

5. When deriving a horizontal fragmentation for relation S from a horizontally fragmented relation R

- ☐ Some primary key attribute in R must be a foreign key in S
- ☐ Some primary key attribute in S must be a foreign key in R
- ☐ Both are required

2.2 Graph Databases (week 3)

2.2.1 Semi-structured Data

1. Semi-structured data

- ☐ Is always schema-less
- ☐ Always embeds schema information into the data
- ☐ Must always be hierarchically structured
- ☐ Can never be indexed

2. Why is XML a document model?

- ☐ It supports application-specific markup
- ☐ It supports domain-specific schemas
- ☐ It has a serialized representation
- ☐ It uses HTML tags

2.2.2 Graph Data Model

1. In a graph database

- ☐ There is a unique root node
- ☐ Each node has a unique identifier
- ☐ Data values in leaf nodes are unique
- ☐ The labels of edges leaving a node are different
- ☐ There is a unique path from the root to each leaf

2. The simulation relationship is a relation

- ☐ Among nodes in the data and schema graph
- ☐ Among edges in the data and schema graph
- ☐ Among sets of nodes in the data and schema graph
- ☐ Among sets of edges in the data and schema graph

3. Which is true?

- ☐ For each labelled edge in S a corresponding edge in D can be identified
- ☐ For each root node in S a corresponding root node D can be identified
- ☐ For each leaf node in D a corresponding typed node in S can be identified

- ☐ For each node in S a unique path reaching it from a root node can be identified
- 4. If there exists a uniquely defined simulation relationship among a graph database D and a schema graph S
 - ☐ The data and schema graph are simulation equivalent
 - ☐ Ambiguous classification cannot occur
 - ☐ Multiple classification cannot occur
- 5. If schema graph S_1 subsumes S_2
 - ☐ Every graph database corresponding to S_1 corresponds also to S_2
 - ☐ S_2 simulates S_1
 - ☐ S_1 has fewer nodes than S_2

2.2.3 Schema Extraction

1. Which is wrong? In a dataguide
 - ☐ Every path in the data graph occurs only once
 - ☐ Every node in the data graph occurs only in one data guide node
 - ☐ Every data guide node has a unique set of nodes
 - ☐ A leaf node in the data graph corresponds always to a leaf node in the data guide
2. In a non-deterministic schema graph
 - ☐ Every node of the data graph occurs exactly once
 - ☐ Every path of the data graph occurs at most once
 - ☐ Every label of an outgoing edge of a node in the schema graph is unique

Part III Search

3 Information Retrieval and Data Mining

3.1 Information Retrieval (week 4)

3.1.1 Information Retrieval

1. A retrieval model attempts to model
 - ☐ The interface by which a user is accessing information
 - ☐ The importance a user gives to a piece of information
 - ☐ The formal correctness of a query formulation by user
 - ☐ All of the above
2. If the top 100 documents contain 50 relevant documents
 - ☐ The precision of the system at 50 is 0.5
 - ☐ The precision of the system at 100 is 0.5
 - ☐ The recall of the system is 0.5
 - ☐ None of the above
3. If retrieval system A has a higher precision than system B
 - ☐ The top k documents of A will have higher similarity values than the top k documents of B

- ☐ The top k documents of A will contain more relevant documents than the top k documents of B
- ☐ A will recall more documents above a given similarity threshold than B
- ☐ Relevant documents in A will have higher similarity values than in B

3.1.2 Text-based Information Retrieval

1. Full-text retrieval means that
 - ☐ The document text is grammatically deeply analyzed for indexing
 - ☐ The complete vocabulary of a language is used to extract index terms
 - ☐ All words of a text are considered as potential index terms
 - ☐ All grammatical variations of a word are indexed
2. The term-document matrix indicates
 - ☐ How many relevant terms a document contains
 - ☐ How relevant a term is for a given document
 - ☐ How often a relevant term occurs in a document collection
 - ☐ Which relevant terms are occurring in a document collection
3. Let the query be represented by the following vectors: (1, 0, -1) (0, -1, 1); the document by the vector (1, 0, 1)
 - ☐ Matches the query because it matches the first query vector
 - ☐ Matches the query because it matches the second query vector
 - ☐ Does not match the query because it does not match the first query vector
 - ☐ Does not match the query because it does not match the second query vector
4. Which is right? The term frequency is normalized
 - ☐ By the maximal frequency of a term in the document
 - ☐ By the maximal frequency of a term in the document collection
 - ☐ By the maximal frequency of a term in the vocabulary
 - ☐ By the maximal term frequency of any document in the collection
5. The inverse document frequency of a term can increase
 - ☐ By adding the term to a document that contains the term
 - ☐ By adding a document to a document collection that does not contain the term
 - ☐ By removing a document from the document collection that does not contain the term
 - ☐ By adding a document to a document collection that contains the term

3.2 Advanced Retrieval Models (week 5)

3.2.1 Latent Semantic Indexing


1. In vector space retrieval each row of the matrix M^T corresponds to
 - ☐ A document
 - ☐ A concept
 - ☐ A query
 - ☐ A query result
2. Applying SVD to a term-document matrix \mathbf{M} . Each concept is represented
 - ☐ As a singular value
 - ☐ As a linear combination of terms of the vocabulary
 - ☐ As a linear combination of documents in the document collection
 - ☐ As a least square approximation of the matrix \mathbf{M}
3. The number of term vectors in the SVD for LSI
 - ☐ Is smaller than the number of rows in the matrix \mathbf{M}
 - ☐ Is the same as the number of rows in the matrix \mathbf{M}
 - ☐ Is larger than the number of rows in the matrix \mathbf{M}
4. A query transformed into the concept space for LSI has
 - ☐ s components (number of singular values)
 - ☐ m components (size of vocabulary)
 - ☐ n components (number of documents)

3.2.2 User Relevance Feedback

1. Can documents which do not contain any keywords of the original query receive a positive similarity coefficient after relevance feedback ?
 - ☐ No
 - ☐ Yes, independent of the values β and γ
 - ☐ Yes, but only if $\beta > 0$
 - ☐ Yes, but only if $\gamma > 0$

3.2.3 Link-based Ranking

2. A positive random jump value for exactly one node implies that
 - ☐ a random walker can leave the node even without outgoing edges
 - ☐ a random walker can reach the node multiple times even without outgoing edges
 - ☐ a random walker can reach the node even without incoming edges
 - ☐ none of the above
3. Given the graph below and an initial hub vector of $(1, 1, 1)$. The hub-authority ranking will result in the following



- ☐ authority vector $(0, 0, 1)$; hub vector $(1, 1, 0)$
- ☐ authority vector $(0, 0, 2)$; hub vector $(2, 2, 0)$
- ☐ authority vector $(0, 0, 1)$; hub vector $(\frac{1}{2}, \frac{1}{2}, 0)$
- ☐ authority vector $(0, 0, 2)$; hub vector $(1, 1, 0)$

3.2.4 Inverted Files (week 6)

1. A posting indicates
 - ☐ The frequency of a term in the vocabulary
 - ☐ The frequency of a term in a document
 - ☐ The occurrence of a term in a document
 - ☐ The list of terms occurring in a document
2. When indexing a document collection using an inverted file, the main space requirement is implied by
 - ☐ The access structure
 - ☐ The vocabulary
 - ☐ The index file
 - ☐ The postings file
3. Using a trie in index construction
 - ☐ Helps to quickly find words that have been seen before
 - ☐ Helps to quickly decide whether a word has not seen before
 - ☐ Helps to maintain the lexicographic order of words seen in the documents
 - ☐ All of the above
4. Maintaining the order of document identifiers when partitioning the document collection is important
 - ☐ In the index merging approach for single node machines
 - ☐ In the map-reduce approach for parallel clusters
 - ☐ In both
 - ☐ In neither of the two

3.2.5 Distributed Retrieval

1. When applying Fagin's algorithm for a query with three different terms for finding the k top documents, the algorithm will scan
 - ☐ 2 different lists
 - ☐ 3 different lists
 - ☐ k different lists
 - ☐ it depends how many rounds are taken
2. Once k documents have been identified that occur in all of the lists

- ☐ These are the top- k documents
- ☐ The top- k documents are among the documents seen so far
- ☐ The search has to continue in round-robin till the top- k documents are identified
- ☐ Other documents have to be searched to complete the top- k list

Credits

Quiz questions were taken from the lecture notes of Prof. Karl Aberer.