



## Specification for Approval

Photoelectric parameters are divided into BIN specifications

### 1. Bin Range of Luminous Intensity

| Bin | Min | Max | Unit | Condition |
|-----|-----|-----|------|-----------|
| P05 | 7   | 8.5 | MCD  | IF =5mA   |
| P06 | 8.5 | 10  |      |           |
| P07 | 10  | 12  |      |           |
| P08 | 12  | 14  |      |           |
| P09 | 14  | 17  |      |           |
| P10 | 17  | 20  |      |           |
| P11 | 20  | 24  |      |           |

Notes: Tolerance of Luminous Intensity:  $\pm 10\%$

### 2. Bin Range of Forward Voltage

| Bin | Min | Max | Unit | Condition |
|-----|-----|-----|------|-----------|
| VD  | 1.7 | 1.8 | V    | IF =5mA   |
| VE  | 1.8 | 1.9 |      |           |
| VF  | 1.9 | 2.0 |      |           |
| VG  | 2.0 | 2.1 |      |           |
| VH  | 2.1 | 2.2 |      |           |
| VI  | 2.2 | 2.3 |      |           |

Notes: Tolerance of Forward Voltage:  $\pm 0.05V$

### 3. Bin Range of Wavelength

| Bin  | Min | Max | Unit | Condition |
|------|-----|-----|------|-----------|
| YG9  | 568 | 569 | nm   | IF = 5mA  |
| YG10 | 569 | 570 |      |           |
| YG11 | 570 | 571 |      |           |
| YG12 | 571 | 572 |      |           |
| YG13 | 572 | 573 |      |           |
| YG14 | 573 | 574 |      |           |

Notes: Tolerance of Wavelength:  $\pm 0.5nm$