



presents the

REFERENCE IMPLEMENTATION

of the remarkable

DAI CREDIT SYSTEM

issuing a diversely collateralized stablecoin

with last update on March 8, 2017.

Contents

1	Introduction	5
1.1	Reference implementation	6
I	Implementation	7
2	Preamble	8
3	Types	9
3.1	Numeric types	9
3.2	Identifiers and addresses	10
3.3	Gem — ERC20 token model	10
3.4	Jar — collateral type	11
	gem — collateral token	11
	tag — market price of token	11
	zzz — expiration date of token price feed	11
3.5	Ilk — CDP type	11
	jar — collateral token vault	11
	mat — liquidation ratio	11
	axe — liquidation penalty ratio	11
	hat — debt ceiling	11
	tax — stability fee	11
	lag — price feed limbo duration	11
	rho — timestamp of last drip	11
	din — total outstanding dai	11
	chi — price of debt coin for CDP type	11
3.6	Urn — collateralized debt position (CDP)	11
	cat — address of liquidation initiator	11
	vow — address of liquidation contract	11
	lad — DAI issuer / CDP owner	11
	ilk — CDP type	11
	art — debt denominated in debt units	11

	jam — collateral denominated in debt units	11
3.7	Vat — CDP engine	12
	fix — market price of DAI denominated in SDR	12
	par — target price of DAI denominated in SDR	12
	how — sensitivity parameter	12
	way — rate of target price change	12
	tau — timestamp of last revaluation	12
	joy — unprocessed stability fee revenue	12
	sin — bad debt from liquidated CDPs	12
3.8	System model	12
	era — Current timestamp	12
3.9	Default data	13
4	Acts	15
4.1	Risk assessment	16
	gaze — identify CDP risk stage	16
4.2	Lending	17
	open — create CDP account	17
	lock — deposit collateral	17
	free — withdraw collateral	18
	draw — issue dai as debt	18
	wipe — repay debt and burn dai	19
	give — transfer CDP account	19
	shut — wipe, free, and delete CDP	19
4.3	Frequent adjustments	21
	prod — perform revaluation and rate adjustment	21
	drip — update value of debt unit	22
4.4	Price feedback	22
	mark — update market price of dai	22
	tell — update market price of collateral token	22
4.5	Liquidation and settlement	23
	bite — mark CDP for liquidation	23
	grab — take tokens to begin CDP liquidation	23
	heal — process bad debt	23
	love — process stability fee revenue	24
4.6	Governance	24
	form — create a new CDP type	24
	frob — set the sensitivity parameter	24
	chop — set liquidation penalty	24
	cork — set debt ceiling	24
	calm — set limbo duration	24

	<code>cuff</code> — set liquidation ratio	24
	<code>crop</code> — set stability fee	25
4.7	Minting, burning, and transferring	25
	<code>pull</code> — take tokens to vat	25
	<code>push</code> — send tokens from vat	25
	<code>mint</code> — increase supply	25
	<code>burn</code> — decrease supply	25
4.8	Test-related manipulation	26
	<code>warp</code> — travel in time	26
4.9	Other stuff	26
5	Act framework	27
5.1	Act descriptions	27
5.2	The Maker monad	28
5.3	Accessor aliases	28
5.4	Asserting	29
5.5	Modifiers	29
	<code>auth</code> — authenticating actions	29
6	Testing	30
A	Prelude	32
B	Act type signatures	35

List of Tables

4.1	Urn acts in the five stages of risk	17
-----	---	----

List of Figures

Chapter 1

Introduction

The DAI CREDIT SYSTEM, henceforth also “Maker,” is a network of Ethereum contracts designed to issue the DAI currency token and automatically adjust incentives in order to keep dai market value stable relative to SDR¹ in the short and medium term.

New dai enters the money supply when a borrower takes out a loan backed by an excess of collateral locked in Maker’s token vault. The debt and collateral amounts are recorded in a *collateralized debt position*, or CDP. Thus all outstanding dai represents some CDP owner’s claim on their collateral.

Maker’s knowledge of the market values of dai and the various tokens used as collateral comes from *price feeds*. Prices are used to continuously assess the risk of each CDP. If the value of a CDP’s collateral drops below a certain multiple of its debt, it is marked for liquidation, which triggers a decentralized auction mechanism.

Another token, MKR, is also controlled by Maker, acting as a “share” in the system itself. When a CDP liquidation fails to recover the full value of debt, Maker mints more MKR and auctions it out. Thus MKR is used to fund last resort market making. The value of the MKR token is based on the *stability fee* imposed on all dai loans: stability fee revenue goes toward buying MKR for burning.

This document is an executable technical specification of the exact workings of the Maker smart contracts.

¹“Special Drawing Rights” (ticker symbol XDR), the international reserve asset created by the International Monetary Fund, whose value is derived from a weighted basket of world currencies. In the long term, the value of dai may diverge from the value of SDR; whether in an inflationary or deflationary way will depend on market forces.

1.1 Reference implementation

The version of this system that will be deployed on the Ethereum blockchain is written in Solidity, which is a workable smart contract implementation language. This reference implementation is a precise model of the behavior of those contracts, written as a “literate” Haskell program. The motivations for such a reference implementation include:

1. **Comparison.** Checking two free-standing implementations against each other is a well-known way of ensuring that they both behave as intended.
2. **Testing.** Haskell lets us use flexible and powerful testing tools such as QuickCheck and SmallCheck for comprehensively verifying key properties as a middle ground between unit testing and formal verification.
3. **Explicitness.** Coding the contract behavior in Haskell, a purely functional language, enforces explicit description of aspects which Solidity leaves implicit. For example, a Solidity program can read previously unwritten storage and get back a zero value, whereas in Haskell we must give explicit defaults. The state rollback behavior of failed actions is also explicit in the type of the execution function, which may return an error.
4. **Type correctness.** While Solidity does have a static type system, it is not expressive enough to encode the distinctions made by our system. In particular, the two different decimal fixed point number types that we use are typed in Solidity with one and the same `uint128` type. In Haskell we can make this distinction explicit.
5. **Formality.** The work of translating a Solidity program into a purely functional program opens up opportunities for certain types of formal verification. In particular, this document will be useful for modelling aspects of the system in a proof assistant like Agda, Idris, Coq, or Isabelle. We can also use logical tools for Haskell, such as Liquid Haskell (which provides compile time logical property checking) and `sbv` (a toolkit for model checking and symbolic execution).
6. **Simulation.** Solidity is highly specific to the Ethereum blockchain environment and as such does not have facilities for interfacing with files or other computer programs. This makes the Solidity implementation of the system less useful for doing simulations of the system’s economic, game-theoretic, or statistical aspects.

Part I

Implementation

Chapter 2

Preamble

We replace the default prelude module with our own. This brings in dependencies and hides unneeded symbols. Consult [Appendix A](#) to see exactly what is brought into scope.

```
module Maker where  
import Maker.Prelude  Fully import the Maker prelude  
import Prelude ()      Import nothing from Prelude  
  
import GHC.Exts (Constraint)
```


Chapter 3

Types

3.1 Numeric types

The system uses two different precisions of decimal fixed point numbers, which we call *wads* and *rays*, having respectively 18 digits of precision (used for token quantities) and 36 digits (used for precise rates and ratios).

Define the distinct *wad* type for currency quantities

```
newtype Wad = Wad (Fixed E18)
deriving (Ord, Eq, Num, Real, Fractional, RealFrac)
```

Define the distinct *ray* type for precise rate quantities

```
newtype Ray = Ray (Fixed E36)
deriving (Ord, Eq, Num, Real, Fractional, RealFrac)
```

We must define the E18 and E36 symbols and their fixed point multipliers.

```
data E18; data E36
instance HasResolution E18 where
  resolution _ = 10  $\uparrow$  (18 :: Integer)
instance HasResolution E36 where
  resolution _ = 10  $\uparrow$  (36 :: Integer)
```

Haskell number types are not automatically converted, so in calculations that combine *wads* and *rays*, we convert explicitly with a *cast* function.

Convert via fractional *n/m* form.

```
cast :: (Real a, Fractional b)  $\Rightarrow$  a  $\rightarrow$  b
cast = fromRational  $\circ$  toRational
```

We also define a type for time durations in whole seconds.

```
newtype Sec = Sec Int
  deriving (Eq, Ord, Enum, Num, Real, Integral)
```

3.2 Identifiers and addresses

There are several kinds of identifiers used in the system, and we can use types to distinguish them.

The type parameter a creates distinct types.
For example, `Id Foo` and `Id Bar` are incompatible.

```
data Id  $a$  = Id String
  deriving (Show, Eq, Ord)
```

We define another type for representing Ethereum account addresses.

```
data Address = Address String
  deriving (Ord, Eq, Show)
```

We also have three predefined entity identifiers.

```
The DAI token address
 $id_{\text{DAI}}$  = Id "Dai"

The CDP engine address
 $id_{\text{vat}}$  = Address "Vat"

The account with ultimate authority
 $\diamond$  Kludge until authority is modelled
 $id_{\text{god}}$  = Address "God"
```

This section introduces the records stored by the Maker system.

3.3 Gem — ERC20 token model

```
data Gem = Gem {
  gemTotalSupply :: Wad,
  gemBalanceOf   :: Map Address      Wad,
  gemAllowance   :: Map (Address, Address) Wad
} deriving (Eq, Show)
```

3.4 Jar — collateral type

```
data Jar = Jar {  
  jarGem :: Gem,   Collateral token  
  jarTag  :: Wad,   Market price  
  jarZzz  :: Sec    Price expiration  
} deriving (Eq, Show)
```

3.5 Ilk — CDP type

```
data Ilk = Ilk {  
  ilkJar  :: Id Jar,   Collateral vault  
  ilkAxe  :: Ray,      Liquidation penalty  
  ilkHat  :: Wad,      Debt ceiling  
  ilkMat  :: Ray,      Liquidation ratio  
  ilkTax  :: Ray,      Stability fee  
  ilkLag  :: Sec,      Limbo duration  
  ilkRho  :: Sec,      Last dripped  
  ilkRum  :: Wad,      Total debt in debt unit  
  ilkChi  :: Ray       Value of debt unit  
} deriving (Eq, Show)
```

3.6 Urn — collateralized debt position (CDP)

```
data Urn = Urn {  
  urnCat  :: Maybe Address, Address of liquidation initiator  
  urnVow  :: Maybe Address, Address of liquidation contract  
  urnLad  :: Address,       Issuer  
  urnIlk  :: Id Ilk,        CDP type  
  urnArt  :: Wad,           Outstanding debt in debt units  
  urnJam  :: Wad            Collateral amount in debt units  
} deriving (Eq, Show)
```

3.7 Vat — CDP engine

```
data Vat = Vat {  
    vatFix    :: Wad,           Market price  
    vatHow    :: Ray,          Sensitivity  
    vatPar    :: Wad,          Target price  
    vatWay    :: Ray,          Target rate  
    vatTau    :: Sec,          Last prodded  
    vatJoy    :: Wad,          Unprocessed stability fees  
    vatSin    :: Wad,          Bad debt from liquidated CDPs  
    vatJars   :: Map (Id Jar) Jar, Collateral tokens  
    vatIlks   :: Map (Id Ilk) Ilk,  CDP types  
    vatUrns   :: Map (Id Urn) Urn   CDPs  
} deriving (Eq, Show)
```

3.8 System model

```
data System = System {  
    systemVat      :: Vat,      Root Maker entity  
    systemEra      :: Sec,      Current time stamp  
    systemSender   :: Address,  Sender of current act  
    systemAccounts :: [Address] For test suites  
} deriving (Eq, Show)
```

Lens fields

```
makeFields '' Gem  
makeFields '' Jar  
makeFields '' Ilk  
makeFields '' Urn  
makeFields '' Vat  
makeFields '' System
```

3.9 Default data

```

defaultIlk :: Id Jar → Ilk
defaultIlk idjar = Ilk {
  ilkJar   = idjar,
  ilkAxe  = Ray 1,
  ilkMat  = Ray 1,
  ilkTax  = Ray 1,
  ilkHat  = Wad 0,
  ilkLag  = Sec 0,
  ilkChi  = Ray 1,
  ilkRum  = Wad 0,
  ilkRho  = Sec 0
}

```

```

defaultUrn :: Id Ilk → Address → Urn
defaultUrn idilk idlad = Urn {
  urnVow = Nothing,
  urnCat = Nothing,
  urnLad = idlad,
  urnIlk = idilk,
  urnArt = Wad 0,
  urnJam = Wad 0
}

```

```

initialVat :: Ray → Vat
initialVat how0 = Vat {
  vatTau   = 0,
  vatFix   = Wad 1,
  vatPar   = Wad 1,
  vatHow   = how0,
  vatWay   = Ray 1,
  vatJoy   = Wad 0,
  vatSin   = Wad 0,
  vatIlks  = ∅,
  vatUrns  = ∅,
  vatJars  =
    singleton idDAI Jar {
      jarGem = Gem {

```

```

      gemTotalSupply = 0,
      gemBalanceOf  =  $\emptyset$ ,
      gemAllowance  =  $\emptyset$ 
    },
    jarTag = Wad 0,
    jarZzz = 0
  }
}

```

```

initialSystem :: Ray → System
initialSystem how0 = System {
  systemVat      = initialVat how0,
  systemEra      = 0,
  systemSender   = idgod,
  systemAccounts = mempty
}

```

Chapter 4

Acts

The *acts* are the basic state transitions of the credit system.

For details on the underlying “Maker monad,” which specifies how the act definitions behave with regard to state and rollback thereof, see [chapter 5](#).

4.1 Risk assessment

We divide an urn's situation into five stages of risk. Table 4.1 shows which acts each stage allows. The stages are naturally ordered from more to less risky.

```
data Stage = Dread | Grief | Panic | Worry | Anger | Pride
deriving (Eq, Ord, Show)
```

First we define a pure function *analyze* that determines an urn's stage.

```
analyze era0 par0 urn0 ilk0 jar0 =
  if
    Undergoing liquidation?
      | view vow urn0 ≠ Nothing → Dread
    Liquidation triggered?
      | view cat urn0 ≠ Nothing → Grief
    Undercollateralized?
      | pro < min → Panic
    Price feed expired?
      | era0 > view zzz jar0 + view lag ilk0 → Panic
    Price feed in limbo?
      | view zzz jar0 < era0 → Worry
    Debt ceiling reached?
      | cap > view hat ilk0 → Anger
    Safely overcollateralized
      | otherwise → Pride
  where
    CDP's collateral value in SDR:
      pro = view jam urn0 * view tag jar0
    CDP type's total debt in SDR:
      cap = (view rum ilk0 * cast (view chi ilk0)) :: Wad
    CDP's debt in SDR:
      con = view art urn0 * cast (view chi ilk0) * par0
    Required collateral as per liquidation ratio:
      min = con * view mat ilk0
```


Table 4.1: Urn acts in the five stages of risk

	give	shut	lock	wipe	free	draw	bite	grab	plop	
Pride	•	•	•	•	•	•				overcollateralized
Anger	•	•	•	•	•					debt ceiling reached
Worry	•	•	•	•						price feed in limbo
Panic	•	•	•	•			•			undercollateralized
Grief	•							•		liquidation initiated
Dread	•								•	liquidation in progress

Now we define the internal act **gaze** which returns the value of *analyze* after ensuring the system state is updated.

```

gaze  $id_{urn}$  = do
  Perform dai revaluation and rate adjustment
  prod
  Update price of specific debt unit
   $id_{ilk} \leftarrow look\ (vat \circ urns \circ ix\ id_{urn} \circ ilk)$ 
  drip  $id_{ilk}$ 
  Read parameters for risk analysis
   $era_0 \leftarrow view\ era$ 
   $par_0 \leftarrow view\ (vat \circ par)$ 
   $urn_0 \leftarrow look\ (vat \circ urns \circ ix\ id_{urn})$ 
   $ilk_0 \leftarrow look\ (vat \circ ilks \circ ix\ (view\ ilk\ urn_0))$ 
   $jar_0 \leftarrow look\ (vat \circ jars \circ ix\ (view\ jar\ ilk_0))$ 
  Return risk stage of CDP
   $return\ (analyze\ era_0\ par_0\ urn_0\ ilk_0\ jar_0)$ 

```

4.2 Lending

```

open  $id_{urn}\ id_{ilk}$  =
  do
     $id_{lad} \leftarrow view\ sender$ 
     $vat \circ urns \circ at\ id_{urn} \text{ ?= } defaultUrn\ id_{ilk}\ id_{lad}$ 

```

```

lock  $id_{urn}\ x$  = do
  Ensure CDP exists; identify collateral type

```

$id_{ilk} \leftarrow look\ (vat \circ urns \circ ix\ id_{urn} \circ ilk)$
 $id_{jar} \leftarrow look\ (vat \circ ilks \circ ix\ id_{ilk} \circ jar)$

Record an increase in collateral

$vat \circ urns \circ ix\ id_{urn} \circ jam \ +=\ x$

Take sender's tokens

$id_{lad} \leftarrow view\ sender$

$pull\ id_{jar}\ id_{lad}\ x$

free $id_{urn}\ wad_{gem} = \mathbf{do}$

Fail if sender is not the CDP owner

$id_{sender} \leftarrow view\ sender$

$id_{lad} \leftarrow look\ (vat \circ urns \circ ix\ id_{urn} \circ lad)$

$aver\ (id_{sender} \equiv id_{lad})$

Decrease the collateral amount

$vat \circ urns \circ ix\ id_{urn} \circ jam \ -=\ wad_{gem}$

Roll back if undercollateralized

$gaze\ id_{urn} \gg= aver \circ (\equiv\ Pride)$

Send the collateral to the CDP owner

$id_{ilk} \leftarrow look\ (vat \circ urns \circ ix\ id_{urn} \circ ilk)$

$id_{jar} \leftarrow look\ (vat \circ ilks \circ ix\ id_{ilk} \circ jar)$

$push\ id_{jar}\ id_{lad}\ wad_{gem}$

draw $id_{urn}\ wad_{DAI} = \mathbf{do}$

Fail if sender is not the CDP owner

$id_{sender} \leftarrow view\ sender$

$id_{lad} \leftarrow look\ (vat \circ urns \circ ix\ id_{urn} \circ lad)$

$aver\ (id_{sender} \equiv id_{lad})$

Update value of debt unit

$id_{ilk} \leftarrow look\ (vat \circ urns \circ ix\ id_{urn} \circ ilk)$

$chi_1 \leftarrow drip\ id_{ilk}$

Denominate draw amount in debt unit

let $wad_{chi} = wad_{DAI} / cast\ chi_1$

Increase debt

$vat \circ urns \circ ix\ id_{urn} \circ art \ +=\ wad_{chi}$

Roll back unless overcollateralized

```

    gaze  $id_{urn} \gg= \text{aver} \circ (\equiv \text{Pride})$ 
Mint dai and send to the CDP owner
    mint  $id_{DAI}$   $wad_{DAI}$ 
    push  $id_{DAI}$   $id_{lad}$   $wad_{DAI}$ 

wipe  $id_{urn}$   $wad_{DAI}$  = do
    Fail if sender is not the CDP owner
     $id_{sender} \leftarrow \text{view sender}$ 
     $id_{lad} \leftarrow \text{look} (\text{vat} \circ \text{urns} \circ ix \ id_{urn} \circ lad)$ 
     $\text{aver} (id_{sender} \equiv id_{lad})$ 
    Update value of debt unit
     $id_{ilk} \leftarrow \text{look} (\text{vat} \circ \text{urns} \circ ix \ id_{urn} \circ ilk)$ 
     $chi_1 \leftarrow \text{drip } id_{ilk}$ 
    Roll back unless overcollateralized
    gaze  $id_{urn} \gg= \text{aver} \circ (\equiv \text{Pride})$ 
    Denominate dai amount in debt unit
    let  $wad_{chi} = wad_{DAI} / \text{cast } chi_1$ 
    Reduce debt
     $\text{vat} \circ \text{urns} \circ ix \ id_{urn} \circ \text{art} -= wad_{chi}$ 
    Take dai from CDP owner, or roll back
    pull  $id_{DAI}$   $id_{lad}$   $wad_{DAI}$ 
    Destroy dai
    burn  $id_{DAI}$   $wad_{DAI}$ 

```

```

give  $id_{urn}$   $id_{lad}$  = do
     $x \leftarrow \text{look} (\text{vat} \circ \text{urns} \circ ix \ id_{urn} \circ lad)$ 
     $y \leftarrow \text{view sender}$ 
     $\text{aver} (x \equiv y)$ 
     $\text{vat} \circ \text{urns} \circ ix \ id_{urn} \circ lad := id_{lad}$ 

```

```

shut  $id_{urn}$  = do
    Update value of debt unit
     $id_{ilk} \leftarrow \text{look} (\text{vat} \circ \text{urns} \circ ix \ id_{urn} \circ ilk)$ 
     $chi_1 \leftarrow \text{drip } id_{ilk}$ 

```

Attempt to repay all the CDP's outstanding dai

$$\mathbf{art}_0 \leftarrow \mathit{look} (\mathbf{vat} \circ \mathbf{urns} \circ \mathit{ix} \ id_{\mathbf{urn}} \circ \mathbf{art})$$

$$\mathbf{wipe} \ id_{\mathbf{urn}} (\mathbf{art}_0 * \mathit{cast} \ \mathbf{chi}_1)$$

Reclaim all the collateral

$$\mathbf{jam0} \leftarrow \mathit{look} (\mathbf{vat} \circ \mathbf{urns} \circ \mathit{ix} \ id_{\mathbf{urn}} \circ \mathbf{jam})$$

$$\mathbf{free} \ id_{\mathbf{urn}} \ \mathbf{jam0}$$

Nullify the CDP

$$\mathbf{vat} \circ \mathbf{urns} \circ \mathit{at} \ id_{\mathbf{urn}} := \mathbf{Nothing}$$

4.3 Frequent adjustments

```

prod = do
  era0 ← view era
  tau0 ← view (vat ∘ tau)
  fix0 ← view (vat ∘ fix)
  par0 ← view (vat ∘ par)
  how0 ← view (vat ∘ how)
  way0 ← view (vat ∘ way)
  let
    Time difference in seconds
    age = era0 − tau0
    Current target rate applied to target price
    par1 = par0 * cast (way0 ↑↑ age)
    Sensitivity parameter applied over time
    wag = how0 * fromIntegral age
    Target rate scaled up or down
    way1 = inj (prj way0 +
                  if fix0 < par0 then wag else − wag)
  vat ∘ par := par1
  vat ∘ way := way1
  vat ∘ tau := era0
  where
    Convert between multiplicative and additive form
    prj x = if x ≥ 1 then x − 1 else 1 − 1 / x
    inj x = if x ≥ 0 then x + 1 else 1 / (1 − x)

```

```

drip  $id_{ilk}$  = do
  Current time stamp
   $era_0 \leftarrow view\ era$ 
  Time stamp of previous drip
   $\rho_0 \leftarrow look\ (vat \circ ilks \circ ix\ id_{ilk} \circ \rho)$ 
  Current stability fee
   $tax_0 \leftarrow look\ (vat \circ ilks \circ ix\ id_{ilk} \circ tax)$ 
  Current value of debt unit
   $chi_0 \leftarrow look\ (vat \circ ilks \circ ix\ id_{ilk} \circ chi)$ 
  Current total debt in debt units
   $rum0 \leftarrow look\ (vat \circ ilks \circ ix\ id_{ilk} \circ rum)$ 
  Current unprocessed stability fee revenue
   $joy_0 \leftarrow look\ (vat \circ ilks \circ ix\ id_{ilk} \circ joy)$ 
  let
     $age = era_0 - \rho_0$ 
     $chi_1 = chi_0 * tax_0 \uparrow\uparrow age$ 
     $joy_1 = joy_0 + (cast\ (chi_1 - chi_0) :: Wad) * rum0$ 
     $vat \circ ilks \circ ix\ id_{ilk} \circ chi := chi_1$ 
     $vat \circ ilks \circ ix\ id_{ilk} \circ \rho := era_0$ 
     $vat \circ ilks \circ ix\ id_{ilk} \circ joy := joy_1$ 
  return  $chi_1$ 

```

4.4 Price feedback

```

mark  $id_{jar}$  tag1 zzz1 =
  auth $ do
    jarAt  $id_{jar} \circ tag := tag_1$ 
    jarAt  $id_{jar} \circ zzz := zzz_1$ 

```

```

tell  $x =$ 
  auth $ do
    vat  $\circ fix := x$ 

```

4.5 Liquidation and settlement

```

bite  $id_{urn}$  = do
  Fail if CDP is not in need of liquidation
  gaze  $id_{urn} \gg= \text{aver} \circ (\equiv \text{Panic})$ 
  Record the sender as the liquidation initiator
   $id_{cat} \leftarrow \text{view sender}$ 
   $\text{vat} \circ \text{urns} \circ ix\ id_{urn} \circ \text{cat} := id_{cat}$ 
  Read current debt
   $\text{art}_0 \leftarrow \text{look} (\text{vat} \circ \text{urns} \circ ix\ id_{urn} \circ \text{art})$ 
  Update value of debt unit
   $id_{ilk} \leftarrow \text{look} (\text{vat} \circ \text{urns} \circ ix\ id_{urn} \circ \text{ilk})$ 
   $\text{chi}_1 \leftarrow \text{drip } id_{ilk}$ 
  Read liquidation penalty ratio
   $id_{ilk} \leftarrow \text{look} (\text{vat} \circ \text{urns} \circ ix\ id_{urn} \circ \text{ilk})$ 
   $\text{axe}_0 \leftarrow \text{look} (\text{vat} \circ \text{ilks} \circ ix\ id_{ilk} \circ \text{axe})$ 
  Apply liquidation penalty to debt
  let  $\text{art}_1 = \text{art}_0 * \text{axe}_0$ 
  Update CDP debt
   $\text{vat} \circ \text{urns} \circ ix\ id_{urn} \circ \text{art} := \text{art}_1$ 
  Record as bad debt
   $\text{sin} += \text{art}_1 * \text{chi}_1$ 

```

```

grab  $id_{urn}$  =
  auth $ do
    Fail if CDP is not marked for liquidation
    gaze  $id_{urn} \gg= \text{aver} \circ (\equiv \text{Grief})$ 
    Record the sender as the CDP's settler
     $id_{vow} \leftarrow \text{view sender}$ 
     $\text{vat} \circ \text{urns} \circ ix\ id_{urn} \circ \text{vow} := id_{vow}$ 
    Clear the CDP's requester of liquidation
     $\text{vat} \circ \text{urns} \circ ix\ id_{urn} \circ \text{cat} := \text{Nothing}$ 

```

```

heal wadDAI =

```

```

auth $ do
  vat ∘ sin == wadDAI

```

```

love wadDAI =
  auth $ do
    vat ∘ joy == wadDAI

```

4.6 Governance

```

form idilk idjar =
  auth $ do
    vat ∘ ilks ∘ at idilk ?= defaultIlk idjar

```

```

frob how' =
  auth $ do
    vat ∘ how := how'

```

```

chop idilk axe1 =
  auth $ do
    vat ∘ ilks ∘ ix idilk ∘ axe := axe1

```

```

cork idilk hat1 =
  auth $ do
    vat ∘ ilks ∘ ix idilk ∘ hat := hat1

```

```

calm idilk lag1 =
  auth $ do
    vat ∘ ilks ∘ ix idilk ∘ lag := lag1

```



```

cuff  $id_{ilk}$   $mat_1$  =
  auth $ do
     $vat \circ ilks \circ ix \ id_{ilk} \circ mat := mat_1$ 

```

```

crop  $id_{ilk}$   $tax_1$  =
  auth $ do
    drip  $id_{ilk}$ 
     $vat \circ ilks \circ ix \ id_{ilk} \circ tax := tax_1$ 

```

4.7 Minting, burning, and transferring

```

pull  $id_{jar}$   $id_{lad}$   $w$  = do
   $g \leftarrow look \ (jarAt \ id_{jar} \circ gem)$ 
   $g' \leftarrow transferFrom \ id_{lad} \ id_{vat} \ w \ g$ 
   $jarAt \ id_{jar} \circ gem := g'$ 

```

```

push  $id_{jar}$   $id_{lad}$   $w$  = do
   $g \leftarrow look \ (jarAt \ id_{jar} \circ gem)$ 
   $g' \leftarrow transferFrom \ id_{vat} \ id_{lad} \ w \ g$ 
   $jarAt \ id_{jar} \circ gem := g'$ 

```

```

mint  $id_{jar}$   $wad_0$  = do
   $jarAt \ id_{jar} \circ gem \circ totalSupply \quad += wad_0$ 
   $jarAt \ id_{jar} \circ gem \circ balanceOf \circ ix \ id_{vat} \quad += wad_0$ 

```

```

burn  $id_{jar}$   $wad_0$  = do
   $jarAt \ id_{jar} \circ gem \circ totalSupply \quad -= wad_0$ 
   $jarAt \ id_{jar} \circ gem \circ balanceOf \circ ix \ id_{vat} \quad -= wad_0$ 

```

4.8 Test-related manipulation

```
warp t =  
  auth $ do  
    era += t
```

4.9 Other stuff

```
perform :: Act → Maker ()  
perform x =  
  let ?act = x in case x of  
    Form id jar   → form id jar  
    Mark jar tag zzz → mark jar tag zzz  
    Open id ilk   → open id ilk  
    Tell wad      → tell wad  
    Frob ray      → frob ray  
    Prod          → prod  
    Warp t        → warp t  
    Give urn lad  → give urn lad  
    Pull jar lad wad → pull jar lad wad  
    Lock urn wad  → lock urn wad  
  
transferFrom  
  :: (MonadError Error m)  
  ⇒ Address → Address → Wad  
  → Gem → m Gem  
  
transferFrom src dst wad gem =  
  case view (balanceOf ∘ at src) gem of  
    Nothing →  
      throwError AssertionError  
    Just balance → do  
      aver (balance ≥ wad)  
      return $ gem &~ do  
        balanceOf ∘ ix src -= wad  
        balanceOf ∘ at dst %=  
          (λcase  
            Nothing → Just wad  
            Just x   → Just (wad + x))
```

Chapter 5

Act framework

5.1 Act descriptions

We define the Maker act vocabulary as a data type.

```
data Act =  
  Bite (Id Urn)  
| Draw (Id Urn) Wad  
| Form (Id Ilk) (Id Jar)  
| Free (Id Urn) Wad  
| Frob Ray  
| Give (Id Urn) Address  
| Grab (Id Urn)  
| Heal Wad  
| Lock (Id Urn) Wad  
| Love Wad  
| Mark (Id Jar) Wad      Sec  
| Open (Id Urn) (Id Ilk)  
| Prod  
| Pull (Id Jar) Address Wad  
| Shut (Id Urn)  
| Tell Wad  
| Warp Sec  
| Wipe (Id Urn) Wad  
  
Test acts  
| Addr Address  
deriving (Eq, Show)
```

Acts can fail. We divide the failure modes into general assertion failures and authentication failures.

```
data Error = AssertError | AuthError
deriving (Show, Eq)
```

5.2 The Maker monad

The reader does not need any abstract understanding of monads to understand the code. What they give us is a nice syntax—the **do** notation—for expressing exceptions and state in a way that is still purely functional.

```
newtype Maker a =
  Maker (StateT System (Except Error) a)
deriving
  (Functor, Applicative, Monad,
   MonadError Error,
   MonadState System)

exec :: System
     → Maker ()
     → Either Error System
exec sys (Maker m) =
  runExcept (execStateT m sys)
```

The following instance makes the mutable state also available as read-only state.

```
instance MonadReader System Maker where
  ask = Maker get
  local f (Maker m) = Maker $ do
    s ← get; put (f s)
    x ← m; put s
  return x
```

5.3 Accessor aliases

```
ilkAt id = vat ∘ ilks ∘ ix id
urnAt id = vat ∘ urns ∘ ix id
jarAt id = vat ∘ jars ∘ ix id
```

5.4 Asserting

```
aver :: Fails m  $\Rightarrow$  Bool  $\rightarrow$  m ()  
aver x = unless x (throwError AssertionError)  
look :: (Fails m, Reads r m)  
       $\Rightarrow$  Getting (First a) r a  $\rightarrow$  m a  
look f = preview f  $\gg=$   $\lambda$ case  
    Nothing  $\rightarrow$  throwError AssertionError  
    Just x  $\rightarrow$  return x
```

5.5 Modifiers

```
auth ::  
    (IsAct, Fails m,  
     Reads r m,  
     HasSender r Address)  
     $\Rightarrow$  m a  $\rightarrow$  m a
```

```
auth continue = do  
    s  $\leftarrow$  view sender  
    unless (s  $\equiv$  idgod)  
        (throwError AuthError)  
    continue
```

Chapter 6

Testing

Sketches for property stuff...

```
data Parameter =  
  Fix | Par | Way
```

maintains

```
:: Eq a => Lens' System a -> Maker ()  
  -> System -> Bool
```

maintains $p = \lambda m \text{ sys}_0 \rightarrow$

```
case exec sys0 m of
```

On success, data must be compared for equality

```
  Right sys1 -> view p sys0 ≡ view p sys1
```

On rollback, data is maintained by definition

```
  Left _ -> True
```

changesOnly

```
:: Lens' System a -> Maker ()  
  -> System -> Bool
```

changesOnly $p = \lambda m \text{ sys}_0 \rightarrow$

```
case exec sys0 m of
```

On success, equalize p and compare

```
  Right sys1 -> set p (view p sys1) sys0 ≡ sys1
```

On rollback, data is maintained by definition

```
  Left _ -> True
```

also :: Lens' s $a \rightarrow$ Lens' s $b \rightarrow$ Lens' s (a, b)

also f $g = \text{lens getter setter}$

where

getter $x = (\text{view } f \ x, \text{view } g \ x)$

setter $x \ (a, b) = \text{set } f \ a \ (\text{set } g \ b \ x)$

keeps $:: \text{Parameter} \rightarrow \text{Maker } () \rightarrow \text{System} \rightarrow \text{Bool}$

keeps **Fix** = *maintains* (**vat** \circ **fix**)

keeps **Par** = *maintains* (**vat** \circ **par**)

keeps **Way** = *maintains* (**vat** \circ **way**)

Thus:

foo **sys**₀ = *all* ($\lambda f \rightarrow f \ \text{sys}_0$)
 [*changesOnly* ((**vat** \circ **par**) ‘also’
 (**vat** \circ **way**))
 (*perform* **Prod**)]

Appendix A

Prelude

```
module Maker.Prelude (  
    module Maker.Prelude,  
    module X  
) where  
  
import Prelude as X (  
    Conversions to and from strings  
    Read (.), Show (.),  
    Comparisons  
    Eq (.), Ord (.),  
    Core abstractions  
    Functor    (fmap),  
    Applicative (),  
    Monad      (return, (>>=)),  
    Numeric classes  
    Num (), Integral (), Enum (),  
    Numeric conversions  
    Real (toRational), Fractional (fromRational),  
    RealFrac (truncate),  
    fromIntegral,  
    Simple types  
    Integer, Int, String,  
    Algebraic types  
    Bool    (True, False),
```


Maybe (Just, Nothing),
 Either (Right, Left),
 Functional operators
 (\circ), ($\$$),
 Numeric operators
 ($+$), ($-$), ($*$), ($/$), (\uparrow), ($\uparrow\uparrow$),
 Utilities
all,
 Constants
mempty, \perp , *otherwise*)

We use a typical composition of monad transformers from the `mtl` library to structure stateful actions. See section 5.2 (*The Maker monad*).

```

import Control.Monad.State as X (
  MonadState,    Type class of monads with state
  StateT,        Type constructor that adds state to a monad type
  execStateT,    Runs a state monad with given initial state
  get,           Gets the state in a do block
  put)           Sets the state in a do block

import Control.Monad.Reader as X (
  MonadReader,  Type class of monads with “environments”
  ask,          Reads the environment in a do block
  local)        Runs a sub-computation with a modified environment

import Control.Monad.Writer as X (
  MonadWriter,  Type class of monads that emit logs
  WriterT,      Type constructor that adds logging to a monad type
  Writer,       Type constructor of logging monads
  runWriterT,   Runs a writer monad transformer
  execWriterT,  Runs a writer monad transformer keeping only logs
  execWriter)   Runs a writer monad keeping only logs

import Control.Monad.Except as X (
  MonadError,   Type class of monads that fail
  Except,       Type constructor of failing monads
  throwError,   Short-circuits the monadic computation
  runExcept)    Runs a failing monad
  
```

Our numeric types use decimal fixed-point arithmetic.

```

import Data.Fixed as X (
  Fixed,        Type constructor for numbers of given precision
  HasResolution (. .)) Type class for specifying precisions
  
```

We rely on the `lens` library for accessing nested values. There is no need to understand the theory behind lenses to understand this program. The notation $a \circ b \circ c$ denotes a nested accessor much like `a.b.c` in C-style languages; for more details, consult lens documentation¹.

```
import Control.Lens as X (
    Lens',
    lens,
    makeFields,    Defines lenses for record fields
    set,           Writes a lens
    view, preview, Reads a lens in a do block
    (&~),          Lets us use a do block with setters  $\diamond$  Get rid of this.
    ix,           Lens for map retrieval and updating
    at,           Lens for map insertion

    Operators for partial state updates in do blocks:
    (:=),         Replace
    (==), (+=),   Update arithmetically
    (%=),         Update according to function
    (?=))         Insert into map
```

Where the Solidity code uses `mapping`, we use Haskell’s regular tree-based map type².

```
import Data.Map as X (
    Map,         Type constructor for mappings
    ∅,           Polymorphic empty mapping
    singleton)   Creates a mapping with a single key–value pair
```

For sequences of log entries, we use a sequence structure which has better time complexity than regular lists.

```
import           Data.Sequence as X (Seq)
import qualified Data.Sequence as Sequence
```

Some less interesting imports are omitted from this document.

¹Gabriel Gonzalez’s 2013 article *Program imperatively using Haskell* is a good introduction.

²We assume the axiom that Keccak hash collisions are impossible.

Appendix B

Act type signatures

```
type Reads r m = MonadReader r m
type Writes w m = MonadState w m
type Fails m = MonadError Error m
type IsAct = ?act :: Act
```

```
type Numbers wad ray sec =
  (wad~Wad, ray~Ray, sec~Sec)
```

We see that `drip` may fail; it reads an `ilk`'s `tax`, `cow`, `rho`, and `bag`; and it writes those same parameters except `tax`.

```
drip ::
  (Fails m,
   Reads r m,
   HasEra r Sec,
   HasVat r vatr,
   HasIlks vatr (Map (Id Ilk) ilkr),
   HasTax ilkr Ray,
   HasRho ilkr Sec,
   HasChi ilkr Ray,
   HasRum ilkr Wad,
   HasJoy ilkr Wad,
  Writes w m,
  HasVat w vatw,
  HasIlks vatw (Map (Id Ilk) ilkw),
  HasRho ilkw Sec,
```

HasJoy ilk_w Wad,
 HasChi ilk_w Ray)
 $\Rightarrow \text{Id I1k} \rightarrow m \text{ Ray}$

form ::

(IsAct, Fails m ,
 Reads $r \ m$, HasSender r Address,
 Writes $w \ m$, HasVat $w \ \text{vat}_w$,
 HasIlks vat_w (Map (Id I1k) I1k))
 $\Rightarrow \text{Id I1k} \rightarrow \text{Id Jar} \rightarrow m \ ()$

frob :: (IsAct, Fails m ,
 Reads $r \ m$, HasSender r Address,
 Writes $w \ m$, HasVat $w \ \text{vat}_w$,
 HasHow $\text{vat}_w \ \text{ray}$)
 $\Rightarrow \text{ray} \rightarrow m \ ()$

open ::

(IsAct,
 Reads $r \ m$, HasSender r Address,
 Writes $w \ m$, HasVat $w \ \text{vat}_w$,
 HasUrns vat_w (Map (Id Urn) Urn))
 $\Rightarrow \text{Id Urn} \rightarrow \text{Id I1k} \rightarrow m \ ()$

give ::

(IsAct, Fails m ,
 Reads $r \ m$, HasSender r Address,
 HasVat $r \ \text{vat}_r$,
 HasUrns vat_r (Map (Id Urn) urn_r),
 HasLad urn_r Address,
 Writes $w \ m$, HasVat $w \ \text{vat}_r$)
 $\Rightarrow \text{Id Urn} \rightarrow \text{Address} \rightarrow m \ ()$

lock ::

(IsAct, Fails m ,
 Reads $r \ m$,
 HasSender r Address,
 HasVat $r \ \text{vat}_r$,

```

    HasUrns  $\text{vat}_r$  (Map (Id Urn)  $\text{urn}_r$ ),
    HasIlk  $\text{urn}_r$  (Id Ilk),
    HasIlks  $\text{vat}_r$  (Map (Id Ilk)  $\text{ilk}_r$ ),
    HasJar  $\text{ilk}_r$  (Id Jar),
    HasJars  $\text{vat}_r$  (Map (Id Jar)  $\text{jar}_r$ ),
    HasGem  $\text{jar}_r$  Gem,
Writes  $w$   $m$ ,
  HasVat  $w$   $\text{vat}_w$ ,
    HasJars  $\text{vat}_w$  (Map (Id Jar)  $\text{jar}_r$ ),
    HasUrns  $\text{vat}_w$  (Map (Id Urn)  $\text{urn}_w$ ),
    HasJam  $\text{urn}_w$  Wad)
 $\Rightarrow$  Id Urn  $\rightarrow$  Wad  $\rightarrow m$  ()

```

```

mark ::
(IsAct, Fails  $m$ ,
 Reads  $r$   $m$ , HasSender  $r$  Address,
 Writes  $w$   $m$ , HasVat  $w$   $\text{vat}_w$ ,
   HasJars  $\text{vat}_w$  (Map (Id Jar)  $\text{jar}_w$ ),
   HasTag  $\text{jar}_w$  wad,
   HasZzz  $\text{jar}_w$  sec)
 $\Rightarrow$  Id Jar  $\rightarrow$  wad  $\rightarrow$  sec  $\rightarrow m$  ()

```

```

tell ::
(IsAct, Fails  $m$ ,
 Reads  $r$   $m$ , HasSender  $r$  Address,
 Writes  $w$   $m$ , HasVat  $w$   $\text{vat}_w$ ,
   HasFix  $\text{vat}_w$  wad)
 $\Rightarrow$  wad  $\rightarrow m$  ()

```

```

prod ::
(IsAct,
 Reads  $r$   $m$ ,
   HasSender  $r$  Address,
   HasEra  $r$  sec,
   HasVat  $r$   $\text{vat}_r$ , (HasPar  $\text{vat}_r$  wad,
     HasTau  $\text{vat}_r$  sec,
     HasHow  $\text{vat}_r$  ray,
     HasWay  $\text{vat}_r$  ray,
     HasFix  $\text{vat}_r$  wad),

```

Writes w m ,
 HasVat w vat_w , (HasPar vat_w wad ,
 HasWay vat_w ray ,
 HasTau vat_w sec),
 Integral sec ,
 Ord wad , Fractional wad ,
 Fractional ray , Real ray)
 $\Rightarrow m$ ()

warp ::
 (IsAct, Fails m ,
 Reads r m , HasSender r Address,
 Writes w m , HasEra w sec ,
 Num sec)
 $\Rightarrow \text{sec} \rightarrow m$ ()

pull ::
 (Fails m ,
 Reads r m ,
 HasVat r vat_r , HasJars vat_r (Map (Id Jar) jar_r),
 HasGem jar_r Gem,
 Writes w m ,
 HasVat w vat_w , HasJars vat_w (Map (Id Jar) jar_r))
 $\Rightarrow \text{Id Jar} \rightarrow \text{Address} \rightarrow \text{Wad} \rightarrow m$ ()

push ::
 (Fails m ,
 Reads r m ,
 HasVat r vat_r , HasJars vat_r (Map (Id Jar) jar_r),
 HasGem jar_r Gem,
 Writes w m ,
 HasVat w vat_w , HasJars vat_w (Map (Id Jar) jar_r))
 $\Rightarrow \text{Id Jar} \rightarrow \text{Address} \rightarrow \text{Wad} \rightarrow m$ ()

mint ::
 (Fails m ,
 Writes w m ,
 HasVat w vat_w , HasJars vat_w (Map (Id Jar) jar_r),
 HasGem jar_r gem_r ,

```

HasTotalSupply gem_r Wad,
HasBalanceOf gem_r (Map Address Wad))
⇒ Id Jar → Wad → m ()

```

```

burn ::
(Fails m,
Writes w m,
HasVat w vat_w, HasJars vat_w (Map (Id Jar) jar_r),
HasGem jar_r gem_r,
HasTotalSupply gem_r Wad,
HasBalanceOf gem_r (Map Address Wad))
⇒ Id Jar → Wad → m ()

```

```

grab ::
(IsAct, Fails m,
Numbers wad ray sec,
Reads r m,
HasSender r Address,
HasEra r Sec,
HasVat r vat_r,
HasFix vat_r wad,
HasPar vat_r wad,
HasHow vat_r ray,
HasWay vat_r ray,
HasTau vat_r sec,
HasUrns vat_r (Map (Id Urn) urn_r),
HasJam urn_r wad,
HasArt urn_r wad,
HasCat urn_r (Maybe Address), HasVow urn_r (Maybe Address),
HasIlk urn_r (Id Ilk),
HasIlks vat_r (Map (Id Ilk) ilk_r),
HasHat ilk_r wad,
HasMat ilk_r wad,
HasRum ilk_r wad,
HasJoy ilk_r wad,
HasTax ilk_r ray,
HasLag ilk_r sec,
HasChi ilk_r ray, HasRho ilk_r sec,
HasJar ilk_r (Id Jar),
HasJars vat_r (Map (Id Jar) jar_r),

```

```

    HasGem jarr Gem,
    HasTag jarr wad,
    HasZzz jarr sec,
Writes w m,
  HasVat w vatw,
    HasTau vatw sec,
    HasWay vatw ray, HasPar vatw wad,
    HasUrns vatw (Map (Id Urn) urnw),
      HasJam urnw wad, HasArt urnw wad,
      HasVow urnw Address,
      HasCat urnw (Maybe Address),
    HasIlks vatw (Map (Id Ilk) ilkw),
      HasJoy ilkw wad,
      HasChi ilkw ray,
      HasRho ilkw sec,
    HasJars vatw (Map (Id Jar) jarr)
) ⇒ Id Urn → m ()

```