

Linux Administration with Ansible: Writing Ansible Playbooks

Writing in YAML



Andrew Mallett

Linux Author and Trainer

@theurbanpenguin www.theurbanpenguin.com



Overview



In this course you will learn to create repeatably correct configurations in Ansible using Playbooks

Course Overview

- Understanding YAML
- Playbooks vs Scripts
- Linting YAML
- Common Playbook Solutions

Module Overview

- Configuring Editors for YAML
- Using VS Code
- Creating and Linting Simple Playbooks



Lab Systems



Three Virtual Systems

- VirtualBox / Vagrant
- RHEL 8, Ubuntu 20.04, Centos Stream
- Using multiple Linux distributions throughout the course allows us to see the power of Ansible at its agnostic best
- Lab setup in Getting Started with Ansible



YAML Ain't Markup Language.

YAML Represents Data Structures in Text Files





Online YAML Parser

<https://yaml-online-parser.appspot.com/>
<https://jsonformatter.org/yaml-parser>



Demo



For our first demonstration we will:

- connect to the online YAML parser



```
$ # cat file file1
```

```
user:
```

```
  name: bob
```

```
  dept: sales
```

```
user:
```

```
  name: bob
```

```
  dept: sales
```

Significant White Space

In YAML, leading whitespace is significant, meaning we do not need the array of brackets seen in JSON. Indent related keys with two spaces, convert tabs to spaces to make life easier

```
# cat -vet file file1
```

```
user:$
```

```
^Iname: bob$
```

```
^Idept: sales$
```

```
user:$
```

```
    name: bob$
```

```
    dept: sales$
```

These Files Look Similar

But they are not, one uses 8 spaces as an indent level the other uses a tab

Configuring Nano

`~/.nanorc`

```
set autoindent  
set tabsize 2  
set tabstospaces
```

Configuring Vim

`~/.vimrc`

```
syntax on  
set bg=dark  
autocmd FileType yaml setlocal ai et ts=2 sw=2 cuc cul
```

! Untitled-1.yml

```
1  user:
2    name: bob
3    dept: sales
4    skills:
5      - perl
6      - python
7      - ps1
```

Microsoft Visual Studio Code (community edition) is ready go with YAML files and is free



Demo



In this demonstration we identify the problems that tabs can cause in YAML files



Demo



Creating a `~/.nanorc` file for those using Nano as a text editor



Demo



**Creating a `~/.vimrc` file for those using Vim
as a text editor**



Demo



Using Visual Studio Code as an IDE for YAML



```
$ mkdir -p ~/ansible/simple

$ cd ~/ansible/simple

$ vim FirstPlay.yaml

- name: My First Play
  hosts: all
  become: true
  tasks:
    - name: My First Task
      package:
        name: tree
        state: present
```

Creating Playbooks

Using Playbooks, we can reference the same configuration and inventory used with ad-hoc commands. A Playbook will contain at least one Play and one or more Tasks within the Play


```
$ pip3 install ansible-lint --user
$ ansible-lint -v FirstPlay.yaml
Failed to guess project directory using git:
WARNING  Overriding detected file kind 'yaml' with 'playbook' for given positional
argument: FirstPlay.yaml
INFO     Executing syntax check on FirstPlay.yaml (0.33s)
```

Linting YAML

We can install the ansible-lint Python modules that will check your Playbook against style guidelines. Here there are no errors.

```
$ ansible-playbook FirstPlay.yaml --syntax-check
```

```
playbook: FirstPlay.yaml
```

Syntax Check

We can also check the correct syntax is employed in the playbook

```
$ ansible-playbook -C -v FirstPlay.yaml
Using /home/vagrant/.ansible.cfg as config file
...
changed: [192.168.33.11] => {"changed": true, "msg": "Check mode: No changes made, but
would have if not in check mode", "rc": 0, "results": ["Installed: tree-1.7.0-
15.el8.x86_64"]}
...
```

Implementing a No-Operation Check

Going beyond syntax checking we can try the option `-C` to check the operation without implementing change . This works best with the verbose option `-v`

Demo



Writing Playbooks:

- Writing a YAML Playbook
- Linting Playbooks
- Checking Playbook
- Implementing Playbooks





Default Task

The default task collects facts about the operating system. If these facts are not needed, we can turn it off in the Play



```
- name: My First Play
  hosts: all
  become: true
  tasks:
    - name: My First Task
      package:
        name: tree
        state: present

    - name: Print Progress
      debug:
        msg: "This is {{ ansible_os_family }}"
```

Debug and Show Progress

In many languages, being able to print variables and the progress is very useful in ensuring the correct operation. We can use the gathered facts as variables in the Playbook.

Demo



Extending and Debugging Playbooks:

- Understand `gather_facts`
- Use variables and debug messages



```
$ find /usr/lib -name 'debug.py'
```

```
$ find /usr/lib -name 'package.py'
```

Locating Modules

Tasks execute Python modules; these are files in the file system

Demo



Locating Ansible Modules



Summary



In this module we have introduced the course highlights to you.

Course Highlights

- Compare scripts with Playbooks
- Writing Playbooks
- Common Tasks

In this Module

- Learned YAML
- Configured Editor
- Created a Playbook



Scripting Linux Administration

