

# mbruner3\_mod4

Mark Bruner

9/21/2020

```
library(lpSolveAPI)
```

## Defining decision variables and objective function

```
factory <- make.lp(0, 9)
lp.control(factory, sense = "max")
```

```
## $anti.degen
## [1] "fixedvars" "stalling"
##
## $basis.crash
## [1] "none"
##
## $bb.depthlimit
## [1] -50
##
## $bb.floorfirst
## [1] "automatic"
##
## $bb.rule
## [1] "pseudononint" "greedy"      "dynamic"      "rcostfixing"
##
## $break.at.first
## [1] FALSE
##
## $break.at.value
## [1] 1e+30
##
## $epsilon
##      epsb      epsd      epsel      epsint  epsperturb  epspivot
##      1e-10      1e-09      1e-12      1e-07      1e-05      2e-07
##
## $improve
## [1] "dualfeas" "thetagap"
##
## $infinite
## [1] 1e+30
##
```

```

## $maxpivot
## [1] 250
##
## $mip.gap
## absolute relative
##      1e-11      1e-11
##
## $negrange
## [1] -1e+06
##
## $obj.in.basis
## [1] TRUE
##
## $pivoting
## [1] "devex"      "adaptive"
##
## $presolve
## [1] "none"
##
## $scalelimit
## [1] 5
##
## $scaling
## [1] "geometric"    "equilibrate" "integers"
##
## $sense
## [1] "maximize"
##
## $simplextype
## [1] "dual"      "primal"
##
## $timeout
## [1] 0
##
## $verbose
## [1] "neutral"

```

```
set.objfn(factory, c(420, 360, 300, 420, 360, 300, 420, 360, 300))
```

## set constraints

### Capacity Constraints

```

add.constraint(factory, c(rep(1, 3)), indices = c(1, 2, 3), "<=", 750)
add.constraint(factory, c(rep(1, 3)), indices = c(4, 5, 6), "<=", 900)
add.constraint(factory, c(rep(1, 3)), indices = c(7, 8, 9), "<=", 450)

```

### Square Footage

```

add.constraint(factory, c(20, 15, 12), indices = c(1, 2, 3), "<=", 13000)
add.constraint(factory, c(20, 15, 12), indices = c(4, 5, 6), "<=", 12000)
add.constraint(factory, c(20, 15, 12), indices = c(7, 8, 9), "<=", 5000)

```

Sales

```
add.constraint(factory, c(rep(1, 3)), indices = c(1, 4, 7), "<=", 900)
add.constraint(factory, c(rep(1, 3)), indices = c(2, 5, 8), "<=", 1200)
add.constraint(factory, c(rep(1, 3)), indices = c(3, 6, 9), "<=", 750)
```

Same percentage of capacity

```
add.constraint(factory, c(rep(900, 3), rep(-750, 3)), indices = c(1, 2, 3, 4, 5, 6), "=", 0)
add.constraint(factory, c(rep(450, 3), rep(-750, 3)), indices = c(1, 2, 3, 7, 8, 9), "=", 0)

set.bounds(factory, lower = c(rep(0, 9)), columns = c(1:9))
```

## Decision Variable Names

```
RowNames <- c("Capacity 1", "Capacity 2", "Capacity 3", "Sqft1", "Sqft2", "Sqft3", "Sales 1", "Sales 2")
ColNames <- c("L1", "M1", "S1", "L2", "M2", "S2", "L3", "M3", "S3")
dimnames(factory) <- list(RowNames, ColNames)
dimnames(factory)
```

```
## [[1]]
## [1] "Capacity 1" "Capacity 2" "Capacity 3" "Sqft1"      "Sqft2"
## [6] "Sqft3"      "Sales 1"    "Sales 2"    "Sales 3"    "Same 1"
## [11] "Same 2"
##
## [[2]]
## [1] "L1" "M1" "S1" "L2" "M2" "S2" "L3" "M3" "S3"
```

## Solve LP model

```
solve(factory)
```

```
## [1] 0
```

Optimize Objective Function

```
get.objective(factory)
```

```
## [1] 696000
```

Decision Variables

```
get.variables(factory)
```

```
## [1] 516.6667 177.7778 0.0000 0.0000 666.6667 166.6667 0.0000 0.0000
## [9] 416.6667
```

## Interpreting the output from optimization routines

In order to satisfy the constraints on the LP Model, the Weigelt Corporation should produce the following quantities of L, M, and S at each factory:

Factory 1 (space = 13000 sq ft and capacity is 750 units.)  $L1 = 516.6667$   $M1 = 177.7778$   
 $S1 = 0.00000$

Factory 2 (space = 12000 sq ft and capacity is 900 units.)  $L2 = 0.00000$   $M2 = 666.6667$   $S2 = 166.6667$

Factory 3 (space = 5000 sq ft and capacity is 450 units.)  $L3 = 0$   $M3 = 0$   $S3 = 416.6667$

## Interpreting optimal objective function value:

If the above production occurs at each factory, optimal amount of money they can expect in profit per day.  
~\$696,000