| Refer | e Value | Footprint | Description |
|-------|------------------|--|---|
| U2 | MIC5205-3.3YM5 | Package_TO_SOT_SMD:SOT-23-5 | 150mA low dropout linear regulator, fixed 3.3V output, SOT-23-5 |
| U1 | ATMEGA328P-AU | ATMEGA328P-AU:QFP80P900X900X120-32N | |
| Y1 | ABM3-16.000MHz | ABM3-16:XTAL500X320X130N | |
| J2 | microSD CARD | MEM2067-02-180-00-A_REVB:GCT_MEM2067-02-180-00-A_REVB | |
| R2 | 10K | Resistor_SMD:R_0805_2012Metric | Resistor |
| C1 | 0.1uF | Capacitor_SMD:C_0805_2012Metric | Unpolarized capacitor |
| R3 | 330 | Resistor_SMD:R_0805_2012Metric | Resistor |
| R1 | 1K | Resistor_SMD:R_0805_2012Metric | Resistor |
| D2 | Green LED | LED_SMD:LED_0805_2012Metric | Light emitting diode |
| D1 | Blue LED | LED_SMD:LED_0805_2012Metric | Light emitting diode |
| C3 | 0.1uF | Capacitor_SMD:C_0805_2012Metric | Unpolarized capacitor |
| C2 | 10uF | Capacitor_SMD:C_0805_2012Metric | Polarized capacitor, small US symbol |
| J4 | Conn_01x01 | Connector_PinHeader_2.54mm:PinHeader_1x01_P2.54mm_Vertical | Generic connector, single row, 01x01 |
| J3 | Conn_01x04 | Connector_PinHeader_2.54mm:PinHeader_1x04_P2.54mm_Vertical | Generic connector, single row, 01x04 |
| J1 | Conn_01x05 | Connector_PinHeader_2.54mm:PinHeader_1x05_P2.54mm_Vertical | Generic connector, single row, 01x05 |
| H1 | MountingHole_Pad | MountingHole:MountingHole_2.2mm_M2_Pad_Via | Mounting Hole with connection |
| H2 | MountingHole_Pad | MountingHole:MountingHole_2.2mm_M2_Pad_Via | Mounting Hole with connection |
| Н3 | MountingHole_Pad | MountingHole:MountingHole_2.2mm_M2_Pad_Via | Mounting Hole with connection |
| H4 | MountingHole_Pad | MountingHole:MountingHole_2.2mm_M2_Pad_Via | Mounting Hole with connection |
| C5 | 18pF | Capacitor_SMD:C_0805_2012Metric | Unpolarized capacitor |
| C4 | 18pF | Capacitor_SMD:C_0805_2012Metric | Unpolarized capacitor |
| C6 | 0.1uF | Capacitor_SMD:C_0805_2012Metric | Unpolarized capacitor |