

KATO KC40 Centrifugal Pump coupled to a KATO KD120-N Diesel Engine

Test Report No.	:	2014 - 22
Date of Test	:	March 4, 2014
Test Valid Until	:	March 4, 2019
Brand	:	KATO
Model	:	KC40
Serial No.	:	2010530
Type and Size	:	Single-end suction, 100 x 100 mm, Non-Self Priming Centrifugal pump
Manufacturer	:	KATO METAL CORP. Valenzuela City
Test Requested by	:	TRAMAT MERCANTILE, INC. 747-749 Sabino Padilla St., Sta. Cruz, Manila
Machine Classification	:	Commercial

SUMMARY

The KATO KC40 centrifugal pump coupled to a KATO KD120-N diesel engine was tested for performance and suction condition. It was tested at the recommended full throttle speed setting of the engine. The engine and pump both used double groove B-section pulleys with actual diameter of 102 mm (4.0 inches), and two pieces of V-belts. The engine and pump were mounted on a steel base.

The Maximum Total Head (H) was 25.2 m at zero discharge condition. The shaft speed of the pump and engine at this point were 2646 and 2452 rpm, respectively with Engine Fuel Consumption Rate of 1.97 L/h. The Maximum Discharge Capacity of 28.0 L/s occurred at 6.77 m Total Head with Maximum Fuel Consumption Rate of 3.35 L/h. The shaft speed of the pump and engine at this point were 2418 and 2295 rpm respectively.

The Maximum System Efficiency of 9.56% occurred at 15.5 L/s Discharge Capacity.

The suction condition of the pump was also tested. With zero discharge, the Maximum Total Suction Lift was 6.0 m. The Net Positive Suction Head Available at this point was 3.87 m.

PURPOSE AND SCOPE OF TEST

The purpose of the test was to establish the pump performance which included the Fuel Consumption Rate and the Total Head at varying discharge capacities and suction conditions. The pump was mounted on the laboratory test set-up shown in **Figure 1**.

The test was conducted on March 4, 2014 at the AMTEC Test Laboratory, UPLB, College, Laguna.




Figure 1. KATO KC40 Centrifugal pump coupled to KATO KD120-N Diesel Engine on the test set-up

METHOD OF TEST

The pump was tested following the “Philippine Agricultural Engineering Standards, PAES 115:2000, Agricultural Machinery – Centrifugal, Mixed-Flow, Axial-Flow Water Pumps – Methods of Test”.

DESCRIPTION OF THE PUMP

The KATO KC40 Centrifugal pump coupled to KATO KD120-N Diesel Engine shown in **Figure 2**, was a single-end suction, 100 mm x 100 mm, centrifugal pump coupled to 8.82 kW (11.8 Hp) KATO KD120-N diesel engine. The pump and engine were mounted on a steel base. The power from the engine was transmitted to the pump shaft through a double groove B-section pulley and V-belts. The actual diameter of the engine and pump pulleys was 102 mm (4.0 inches). The suction inlet and discharge outlet were threaded and designed for a 100 mm diameter pipe. The impeller was a semi-open type made of brass material connected to the pump shaft through a thread. It was housed in a cast iron volute casing. The priming inlet was located on top of the pump beside the discharge outlet. The discharge outlet was located on top of the pump facing upward. The stuffing box used a packing seal. The pump shaft rotated on ball bearing kept in place by a bearing housing integral to the casing.

The prime mover, an 8.82 kW KATO KD120-N diesel engine was a four-stroke, water-cooled, single horizontal cylinder diesel engine. Fuel feed system was of gravity type with the fuel tank located on top of the engine. It utilized an oil-bath type air cleaner. Lubrication system was force-feed lubricating type. Cooling was done by water circulating from cylinder jacket to the radiator using thermo-siphon principle. A fan driven by the pulley on the flywheel was used to cool the warm water in the radiator. It was started using manual cranking lever aided by a manually actuated decompression lever. A muffler was used in the exhaust system.

Table 1 shows the detailed specifications of the pump.




Figure 2. KATO KC40 Centrifugal Pump coupled to a KATO KD120-N Diesel Engine

PUMPSET SPECIFICATIONS

Table 1. Detailed specifications of the KATO KC40 Centrifugal Pump coupled to KATO KD120-N Diesel Engine

1.	Brand	:	KATO
2.	Model	:	KC40
3.	Serial No.	:	2010530
4.	Make	:	KATO METAL CORP. Valenzuela City
5.	Type	:	Single-end suction, Centrifugal pump
6.	Size (mm)	:	100 x 100
7.	Overall Dimension and Weight (Including mounting frame and engine)		
7.1	Length (mm)	:	1315
7.2	Width (mm)	:	400
7.3	Height (mm)	:	600
7.4	Weight (kg)	:	158
8.	Impeller		
8.1	Type	:	Semi-open
8.2	Diameter (mm)	:	175
8.3	Width (mm)	:	32.3
8.4	No. of vanes	:	8
8.5	Material	:	Brass
9.	Suction Inlet		
9.1	Type	:	Threaded flange
9.2	Diameter (mm)	:	100
9.3	Material	:	Cast Iron

Table 1. (Cont'n)

10.	Discharge Outlet		
10.1	Type	:	Threaded flange
10.2	Diameter (mm)	:	100
10.3	Material	:	Cast Iron
11.	Casing		
11.1	Type	:	Volute
11.2	Material	:	Cast Iron
12.	Stuffing box	:	Packing Seal
13.	Rotation	:	Clockwise when facing the suction inlet
14.	Rated speed (rpm)	:	2400
15.	Rated Maximum Discharge Capacity (L/s)	:	1.94
16.	Rated Maximum Total Head (m)	:	18.3
17.	Prime mover (based on Plate Rating)		
17.1	Brand	:	KATO
17.2	Model	:	KD120-N
17.3	Serial No.	:	RD120N-PH/R1100029
17.4	Make	:	GOLDEN FLYING FISH DIESEL ENGINE CO., LTD.
17.5	Type	:	Single cylinder, 4-stroke, water-cooled, horizontal cylinder diesel engine
17.6	Rated Output Power (kW)		
	Maximum	:	8.82 @ 2400 rpm
	Continuous	:	8.08 @ 2400 rpm

Table 1. (Cont'n)

17.8	Bore x Stroke (mm)	:	No Data
17.9	Displacement Volume (cc)	:	651
17.10	Cooling System	:	Water-cooled
17.11	Lubricating System	:	Force-feed
17.12	Starting System	:	Rope-recoil
17.13	Air Cleaner	:	Oil Bath type
17.14	Exhaust System	:	Muffler

PERFORMANCE TEST

Results of performance test are shown in **Table 2** and plotted in **Figure 3**.

Pump Tested : KATO KC40 coupled to
KATO KD120-N diesel engine

Date of Test : March 4, 2014

Test Condition

Ambient Temperature (°C) : 28.0

Atmospheric Pressure (mb) : 1013

Pumping Water Temperature (°C) : 28.3

Table 2. Results of Performance Test

ENGINE SHAFT SPEED (rpm)	PUMP SHAFT SPEED (rpm)	FUEL CONSUMP- TION (L/h)	TOTAL HEAD (m)	DISCHARGE CAPACITY (L/s)	WATER POWER (kW)	INPUT POWER (kW)	SYSTEM EFFICIENCY (%)
2452	2646	1.97	25.2	0	0	20.5	0
2425	2600	2.94	23.2	11.6	2.63	30.6	8.61
2400	2553	3.26	21.3	15.5	3.24	33.9	9.56
2377	2519	3.78	20.1	17.2	3.39	39.3	8.62
2334	2464	4.59	18.1	20.1	3.56	47.7	7.45
2282	2403	4.20	16.2	22.3	3.55	43.7	8.13
2241	23531	4.08	13.8	24.6	3.34	42.4	7.86
2237	2339	4.06	12.5	25.7	3.15	42.2	7.47
2250	2324	4.05	10.4	25.5	2.59	42.1	6.14
2295	2418	3.35	6.77	28.0	1.86	34.8	5.34




Figure 3. Performance characteristic curves of the KATO KC40 centrifugal pump coupled to KATO KD120-N diesel engine

CAVITATION TEST

Results of Cavitation Test are shown in **Table 3**.

Pump Tested	:	KATO KC40 coupled to KATO KD120-N diesel engine
Date of Test	:	March 4, 2014
Test Condition		
Ambient Temperature (°C)	:	30.5
Atmospheric Pressure (mb)	:	1013
Pumping Water Temperature (°C)	:	29.0

Table 3. Results of Cavitation Test

ENGINE SHAFT SPEED (rpm)	PUMP SHAFT SPEED (rpm)	TOTAL SUCTION LIFT (m)	NET POSITIVE SUCTION HEAD AVAILABLE (m)	TOTAL HEAD (m)	DISCHARGE CAPACITY (L/s)
2229	2362	1.63	8.24	37.0	27.0
2305	2444	2.71	7.16	34.6	27.2
2379	2533	4.31	5.56	32.8	20.8
2401	2573	6.0	3.87	32.3	0

DATA COMPUTATION

ANNEX 1. Formula used during calculation and testing

1. Total Head (m), H

$$TDH = H_d - H_s$$

$$\text{Where: } H_d = \frac{P_2}{\gamma} + \frac{V_2^2}{2g} + Z_2$$

$$H_s = \frac{P_1}{\gamma} + \frac{V_1^2}{2g} + Z_1$$

H_d = Total Discharge Head (m)

H_s = Total Suction Lift/Head (m)

$\frac{P_2}{\gamma}$ = Pressure gage reading on the discharge pipe at gage connection converted to meter

$\frac{P_1}{\gamma}$ = Vacuum gage reading on the suction pipe at the point of gage connection converted to meter

$\frac{V_2^2}{2g}$ = Velocity head on the discharge pipe converted to meter.

Computed by determining the velocity of liquid on the pipe by formula, $V = Q/A$ where V, velocity of liquid inside the pipe in meter per second, Q, Discharge rate of the pump in liters per second, and A, Cross-sectional area of the pipe in square meter.

$\frac{V_1^2}{2g}$ = Velocity head on the suction pipe converted to meter

Annex (Cont'n)

Z_2 = The distance from the center of the pressure gage face to the centerline of the pump in meters

Z_1 = The distance from the center of the vacuum gage face to the centerline of the pump in meters

2. Discharge Capacity, Q, in liters per second (L/s) is determined through gravimetric method using a platform scale and a stopwatch.
3. Water Power, WP, is the output power of the pump in kilowatt (kW) and computed using:

$$WP = \frac{H \times Q}{102}$$

4. Input Power, IP, is the power on the input shaft of the pump. This is the power in kilowatt required to drive the pump and is determined by the formula:

$$IP = \frac{T \times N}{974}$$

Where:

T = Torque in kilogram-meter, on the input shaft of the pump and determined by a dynamometer

N = Input shaft angular speed in RPM

5. Pump Efficiency, η ,

$$\eta = \frac{WP}{IP}$$

6. Net Positive Suction Head Available, NPSHA. This is the net force (converted to meter) needed to push the water inside the pipe and computed by the formula:

$$NPSHA = P_{atm} - P_{vp} - H_s$$

Where:

P_{atm} = Atmospheric pressure during the test converted to meters

P_{vp} = Vapor pressure of the test liquid at certain temperature converted to meters

Test Engineers:

JASPER CEASAR S. OGANA

ROMULO E. EUSEBIO

Checked by:

DARWIN C. ARANGUREN

Approved for release:

DELFIN C. SUMINISTRADO

Director

Date

N.B.

This test report should not be used for advertisement or for promotion of the product but only for evaluation purposes and should not be reproduced in whole or in part without the permission of AMTEC.