



AMTEC

AGRICULTURAL MACHINERY TESTING AND EVALUATION CENTER

TEST REPORT NO. 2014 - 151



EAGLE NS100 Centrifugal Pump coupled to KUBOTA RK70-S Diesel Engine

EAGLE NS100 Centrifugal Pump coupled to a KUBOTA RK70-S Diesel Engine

Test Report No.	:	2014 - 151
Date of Test	:	October 15, 2014
Test Valid Until	:	October 15, 2019
Brand	:	EAGLE
Model	:	NS100
Serial No.	:	025883
Type and Size	:	Single-end suction, 100 x 100 mm, Self Priming Centrifugal pump
Manufacturer	:	SUPERCAST FOUNDRY & MACHINERY CORP. P. Gregorio St., Lingunan, Valenzuela City
Test Requested by	:	KUBOTA PHILS., INC. 232 Quirino Highway, Baesa, Quezon City 1106 Metro Manila
Machine Classification	:	Commercial

SUMMARY

The EAGLE NS100 centrifugal pump coupled to a KUBOTA RK70-S diesel engine was tested for performance and suction condition. It was tested at the recommended full throttle speed setting of the engine. The engine and pump both used double groove B-section pulleys with actual diameters of 114 mm (4.5 inches), each and two pieces of V-belts. The engine and pump were mounted on a steel base.

The Maximum Total Head (H) was 16.5 m at zero discharge condition. The shaft speed of the pump and engine at this point were 1917 and 1864 rpm, respectively with Engine Fuel Consumption Rate of 2.24 L/h. The Maximum Discharge Capacity of 19.7 L/s occurred at 6.53 m Total Head with Fuel Consumption Rate of 1.67 L/h. The shaft speed of the pump and engine at this point were 1560 and 1508 rpm respectively. The Maximum System Efficiency of 8.30% occurred at 15.5 L/s Discharge Capacity.

The suction condition of the pump was also tested. With zero discharge, the Maximum Total Suction Lift was 7.10 m. The Net Positive Suction Head Available at this point was 2.98 m.

PURPOSE AND SCOPE OF TEST

The purpose of the test was to establish the pump performance which included the Fuel Consumption Rate and the Total Head at varying discharge capacities and suction conditions. The pump was mounted on the laboratory test set-up shown in **Figure 1**.

The test was conducted on October 15, 2014 at the AMTEC Test Laboratory, UPLB, College, Laguna.



Figure 1. EAGLE NS100 Centrifugal pump coupled to KUBOTA RK70-S Diesel engine on the test set-up

METHOD OF TEST

The pumpset was tested following the “Philippine Agricultural Engineering Standards, PAES 115:2000, Agricultural Machinery – Centrifugal, Mixed-Flow, Axial-Flow Water Pumps – Methods of Test”.

DESCRIPTION OF THE PUMP

The EAGLE NS100 Centrifugal pump coupled to KUBOTA RK70-S Diesel Engine shown in **Figure 2**, was a single-end suction, 100 mm x 100 mm, centrifugal pump coupled to a 5.22 kW (7.0 Hp) KUBOTA RK70-S diesel engine. The pump and engine were mounted on a steel base. The power from the engine was transmitted to the pump shaft through a double groove B-section pulley and V-belts. The actual diameter of the engine and pump pulleys were both 114 mm (4.5 inches). The suction inlet and discharge outlet were threaded and designed for a 100 mm diameter pipe. The impeller was a semi-open type made of cast iron material connected to the pump shaft through a thread with locknut. It was housed in a cast iron volute casing with priming chamber provided with priming inlet and drain outlet. The discharge outlet was located on top of the pump facing upward, while the suction inlet is placed at the inlet to maintain sufficient amount of liquid inside the chamber. The stuffing box used a packing seal. The pump shaft rotated on ball bearing housing bolted to the casing.

The prime mover, a 5.22 kW KUBOTA RK70-S diesel engine was a four-stroke, water-cooled, single horizontal cylinder diesel engine. Fuel feed system was of gravity type with the fuel tank located on top of the engine. It utilized an oil-bath type air cleaner. Lubrication system was force-feed lubricating type. Cooling was done by water circulating from cylinder jacket to the radiator using thermo-siphon principle. A fan driven by the pulley on the flywheel was used to cool the warm water in the radiator. It was started using manual cranking lever aided by a manually actuated decompression lever. A muffler was used in the exhaust system. **Table 1** shows the detailed specifications of the pump.



Figure 2. EAGLE NS100 Centrifugal Pump coupled to a KUBOTA RK70-S Diesel Engine

PUMPSET SPECIFICATIONS

Table 1. Detailed specifications of the EAGLE NS100 Centrifugal Pump coupled to KUBOTA RK70-S Diesel Engine

1.	Brand	:	EAGLE
2.	Model	:	NS100
3.	Serial No.	:	025883
4.	Make	:	SUPERCAST FOUNDRY & MACHINERY CORP. P. Gregorio St., Lingunan, Valenzuela City
5.	Type	:	Single-end suction, Self priming Centrifugal Pump
6.	Size (mm)	:	100 x 100
7.	Overall Dimension and Weight (Including mounting frame and engine)		
7.1	Length (mm)	:	1200
7.2	Width (mm)	:	470
7.3	Height (mm)	:	580
7.4	Weight (kg)	:	130
8.	Impeller		
8.1	Type	:	Semi-open
8.2	Diameter (mm)	:	195
8.3	Width (mm)	:	33.1
8.4	No. of vanes	:	4
8.5	Material	:	Cast Iron
9.	Suction Inlet		
9.1	Type	:	Threaded flange
9.2	Diameter (mm)	:	100
9.3	Material	:	Cast Iron
10.	Discharge Outlet		
10.1	Type	:	Threaded flange
10.2	Diameter (mm)	:	100
10.3	Material	:	Cast Iron

Table 1. (Cont'n)

11.	Casing		
11.1	Type	:	Volute
11.2	Material	:	Cast Iron
12.	Stuffing box	:	Packing Seal
13.	Rotation	:	Clockwise when facing the suction inlet
14.	Rated speed (rpm)	:	2200
15.	Rated Maximum Discharge Capacity (L/s)	:	28.3
16.	Rated Maximum Total Head (m)	:	25.0
17.	Primemover (based on Plate Rating)		
17.1	Brand	:	KUBOTA
17.2	Model	:	RK70-S
17.3	Serial No.	:	RK70-AEG0C58
17.4	Make	:	P.T. KUBOTA INDONESIA Indonesia
17.5	Type	:	Single cylinder, 4-stroke, water-cooled, horizontal cylinder diesel engine
17.6	Rated Output Power (kW)		
	Maximum	:	5.22 @ 2400 rpm
	Continuous	:	4.48 @ 2200 rpm
17.7	Bore x Stroke (mm)	:	No Data
17.8	Displacement Volume (cc)	:	376
17.9	Cooling System	:	Water-cooled
17.10	Lubricating System	:	Force-feed
17.11	Starting System	:	Manual cranking
17.12	Air Cleaner	:	Oil Bath type
17.13	Exhaust System	:	Muffler

PERFORMANCE TEST

Results of performance test are shown in **Table 2** and plotted in **Figure 3**.

Pumpset Tested : EAGLE NS100 coupled to
KUBOTA RK70-S Diesel Engine

Date of Test : October 15, 2014

Test Condition

Ambient Temperature (°C) : 26.6
Atmospheric Pressure (mb) : 1013
Pumping Water Temperature (°C) : 21.0

Table 2. Results of Performance Test

ENGINE SHAFT SPEED (rpm)	PUMP SHAFT SPEED (rpm)	FUEL CONSUMP- TION (L/h)	TOTAL HEAD (m)	DISCHARGE CAPACITY (L/s)	WATER POWER (kW)	INPUT POWER (kW)	SYSTEM EFFICIENCY (%)
1864	1917	2.24	16.5	0	0	23.3	0
1885	1943	2.21	15.6	2.00	0.31	23.0	1.33
1891	1949	2.21	14.2	4.97	0.69	23.0	3.01
1850	1907	2.17	13.1	7.61	0.98	22.6	4.34
1797	1854	2.14	12.1	9.87	1.17	22.3	5.23
1682	1738	1.90	11.2	13.0	1.42	19.7	7.22
1621	1677	1.76	10.1	15.5	1.52	18.4	8.30
1566	1614	1.73	8.79	16.7	1.44	18.0	8.01
1539	1589	1.69	7.45	18.5	1.35	17.6	7.67
1508	1560	1.67	6.53	19.7	1.26	17.4	7.25




Figure 2. Performance characteristic curves of the EAGLE NS100 Centrifugal Pump coupled to KUBOTA RK70-S Diesel Engine

CAVITATION TEST

Results of Cavitation Test are shown in **Table 3**.

Pumpset Tested	:	EAGLE NS100 coupled to KUBOTA RK70-S Diesel Engine
Date of Test	:	October 15, 2014
Test Condition		
Ambient Temperature (°C)	:	27.0
Atmospheric Pressure (mb)	:	1013
Pumping Water Temperature (°C)	:	21.5

Table 3. Results of Cavitation Test

ENGINE SHAFT SPEED (rpm)	PUMP SHAFT SPEED (rpm)	TOTAL SUCTION LIFT (m)	NET POSITIVE SUCTION HEAD AVAILABLE (m)	TOTAL HEAD (m)	DISCHARGE CAPACITY (L/s)
1514	1565	0.09	9.99	6.41	19.6
1537	1587	1.70	8.38	7.58	18.0
1560	1611	3.17	6.91	8.16	16.3
1593	1646	4.56	5.52	9.09	15.1
1641	1670	5.77	4.31	10.0	12.3
1788	1844	7.10	2.98	11.1	0

DATA COMPUTATION

ANNEX 1. Formula used during calculation and testing

1. Total Head (m), H

$$TDH = H_d - H_s$$

Where: $H_d = \frac{P_2}{\gamma} + \frac{V_2^2}{2g} + Z_2$

$$H_s = \frac{P_1}{\gamma} + \frac{V_1^2}{2g} + Z_1$$

H_d = Total Discharge Head (m)

H_s = Total Suction Lift/Head (m)

$\frac{P_2}{\gamma}$ = Pressure gage reading on the discharge pipe at
gage connection converted to meter

$\frac{P_1}{\gamma}$ = Vacuum gage reading on the suction pipe at the
point of gage connection converted to meter

$\frac{V_2^2}{2g}$ = Velocity head on the discharge pipe converted
to meter. Computed by determining the velocity
of liquid on the pipe by formula, $V = Q/A$ where
 V , velocity of liquid inside the pipe in meter per
per second, Q , Discharge rate of the pump in
liters per second, and A , Cross-sectional area
of the pipe in square meter.

$\frac{V_1^2}{2g}$ = Velocity head on the suction pipe converted to
meter

Annex (Cont'n)

Z_2 = The distance from the center of the pressure gage face to the centerline of the pump in meters

Z_1 = The distance from the center of the vacuum gage face to the centerline of the pump in meters

2. Discharge Capacity, Q , in liters per second (L/s) is determined through gravimetric method using a platform scale and a stopwatch.
3. Water Power, WP , is the output power of the pump in kilowatt (kW) and computed using:

$$WP = \frac{H \times Q}{102}$$

4. Input Power, IP , is the power on the input shaft of the pump. This is the power in kilowatt required to drive the pump and is determined by the formula:

$$IP = \frac{T \times N}{974}$$

Where:

T = Torque in kilogram-meter, on the input shaft of the pump and determined by a dynamometer

N = Input shaft angular speed in RPM

5. Pump Efficiency, η ,

$$\eta = \frac{WP}{IP}$$

6. Net Positive Suction Head Available, $NPSHA$. This is the net force (converted to meter) needed to push the water inside the pipe and computed by the formula:

$$NPSHA = P_{atm} - P_{vp} - H_s$$

Where:

P_{atm} = Atmospheric pressure during the test converted to meters

P_{vp} = Vapor pressure of the test liquid at certain temperature converted to meters

Test Engineers:

CONRAD IAN S. TAN

ROMULO E. EUSEBIO

Checked by:

DARWIN C. ARANGUREN

Approved for release:

DELFIN C. SUMINISTRADO

Director

Date

N.B.

This test report should not be used for advertisement or for promotion of the product but only for evaluation purposes and should not be reproduced in whole or in part without the permission of AMTEC.