



NOTES:

1. ALL DIMENSIONS IN MM
2. GENERAL TOLERANCE: X.X = ± 0.4
X.XX = ± 0.25
3. TERM. NUMBERS FOR REFERENCE ONLY.
4. CONTACT RATING: 0.2A @ 30VDC
5. TRAVEL: 3.0 mm
- ▲ 6. OPERATING FORCE: $200 \pm 100\text{gf}$
7. LIFE EXPECTANCY: 10,000 CYCLES
8. OPERATING TEMP: -20°C to 70°C
9. ▲ DENOTES CRITICAL PARAMETER
10. 2011/65/EU (ROHS) COMPLIANT



B	23226	Drawing updated and redrawn	2/19/18	MW
REV	PCR NO	DESCRIPTION	DATE	BY

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY
TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED

TITLE EG1201 (SOLDER LUG, NON-SHORTING)

SCALE 2:1	DATE 2/19/2018	DR MW	DWG P040010	REV B
--------------	-------------------	----------	----------------	----------

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[E-Switch:](#)

[EG1201](#)