PATCH MY PC

Company Portal Deep Dive

From Opening to Installing

Speaker for today

Rudy Ooms

The Company Portal

The magic of the "Install" button
and everything that needs to
happen BEFORE and AFTER



Agenda

- The Full Flow
- The Company Portal Signing In
- WAM not Wham!
- Apps Seem to Appear
- The Install Handoff
- The Download/Decryption

The Full flow....

(please pay attention)



Open Company Portal

SSO kicks in, you don't need to enter your credentials (WAM Kicks in!)

Apps appear

All the apps that are available are loaded (Metadata Catalog)

Click Install

With a simple click the user can trigger the install. The install is handed over to the IME

App Installed

IME tries to detect the app and reports the result.

The “Text” Version

Open Company Portal
SSO kicks in, you don’t need to enter your credentials

Apps appear
All the apps that are available are loaded

Click Install
With a simple click the user can trigger the install

App Installed
IME reports the result.

Hidden underneath: **(what I will explain in detail)**

- WAM gets a token for the App catalog service and SideCar Service
- The token is sent over to get the App Metadata (Assigned Available Apps Information)
- The InstallAppRequest is sent over to the StatelessIWService (Information Worker Service)
- StatusService kicks off App Checkin and monitors the status
- SideCar returns package instructions
- DecryptInfo and the device key unlock the package

Before we even click on Install… there is a lot happening in the background… let’s take it apart one by one

0.1 Company Portal Signing in

Company Portal Signing In

The user only notice the Signing In. The Company Portal is already asking for access.

1. Company Portal opens

When opening the CP, we need to perform authentication





To perform Authentication, we need a valid token to communicate with the services

02. WAM not Wham!

WAM: The Authentication Broker

The Company Portal Uses WAM (Web Account Manager) to get a "Badge" for the requested Services during sign-in

2. WAM gets involved

Windows helps request a token for the services.

- WAM checks who the user is.
- WAM uses the user's work account. Including PRT backed SSO
- WAM requests an access token for the specific requested service.
- WAM gives the token back to the app.
- The "App" can now connect without asking the user to sign in again.

We need 2 Tokens

The IWService and SideCar Service require authentication

The Company portal requires 2 tokens to get the "job" done!!!



IWService is the Intune backend path Company Portal uses to load the app catalog.

The IWService Token

We need something to Authenticate…

How does that Work?

The Company Portal asks WAM for a token scoped to the IWService service

```
PS C:\temp> .\Test-IWServiceWamToken_fixed.ps1 -showtoken

Security warning
Run only scripts that you trust. While scripts from the internet can be useful, this script can pote
Unblock-File cmdlet to allow the script to run without this warning message. Do you want to run C:\t
[D] Do not run  [R] Run once  [S] Suspend  [?] Help (default is "D"): r

Current Windows sign in state
----------------------------
AzureAdJoined : YES
DomainJoined : NO
AzureAdPrt : YES
AzureAdPrtUpdateTime : 2025-05-23 07:28:30.000 UTC
AzureAdPrtExpiryTime : 2025-06-06 07:28:29.000 UTC
WamDefaultSet : YES
WamDefaultAuthority : organizations

Requesting the IWService token through WAM
------------------------------------------
[VERB][WAM] Loaded C:\Windows\Microsoft.NET\Framework64\v4.0.30319\System.Runtime.WindowsRuntime.dll
[VERB][WAM] WinRT types loaded.
[INFO][WAM] Finding the Microsoft Entra WAM provider.
[VERB][WAM] Trying provider authority https://login.microsoftonline.com/common
[INFO][WAM] Provider found: Work or school account
[VERB][WAM] Provider authority: https://login.microsoftonline.com/common
[INFO][Identity] Client ID: 9ba1a5c7-f17a-4de9-a1f1-6178c8d51223
[INFO][Identity] Resource: b8066b99-6e67-41be-abfa-75db1a2c8809
[INFO][Identity] Correlation ID: 9574cc12-1048-464b-a7ae-288ed7b94f7a
[VERB][WAM] Resource set through WebTokenRequest.AppProperties using IDictionary<string,string>.
[INFO][WAM] Calling GetTokenSilentlyAsync.
[INFO][Identity] WAM returned the token silently.
[INFO][Identity] WAM account: rudy@patchmypc.com


Result        : WAM returned an IWService token silently
User          : rudy@patchmypc.com
Audience      : b8066b99-6e67-41be-abfa-75db1a2c8809
TenantId      : b79783df-131e-4d00-8303-6f66c0fa4bfb
ApplicationId : 9ba1a5c7-f17a-4de9-a1f1-6178c8d51223
IssuedAt      : 6/10/2026 11:19:22 AM
Expires       : 6/10/2026 12:28:47 PM
TokenLength   : 2282


WARNING: The complete token is sensitive.
eyJ0eXAiO: [redacted] mFVeVJZMl82TzhLMCIsImtpZCI6IndoMDZz
tYWJmYS03I [redacted] dC9iNzk3ODNkZi0xMzFlLTRkMDAtODMwMy0
4cCI6MTc4I [redacted] UVdsMzdiMEJJcHVUeEhKZmk5dExYRUNvRFp
```

The returned token contains the Proper IWService audience : b8066…..

Different Rooms

Different services need different tokens

The 'IWService' token is required to retrieve all the Available Apps and its metadata.

The IME uses the SideCar token to request the Application data from the SideCar service.

IWService: Company Portal → loads the available apps and icons
SideCar: IME → gets policy and content info

The SideCar Token

The IME also needs a separate bearer token....

How does that Work?

The Company Portal asks WAM for a token scoped to the SideCar Service

We need this token to Authenticate against the SideCar Service! 26a4ae64...

```
Requesting the IME SideCar token through WAM
----------------------------------------------
Client application: Microsoft Intune Windows Agent
Requested resource: Intune SideCar / Check-in service
[VERB][WAM] Loaded C:\Windows\Microsoft.NET\Framework64\v4.0.30319\System.Runtime.WindowsRuntime.dll
[VERB][WAM] WinRT types loaded.
[INFO][WAM] Finding the Microsoft Entra WAM provider.
[VERB][WAM] Trying provider authority https://login.microsoftonline.com/common
[INFO][WAM] Provider found: Work or school account
[VERB][WAM] Provider authority: https://login.microsoftonline.com/common
[INFO][Identity] Client ID: fc0f3af4-6835-4174-b806-f7db311fd2f3
[INFO][Identity] Resource: 26a4ae64-5862-427f-a9b0-044e62572a4f
[INFO][Identity] Correlation ID: 6f21f2d4-290d-49b2-bad3-9f0b9092e535
[VERB][WAM] Resource set through WebTokenRequest.AppProperties using IDictionary<string,string>.
[INFO][WAM] Calling GetTokenSilentlyAsync.
[INFO][Identity] WAM returned the token silently.
[INFO][Identity] WAM account: rudy@patchmypc.com


Result              : WAM returned an IME SideCar token silently
User                : rudy@patchmypc.com
Audience            : 26a4ae64-5862-427f-a9b0-044e62572a4f
ExpectedAudience    : 26a4ae64-5862-427f-a9b0-044e62572a4f
AudienceMatches     : True
TenantId            : b79783df-131e-4d00-8303-6f66c0fa4bfb
CallingApplication  : fc0f3af4-6835-4174-b806-f7db311fd2f3
ExpectedClientId    : fc0f3af4-6835-4174-b806-f7db311fd2f3
IssuedAt            : 6/10/2026 11:38:50 AM
Expires             : 6/10/2026 12:45:53 PM
TokenLength         : 2206


WARNING: The complete token is sensitive.
```


```
eyJ0e [redacted] IsImtpZCI6IndoMDZzRWt6TE
tYTli [redacted] zFlLTRkMDAtODMwMy02ZjY2Y
4cCI6 [redacted] 2JYdUlreFdxMU9rYng3QVU0N
aTjIz [redacted] UVoTnFFWThKUnJaY0RSdm1Uc
yVkdy [redacted] i1mN2RiMzExZmQyZjMiLCJhc
lLWRl [redacted] XAiOiJ1c2VyIiwiaXBhZGRyI
zOGVi [redacted] CJwd2RfdXJsIjoiaHR0cHM6L
```

03. Apps Appear

What comes after the WAM

3. Catalog can be called

Company Portal can now ask which apps it may show.





The Token is then sent over to the IWService

The MetaData = App Information




```
GET /TrafficGateway/.../IWService/Applications

 Authorization: Bearer <catalog token>
 (the token that WAM just got us)

 Purpose:
 return app metadata for this user/device
```

The returned IWService metadata (JSON) contains the information to show the app information and the fancy icons

The IWService….

Which was exactly what was broken last week



Jun 19, 2026, 6:30 PM GMT+2

We've identified that a portion of service infrastructure that facilitates loading apps in the Intune Company Portal for Windows and the web wasn't receiving request traffic as expected and caused impact. While we're continuing to investigate the reason it stopped receiving request traffic, we've confirmed that redirecting the request traffic to a functioning portion of infrastructure remediated the impact.

This is the final update for the event.

If there is an issue with the IWService, that required metadata will NOT be returned!

With it the Company Portal will fail loading the Apps!

GET request to fef.amsub0102.manage.microsoft.com/TrafficGateway/TrafficRoutingService/IWService/StatelessIWService/Applications. Status:500 (Internal Server Error)

04. The Install Handoff

The Install Handoff

What happens if we click “Install”

4.The Company Portal turns the 'click' into install intent.

It sends the install request to IWService
with the IWService token
This request tells Intune, that a certain device
NEEDS to have that app installed... NOW!!!




```
2 references
private async Task SendIwServiceInstallRequestAsync(DownloadContext ctx, AppRow app)
{
    var token = await GetWamTokenAsync(CompanyPortalClientId, IwServiceResource, "AcquireIWServiceTokenForInstallRequest");
    var baseUrl = GetIwServiceBaseUrlFromSideCarEndpoint(ctx.Endpoint);
    var iwServiceDeviceKey = await ResolveIwServiceDeviceKeyAsync(baseUrl, token, ctx.DeviceId);

    Log($"Sending IWService install request for available app [{app.Name}] [{app.Id}].");
    Log($"Local MDM certificate device id: {ctx.DeviceId}");
    Log($"IWService ApplicationState device key: {iwServiceDeviceKey}");

    var attempts = new List<(string StateDeviceId, string QueryDeviceId, string Reason)>
    {
        (iwServiceDeviceKey, iwServiceDeviceKey, "IWService device key for ApplicationState and device-id query"),
        (iwServiceDeviceKey, ctx.DeviceId, "IWService device key for ApplicationState, MDM cert device id for query"),
        (ctx.DeviceId, iwServiceDeviceKey, "MDM cert device id for ApplicationState, IWService device key for query"),
        (ctx.DeviceId, ctx.DeviceId, "MDM cert device id for ApplicationState and query fallback")
    }
```

But... The Company Portal needs a “bridge” to
the IME to wake it up!
It needs to start doing its job!

The Install Handoff

Company portal <-> IMEBridge <-> IME



The IMEBridge is the local path Company Portal uses to wake the IME and start the app check in flow.



The StatusService

The Company Portal performs an App Check-in to kick off the download/install/monitoring


```
AllowedImpersonationLevel=Impersonation
Opened StatusService channel: net.pipe://localhost/IntuneManagementExtension/StatusService/
StatusService version=6
```

The StatusService nudges the IME and monitors the progress/status

The IME handles the Win32App Install....

Using the StatusService Pipe

The Funny thing … we can do the same thing ourselves..



05. The Download + Decryption

First find where SideCar lives

Before the IME can ask the SideCar, it first needs to know where the SideCar lives for this tenant

- The MDM device certificate is used to ask Location Service where SideCar lives



The OID is your tenant id (scrambled around)

```
2026-06-08 14:15:04      Querying discovery endpoint: https://r.manage.microsoft.com/RestUserAuthLocationService/
RestUserAuthLocationService/Certificate/ServiceAddresses
2026-06-08 14:15:05      Found SideCarGatewayService URL: https://agents.amsua0702.manage.microsoft.com/
TrafficGateway/TrafficRoutingService/SideCar/StatelessSideCarGatewayService
```

IME asks for Policies

It needs to send the SideCar token to the service

With the right SideCar endpoint found, IME asks for Policies (Install/Uninstall/Detection Rules etc)

PUT <SideCarGatewayService>
/SideCarGatewaySessions(…)

RequestContentType = GetPolicies

`Authorization: Bearer <SideCar Token>`
(the sidecar token that WAM got us)

Remember…. Different rooms… different tokens..

IME asks for ContentInfo

This is where the content info becomes the download link

After policy, IME asks for ContentInfo. This gives the content location AND decryption information.

PUT <SideCarGatewayService> /SideCarGatewaySessions(…)

RequestContentType = GetContentInfo


```
{
  "odata.metadata": "https://agents.amsua0702.manage.microsoft.com/SideCar/StatelessSideCarGatewayService/$metadata#SideCarGatewaySessions/@Element",
  "odata.id": "urn:StatelessSideCarGatewayService/SideCarGatewaySessions(guid\u0027fc73d34c-825d-4393-96d9-1bef014e0147\u0027)",
  "Key": "\u003Credacted\u003E",
  "SessionId": "fc73d34c-825d-4393-96d9-1bef014e0147",
  "RequestContentType": "GetContentInfo",
  "RequestPayload": "",
  "ResponseContentType": "GetContentInfo",
  "ResponsePayload": "{\u0022ApplicationId\u0022:\u00223d05c6d8-d28e-49d1-afb2-8f6a3d58e33b\u0022,\u0022ApplicationVersion\u0022:\u00221\u0022,\u0022Intent
\u0022:0,\u0022CertificateBlob\u0022:null,\u0022ContentInfo\u0022:\u0022{\\\u0022DownloadType\\\u0022:2,\\\u0022AzureStorageLink\\\u0022:null,
\\\u0022DownloadServiceLink\\\u0022:null,\\\u0022ContentEncryptionKey\\\u0022:null,\\\u0022UploadLocation\\\u0022:\\\u0022http://swda02-
mscdn.manage.microsoft.com/38327286-5a82-4cc7-94c1-c800b540c2d4/419e07e0-3135-46ce-a0ab-03887ee92f06/41edfae7-9b09-481d-b726-b3a43913369c.intunewin.bin\\\u0022,
\\\u0022OriginalSize\\\u0022:433063363,\\\u0022DoFileId\\\u0022:\\\u0022501FCB7D-A970-4E34-A753-4B48FE5D8BEF_38327286-5a82-4cc7-94c1-c800b540c2d4_
419e07e0-3135-46ce-a0ab-03887ee92f06_41edfae7-9b09-481d-b726-b3a43913369c-intunewin-bin_3d05c6d8-d28e-49d1-afb2-8f6a3d58e33b_1\\\u0022,\\\u0022FileSource
\\\u0022:0,\\\u0022FileFormat\\\u0022:0}\u0022,\u0022SecondaryContentInfo\u0022:null,\u0022DecryptInfo\u0022:\u0022\\\u003cEncryptedMessage xmlns=
\\\u0022http://schemas.datacontract.org/2004/07/Microsoft.Management.Services.Common.Cryptography\\\u0022 xmlns:i=\\\u0022http://www.w3.org/2001/XMLSchema-
instance\\\u0022\\\u003e\\\u003cEncryptedContent\\\u003eMIIDAwYJKoZIhvcNAQcDoIIC9DCCAvACAQIxggEwMIIBLAIBAoAU8i/A
\u002BuvnMYuGowd1GlGCHYu9iF4wDQYJKoZIhvcNAQEBBQAEggEASrQkP8ynA4dc4T0KINu4S0hekMWWYW4CuVGPHCFo4p/5fcHgyJ5ucVLQS50lHknnStxZxEo43X9ELSlrIa4yR1KvA3z\u002Bz
\u002Bk/x4NmumcUuJb7fmbPLg1DZhrLRqaAGPB4UVauPBcUSul2zxMh\u002Btq05\u002BCph4n919yiCNqTHrVc7Yy0S6YMzikZb9MabTn\u002BWJS52aEc411lk\u002BX3lkb/EEpvXpiAsh
\u002BZMBEfcQ9GkP\u002Bo\u002BSGkSf9cE2eTsqXxmZCsmtuO2sGswfPPH1lHyEebd2zTSm4VVNi1yJW1TRvFX4LE\u002Bv1flo
\u002B15VAXmdoHZXhQ5GvgBtHgxAs6PprG2Zagk29NJDCCAbUGCSqGSIb3DQEHATAUBggqhkiG9w0DBwQIv6ZcTurvZOiAggGQ8hs1qi0Hu45QNppivlXcR4N3vUoO9X1OVVptgi2WzAosgORnrDK1EIl4ik2ag
DbMScLrNyYekvsufh363kT7sljGmldKIVQq0zFr/MytxotDQtqg5FhH0pXnM1MQCEQRQI7ic6zRfjD4RdgiC3aaQlmwEP691ZzuOWnB94vBKtFuul
\u002BfdmCwx7oPgYSEF20b6nt2GsB9MYvqZ3pn2YU7MsAjE9XjIZtB1fXVaQjNcP1U/SUv044C4cCLwCtGRrIfTVpunFSEw8JSF4nFiiPb3Ki1GCC2X1JO8DbabxaHeRyEqtaqcSFh9GRKja8hr2Naj0fzXSBez
yWLyLjpLbVB1i9GQwBVgbYSTrGsyILds\u002BVHYui3ZLoiFoj3z8FzekyZaSJhcTAjLm7dird\u002B\u002BVxTmKiuesa3rWcap1AC85vS2qGohw3O9xyV
\u002BouJ6El2vP/hp3ETBxeURoyuG8WQzRWM0h8mUWrD5Y/T6B03ShHG\u002BtZy2Ozpcxo75T\u002Bjl Ug68uq9/IOgCUP3SYTvES2T24NvFw==\\\u003c/EncryptedContent\\\u003e
\\\u003cRecipientCertThumbprints xmlns:a=\\\u0022http://schemas.microsoft.com/2003/10/Serialization/Arrays\\\u0022\\\u003e\\\u003ca:string
\\\u003e8BE0A5B2C19F9A4300E49D82A939F349CCCB3A0C\\\u003c/a:string\\\u003e\\\u003c/RecipientCertThumbprints\\\u003e\\\u003c/EncryptedMessage\\\u003e\u0022,
\u0022TargetingMethod\u0022:0,\u0022ErrorCode\u0022:null,\u0022TargetType\u0022:0,\u0022InstallContext\u0022:0,\u0022EspPhase\u0022:0,\u0022ApplicationName
\u0022:null,\u0022AssignmentFilterIds\u0022:null,\u0022ManagedInstallerStatus\u0022:1,\u0022ApplicationEnforcement\u0022:0,\u0022SupplementalContentIds
\u0022:null,\u0022SupplementalContentInfos\u0022:null,\u0022AppTypeSpecificProperties\u0022:null,\u0022AppTypeSpecificPropertiesFormat\u0022:0}",
  "ClientInfo": "",
```


ContentInfo is not the package. It tells IME where to get the file and how to decrypt it

IME downloads and decrypts

The IME downloads the content, decrypts it using the decryption key it downloaded.


```
{
  "odata.metadata": "https://agents.amsua0702.manage.microsoft.com/SideCar/StatelessSideCarGatewayService/$metadata#SideCarGatewaySessions/@Element",
  "odata.id": "urn:StatelessSideCarGatewayService/SideCarGatewaySessions(guid\u0027fc73d34c-825d-4393-96d9-1bef014e0147\u0027)",
  "Key": "\u003Credacted\u003E",
  "SessionId": "fc73d34c-825d-4393-96d9-1bef014e0147",
  "RequestContentType": "GetContentInfo",
  "RequestPayload": "",
  "ResponseContentType": "GetContentInfo",
  "ResponsePayload": "{\u0022ApplicationId\u0022:\u00223d05c6d8-d28e-49d1-afb2-8f6a3d58e33b\u0022,\u0022ApplicationVersion\u0022:\u00221\u0022,\u0022Intent
\u0022:0,\u0022CertificateBlob\u0022:null,\u0022ContentInfo\u0022:\u0022{\\\u0022DownloadType\\\u0022:2,\\\u0022AzureStorageLink\\\u0022:null,
\\\u0022DownloadServiceLink\\\u0022:null,\\\u0022ContentEncryptionKey\\\u0022:null,\\\u0022UploadLocation\\\u0022:\\\u0022http://swda02-
mscdn.manage.microsoft.com/38327286-5a82-4cc7-94c1-c800b540c2d4/419e07e0-3135-46ce-a0ab-03887ee92f06/41edfae7-9b09-481d-b726-b3a43913369c.intunewin.bin\\\u0022,
\\\u0022OriginalSize\\\u0022:433063363,\\\u0022DoFileId\\\u0022:\\\u0022501FCB7D-A970-4E34-A753-4B48FE5D8BEF_38327286-5a82-4cc7-94c1-c800b540c2d4_
419e07e0-3135-46ce-a0ab-03887ee92f06_41edfae7-9b09-481d-b726-b3a43913369c-intunewin-bin_3d05c6d8-d28e-49d1-afb2-8f6a3d58e33b_1\\\u0022,\\\u0022FileSource
\\\u0022:0,\\\u0022FileFormat\\\u0022:0}\u0022,\u0022SecondaryContentInfo\u0022:null,\u0022DecryptInfo\u0022:\u0022\\u003cEncryptedMessage xmlns=
\\\u0022http://schemas.datacontract.org/2004/07/Microsoft.Management.Services.Common.Cryptography\\\u0022 xmlns:i=\\\u0022http://www.w3.org/2001/XMLSchema-
instance\\\u0022\\u003e\\u003cEncryptedContent\\u003eMIIDAwYJKoZIhvcNAQcDoIIC9DCCAvACAQIxggEwMIIBLAIBAoAU8i/A
\u002BuvnMYuGowd1GlGCHYu9iF4wDQYJKoZIhvcNAQEBBQAEggEASrQkP8ynA4dc4T0KINu4S0hekMWWYW4CuVGPHCFo4p/5fcHgyJ5ucVLQS50lHknnStxZxEo43X9ELSlrIa4yR1KvA3z\u002Bz
\u002Bk/x4NmumcUuJb7fmbPLg1DZhrLRqaAGPB4UVauPBcUSul2zxMh\u002Btq05\u002BCph4n919yiCNqTHrVc7Yy0S6YMzikZb9MabTn\u002BWJS52aEc411lk\u002BX3lkb/EEpvXpiAsh
\u002BZMBEfcQ9GkP\u002Bo\u002BSGkSf9cE2eTsqXxmZCsmtuO2sGswfPPH1lHyEebd2zTSm4VVNi1yJW1TRvFX4LE\u002Bv1flo
\u002B15VAXmdoHZXhQ5GvgBtHgxAs6PprG2Zagk29NJDCCAbUGCSqGSIb3DQEHATAUBggqhkiG9w0DBwQIv6ZcTurvZOiAggGQ8hs1qi0Hu45QNppivlXcR4N3vUoO9X1OVVptgi2WzAosgORnrDK1EIl4ik2ag
DbMScLrNyYekvsufh363kT7sljGmldKIVQq0zFr/MytxotDQtqg5FhH0pXnM1MQCEQRQI7ic6zRfjD4RdgiC3aaQlmwEP691ZzuOWnB94vBKtFuul
\u002BfdmCwx7oPgYSEF20b6nt2GsB9MYvqZ3pn2YU7MsAjE9XjIZtB1fXVaQjNcP1U/SUv044C4cCLwCtGRrIfTVpunFSEw8JSF4nFiiPb3Ki1GCC2X1JO8DbabxaHeRyEqtaqcSFh9GRKja8hr2Naj0fzXSBez
yWLyLjpLbVB1i9GQwBVgbYSTrGsyILds\u002BVHYui3ZLoiFoj3z8FzekyZaSJhcTAjLm7dird\u002B\u002BVxTmKiuesa3rWcap1AC85vS2qGohw3O9xyV
\u002BouJ6El2vP/hp3ETBxeURoyuG8WQzRWM0h8mUWrD5Y/T6B03ShHG\u002BtZy2Ozpcxo75T\u002Bj1Ug68uq9/IOgCUP3SYTvES2T24NvFw==\\u003c/EncryptedContent\\u003e
\\u003cRecipientCertThumbprints xmlns:a=\\\u0022http://schemas.microsoft.com/2003/10/Serialization/Arrays\\\u0022\\u003e\\u003ca:string
\\u003e8BE0A5B2C19F9A4300E49D82A939F349CCCB3A0C\\u003c/a:string\\u003e\\u003c/RecipientCertThumbprints\\u003e\\u003c/EncryptedMessage\\u003e\u0022,
\u0022TargetingMethod\u0022:0,\u0022ErrorCode\u0022:null,\u0022TargetType\u0022:0,\u0022InstallContext\u0022:0,\u0022EspPhase\u0022:0,\u0022ApplicationName
\u0022:null,\u0022AssignmentFilterIds\u0022:null,\u0022ManagedInstallerStatus\u0022:1,\u0022ApplicationEnforcement\u0022:0,\u0022SupplementalContentIds
\u0022:null,\u0022SupplementalContentInfos\u0022:null,\u0022AppTypeSpecificProperties\u0022:null,\u0022AppTypeSpecificPropertiesFormat\u0022:0}",
  "ClientInfo": "",
```


The contents are extracted to the IMECache Folder.

PUT <SideCarGatewayService>
/SideCarGatewaySessions(…)

RequestContentType = GetContentInfo


```
{\u0022ApplicationId\u0022:\u00223d05c6d8-d28e-49d1-afb2-8f6a3d
cateBlob\u0022:null,\u0022ContentInfo\u0022:\u0022{\\\u0022Down
eLink\\\u0022:null,\\\u0022ContentEncryptionKey\\\u0022:null,\\
.com/38327286-5a82-4cc7-94c1-c800b540c2d4/419e07e0-3135-46ce-a0
\u0022:433063363,\\\u0022DoFileId\\\u0022:\\\u0022501FCB7D-A970
b-03887ee92f06_41edfae7-9b09-481d-b726-b3a43913369c-intunewin-b
```


Without the Decryption key….
We can't decrypt the
IntunewinFile

UploadLocation points to the encrypted content. DecryptInfo holds the protected unlock information.

IME Installs and Reports

The Win32App finally gets installed

The installer will be kicked off from the IMECache
It starts installing the Win32App and will report the status

App install continues



Detection reevaluated



Toast Success or Company Portal update

Which we all hope to see



Final Summary