Assignment No	1
Title	Range List And Hash
Objective	
Roll No	MCA2649

Source Code:

```
CREATE TABLE sales_range
(salesman_id NUMBER(5),
salesman_name VARCHAR2(30),
sales_amount NUMBER(10),
sales_date DATE)
PARTITION BY RANGE(sales_date)
(
PARTITION sales_jan2026 VALUES LESS
THAN(TO_DATE('01/02/2026','DD/MM/YYYY')),
PARTITION sales_feb2026 VALUES LESS
THAN(TO_DATE('01/03/2026','DD/MM/YYYY')),
PARTITION sales_march2026 VALUES LESS
THAN(TO_DATE('01/04/2026','DD/MM/YYYY')),
PARTITION sales_april2026 VALUES LESS
THAN(TO_DATE('01/05/2026','DD/MM/YYYY'))
);
```

Output:

```
SQL> select * from sales_range;

SALESMAN_ID SALESMAN_NAME                    SALES_AMOUNT SALES_DAT
----------- ------------------------------ ------------ ---------
          1 John Smith                             5000 26-JAN-26
          5 Shruti Kumari                         15000 01-JAN-26
          2 Satish Rathod                         10000 25-FEB-26
          6 Tejas                                  8000 04-FEB-26
          3 Khushi Chauhan                        15000 20-MAR-26
          7 Anuj                                   8000 06-MAR-26
          4 Vishal CHauhan                         3000 12-APR-26

7 rows selected.
```

```
SQL> SELECT * from sales_range PARTITION(sales_jan2026);

SALESMAN_ID SALESMAN_NAME                    SALES_AMOUNT SALES_DAT
----------- ------------------------------ ------------ ---------
          1 John Smith                             5000 26-JAN-26
          5 Shruti Kumari                         15000 01-JAN-26
```

```
SQL> SELECT * from sales_range PARTITION(sales_feb2026);

SALESMAN_ID SALESMAN_NAME                    SALES_AMOUNT SALES_DAT
----------- ------------------------------ ------------ ---------
          2 Satish Rathod                         10000 25-FEB-26
          6 Tejas                                  8000 04-FEB-26
```

```
SQL> SELECT * from sales_range PARTITION(sales_march2026);

SALESMAN_ID SALESMAN_NAME                    SALES_AMOUNT SALES_DAT
----------- ------------------------------ ------------ ---------
          3 Khushi Chauhan                        15000 20-MAR-26
          7 Anuj                                   8000 06-MAR-26
```

```
SQL> SELECT * from sales_range PARTITION(sales_april2026);

SALESMAN_ID SALESMAN_NAME                    SALES_AMOUNT SALES_DAT
----------- ------------------------------ ------------ ---------
          4 Vishal CHauhan                         3000 12-APR-26
          8 Sidesh                                 9000 06-APR-26
```

```
SQL> SELECT table_name, partition_name, high_value, num_rows
  2  FROM user_tab_partitions
  3  WHERE table_name = 'SALES_RANGE';

TABLE_NAME
------------------------------------------------------------------------------
PARTITION_NAME
------------------------------------------------------------------------------
HIGH_VALUE
------------------------------------------------------------------------------
  NUM_ROWS
----------
SALES_RANGE
SALES_APRIL2026
TO_DATE(' 2026-05-01 00:00:00', 'SYYYY-MM-DD HH24:MI:SS', 'NLS_CALENDAR=GREGORIA
```

```
SQL> ALTER TABLE sales_range TRUNCATE PARTITION sales_jan2026;

Table truncated.

SQL> SELECT * from sales_range PARTITION(sales_jan2026);

no rows selected
```

```
SQL> ALTER TABLE sales_range drop PARTITION sales_jan2026;

Table altered.
```

Source Code:

```
CREATE TABLE Student (
   student_id NUMBER(5),
   student_name VARCHAR2(20),
   student_dob DATE)
PARTITION BY LIST (student_name) (
   PARTITION stu_divA VALUES ('a','b','c','d','e','f','g','h','i','j','k'),
   PARTITION stu_divB VALUES ('n','o','p','q','r','s','t','u','v','w','x','y','z'));
```

Output:

```
SQL> CREATE TABLE Student (
  2      student_id NUMBER(5),
  3      student_name VARCHAR2(20),
  4      student_dob DATE)
  5  PARTITION BY LIST (student_name) (
  6      PARTITION stu_divA VALUES ('a','b','c','d','e','f','g','h','i','j','k'),
  7      PARTITION stu_divB VALUES ('n','o','p','q','r','s','t','u','v','w','x','y'
,'z'));

Table created.
```

```
SQL> select * from student;

STUDENT_ID STUDENT_NAME          STUDENT_D
---------- -------------------- ---------
       221 j                    15-SEP-58
       321 a                    19-AUG-58
       322 d                    19-NOV-58
       323 w                    19-AUG-58
       324 s                    19-JAN-58
       325 t                    19-FEB-58

6 rows selected.
```

```
SQL> select * from student partition(stu_divA);

STUDENT_ID STUDENT_NAME          STUDENT_D
---------- -------------------- ---------
       221 j                    15-SEP-58
       321 a                    19-AUG-58
       322 d                    19-NOV-58
```

```
SQL> select * from student partition(stu_divB);

STUDENT_ID STUDENT_NAME          STUDENT_D
---------- -------------------- ---------
       323 w                    19-AUG-58
       324 s                    19-JAN-58
       325 t                    19-FEB-58
```

```
SQL> alter table student add partition stu_null values(NULL);

Table altered.
```

```
SQL> select * from Student partition(stu_null);

no rows selected
```

```
SQL> SELECT table_name, partition_name, high_value, num_rows
  2  FROM user_tab_partitions
  3  WHERE table_name = 'STUDENT';

TABLE_NAME
--------------------------------------------------------------------------------
PARTITION_NAME
--------------------------------------------------------------------------------
HIGH_VALUE
--------------------------------------------------------------------------------
  NUM_ROWS
----------
STUDENT
STU_DIVA
'a', 'b', 'c', 'd', 'e', 'f', 'g', 'h', 'i', 'j', 'k'
```

```
SQL> alter table Student add partition stu_default values(DEFAULT);

Table altered.

SQL> select * from Student partition(stu_default);

no rows selected
```