

How To Get Started With Azure AKS

Building the Kubernetes cluster and deploy a sample app



Bhargav Bachina

Jul 23, 2020 · 6 min read ★



Photo by [Nick Fewings](#) on [Unsplash](#)

AKS is Microsoft Azure's managed Kubernetes solution that lets you run and manage containerized applications in the cloud. Since this is a managed Kubernetes service, Microsoft takes care of a lot of things for us such as security, maintenance, scalability, and monitoring. This makes us quickly deploy our applications into the Kubernetes cluster without worrying about the underlying details of building it.

In this post, we will see how we can build the Kubernetes cluster on Azure AKS, Accessing clusters from outside, configuring kubectl to work with AKS cluster, and

many more.

- *Prerequisites*
- *Install Azure CLI and Configure*
- *Creating AKS Cluster*
- *Configure Kuebctl With AKS Cluster*
- *Example Project*
- *Create a Deployment and Access it*
- *Kubernetes Dashboard*
- *Delete the Cluster*
- *Summary*
- *Conclusion*

Prerequisites

The prerequisites to this post are Docker essentials and Kuberneasts essentials. We are not going to discuss the basics such as what is a container or what is Kubernetes, rather, we will see how to build a Kubernetes cluster on Azure AKS. Below are the prerequisites you should know before going through this article

Docker Essentials

You need to understand Docker concepts such as creating images, container management, etc. Below are some of the links that you can understand about Docker if you are new.

- [Docker Docs](#)
- [Docker — A Beginner's guide to Dockerfile with a sample project](#)
- [Docker — Image creation and Management](#)
- [Docker — Container Management With Examples](#)
- [Understanding Docker Volumes with an example](#)

Kubernetes Essentials


You need to understand Kubernetes' essentials as well along with Docker essentials. Here are some of the docs to help you understand the concepts of Kubernetes.

- [Kubernetes Docs](#)
- [How to Get Started with Kubernetes](#)
- [Some Example Projects](#)

Microsoft Azure Account


You should have a Microsoft Azure Account. You can get a free account for one year. You should see the below screen after you login.

- [Azure Account](#)



Azure Home Screen

You need to create a subscription for your account. The most common is Pay As You Go subscription.





Learn more

Professional Direct support
 Purchase Professional Direct support, ideal for companies with substantial business critical dependence on Azure. Includes faster initial response for technical issues, escalation management and account management.

 Learn more

Standard support
 Purchase Standard support, appropriate for companies with business critical dependence on Azure. Includes reactive 24 x 7 technical support, fast initial response and ability to set severity of issues.

 Learn more

Azure in Open
 Purchase Microsoft Azure services from your Partner, using Microsoft's Open Volume Licensing program.

 Learn more

Subscription Offers

Home > Subscriptions

bachina

Add

View list of subscriptions for which you have role-based access control (RBAC) permissions to manage Azure resources. To view subscriptions for which you have billing access, [click here](#).
 Showing subscriptions in bachina directory. Don't see a subscription? [Switch directories](#).

My role Status

8 selected 3 selected

Apply

Showing 1 of 1 subscriptions ☒ Show only subscriptions selected in the [global subscriptions filter](#)

Search to filter items...

Subscription name	Subscription ID	My role	Current cost	Status
Pay-As-You-Go	bc5fbeca-2e67-4bfb-85bb-58480ab3bb30	Account admin	\$0.14	Active

Pay-As-You-Go Subscription

You need a subscription to be associated with your tenant so that all the cost is billed to this subscription.

Install Azure CLI and Configure

Once you have the Azure Account you can install Azure CLI. You can go to the below documentation and install Azure CLI based on your operation system. You can configure Azure CLI with your subscription.

- [Install Azure CLI](#)
- [Login into your account](#)

```
Bhargavs-MacBook-Pro:sample-workspace bhargavbachina$ az login
You have logged in. Now let us find all the subscriptions to which you have access...
[
  {
    "cloudName": "AzureCloud",
    "homeTenantId": "44e2e07f-a19d-42b6-80a9-a8e4097f3948",
    "id": "bc5fbeca-2e67-4bfb-85bb-58480ab3bb30",
```

```

    "isDefault": true,
    "managedByTenants": [],
    "name": "Pay-As-You-Go",
    "state": "Enabled",
    "tenantId": "44e2e07f-a19d-42b6-80a9-a8e4097f3948",
    "user": {
      "name": "bhargavbachina87@gmail.com",
      "type": "user"
    }
  }
}
]

```

az login

Let's list the subscription with the following command

```
az account list
```

Creating AKS Cluster

First, you need a resource group for all your resources. Let's create a resource with the following command

```
az group create --name myAKSGroup --location eastus
```

```

Bhargavs-MacBook-Pro:sample-workspace bhargavbachina$ az group create --name myAKSGroup --location eastus
{
  "id": "/subscriptions/bc5fbeca-2e67-4bfb-85bb-58480ab3bb30/resourceGroups/myAKSGroup",
  "location": "eastus",
  "managedBy": null,
  "name": "myAKSGroup",
  "properties": {
    "provisioningState": "Succeeded"
  },
  "tags": null,
  "type": "Microsoft.Resources/resourceGroups"
}


```

Resource Group Created

Let's create a cluster with the following command. Notice that we are using the same resource group that we created above. You can see the JSON formatted result after a few minutes.

```
az aks create --resource-group myAKSGroup --name sampleAKSCluster --
node-count 3 --enable-addons monitoring --generate-ssh-keys
```

You can see the following cluster in the console.



sampleAKSCluster

Example Project

We have created the Kubernetes cluster on AKS. It's time to look at the example project that we are deploying. Here is the Github link you can clone it and run it on your machine.

```
// clone the project
git clone https://github.com/bbachi/sample-app-aks.git

// Running on docker
docker build -t sample-aks-image .
docker run -d --name sample-aks -p 80:80 sample-aks-image

// tag and push the image
docker tag sample-aks-image bbachin1/sample-aks-image
docker push bbachin1/sample-aks-image
```

This is a simple HTML file serving through the Nginx server.

1 FROM nginx:alpine

```
2
3 COPY ./html/ /usr/share/nginx/html
4
5 EXPOSE 80
6
7 ENTRYPOINT ["nginx", "-g", "daemon off;"]
```

Dockerfile hosted with ❤ by GitHub

[view raw](#)

```
1 <!DOCTYPE html>
2 <html>
3   <title>Sample AKS App</title>
4   <body>
5     <h1>This is a sample AKS App</h1>
6     <p>Deployed in Azure AKS</p>
7   </body>
8 </html>
```

index.html hosted with ❤ by GitHub

[view raw](#)

sample application

Here is the manifest.yml file for the Kubernetes deployment and service objects

```
1  apiVersion: apps/v1
2  kind: Deployment
3  metadata:
4    creationTimestamp: null
5    labels:
6      app: sample-aks-app
7    name: sample-aks-app
8  spec:
9    replicas: 5
10   selector:
11     matchLabels:
12       app: sample-aks
13   strategy: {}
14   template:
15     metadata:
16       creationTimestamp: null
17     labels:
18       app: sample-aks
19     spec:
20       containers:
21       - image: docker.io/bbachin1/sample-aks-image
22         name: sampleapp
23         imagePullPolicy: Always
24         resources: {}
25       ports:
```



```
26         - containerPort: 80
27     status: {}
28     ---
29     apiVersion: v1
30     kind: Service
31     metadata:
32       name: sample-aks-app
33     spec:
34       type: LoadBalancer
35       ports:
36         - port: 80
37       selector:
38         app: sample-aks
```

manifest.yml hosted with  by GitHub

[view raw](#)

manifest.yml

Configure Kubectl With AKS Cluster

Kubectl is the command-line utility for the Kubernetes. You need to install kubectl before you configure it. Run the first command only if you don't have kubectl on your local machine.

```
// install CLI
az aks install-cli

// connect to your cluster
az aks get-credentials --resource-group myAKSGroup --name
sampleAKSCluster

// get all the contexts
kubectl config get-contexts

// verify the current context
kubectl config current-context

// get the node
kubectl get nodes
```

```
Bhargavs-MacBook-Pro:sample-workspace bhargavbachina$ kubectl get nodes
NAME                                STATUS    ROLES    AGE   VERSION
aks-nodepool1-26533642-vmss000000  Ready    agent    11m   v1.16.10
aks-nodepool1-26533642-vmss000001  Ready    agent    11m   v1.16.10
aks-nodepool1-26533642-vmss000002  Ready    agent    11m   v1.16.10
```


kubectl get nodes

Create a Deployment and Access it


Let's create a deployment with the following command and make sure you are in the root folder of the application. Since you are using type LoadBalancer you can have ingress traffic from the web.

```
// create a deployment
kubectl create -f manifest.yml
```

```
// verify the deployment
kubectl get deploy
kubectl get po
kubectl get service
```

```
Bhargavs-MacBook-Pro:~$ kubectl get service
NAME                TYPE          CLUSTER-IP    EXTERNAL-IP    PORT(S)          AGE
kubernetes           ClusterIP     10.0.0.1      <none>         443/TCP          4h2m
sample-aks-app       LoadBalancer  10.0.43.252   52.149.170.68  80:32011/TCP     75m
```

kubectl get service



Accessing it from the browser


Kubernetes Dashboard

We are done with the deployment and accessing it from the external browser. Let's see our objects in the Kubernetes dashboard with the following command. Make sure you have the correct resource group name and cluster and the following command opens the Kubernetes dashboard in the browser.

```
az aks browse --resource-group myAKSGroup --name sampleAKSCluster
```


You can access the dashboard with either Kubeconfig or Token. You can get the token with the following command.


```
kubectl config view
```



Kubernetes dashboard

Once you log in with token and you can see the following dashboard with all the Kubernetes objects.





Kubernetes Dashboard

Sometime you might get the following error. If you get this error you have to delete and create *cluster role binding*.

az aks dashboard is empty "There is nothing to display here"

solution

```
// Run the following commands
```

```
kubectl delete clusterrolebinding kubernetes-dashboard
```

```
kubectl delete clusterrolebinding kubernetes-dashboard -n kube-system
```

```
kubectl create clusterrolebinding kubernetes-dashboard --clusterrole=cluster-admin --serviceaccount=kube-system:kubernetes-dashboard --user=clusterUser
```

Delete the Cluster

You can just delete the cluster or the resource group. I created a resource group just for this so I am deleting the resource group with the following command. Make sure you delete if you don't want to incur charges.

```
az group delete --name myAKSGroup
```

Summary

- AKS is Microsoft Azure's managed Kubernetes solution that lets you run and manage containerized applications in the cloud.
- Before starting this, you need to have docker and Kubernetes essentials. If you don't have these essentials please go through these with the links provided.
- You need to create a Microsoft [Azure Account](#) here.
- You need a subscription to be associated with your tenant so that all the cost is billed to this subscription.
- You can create the AKS cluster through a portal, Azure CLI, REST API as well.
- You can install Azure CLI and configure it to use with your AKS Cluster.
- Configure kubectl to use the AKS cluster.
- Create a deployment and service with Loadbalancer so that you can access it from outside.
- You can access the dashboard with either Kubeconfig or Token.
- Make sure you delete if you don't want to incur charges.

Conclusion

This is a very basic and beginner guide for managed Kubernetes service AKS from Azure. In future posts, we will explore more options such as RBAC, monitoring, etc.

Sign up for BB Tutorials & Thoughts

By Bachina Labs

Tutorials Ranging from Beginner guides to advanced on Frontend, Backend, Blockchain, Docker, k8s, DevOps, Cloud, AI, ML. Thank you for subscribing and let me know if you want me cover anything?

[Take a look.](#)

Get this newsletter

Emails will be sent to marcus.brito@deal.com.br.
[Not you?](#)

[Kubernetes](#)

[Azure](#)

[Cloud Computing](#)

[Software Development](#)

[Software Engineering](#)

[About](#) [Help](#) [Legal](#)

Get the Medium app

