

# MetaC 1.0

David McAllester

September 25, 2019

## Abstract

MetaC provides a read-eval-print loop (a REPL) and notebook interactive development environment (a NIDE) for C programming. MetaC can also be described as a Lisp-inspired programming environment for C. The REPL and the NIDE are capable of incrementally compiling and executing C statements and incremental procedure definitions in a persistent C process. This is done by compiling and loading dynamic load libraries.

MetaC also extends C with Lisp-like features. More specifically, MetaC provides a C-like universal syntax, computed macros, backquote [1], and pattern-matching. The implementation is bootstrapped — it is implemented in itself. These C extensions are intended to support the development of high level frameworks with notebook interfaces as direct extensions of C. This is in contrast to scripting-C hybrids such as Matlab, Numpy, TensorFlow or PyTorch.

The NIDE is implemented in Emacs piped to a MetaC REPL. Presumably notebook IDEs for C or C++ could also be implemented as extensions of Atom or Visual Studio Code piped to a persistent process.

Dynamic linking is difficult to implement robustly. MetaC release 1.0 runs under both Ubuntu 18.04.1 / gcc 7.3.0 and MAC OSX 10.11.4 / gcc Apple LLVM version 7.3.0 (clang-703.0.31).

**Acknowledgement:** I would like to thank Bob Givan for his aid in exercising and polishing MetaC and his continuing efforts on MathZero.

# Contents

<b>1</b>	<b>Introduction and Overview</b>	<b>4</b>
1.1	Installation . . . . .	4
1.2	Hello World . . . . .	5
1.3	C Statements and C Expressions . . . . .	5
1.4	Definitions of Types and Procedures . . . . .	6
1.5	The Global Variable Array Restriction . . . . .	7
1.6	The Single Symbol Type Restriction . . . . .	8
1.7	Backquote and Universal Syntax . . . . .	8
1.8	Pattern Matching . . . . .	9
1.9	Gensym and Macro Definitions . . . . .	10
1.10	The Notebook IDE . . . . .	12
<b>2</b>	<b>Miscellaneous Features</b>	<b>14</b>
2.1	Interning and Properties . . . . .	14
2.2	Memory Frames . . . . .	14
2.3	Undo Frames . . . . .	15
2.4	Bootstrapping and File Expansion . . . . .	16
2.5	Macro Effects . . . . .	17
2.6	Macro Preliminary Definitions . . . . .	17
<b>3</b>	<b>Universal Syntax</b>	<b>17</b>
3.1	Universal Expressions: cons-car-cdr . . . . .	18
3.2	Universal Expressions: Phantom Brackets . . . . .	19
3.3	The Reader Specification . . . . .	19
3.4	Backquote and Pattern Matching Revisited . . . . .	21
<b>4</b>	<b>List of MetaC Primitives</b>	<b>23</b>

4.1	Expressions . . . . .	24
4.2	Properties . . . . .	24
4.3	Errors and Breakpoints . . . . .	25
4.4	Reading and Printing . . . . .	25
4.5	Macro Expansion . . . . .	25
4.6	List Processing . . . . .	25
4.7	Memory Frames . . . . .	26
4.8	Undo Frames . . . . .	26
4.9	Bootstrapping and File Expansion . . . . .	26

# 1 Introduction and Overview

## 1.1 Installation

To install the REPL:

1. Clone the MetaC repository in a local MetaC directory.
2. Edit the last line of the file `mcA.c` to give your MetaC directory.
3. From a shell running in your MetaC directory type `make MC`.
4. From the same shell type `MC` to get the command line prompt `MC>`.

To install the NIDE:

1. Clone the MetaC repository in a local MetaC directory.
2. Edit the last line of the file `mcA.c` to give your MetaC directory.
3. Add `(load "<MetaC directory>/mc.el")` to your `.emacs` file.
4. Edit the first line of `mc.el` to give the path to your `gdb` executable (the Gnu debugger).
5. Edit the second line of `mc.el` to give the path to your MetaC directory.
6. From a shell running in your MetaC directory type `make NIDE`.
7. Start or restart Emacs.<sup>1</sup>

The NIDE can be run on any file with extension `.mc` in any directory. To experiment with the NIDE use Emacs to visit the file `NIDE-examples.mc` from the MetaC repository. Type `C-z s` (control-z followed by s) to start (or restart) the C kernel. Typing `C-z x` will run the cell containing the cursor and print the result in a C comment at the bottom of the cell. This is substantially equivalent to typing the cell contents into the REPL. More Emacs key bindings and other features of the NIDE are described in section 1.10.

The following examples use the REPL. However, all of these examples can be run as cells in the NIDE.

---

<sup>1</sup>If you load `mc.el` into a running emacs MetaC will not be available in buffers created before the load.

## 1.2 Hello World

```
bash$ make MC
...

bash$ MC

MC> '{hello world}'

hello world

MC>
```

In the above example the backquote expression given to the REPL macro-expands to a C expression which evaluates to a MetaC universal syntax expression which prints as `hello world`. MetaC universal syntax expressions are described in more detail below.

## 1.3 C Statements and C Expressions

We can also declare global variables and execute statements from the REPL.

```
MC> int x[10];

done

MC> for(int i = 0; i < 10; i++)x[i] = i;

done

MC> for(int i = 0; i < 10; i++)fprintf(stdout,"%d",x[i]);

0123456789done

MC>int_exp(x[5])

5

MC>
```

In C syntax one distinguishes C expressions from C statements. A C statement is executed for effect while a C expression is evaluated for value. The REPL

can be given either a statement or an expression. When given a C statement, the REPL simply prints “done” after executing the statement. When given a C expression the REPL computes and prints the value. The REPL assumes that the value of a C expression is a universal syntax tree (also called an expression, giving a second, and confusing, sense of the term “expression”). The procedure `int_exp` above converts an integer to a universal syntax expression. Universal syntax expressions are abstract syntax trees but can be viewed as representations of strings.

If a C statement executes a `return` outside of any procedure then that value is returned to the REPL and printed. For example, the above session can be extended with the following.

```
MC>{int sum = 0; for(int i = 0; i < 10; i++)sum += x[i]; return int_exp(sum);}
45
MC>
```

## 1.4 Definitions of Types and Procedures

One can also define new data types and procedures from the REPL.

```
MC>typedef struct myexpstruct{
    char * label;
    struct myexpstruct * car;
    struct myexpstruct * cdr;} myexpstruct, *myexp;
```

done

```
MC> myexp mycons(char*s,myexp x,myexp y){
    myexp cell=malloc(sizeof(myexpstruct));
    cell->label=s;
    cell->car=x;
    cell->cdr=y;
    return cell;}
```

done

```
MC> expptr myexp_exp(myexp x){
    if(x==NULL)return string_atom("nil");
    return
        '{$string_atom(x->label)}
```

```

    ${myexp_exp(x->car)}
    ${myexp_exp(x->cdr)}};
}

done

```

Note that the last procedure has output type `expptr`. This is the type of the value returned by a backquote expression — the type of MetaC universal syntax expressions.

```
MC> myexp_exp(mycons("foo",mycons("bar",NULL,NULL),NULL))
```

```

foo bar nil nil nil
MC>

```

Procedures can also be redefined at the REPL provided that the signature (argument types and return type) remains the same. Changing a procedure signature requires restarting the MetaC REPL. This restriction ensures meaningful C type checking in the presence of dynamic linking.

## 1.5 The Global Variable Array Restriction

To simplify dynamic linking, all global data variables must be arrays. One can always use single element arrays to represent non-array variables. To make this more convenient we allow single element arrays to be declared with an initial value in a manner similar to non-array data variables. For example, we can declare and assign a variable `y` as follows.

```
MC> int y[0] = 2;

done

```

MetaC treats `int y[0] = 2;` as equivalent to

```

MC> int y[1];

done

MC> y[0] = 2;

done

```

We can continue with

```
MC> y[0] += 1;
```

```
done
```

```
MC> int_exp(y[0])
```

```
3
```

```
MC>
```

Here assignments to `y[0]` are allowed but assignments to `y` are not — assignments to array variables are not allowed in *C*. As noted above, this restriction greatly simplifies dynamic linking of data variables.

## 1.6 The Single Symbol Type Restriction

To simplify the implementation of MetaC all type expressions appearing in procedure signatures and global array declarations must be single symbols. Arbitrary types can be given single symbol names using `typedef`.

## 1.7 Backquote and Universal Syntax

We now consider backquote and universal syntax in more detail. Backquote can be used in a manner analogous to string formatting.

```
MC> expptr friend[0] = '{Bob Givan};
```

```
done
```

```
MC> int height[0] = 6;
```

```
done
```

```
MC> '{My friend ${friend[0]} is ${int_exp(height[0])} feet tall.}
```

```
My friend Bob Givan is 6 feet tall.
```

```
MC>
```



While universal syntax expressions can be viewed as representations of strings, universal syntax expressions are actually abstract syntax trees. The tree structure plays an important role in pattern matching.

## 1.8 Pattern Matching

MetaC provides a pattern matching case construct `ucase` (universal case). The basic form of the case construct is

```
ucase{e;
  <pattern1>:{<body1>}
  ...
  <patternn>:{<bodyn>}}
```

Variables are marked in patterns by the prefix \$.

```
MC>int numeralp(exp_ptr x)
    {if(!atomp(x))return 0;
     char*s=atom_string(x);
     for(int i=0;s[i]!='\0';i++){if(s[i]<'0' || s[i]>'9')return 0;}
     return 1;
    }

done

MC> int value(exp_ptr e)
    {ucase
     {e;
      {$x+$y}:{return value(x)+value(y);}
      {$x*$y}:{return value(x)*value(y);}
      {($x)}:{return value(x);}
      {$z}.numeralp(z)}:{return atoi(atom_string(z));}
     }
     return 0; //this dead code convinces the compiler there is a return value.
    }

done
```

The last clauses of the last procedure uses a condition feature where a pattern can have the form `{<pattern>}.(<condition>)` where `<condition>` is a C expression which must be non-zero in order for the clause to be selected.

```
MC>int_exp(value('{5+2*10}))
```

```
25
```

```
MC>int_exp(value('{foo}))
```

```
match error: the value
```

```
foo
```

```
does not match any of
```

```
{ $z }. (numeralp(z)) { ($x) } { $x*$y } { $x+$y }
```

```
MC>
```

In many situations the choice of the particular tree structure imposed by the MetaC reader is not important as long as the same conventions are used in both the patterns and the expressions they are matching. For example, the expression `a+b+c` will match the pattern `$x+$y+$z` independent of whether `+` is left associative or right associative. But the tree structure does matter in other cases. The pattern `$x*$y` will not match the expression `a+b*c` because the reader brackets `a+b*c` as `<a + (b * c)>`. The pattern `$x*$y` does match `(a+b)*c`. The variable `$any` is special. It acts as a wild card and is not bound to a value.

When a `ucase` is executed the patterns are tried sequentially and stops after the first match. If no pattern matches an error is generated. One can always add a final pattern of `{ $any }` to provide a default catch-all case if that is desired.

In release 1.0 repeated variables, such as in the pattern `{ $x + $x }`, are not supported (and not checked for). If a variable is repeated it will be matched at its last occurrence under depth-first left to right traversal.

## 1.9 Gensym and Macro Definitions

MetaC supports computed macros. Pattern matching and backquote greatly facilitate the writing of computed macros. Backquote and `ucase` are both implemented as computed macros in the bootstrapped implementation. As a very simple example we can define a `dolist` macro at the REPL.

```
MC>umacro{dolist($x,$L){$body}}{
```

```

    expptr rest=gensym("rest");
    return
    '{for(expptr $rest = $L; cellp($rest); $rest = cdr($rest);){
      expptr $x=car($rest);
      $body}};
}

done

MC>macroexpand('{dolist(item,list){f(item);}})

for
  (expptr _genrest33=list;
   cellp(_genrest33);
   _genrest33=cdr(_genrest33);
  ){expptr item=car(_genrest33);f(item);}

MC>

```

The general form of a macro definition is

```
umacro{<pattern>}{<body>}
```

where instances of <pattern> in MetaC code are to be replaced by the value returned by <body> under the variable bindings determined by the match. The pattern is restricted so as to have an identifiable head symbol to which the macro is attached.

The procedure `macroexpand(expptr e)` takes a universal syntax expression and returns the result of repeatedly expanding outermost macros until no further macro expansion is possible.

The macro expansion of the above definition of `dolist` defines a procedure to compute the macro expansion and installs that procedure on a macro property of the symbol `dolist`. A typical macro pattern is a symbol followed by one or more parenthesis expressions in which case the macro is attached to the initial symbol. The macro can also be attached to a binary connective. For the macro pattern `{ $x .> $y }`, the macro is attached to the two-character binary connective `.>`.

It is sometimes useful to see the result of a single step of macro expansion. The procedure `macroexpand1(expptr)` returns the result of a single step of macro expansion on the root of the given argument.

## 1.10 The Notebook IDE

Starting the kernel with the key C-z s creates a running C process. When a cell is executed with the command C-z x the text of the cell is passed to the C process from which a value is returned and then printed inside a comment below the cell. If a comment already occurs directly below the cell this comment is replaced by a new comment containing the response of the REPL. As in a Jupyter notebook, the values returned from the REPL are numbered so that one can see when the cell was executed relative to other cell execution in the notebook. If C-z s is run when a kernel is already running the kernel process is killed and a new one started (as in a Jupyter notebook). When the kernel is restarted the execution numbering is reset to start with 1. Changing a procedure signature (argument and return types) requires restarting the kernel.

**Cell Boundaries.** A cell begins at any nonempty line whose first character is other than white space (space or tab), a close character `')`, `}`, or `]`, or a slash `/`. The cell ends at the beginning of the next non-empty line whose first character is other than white space or a close character or at the end of the file if no such line exists.

Note that a comment starting at the beginning of a line terminates a cell.

### Errors and Breakpoints.

If the cell contains unbalanced parentheses, or non-ascii unicode characters, the NIDE will print **"reader error"** as the value of the cell and display an error message.

If an error occurs while macro-expanding the cell expression, the NIDE will print **"macro expansion error"** as the value of the cell and enter the gdb debugger. Such an error may be due to a bug in a user-written macro and gdb can be useful in this case. Typing the continue command, which can be abbreviated as just **"c"**, will abort the cell execution and return to the NIDE.

If an error occurs while attempting to compile the macro-expanded cell, the NIDE will print **"compilation error"** as the value of the cell and display the compiler errors. These errors contain the name of the C file passed to the compiler. Examining this C file is sometimes helpful.

If an error is trapped by dynamic checking while executing the compiled code for the cell, the NIDE will print **"dynamic-check execution error"** as the value of the cell and enter the gdb debugger. Typing the continue command to gdb will abort execution and return to the NIDE. The procedure **error(char \*)** can be called by the user to declare a dynamic-check error.

If an error is trapped directly by gdb during execution, for example a segmentation fault in user code, the NIDE will print **"gdb-trapped execution error"** as the value of the cell and enter the gdb debugger. In this case the continue

command is ineffective and one must type `p NIDE()` to return to the NIDE.

The MetaC procedure `breakpt(char *)` can be used for breakpoints from which execution can be continued. When `breakpt` is called the NIDE will invoke the debugger with no error message printed in the NIDE but with the string passed to `breakpt` printed in the first line in the debugger window. The `continue` command will continue execution from the breakpoint.

MetaC is designed to minimize the risk of memory corruption when returning to the NIDE from an error. See the discussions of unwind protection in sections 2.2 and 2.3. If there is a concern over memory corruption one can always restart the C process.

**Printing.** The procedure `mcprint` is like `fprintf` but omitting the file argument. The expression `mcprint("x = %s\n",s)` will print to the `*Messages*` buffer in Emacs. The procedure `mcpprint(expptr e)` will pretty-print the expression `e` to the `*Messages*` buffer. When in the gdb debugger entering `pp(<exp>)` will pretty print the given expression.

**Key Bindings.** `mc.el` provides the following key bindings.

C-z s starts or restarts the persistent C process.

C-z x executes the cell containing the cursor.

C-z r executes all cells in the current region sequentially with a different execution number for each cell execution.

C-z b executes the entire buffer

C-z B executes the buffer up to the current cursor position.

C-z a moves to the beginning of the current cell.

C-z p moves to the beginning of the preceding cell.

C-z n moves to the beginning of the next cell.

C-z c removes all cell values. This is useful before a git commit as it can reduce or eliminate file differences.

**Load Statements.** A cell in a code file containing `load(<filename>)` (with no semicolon) will load the cells of the named file (which should be a string constant) into the persistent C process. The extension `.mc` will be automatically added and should not be explicitly given. Load statements can also be given to the REPL to load (and link) C files into the running REPL process.

## 2 Miscellaneous Features

### 2.1 Interning and Properties

In MetaC expressions are interned and have property lists. Interning means that two expressions which have the same tree structure and sequence of leaves are represented by the same data structure with the same memory address. This is sometimes called “hash-consing” and can be expressed in Lisp terminology by saying that “equal” implies “eq”. Hence we have

```
MC> int_exp('{foo(a)} == '{foo(a)})  
1
```

Interned expressions with properties provide the functionality of dictionary data structures such as C++ hashmaps or Python dictionaries. Interning also facilitates the implementation of forward chaining inference algorithms — we do not want to waste time noticing the same consequence over and over again. Interned expressions with property lists can also be viewed as a form of no-SQL database. Interning also allows directed acyclic graphs (dags) to be represented compactly as expressions. This is very convenient for the representation of machine-generated justifications (proofs).

The procedure `setprop(expptr exp, expptr prop, void * value)` sets the given property of the given expression to the given value. The procedure `getprop(expptr exp, expptr prop, void * default)` returns the given property of the given value or the default value if no property value has been assigned. MetaC also provides the procedures `setprop_int(expptr e, expptr p, int n)` and `getprop_int(expptr e, expptr p, int default)`. It is not difficult to define polymorphic macros for setting and extracting properties where the type of the property is passed as an argument. It is also not difficult to assign types to particular properties so that the type argument is not needed in polymorphic property setting and retrieving. However, these features are not present in release 1.0.

### 2.2 Memory Frames

A memory frame is analogous to a stack frame but is only loosely tied to the C stack. The macro `in_memory_frame(<statement>)` will execute the given statement inside a new memory frame. The procedure `stack_alloc(int nbytes)` returns a pointer to a block of the given size allocated from the current memory frame. When `in_memory_frame(<statement>)` exits the memory-frame free pointer (or “stack pointer”) is reset. This frees all memory allocated from the frame. This architecture differs from traditional stack allocation in

that recursive procedures can operate with a single memory frame and return newly allocated memory as values without copying. The allocated storage will not be deallocated until exit from an enclosing use of `in_memory_frame`. MetaC pre-allocates the heap (stack space) used for memory frames. The deallocation (resetting of the `freeptr`) is unwind protected — it will occur when an error is thrown beyond the frame entry point. This avoids a memory leak when returning from an error to the REPL or NIDE.

MetaC clears the base memory frame after every evaluation in the REPL and after every cell evaluation in the NIDE. It is therefore important not to be using stack allocated memory between evaluations.

## 2.3 Undo Frames

Undo frames are similar to memory frames but with the added feature of undoing effects tied to the frame. The macro `exp_from_undo_frame(<expression>)` creates a new undo frame and executes the given expression in the new frame. Memory is allocated from the current undo frame with `undo_alloc(int nbytes)`. Effects are tied to the current undo frame with the C preprocessor macro `undo_set(void * loc, void * val)`. On exit from an undo frame all memory allocated from that frame is reclaimed by resetting a free pointer and all locations assigned by `undo_set` are restored to the values they had before entry to the frame.

In MetaC all expression allocation and property assignments are tied to the current undo frame. On exit from the undo frame the database represented by expression properties is restored to the state that existed on frame entry.

The macro `exp_from_undo_frame(<expression>)` computes the value of the given expression in a new undo frame, then pops that undo frame while copying the computed value into the parent undo frame. The value must be a universal syntax expression (an `exp_ptr`). This is used for returning the “value” or “result” of a large computation while freeing the allocation and undoing the effects of the computation. The macro `exp_from_undo_frame(<expression>)` has unwind protection so that the undo frame is popped (with memory deallocated and effects undone) if an error is thrown in the execution of the expression.

The procedure `clean_undo_frame(exp_ptr e)` is similar to `exp_from_undo_frame` but replaces the current undo frame with a fresh one into which the given expression is copied. In this case there is no allocation from the parent frame. The procedure `clean_undo_frame(exp_ptr e)` can be used for garbage collection as in `(install_live_stuff(clean_undo_frame(compute_live_stuff())))`.

The procedures `exp_from_undo_frame` and `clean_undo_frame` both use expression copying that runs in time proportional to the dag size of the expression. The dag size can be exponentially smaller than the tree size.

`exp_from_undo_frame` is a macro that expands to a C expression. Recall that C expressions have values while C statements do not. Macros that expand to expressions (with values) typically expand to compound expressions of the form `({... <var>;})` where the value returned is the value of the final variable after executing the previous statement. Compound expressions are a GNU C extension.

The base undo frame is not cleared between evaluations. The base frame is holding properties needed for the proper functioning of MetaC. The base frame should not be manually cleared. It is not difficult to write a collector for collecting the state used by the MetaC system which could then be integrated into a user-written state collector for garbage collecting the base frame. However MetaC 1.0 does not support garbage collecting the base undo frame. One can always restart the C process.

## 2.4 Bootstrapping and File Expansion

MetaC is bootstrapped. The makefile for MetaC includes the following.

```
mcB.c : expandA mcB.mc
./expandA mcB.mc mcB.c
```

The executable `expandA` is implemented entirely in C but implements the backquote macro. The executable `expandA` expands backquote expressions appearing in the input file. The file `mcB.mc` implements `ucase` using backquote and the executable `expandB` expands both backquote expressions and `ucase` statements. The makefile also includes.

```
mcC.c : expandB mcC.mc
./expandB mcC.mc mcC.c
```

Here the file `mcC.mc` implements additional macros using both backquote and `ucase`. In the MetaC makefile this is continued up to `mcE.mc` and `expandE`. MetaC provides the procedure `mcexpand(char * f1, char * f2)` which is used in the code for the `expand` commands. This procedure macro-expands the file `f1` and writes the result to file `f2`. The expansion is done using whatever macros are defined in the current state — the expansion uses whatever procedures and operators currently have macro expansion procedure pointers on their property lists.

The procedure `mcexpand(char * f1, char * f2)` is implemented using the MetaC procedure `file_expressions(char * f)`. This procedure takes a file name and returns a list of the expressions contained in the cells of that file.



## 2.5 Macro Effects

Macros expansion can have effects. The macro `umacro` expands to a procedure definition of the macro expansion code but also generates a statement which installs that procedure pointer in the macro property of the head symbol. During macro expansion the MetaC primitive `add_init_form(expptr statement)` is called with a statement that installs the procedure pointer on the appropriate property list. The procedure `add_init_form` is provided to the user for use in defining complex macros requiring this feature.

In file expansion the initialization forms generated during macro expansion are incorporated into an initialization procedure. The macro `init_fun(<fname>)` macro expands to a definition of the given procedure name with no arguments but with the sequence of initialization forms in its body. In the REPL and IDE the initialization forms are run before the macro expansion of the input or cell is run.

## 2.6 Macro Preliminary Definitions

Macro expansion can also generate preliminary definitions. It is possible to implement syntactic closures (lambda) as a macro. A closure consists of a procedure pointer together with values for the free variables of the lambda expression. The lambda macro must first create the procedure that executes the body of the lambda expression and then incorporate that procedure pointer into the expansion of the lambda macro. The construction of the procedure definition is a “preamble” to the macro expansion. MetaC provides the primitive `add_preamble(expptr definition)` for creating preambles during macro expansion. In file expansion these preamble definitions are inserted into the output file before the expression generated by the macro. In the REPL and NIDE these preamble definitions are installed along with the expression created by the macro. MetaC 1.0 supports preambles but does not provide a macro for lambda expressions.

## 3 Universal Syntax

It is not obvious how to implement light weight expression quotation and expression pattern matching for C expressions. The syntax of C is complex. We bypass this complexity by introducing a syntax with the following three “universal” properties.

1. Universal syntax trees are semantics-free. They are simply trees viewed as representations of character strings.

2. The universal syntax reader can read any parenthesis-balanced character string. Here parenthesis-balanced means that every open parenthesis, brace or bracket has a matching closing character and that string quotations are properly closed.
3. The printer inverts the reader. If we read a string  $s$  into a universal syntax expression  $e$  and then print  $e$  back into a string  $s'$  we have that  $s$  and  $s'$  are equivalent in a strong sense. Here we want  $s$  and  $s'$  to be “whitespace equivalent” so as to be treated equivalently by the C lexer.

The emphasis here is on the representation of strings. The reader does not always invert the printer — the expression `<<one two> three>` prints as `one two three` which reads as `<one <two three>>`. But the represented string is preserved. This is fundamentally different from most programming languages supporting symbolic computation (such as Lisp) where it is assumed that the tree structure, rather than the represented string, is fundamental and hence that the reader should invert the printer.

The above universality properties allow one to assign semantics to universal syntax expressions based on the strings that they represent. We can assign C semantics to an expression by printing the expression and passing the resulting string to a C compiler. This string-based semantics is not always compositional with respect to the universal syntax tree structure. However, the tree structure imposed by the reader is designed to approximate the compositional structure of C syntax. In most cases pattern matching on universal syntax expressions recovers substructure that is semantically compositional under C semantics. Parentheses and semicolons can be helpful in aligning universal syntax trees with C semantics. For languages and frameworks implemented as macro packages in MetaC one can guarantee that the universal syntax tree structure has compositional semantics.

### 3.1 Universal Expressions: cons-car-cdr

A universal syntax expression is either an atom (a wrapper around a string), a pair `< $e_1 e_2$ >` where  $e_1$  and  $e_2$  are expressions, or a “parenthesis expression” the form `( $e$ )`, `{ $e$ }`, or `[ $e$ ]` where  $e$  is an expression. All three of these datatypes have the same C type `exp_ptr` (Expression Pointer). For each of the types atom, pair and parenthesis expression there is a constructor procedure, a predicate, and accessor functions as follows.

```
exp_ptr string_atom(char *);
int atomp(exp_ptr);
char * atom_string(exp_ptr); //the argument must be an atom.
```

```

exp_ptr cons(exp_ptr,exp_ptr);
int cellp(exp_ptr);
exp_ptr car(exp_ptr); //the argument must be a cell. returns the first component.
exp_ptr cdr(exp_ptr); //the argument must be a cell. returns the second component.

exp_ptr intern_paren(char,exp_ptr); // the char must be one of '(', '{' or '['
int parenp(exp_ptr);
exp_ptr paren_inside(exp_ptr);

```

## 3.2 Universal Expressions: Phantom Brackets

The MetaC reader maps a character string to a universal syntax expression. A specification of the reader is given in section 3.3. The expression produced by the reader can be represented by “phantom brackets” around the given string where there is a pair of brackets for each cons cell. For example the expression {one two three} reads as {⟨one ⟨two three⟩⟩}. Examples of strings and the phantom bracketing imposed by the reading those strings is given in figure 1. The printer simply removes the phantom brackets and prints the string that the expression represents.

To reduce the clutter of brackets we will adopt two conventions for suppressing brackets — a list convention and a binary operator convention. The list convention abbreviates ⟨zero ⟨one ⟨two three⟩⟩⟩ as ⟨zero one two three⟩. The binary operation convention abbreviates ⟨⟨ $a_1$   $o$   $a_2$ ⟩ where  $o$  is a connective atom as ⟨ $a_1$   $o$   $a_2$ ⟩. For example, the expression {a + b} reads as {⟨⟨a + b⟩⟩} which is then abbreviated as ⟨a + b⟩. We note that The MetaC reader bracketing of

$$\{e_1 ; e_2 ; e_3 ; e_4\}$$

is

$$\{\langle\langle e_1 ; \rangle \langle\langle e_2 ; \rangle \langle\langle e_3 ; \rangle e_4 \rangle \rangle \rangle\}.$$

which can be abbreviated using the binary operation convention as

$$\{\langle e_1 ; \langle e_2 ; \langle e_3 ; e_4 \rangle \rangle \rangle\}$$

or abbreviated with the list convention as

$$\{\langle\langle e_1 ; \rangle \langle e_2 ; \rangle \langle e_3 ; \rangle e_4 \rangle\}.$$

## 3.3 The Reader Specification

The MetaC reader can be described in three phases — preprocessing, lexicalization, and parsing.

```

Hello World  ⇒  ⟨Hello World⟩
one two three ⇒  ⟨one ⟨two three⟩⟩
              =  ⟨one two three⟩
x + y        ⇒  ⟨⟨x +⟩ y⟩
              =  ⟨x + y⟩
x + y * z    ⇒  ⟨x + ⟨y * z⟩⟩
(x + y) * z  ⇒  ⟨⟨(x + y)⟩ * z⟩
foo(int x)   ⇒  ⟨foo (⟨int x⟩)⟩
foo(int x, float y) ⇒  ⟨foo (⟨⟨int x⟩, ⟨float y⟩)⟩⟩
(foo (int x, float y) bar) ⇒  (⟨⟨foo (int x, float y)⟩ bar⟩)

(foo b c)    ⇒  (⟨foo b c⟩)
(foo (b) c)  ⇒  (⟨⟨foo (b)⟩ c⟩)
(foo (b) (c) d e) ⇒  (⟨⟨foo (b) (c)⟩ d e⟩)

($ f b c)    ⇒  (⟨⟨$ f⟩ b c⟩)
($ f (b) (c) d e) ⇒  (⟨⟨⟨$ f⟩ (b) (c)⟩ d e⟩)
($ {f(x)} (b) (c) d e) ⇒  (⟨⟨⟨$ {f(x)}⟩ (b) (c)⟩ d e⟩)

```

Figure 1: **Examples of Reader Bracketings.** Bracketings are shown for the expression that results from reading the given strings. A complete bracketing shows a pair of brackets for every expression pair (cons cell). The second and third example show two conventions for dropping some of the brackets — general sequences are assumed to be right-associative and binary connective applications are assumed to be left-associative. These conventions are used in the other examples. Expressions are printed to files, the REPL or the NIDE without the brackets — the brackets are “phantoms” that show the tree structure. section 3.3.

The MetaC preprocessor replaces each C-style comment with a space character. When processing an entire file, as is done in the MetaC procedure `file.expressions` described in section 2.4, the preprocessor divides the file into cells using the same conventions as is used in the NIDE. A file must be parenthesis-balanced within each cell.

Lexicalization segments a pre-processed character string into a sequence of atoms. The MetaC lexer preserves all non-white characters. For the MetaC lexer each atom is one of the following.

- A symbol. A symbol is a character string consisting of only alpha-numeric characters — upper and lower case letters of the alphabet, plus the decimal numerals, plus underbar. For example `foo_bar1`.
- A connective. A connective is a character string consisting of only “connective characters”. Grouped by precedence, the connective characters are

{;} {,} {::} {⓪} {!, &, ?, !} {=, ~, <, >} {+, -} {\*, /} {%, ^} {., #}.

The characters are listed from low precedence (weakly binding) to high precedence (strongly binding). A connective — a string of connective characters — has the precedence of its first character. The “null connective”  $\epsilon$  intuitively represents the space character used as a connective. The null connective and the null argument are discussed below.

- A quoted string. A character string starting and ending with the same string quotation character. For example `"foo bar"`, `"!:&?;"` or `'a'`.
- A special character atom. These are atoms whose strings are one character long where that character is one of the special characters `'`, `$`, and `\`.

Two strings will be called whitespace-equivalent if they lexicalize to the same sequence of atoms.

The reader is specified by the grammar shown in figure 2.

### 3.4 Backquote and Pattern Matching Revisited

The semantics of backquote is defined in terms of cons-car-cdr view of expressions independent of the MetaC reader. In the typical case, the C value of a backquote expression  $\langle \text{' } \{e\} \rangle$  is the expression (tree)  $e$  with subexpressions (subtrees) of the form  $\langle \$ x \rangle$ , where  $x$  is a symbol, replaced by the C value of  $x$  and subexpressions (subtrees) of the form  $\langle \$ \{w\} \rangle$  replaced by the expression which is the C value of the string represented by the expression  $w$ .

$$\begin{aligned}
E &::= E_\infty \mid E_p \\
E_\infty &::= A \mid \langle A E_\infty \rangle \\
A &::= \text{QUOTE} \mid \text{SYM} \mid P \mid \langle ' A \rangle \mid \langle \$ A \rangle \mid \langle \langle \backslash B \rangle A \rangle \mid \epsilon \\
B &::= \$ \mid \langle \backslash B \rangle \mid \epsilon \\
P &::= (E) \mid \{E\} \mid [E] \\
E_p &::= \langle \langle E_\ell \text{CONN}_p \rangle E_r \rangle \quad p \in \mathcal{R}, \ell > p, r \geq p \\
E_p &::= \langle \langle E_\ell \text{CONN}_p \rangle E_r \rangle \quad p \in \mathcal{L}, \ell \geq p, r > p
\end{aligned}$$

Figure 2: **The grammar defining the MetaC reader.** The nonterminal SYM generates symbol atoms;  $\text{CONN}_p$  generates connective atoms of precedence  $p$ ; and QUOTE generates string quotation atoms. The reader is defined by a deterministic left-to-right shift-reduce parser in which the  $\epsilon$ -productions for  $A$  and  $B$  are selected only when no other option is available. The nonterminal  $E_\infty$  generates “arguments” — expressions not containing connectives outside of parentheses. The nonterminal  $E_p$  generates expressions whose root connective has priority  $p$  (and whose internal connectives have priority at least  $p$ ).  $\mathcal{R}$  is the set of right-associative precedence levels and  $\mathcal{L}$  is the set of left-associative levels. Generated cells of the form  $\langle w \epsilon \rangle$  or  $\langle \epsilon w \rangle$  are replaced by  $w$  with the exception that every binary operation must have a (possibly null) syntax node for each of its two arguments. Having two arguments for all occurrences of binary operations simplifies pattern matching.

Unfortunately this evaluation rule for backquote expressions is incomplete. One of the most confusing situations is where the expansion of a macro contains a backquote. Writing such a macro typically involves nested backquotes. While nested backquotes are confusing, and should be avoided when possible, MetaC supports nested backquotes. We consider a series of backquote expressions each of which evaluates to the previous one.

First we have

$$\text{'}\{a + b + \$\{z\}\}\text{'}$$
 (1)

If the value of variable  $z$  is the expression  $c$  then the value of expression (1) is the expression  $a+b+c$ . The symbol  $\$$  can be included in the value of a backquote expression by quoting it. This gives our second expression.

$$\text{'}\{\text{'}\{a + \$\{y\} + \backslash \$\{z\}\}\text{'}\}\text{'}$$
 (2)

If the value of variable  $y$  is the expression  $b$  then the value expression of (2) is expression (1). We can even have multiple layers of quotation as in the following.

$$\text{'}\{\text{'}\{\text{'}\{\backslash \$\{x\} + \backslash \$\{y\} + \backslash \backslash \$\{z\}\}\text{'}\}\text{'}\}\text{'}$$
 (3)

If the value of variable  $x$  is the expression  $a$  then the value of expression (3) is expression (2).

As with backquote, pattern matching is defined in terms of the cons-car-cdr view of expressions independent of the MetaC reader. We define a substitution to be a mapping from symbol atoms to expressions. For a substitution  $\sigma$  and a pattern  $\{e\}$  we define the expression  $\sigma(e)$  to be the result of replacing each subexpression (subtree) of  $e$  of the form  $\langle \$ x \rangle$  where  $x$  is a symbol atom with  $\sigma(x)$ . A pattern expression (tree)  $\{e\}$  matches an expression (tree)  $w$  with substitution  $\sigma$  if  $\sigma(e) = w$ . An exception to this is the case where a variable occurs multiple times in the pattern. In release 1.0 multiple occurrences of a variable in a pattern is not supported.

## 4 List of MetaC Primitives

We now give a list of the MetaC primitives and pre-installed type definitions. The macros backquote, ucase, and umacro expand to code built on these primitives. We start with type definitions needed for the single atom type restriction needed for the limiting type parsing abilities of MetaC.

```
typedef char * charptr;
typedef void * voidptr;
typedef FILE * FILEptr;
typedef struct expstruct{...} * expptr;
```

## 4.1 Expressions

The macros `backquote` and `ucase` expand into C code using these procedures.

```
expptr string_atom(charptr s);

int atomp(expptr e);

charptr atom_string(expptr a);

expptr cons(expptr x, expptr y);

int cellp(expptr e);

expptr car(expptr x);

expptr cdr(expptr x);

expptr intern_paren(char openchar, expptr arg); \\ openchar must be one of '(', '{' or '['.

int parenp(expptr e);

expptr paren_inside(expptr e);

char constructor(expptr e); //used for paren expressions.
```

We also have integer-expression conversions. The REPL and NIDE require that inputs and cells respectively are expression-valued.

```
expptr int_exp(int i);

int exp_int(expptr s);
```

## 4.2 Properties

The macro `umacro` expands to code that sets the macro property of some atom to a procedure pointer.

```
void setprop(expptr e, expptr key, voidptr val);

expptr getprop(expptr e, expptr key, expptr defaultval);

expptr gensym(charptr s);
```



### 4.3 Errors and Breakpoints

```
void berror(charptr s);

void breakpt(charptr s);

void NIDE();
```

### 4.4 Reading and Printing

The procedure `file_expressions` takes a file name and returns a list of the expressions (in universal syntax) contained in the cells of the file. The procedures `pprint` and `mcpprint` and the macro `mcprint` print to the emacs `*Messages*` buffer in the NIDE.

```
expptr file_expressions(charptr name);

void pprint(expptr e, FILEptr f, int indent); //indent is typically 0

void mcpprint(expptr e);

void mcprint(...)
```

### 4.5 Macro Expansion

```
expptr macroexpand(expptr e);

expptr macroexpand1(expptr e); //this result may contain unexpanded macros

void add_init_form(expptr statement);

void add_preamble(expptr aux_definition);
```

### 4.6 List Processing

In Lisp lists are terminated with the special value `nil`. In MetaC lists any atom in the `cdr` of a cell is treated as `nil`.

```
expptr nil();

expptr append(expptr l1, expptr l2);
```

```

expptr reverse(expptr l);

typedef expptr exp_to_exp(expptr);
typedef void exp_to_void(expptr);

expptr mapcar(exp_to_exp f, expptr l);

void mapc(exp_to_void f, expptr l);

int length(expptr l);

```

## 4.7 Memory Frames

```

in_memory_frame(<statement>)

voidptr stack_alloc(int nbytes);

```

## 4.8 Undo Frames

```

void exp_from_undo_frame(<expression>);

voidptr undo_alloc(int nbytes);

void undo_set(voidptr loc, voidptr val);

void clean_undo_frame(expptr e);

```

## 4.9 Bootstrapping and File Expansion

```

file_expressions(char * fname);

mcexpand(char * fname1, char * fname2);

init_fun(fname)

```

## References

- [1] A. Bawden. Quasiquotation in lisp. In *Proceedings of the 1999 ACM SIG-PLAN Workshop on Partial Evaluation and Semantics-Based Program Ma-*

*nipulation, San Antonio, Texas, USA, January 22-23, 1999. Technical report  
BRICS-NS-99-1, pages 4–12, 1999.*