

In Catilinam IV [★]

Marcus Tullius Cicero ^a, Julius Caesar ^b, Publius Maro Vergilius ^c

^a*Buckingham Palace, Paestum*

^b*Senate House, Rome*

^c*The White House, Baiae*

Abstract

Cum M. Cicero consul Nonis Decembribus senatum in aede Iovis Statoris consuleret, quid de iis coniurationis Catilinae sociis fieri placeret, qui in custodiam traditi essent, factum est, ut duae potissimum sententiae proponerentur, una D. Silani consulis designati, qui morte multandos illos censebat, altera C. Caesaris, qui illos publicatis bonis per municipia Italiae distribuendos ac vinculis sempiternis tenendos existimabat.

Key words: Cicero; Catiline; orations.

1 Introduction

Video, patres conscripti, in me omnium vestrum ora atque oculos esse conversos, video vos non solum de vestro ac rei publicae, verum etiam, si id depulsum sit, de meo periculo esse sollicitos. Est mihi iucunda in malis et grata in dolore vestra erga me voluntas, sed eam, per deos immortales, deponite atque obliti salutis meae de vobis ac de vestris liberis cogitate. Mihi si haec condicio consulatus data est, ut omnis acerbitates, onunis dolores cruciatusque perferrem, feram non solum fortiter, verum etiam lubenter, dum modo meis laboribus vobis populoque Romano dignitas salusque pariat.

2 Work

2.1 The System Model

Let $x \in \mathbb{R}^{n \times 1}$, $y \in \mathbb{R}^{p \times 1}$ and $w \in \mathbb{R}^{r \times 1}$ be the state, measurement, exogenous vectors, respectively, the SIMO/MIMO LTI system addressed in this paper is stated as,

$$\dot{x} = Ax + B_w w + B_u u, y = Cx + D_w w \quad (1)$$

[★] This paper was not presented at any IFAC meeting. Corresponding author M. T. Cicero. Tel. +XXXIX-VI-mmmxxi. Fax +XXXIX-VI-mmmxxv.

Email addresses: `cicero@senate.ir` (Marcus Tullius Cicero), `julius@caesar.ir` (Julius Caesar), `vergilius@culture.ir` (Publius Maro Vergilius).

where $A \in \mathbb{R}^{n \times n}$, $B_w \in \mathbb{R}^{n \times r}$, $C \in \mathbb{R}^{p \times n}$ and $D_w \in \mathbb{R}^{p \times r}$. The following additional rank condition

$$\text{rank}(C) = r < p \quad (2)$$

arises in sparse sensor applications[3], topologies used in Multi Agen Systems(MAS)[2] and distributed networks [5], and is also called Strictly Output Redundant(SOR) system [4]. Here, the system output is overdetermined, therefore,

$$\dim \mathcal{N}(C^T) = p - r \geq 1 \quad (3)$$

or using orthogonality $C^T C^\perp = 0$,

$$\dim \mathcal{N}(C^\perp) = p - r \geq 1 \quad (4)$$

which ensures nontrivial orthogonal component in the output space.

2.2 The Observer Models

The classical Luenberger Observer is defined as,

$$\dot{\hat{x}} = A\hat{x} + B_u u + L(y - \hat{y}), \hat{y} = C\hat{x} \quad (5)$$

where $L \in \mathbb{R}^{n \times p}$ is the observer gain. Assuming (A, C) -pair observable, the error dynamics are obtained for the error $e \triangleq x - \hat{x}$ as,

$$\dot{e} = (A - LC)e + (B_w - D_w L)w \quad (6)$$

The \mathbb{H}_∞ optimal observer for objective function $z = C_z e$ is designed using the following LMI problem[1],

$$\begin{aligned} \min_Y (\gamma) \quad \text{s.t.} \\ \begin{bmatrix} (PA - YC) + (PA - YC)^T & PB_w - YD_w & C_z^T \\ \star & -\gamma I & 0 \\ \star & 0 & -\gamma I \end{bmatrix} \prec 0 \\ P \succ 0 \end{aligned}$$

where the observer gain is recovered with $L = P^{-1}Y$.

2.3 The Projection

The projection defined using Gauge-Invariance principle is "proposed" as follows,

$$\Pi \triangleq I - C(C^T C)^{-1} C^T \quad (7)$$

where the following properties are satisfied,

$$\begin{aligned} \Pi C &= (I - C(C^T C)^{-1} C^T) C = 0 \\ \Pi C^\perp &= (I - C(C^T C)^{-1} C^T) C^\perp = C^\perp, \quad C^T C^\perp = 0 \\ \Pi^2 &= \Pi, \quad \Pi \in \mathbb{R}^{p \times p} \end{aligned} \quad (8)$$

Using the projection on the measured output gives,

$$\Pi y = \Pi(Cx + D_w w) = \Pi D_w w \quad (9)$$

The projection eliminates the state dependency and utilizing

$$D_w w = C\alpha + C^\perp \beta \quad (10)$$

the projection gives,

$$\Pi y = \Pi C\alpha + \Pi C^\perp \beta = C^\perp \beta \quad (11)$$

which is the orthogonal component.

2.4 The GI-Luenberger Observer

The classical Luenberger observer is fed with this orthogonal component forming the GI-Luenberger observer, the observer expression becomes,

$$\dot{\hat{x}} = A\hat{x} + B_u u + L(y - \hat{y}) + \Lambda \Pi y, \quad \hat{y} = C\hat{x} + \Pi y \quad (12)$$

where $\Lambda \in \mathbb{R}^{n \times p}$ and the error dynamics are obtained as,

$$\dot{e} = (A - LC)e + (B_w - LD_w)w - (L - \Lambda)\Pi y \quad (13)$$

or,

$$\begin{aligned} \dot{e} &= (A - LC)e + (B_w - LD_w)w - (L - \Lambda)\Pi D_w w \\ &= (A - LC)e + (B_w + (-L - L\Pi + \Lambda\Pi)D_w)w \end{aligned} \quad (14)$$

3 Numerical Example

3.1 Example 1

References

- [1] Guang-Ren Duan and Hai-Hua Yu. *LMIs in control systems: analysis, design and applications*. CRC press, 2013.
- [2] Reza Olfati-Saber, J Alex Fax, and Richard M Murray. Consensus and cooperation in networked multi-agent systems. *Proceedings of the IEEE*, 95(1):215–233, 2007.
- [3] Yasser Shoukry and Paulo Tabuada. Event-triggered state observers for sparse sensor noise/attacks. *IEEE Transactions on Automatic Control*, 61(8):2079–2091, 2015.
- [4] Guitao Yang, Alexander J Gallo, Angelo Barboni, Riccardo MG Ferrari, Andrea Serrani, and Thomas Parisini. On the output redundancy of lti systems: A geometric approach with application to privacy. *IEEE Transactions on Automatic Control*, 2025.
- [5] Guitao Yang, Hamed Rezaee, Andrea Serrani, and Thomas Parisini. Sensor fault-tolerant state estimation by networks of distributed observers. *IEEE Transactions on Automatic Control*, 67(10):5348–5360, 2022.

A A summary of Latin grammar

B Some Latin vocabulary