

Checks and build acceptance

Read this before ordering full production or planning a flight.

Recorded digital checks

Check	Result
Plywood	22 profiles / 31 pieces; mirrored quantities and revised joints checked.
DXF	66 delivered DXFs checked for millimetre units and file validity.
Printed parts	11 aircraft meshes plus coupon: closed, connected and manifold. Maximum mesh/CAD volume difference 0.052%.
Foam development	33 patterns / 35 blanks. Maximum sampled edge strain 0.367%; seam mismatch 0.027 mm. Physical forming is still required.
Paper templates	Scale, registration and part placement checked. 7 plywood pages, 23 foam pages, 2 tooling pages.

Manufacturing Team

Measure stock; run slot, printer and foam coupons. Dry-fit all parts together. Check bonded joints, wing retention, gear deflection and moving clearances. Record completed masses and any fitting work.

Electronics Team

Identify exact connectors and servo ratings. Verify loaded supply voltage, controls, sensors, range and failsafes. Measure propulsion current, thrust and temperature. Check final mass and balance.

Before flight

The 522 mm aft-nose mark is a provisional geometric reference, not an approved flight CG range. The 9-inch propeller / 40 A ESC combination remains unqualified. Have an experienced fixed-wing pilot review the completed aircraft and its test results.