

HW# 5 - Nick McCullough

March 9, 2022

Problem 8.22

```
clear,clc

% Nick McCullough, AerE 161, HW 5, Problem 8.22
% create variables for different values, rows and columns, from the vector
% of "quizstuff" then using that info, print the student ID number and the
% corresponding average score of each quiz. (use mean function)

- - - (insert your solution here)

% let's start by storing the quiz data in a data file called quizstuff
% quizstuff = [44 7 7.5 8;33 5.5 6 6.5;37 8 8 8;24 6 7 8];

load quizstuff.dat % load data file quizstuff above

[x,y] = size(quizstuff); % rows (x) & columns (y)
for i = 1:x % create the for statement for rows, x
    % create the variable i from title 'students' as shown in instructions
    % the "id_no" is the first column in the table, (i,1)
    students(i).id_no = quizstuff(i,1); % assign the id_no variable
    for j = 2:y % nested loop
        students(i).quiz(j-1) = quizstuff(i,j);
        % this loop creates the quiz variable, y is the columns from quizstuff
    end % end nested loop
end % end loop

% now we have to create the print statement for the quiz averages.
% we can use the mean function to accomplish this if we identify correctly

disp('Student ID #   Average Score') % simple display statement
for i = 1:x % create another for loop
    fprintf('%d \t\t %.1f\n',students(i).id_no,mean(students(i).quiz))
    % prints id# & avg/mean of the students quiz to 1 decimal place
```

HW# 5 - Nick McCullough

March 9, 2022

end % end loop

Output 1:

-----(*insert output (your results) here*)

Student ID #	Average Score
--------------	---------------

44	7.5
----	-----

33	6.0
----	-----

37	8.0
----	-----

24	7.0
----	-----

>>

Problem 9.10

clear,clc

% Nick McCullough, AerE 161, HW 5, problem 9.10

% prompt the user to enter the correct file name if they don't then use a

% loop to error-check until that user enters the right name.

- - - (*insert your solution here*)

file = input('Hello, please enter the file name: ','s'); % input for script

x = fopen(file); % opens file, "file"

while x == -1 % while loop and variable created if doesn't open

file = input('Error, please enter the correct file name: ','s');

end

Output 1:

-----(*insert output (your results) here*)

Hello, please enter the file name: fourty

March 9, 2022

Error, please enter the correct file name: Problem1

How much fuel, in US Gallons, is on board the airplane?:

% it opened my problem 1 file from Project 1 ^

Problem 9.11

% Nick McCullough, AerE 161, HW 5, problem 9.11

% file "potfilenames.dat" stores file names. one per line

% write a script that prints the names of the valid files, once .dat is

% added, valid just means the file exists.

- - - *-(insert your solution here)*

% potfilenames.dat is:

% Hello (Hello.dat)

% This (This.dat)

% Is (Is.dat)

% Nick (Nick.dat)

I did not finish this problem, I couldn't figure out how to open multiple data files or create a loop that prints if it works. I started with an if statement and creating variables for the file name but wasn't sure where to go after getting the file x.

Output 1:

-----*-(insert output (your results) here)*

HW# 5 - Nick McCullough

March 9, 2022

```
x = fopen('potfilenames.dat'); % variable that opens the file
if x == -1 % if statement in case it doesn't open correctly
    disp('Error, file did not open correctly') % disp error
else % else statement
    y = 0; % create variable for 0
    file = fgetl(x); % create variable for the file name

???
```