



Simulation of neutron guides using McStas

ISIS McStas School 2025



Mads Bertelsen
Data Management and Software Centre
European Spallation Source

2025-11-03

1. A beam in free space
2. Neutron mirrors
3. Guides
4. Designing guides
5. Simulation
6. Workflow



Introduction

Beam and its propagation





Introduction

Beam and its propagation





Introduction

Beam and its propagation





Introduction

Beam and its propagation




Introduction

Neutron mirrors




Introduction

Neutron super-mirrors




Ti as spacing for high contrast




Introduction

Neutron super-mirrors



Ti as spacing for high contrast




Introduction

Neutron super-mirrors




$$R(q) = \begin{cases} R_0 & \text{if } q < q_c \\ R_0(1 - \tanh((q - mq_c)/W))(1 - \alpha(q - q_c))/2 & \text{otherwise} \end{cases}$$

McStas standard model



McStas fitted model



$\alpha = 0$
 $W = 0$
Only m
matters
Better mirrors
available
today


Introduction

Neutron guide

Neutron source

Guide

Destination




Introduction

Guide placement in McStas



The center is the front of the guide element

Tip: Insert a guide at the end of the guide




Introduction

Gravity in McStas

- Enabled by adding `-g / --gravitation` on command line or by selecting "Gravity On" in mcgui
- Default ~ gravity on earth



```
#define GRAVITY 9.81 /* [m/s^2] gravitational acceleration */
```


(If on the moon, use `-DGRAVITY=1.62 ;-`)
- For guides, only `Guide_gravity` and `Elliptic_guide_gravity` support parabolic propagation. (Many others propagate linearly in *v direction*.)
- As you will see in the practical, implications are greatest with long wavelengths and at long distances
- "How about e.g. elliptic mirror optic X that does not support gravity?"
 - often a good workaround is to add a monitor close to the surface of object X, this takes care that propagation up to the monitor includes gravitation:
 - Gravity is enabled in any call to `PROP_DT`, `PROP_Z0` etc., but not in `intersect_*` routines (most monitors use `PROP_Z0` directly, no `intersect_*` call first)
 - OK to propagate without gravitation e.g. within sample, through velocity selector etc. / range of ~cm's



Introduction

Neutron guide in phase-space




Introduction

Phase-space theory



- Phase-space properties
 - Often 3D $\rightarrow$ 2 x 2D
 - Propagation (no paths crossing)
 - Liouville's theorem
 - phase-space density can not be increased
- Brilliance transfer
- Losses from:
 - Reflectivity less than 1
 - Not full coverage of phase-space




Introduction

Phase-space theory

- Phase-space properties
 - Often 3D -> 2 x 2D
 - Propagation (no paths crossing)
 - Liouville's theorem
 - phase-space density can not be increased

$$\frac{d\rho}{dt} \leq 0$$

- Brilliance transfer $\mathcal{B} = \frac{\rho_2}{\rho_1}$
- Losses from:
 - Reflectivity less than 1
 - Not full coverage of phase-space




Introduction

Phase-space theory

- Phase-space properties
 - Often 3D -> 2 x 2D
 - Propagation (no paths crossing)
 - Liouville's theorem
 - phase-space density can not be increased

$$\frac{d\rho}{dt} \leq 0$$

- Brilliance transfer $\mathcal{B} = \frac{\rho_2}{\rho_1}$
- Losses from:
 - Reflectivity less than 1
 - Not full coverage of phase-space




Introduction

Define the problem of guide design



- Source
 - Dimensions
- Space constraints
 - Source to optics
 - Optics to destination
- Desired beam
 - Dimensions
 - Divergence
 - Wavelength interval
 - Distance from source
- At least 11 important parameters




In addition:

- Constraints for width and height
- Required gaps for equipment
- Breaking line of sight to reduce background

Introduction

Overall problem


- Not solved
- No solution map from requirements to guide design
- Recommendation map, maybe
- Need to evaluate different possible solutions and compare



Introduction

Overall problem

- Not solved
- No solution map from requirements to guide design
- Recommendation map, maybe
- Need to evaluate different possible solutions and compare



Focusing case: $WM/L_M \geq 2\phi S$


Non-focusing case: $WM/L_M \geq 2\phi(S + 2L_S \tan(\phi))$

W : Guide size M : Moderator size L_M : Guide moderator distance
 ϕ : Divergence requirement S : Sample size L_S : Sample distance

Simulation


Evaluate a design

- Monte Carlo ray-tracing for evaluating performance
- Propagate many rays through optical system




Simulation

Evaluate a design




- Monte Carlo ray-tracing for evaluating performance
- Propagate many rays through optical system
- McStas has large library of components
- Community project, components contributed




Simulation

Popular components: Guide_gravity




Important guide component with gravity, parameter-interface similar to e.g. Guide.comp

Many additional features, channels, fermi chopper, ... (see mcdoc pages for more info)




Simulation

Popular components: Guide_gravity




Important guide component with gravity, parameter-interface similar to e.g. Guide.comp
Many additional features, channels, fermi chopper, ... (see mcdoc pages for more info)




Simulation

Popular components: Elliptical_guide_gravity



Useful for elliptic and parabolic guide geometries, focusing, ballistic, coating distribution, ...


xwidth and yheight at DimensionsAt = "entrance", "mid" or "exit"




Simulation

Breaking line of sight

Bender / Guide_curved component or many straight sections





Solutions / Philosophies / Paradigms




Traditional guides

- Rectangular cross section
- Sensitive to distance to sample
- Handles low divergence well

$3 \times 3 \text{ cm}^2$
 $\pm 0.75^\circ \text{ H}$
 $\pm 1.20^\circ \text{ V}$








Solutions / Philosophies / Paradigms




Traditional guides

- Rectangular cross section
- Sensitive to distance to sample
- Handles low divergence well
- Curve out of line of sight

$3 \times 3 \text{ cm}^2$
 $\pm 0.75^\circ \text{ H}$
 $\pm 1.20^\circ \text{ V}$




Solutions / Philosophies / Paradigms




Traditional guides

- Rectangular cross section
- Sensitive to distance to sample
- Handles low divergence well
- Curve out of line of sight
- Can be tapered - artifacts








Solutions / Philosophies / Paradigms




Ballistic guides

- Increase and decrease rectangular cross section
 - Reduce divergence for transport
 - Increase divergence for delivery
- Sensitive to distance to sample
- Handles larger divergence

$3 \times 3 \text{ cm}^2$
 $\pm 0.75^\circ \text{ H}$
 $\pm 1.20^\circ \text{ V}$








Solutions / Philosophies / Paradigms




Ballistic guides

- Increase and decrease rectangular cross section
 - Reduce divergence for transport
 - Increase divergence for delivery
- Sensitive to distance to sample
- Handles larger divergence
- Can be curved

$3 \times 3 \text{ cm}^2$
 $\pm 0.75^\circ \text{ H}$
 $\pm 1.20^\circ \text{ V}$








Solutions / Philosophies / Paradigms



Selene – Montel optics


- Focusing design
- Allows large distance to sample
- Point to point, scalable, analytical calculation
- Required coating calculated
- Provides control over beam
- Limits:
 - Gravity
 - Beamsize – length connection

$4 \times 4 \text{ mm}^2$
 $\pm 0.25^\circ \text{ H}$
 $\pm 0.25^\circ \text{ V}$



J. Stahn, T. Panzner, U. Filges, C. Marcelot, P. Böni
Study on a focusing, low-background neutron delivery system
NIMA, **2011**, Volume 634, page S12-S16






Solutions / Philosophies / Paradigms



Wolter optics

- Focusing design
- Allows large distance to sample
- Different kinds:
 - Point to point
 - Parallel beam to point
- Provides control over beam
- Limits
 - Gravity
 - Coating
 - Beamsize

$5 \times 5 \text{ mm}^2$
 $\pm 0.5^\circ \text{ H}$
 $\pm 0.8^\circ \text{ V}$






Simulation code by: Giacomo Resta

Dazhi Liu, Boris Khaykovich, Mikhail V. Gubarev, J. Lee Robertson, Lowell Crow, Brian D. Ramsey & David E. Moncton, Demonstration of a novel focusing small-angle neutron scattering instrument equipped with axisymmetric mirrors
Nature Communications 4, **2013**, Article number 2556


Solutions / Philosophies / Paradigms

Nested Mirror Optics


- Hybrid, focusing at either end
- Simulations here by Christoph Herb
- Contributed McStas component



including gravity



Solutions / Philosophies / Paradigms



Minimalist principle



- Calculate the required phase-space volume
 - Needed on sample + expected losses from gaps
- Only allow the guide to take in that amount of phase-space

Focusing case

$$WM/L_M = 2\phi S$$

Non-focusing case

$$WM/L_M = 2\phi(S + 2L_S \tan(\phi))$$



Solutions / Philosophies / Paradigms


ORNL

- Shape developed by Ducu Stoica
- 3 Conditions
 - Direct line of sight
 - One reflection
 - No origins outside moderator

MATH* 

$$\left(\frac{y}{x} - \frac{\theta_0}{\beta} \right) x^\beta = c$$

Discover guide - horizontal




Every trajectory coming from the sample has to end on the moderator surface!

* Frost, M. J.; Stoica, A. D.; Huegle, T. A First-Principles Approach to the Optimization of Neutron-Focusing Guide Design and Development. *Journal of Neutron Research* **2019**, 20 (4), 131–135.

Designing a guide


Workflow

Low brilliance transfer
Iterate task description



Guide simulation

Exercise



- Start from one of the two examples:
 - **Exercise_guides.instr** *Simpler instrument, easy to start with*
 - **Guide_BT_template.instr** *More advanced, has normalization to brilliance transfer*
- Main task: Explore how the guide parameters and geometry impact the results
- Extra tasks:
 - Scan guide length
 - Introduce a gap by using two guide components
 - Use Guide_gravity and extend to 100 m length
 - Investigate the effect of gravity on the transport of long-wavelength neutrons



Thanks for your attention

mads.bertelsen@ess.eu