Common Emacs Commands

`C-a` .... Beginning of line
`C-d` .... End of line
`C-K` .... Kill line
`C-_` .... Undo

`C-x 2` .... Split the window into two
`C-x 1` .... Go back to one window mode
`C-x ^` .... Enlarge window

`Alt-x shell`........ Run the shell in the current window
`Alt-x goto-line`..... Goto a given line

`C-x C-c` .... Save buffer and kill Emacs
`C-x C-s` .... Save buffer

`C-space` .... Set mark
`C-W` .... Cut from the cursor to the mark
`Alt-W` .... Copy from the cursor to the mark
`C-y` .... Paste

Common Linux Commands

`cd` .... Change Directory
`clear` .... Clear terminal screen
`dir` .... Briefly list directory contents
`echo` .... Display message on screen
`exit` .... Exit the shell
`fgrep` .... Search file for lines that match a string
`kill` .... Stop a process from running
`lprint` .... Print a file
`ls` .... List information about file(s)
`ll` .... More verbose version of ls
`man` .... Review the help page of a given command
`mkdir` .... Create new folder(s)
`more` .... Display output one screen at a time
`mv` .... Move or rename files or directories
`passwd` .... Modify a user password
`ps` .... Process status
`pwd` .... Print Working Directory
`rm` .... Remove files
`rmdir` .... Remove folder(s)

`emacs` .... Common code editor
`vi` .... More primitive but ubiquitous editor
`nano` .... Another editor

`g++` .... Compile a C++ program

`sc` .... Run the style checker on a file
`bed` .... Run the test bed on a file
`submit` .... Turn in a file as specified by the program header