

# The Indian Buffet Process

Eli Bingham<sup>1</sup>    Matt Dickenson<sup>2</sup>

<sup>1</sup>University of North Carolina

<sup>2</sup>Duke University

February 10, 2014

- ➊ Introduction
- ➋ Dirichlet and Chinese Restaurant Processes
- ➌ Beta and Indian Buffet Processes
- ➍ Gibbs sampling
- ➎ Demonstration/Visualization
- ➏ Applications: Choice Behavior and Collaborative Filtering
- ➐ Extensions: Topic Models and Cascading IBP
- ➑ Discussion

# Introduction

Indian Buffet Process:

- 1  $N$  customers enter (in sequence) a buffet restaurant with an infinite number of dishes
- 2 First customer fills her plate with  $\text{Poisson}(\alpha)$  number of dishes
- 3  $i^{\text{th}}$  customer samples dishes in proportion to their popularity, with probability  $\frac{m_k}{i}$ , where  $m_k$  is the number of previous customers who sampled dish  $k$
- 4  $i^{\text{th}}$  customer then samples a  $\text{Poisson}(\frac{\alpha}{i})$  number of new dishes




Figure: Griffiths and Ghahramani (2011) Figure 5

# Background: Dirichlet Process

Finite version (Dirichlet distribution):

- Assignment of an object to a class is independent of all other assignments:  $P(c|\theta) = \prod_{i=1}^N P(c_i|\theta) = \prod_{i=1}^N \theta_{c_i}$
- $\theta|\alpha \sim \text{Dirichlet}(\frac{\alpha}{K}, \dots, \frac{\alpha}{K})$  (if symmetric)
- $c_i|\theta \sim \text{Discrete}(\theta)$ , where Discrete : Bernoulli :: Multinomial : Binomial

Integrating out  $\theta$ :  $P(c) = \frac{\prod_{k=1}^K \Gamma(m_k + \frac{\alpha}{K})}{\Gamma(\frac{\alpha}{K})^K} \frac{\Gamma(\alpha)}{\Gamma(N + \alpha)}$

What happens as  $K \rightarrow \infty$ ? We get the Dirichlet process.




Figure: Griffiths and Ghahramani (2011) Figure 1

# Background: Chinese Restaurant Process

- 1  $N$  customers enter (in sequence) a restaurant with an infinite number of tables, each with infinite seating
- 2 First customer sits at first table with probability  $\frac{\alpha}{\alpha} = 1$
- 3  $i^{th}$  customer sits at the  $k^{th}$  table with probability  $\frac{m_k}{i+\alpha-1}$ , where  $m_k$  is the number of previous customers who sat at table  $k$




Figure: Griffiths and Ghahramani (2011) Figure 2

Limitation: each object (customer) can only belong to one class (table).

# Beta Process

# Indian Buffet Process

[mcdickenson.shinyapps.io/ibp-demo](http://mcdickenson.shinyapps.io/ibp-demo)



# Properties of the Resulting Distribution

- The “effective” dimension  $K_+ \sim \text{Poisson}(\alpha H_N)$
- The number of dishes on each customer’s plate is distributed  $\text{Poisson}(\alpha)$  (by exchangeability)
- $\mathbf{Z}$  remains sparse as  $K \rightarrow \infty$ : effective dimensions of  $\mathbf{Z}$  are  $N \times K_+$ , and the expected number of entries is  $N\alpha$

# Inference by Gibbs Sampling

# Application 1: Choice Behavior

## Application 2: Collaborative Filtering

# Extension 1: Topic Modeling

## Extension 2: Collaborative Filtering

# Extensions