

BLK0039-2 - SWEET HOME - PROFUMATORE AMBIENTE TALCO

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: BLK0039-2
Product name: SWEET HOME - PROFUMATORE AMBIENTE TALCO
UFI : 6Q0C-W3XS-XX0U-F315

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified Uses	Industrial	Professional	Consumer
Room deodorant	-	-	✓

Uses Advised Against

Do not use for uses other than those indicated

1.3. Details of the supplier of the safety data sheet

Name: Suarez Company
Full address: Via Pergolesi , 1 ang. Via Monteverdi
District and Country: 20811 Cesano Maderno
Italia
Tel. +39 0362 659766
www.suarezcompany.it

e-mail address of the competent person

responsible for the Safety Data Sheet: info@suarezcompany.it

1.4. Emergency telephone number

For urgent inquiries refer to: Suarez Company
+39 0362 659766
(8:30 - 12:30 13:30-17:30)

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 2	H225	Highly flammable liquid and vapour.
Eye irritation, category 2	H319	Causes serious eye irritation.
Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.

BLK0039-2 - SWEET HOME - PROFUMATORE AMBIENTE TALCO**2.2. Label elements**

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

EUH208 Contains: 7-HYDROXYCITRONELLAL, 2H-CHROMEN-2-ONE, benzyl salicylate
May produce an allergic reaction.

Precautionary
statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice / attention.

P501 Dispose of contents / container in accordance with current regulations.

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration $\geq$ 0.1%.

SECTION 3. Composition/information on ingredients**3.1. Substances**

Information not relevant

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
ETHANOL		
INDEX 603-002-00-5	$74 \leq x < 78$	Flam. Liq. 2 H225, Eye Irrit. 2 H319
EC 200-578-6		Eye Irrit. 2 H319: $\geq 50\%$
CAS 64-17-5		
REACH Reg. 01-2119457610-43		
benzyl salicylate		
INDEX 607-754-00-5	$0,7 \leq x < 0,8$	Eye Irrit. 2 H319, Skin Sens. 1B H317, Aquatic Chronic 3 H412
EC 204-262-9		
CAS 118-58-1		
REACH Reg. 01-2119969442-31		
galaxolide		
INDEX 603-212-00-7	$0,5 \leq x < 0,6$	Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1
EC 214-946-9		
CAS 1222-05-5		
REACH Reg. 01-2119488227-29		
2H-CHROMEN-2-ONE		
INDEX -	$0,4 \leq x < 0,45$	Acute Tox. 4 H302, Skin Sens. 1 H317, Aquatic Chronic 2 H411
EC 202-086-7		ATE Oral: 500 mg/kg
CAS 91-64-5		
REACH Reg. 01-2119943756-26		
2,6-di-tert-butyl-p-cresol		
INDEX -	$0,1 \leq x < 0,15$	Aquatic Chronic 1 H410 M=1
EC 204-881-4		
CAS 128-37-0		
REACH Reg. 01-2119565113-46		
7-HYDROXYCITRONELLAL		
INDEX -	$0,1 \leq x < 0,15$	Eye Irrit. 2 H319, Skin Sens. 1B H317
EC 203-518-7		
CAS 107-75-5		
REACH Reg. 01-2119973482-31		
toluene		
INDEX 601-021-00-3	$0 < x < 0,05$	Flam. Liq. 2 H225, Repr. 2 H361d, Asp. Tox. 1 H304, STOT RE 2 H373, Skin Irrit. 2 H315, STOT SE 3 H336
EC 203-625-9		
CAS 108-88-3		
REACH Reg. 01-2119471310-51-		
ACETONE		
INDEX 606-001-00-8	$0 < x < 0,05$	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066
EC 200-662-2		
CAS 67-64-1		
REACH Reg. 01-2119471330-49		

BLK0039-2 - SWEET HOME - PROFUMATORE AMBIENTE TALCO**METHANOL**

INDEX 603-001-00-X

0 < x < 0,05

Flam. Liq. 2 H225, Acute Tox. 3 H301, Acute Tox. 3 H311, Acute Tox. 3 H331, STOT SE 1 H370

EC 200-659-6

STOT SE 2 H371: ≥ 3% - < 10%

CAS 67-56-1

ATE Oral: 100 mg/kg, ATE Dermal: 300 mg/kg, ATE Inhalation vapours: 3 mg/l

REACH Reg. 01-2119433307-44

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures**4.1. Description of first aid measures**

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

If symptoms occur, whether acute or delayed, consult a doctor.

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures**5.1. Extinguishing media****SUITABLE EXTINGUISHING EQUIPMENT**

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

BLK0039-2 - SWEET HOME - PROFUMATORE AMBIENTE TALCO**5.2. Special hazards arising from the substance or mixture****HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters**GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage**7.1. Precautions for safe handling**

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated

Suarez Company	Revision nr. 1
	Dated 05/12/2024
BLK0039-2 - SWEET HOME - PROFUMATORE AMBIENTE TALCO	First compilation
	Printed on 06/12/2024
	6/25

place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

Storage class TRGS 510 (Germany):
3

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
CZE	Česká Republika	NAŘÍZENÍ VLÁDY ze dne 10. května 2021, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci
DEU	Deutschland	Forschungsgemeinschaft MAK- und BAT-Werte-Liste 2022 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe Mitteilung 58
DNK	Danmark	Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019
ESP	España	Límites de exposición profesional para agentes químicos en España 2023
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en FranceDécret n° 2021-1849 du 28 décembre 2021
FIN	Suomi	HTP-VÄRDEN 2020. Koncentrationer som befunnits skadliga. SOCIAL - OCH HÄLSOVÄRDSMINISTERIETS PUBLIKATIONER 2020:25
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α' 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ ``σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιγόνους παράγοντες κατά την εργασία``»
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnimkemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NOR	Norge	Forskrift om endring i forskrift om tiltaksverdier og grenseverdier for fysiske og kjemiske faktorer i arbeidsmiljøet samt smitterisikogrupper for biologiske faktorer (forskrift om tiltaks- og grenseverdier), 21. august 2018 nr. 1255
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
PRT	Portugal	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006
SWE	Sverige	Hygieniska gränsvärden, Arbetsmiljöverkets föreskrifter och allmänna råd om hygieniska gränsvärden (AFS 2018:1)
SVK	Slovensko	NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénnym a mutagénnym faktorom pri práci v znení neskorších predpisov
SVN	Slovenija	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2023

ETHANOL				
Threshold Limit Value				
Type	Country	TWA/8h	STEL/15min	Remarks /

Suarez Company						Revision nr. 1			
BLK0039-2 - SWEET HOME - PROFUMATORE AMBIENTE TALCO						Dated 05/12/2024			
						First compilation			
						Printed on 06/12/2024			
						7/25			
Observations									
		mg/m3	ppm	mg/m3	ppm				
TLV	BGR	1000							
TLV	CZE	1000		3000					
AGW	DEU	960	500	1920	1000				
MAK	DEU	960	500	1920	1000				
TLV	DNK	1900	1000						
VLA	ESP			1910	1000				
VLEP	FRA	1900	1000	9500	5000				
HTP	FIN	1900	1000	2500	1300				
TLV	GRC	1900	1000						
AK	HUN	1900		7600					
GVI/KGVI	HRV	1900	1000						
TLV	NOR	950	500						
TGG	NLD	260		1900					
NDS/NDSch	POL	1900							
NGV/KGV	SWE	1000	500	1900	1000				
NPEL	SVK	960	500	1920					
WEL	GBR	1920	1000						
TLV-ACGIH				1884	1000				
Predicted no-effect concentration - PNEC									
Normal value in fresh water				0,96	mg/l				
Normal value in marine water				0,79	mg/l				
Normal value for fresh water sediment				3,6	mg/kg				
Normal value for marine water sediment				2,9	mg/kg				
Normal value for water, intermittent release				2,75	mg/l				
Normal value of STP microorganisms				580	mg/l				
Normal value for the food chain (secondary poisoning)				0,38	mg/kg				
Normal value for the terrestrial compartment				0,63	mg/kg				
Health - Derived no-effect level - DNEL / DMEL									
		Effects on consumers			Effects on workers				
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic	
Oral				87 mg/kg bw/d					
Inhalation				114 mg/m3				950 mg/m3	
Skin				206 mg/kg bw/d				343 mg/kg bw/d	
benzyl salicylate									
Predicted no-effect concentration - PNEC									
Normal value in fresh water				0,001	mg/l				
Normal value in marine water				0	mg/l				
Normal value for fresh water sediment				0,583	mg/kg				
Normal value for marine water sediment				0,058	mg/kg				
Normal value for water, intermittent release				0,01	mg/l				

Suarez Company					Revision nr. 1			
					Dated 05/12/2024			
					First compilation			
BLK0039-2 - SWEET HOME - PROFUMATORE AMBIENTE TALCO					Printed on 06/12/2024			
					8/25			
Normal value of STP microorganisms				10	mg/l			
Normal value for the food chain (secondary poisoning)				80	mg/kg			
Normal value for the terrestrial compartment				1,41	mg/kg			
Health - Derived no-effect level - DNEL / DMEL								
Effects on consumers				Effects on workers				
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				0,45 mg/kg bw/d				
Inhalation				0,78 mg/m3	3,17 mg/m3			
Skin				0,45 mg/kg bw/d	0,9 mg/kg bw/d			
galaxolide								
Predicted no-effect concentration - PNEC								
Normal value in fresh water				0,0044	mg/l			
Normal value in marine water				0,00044	mg/l			
Normal value for fresh water sediment				2	mg/kg/d			
Normal value for marine water sediment				0,394	mg/kg/d			
Normal value for water, intermittent release				0,03	mg/l			
Normal value of STP microorganisms				1	mg/l			
Normal value for the food chain (secondary poisoning)				3,3	mg/kg food			
Normal value for the terrestrial compartment				0,31	mg/kg/d			
Health - Derived no-effect level - DNEL / DMEL								
Effects on consumers				Effects on workers				
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				3,8 mg/kg bw/d				
Inhalation				6,5 mg/m3	22 mg/m3			
Skin				36 mg/kg bw/d	60 mg/kg bw/d			
2H-CHROMEN-2-ONE								
Predicted no-effect concentration - PNEC								
Normal value in fresh water				0,019	mg/l			
Normal value in marine water				0,0019	mg/l			
Normal value for fresh water sediment				0,15	mg/kg			
Normal value for marine water sediment				0,015	mg/kg			
Normal value for water, intermittent release				0,0142	mg/l			
Normal value of STP microorganisms				6,4	mg/l			
Normal value for the food chain (secondary poisoning)				30,7	mg/kg			
Normal value for the terrestrial compartment				0,018	mg/kg			
Health - Derived no-effect level - DNEL / DMEL								
Effects on consumers				Effects on workers				
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				0,39 mg/kg bw/d				
Inhalation				1,69 mg/m3	6,78 mg/m3			
Skin				0,39 mg/kg bw/d	0,79 mg/kg bw/d			

Suarez Company						Revision nr. 1		
BLK0039-2 - SWEET HOME - PROFUMATORE AMBIENTE TALCO						Dated 05/12/2024		
						First compilation		
						Printed on 06/12/2024		
						9/25		
2,6-di-tert-butyl-p-cresol								
Predicted no-effect concentration - PNEC								
Normal value in fresh water				0,000199		mg/l		
Normal value in marine water				0,02		µg/l		
Normal value for fresh water sediment				0,0996		mg/kg		
Normal value for marine water sediment				0,00996		mg/kg		
Normal value for water, intermittent release				0,00199		mg/l		
Normal value of STP microorganisms				0,17		mg/l		
Normal value for the food chain (secondary poisoning)				8,33		mg/kg		
Normal value for the terrestrial compartment				0,04769		mg/kg		
Health - Derived no-effect level - DNEL / DMEL								
Effects on consumers				Effects on workers				
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				0,25 mg/kg bw/d				
Inhalation				0,86 mg/m3				3,5 mg/m3
Skin				0,25 mg/kg bw/d				0,5 mg/kg bw/d
7-HYDROXYCITRONELLAL								
Predicted no-effect concentration - PNEC								
Normal value in fresh water				0,0316		mg/l		
Normal value in marine water				0,00316		mg/l		
Normal value for fresh water sediment				0,145		mg/kg		
Normal value for marine water sediment				0,015		mg/kg		
Normal value for water, intermittent release				0,316		mg/l		
Normal value of STP microorganisms				10		mg/l		
Normal value for the terrestrial compartment				0,011		mg/kg		
Health - Derived no-effect level - DNEL / DMEL								
Effects on consumers				Effects on workers				
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				0,6 mg/kg bw/d				
Inhalation	0,5			5,4 mg/m3				18 mg/m3
Skin	0,5 mg/cm2			1,1 mg/kg bw/d	0,5 mg/cm2		0,5	1,9 mg/kg bw/d
METHANOL								
Threshold Limit Value								
Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
TLV	BGR	50				SKIN		
TLV	CZE	250		1000		SKIN		
AGW	DEU	270	200	1080	800	SKIN		
MAK	DEU	270	200	1080	800	SKIN		
TLV	DNK	260	200					

Suarez Company						Revision nr. 1 Dated 05/12/2024 First compilation		
BLK0039-2 - SWEET HOME - PROFUMATORE AMBIENTE TALCO						Printed on 06/12/2024 10/25		
VLA	ESP	266	200	SKIN				
VLEP	FRA	260	200	1300	1000	SKIN		
HTP	FIN	270	200	330	250	SKIN		
TLV	GRC	260	200	325	250			
AK	HUN	260	1040					
GVI/KGVI	HRV	260	200	SKIN				
VLEP	ITA	260	200	SKIN				
TLV	NOR	130	100	SKIN				
TGG	NLD	133	100	SKIN				
VLE	PRT	260	200	SKIN				
NDS/NDSch	POL	100	300					
NGV/KGV	SWE	250	200	350	250	SKIN		
NPEL	SVK	260	200	SKIN				
WEL	GBR	266	200	333	250	SKIN		
OEL	EU	260	200	SKIN				
TLV-ACGIH		262	200	328	250			
Predicted no-effect concentration - PNEC								
Normal value in fresh water				20,8	mg/l			
Normal value in marine water				2,08	mg/l			
Normal value for fresh water sediment				77	mg/kg			
Normal value for marine water sediment				7,7	mg/kg			
Normal value for water, intermittent release				1540	mg/l			
Normal value of STP microorganisms				100	mg/l			
Normal value for the terrestrial compartment				100	mg/kg			
Health - Derived no-effect level - DNEL / DMEL								
	Effects on consumers			Effects on workers				
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		4 mg/kg bw/d		4 mg/kg bw/d				
Inhalation	26 mg/m3	26 mg/m3	26 mg/m3	26 mg/m3	130 mg/m3	130 mg/m3	130 mg/m3	130 mg/m3
Skin		4 mg/kg bw/d		4 mg/kg bw/d		20 mg/kg bw/d		20 mg/kg bw/d
ACETONE								
Threshold Limit Value								
Type	Country	TWA/8h	STEL/15min		Remarks / Observations			
		mg/m3	ppm	mg/m3	ppm			
TLV	BGR	600	1400					
TLV	CZE	800	331,2	1500	621			
AGW	DEU	1200	500	2400 (C)	1000 (C)			
MAK	DEU	1200	500	2400	1000			
TLV	DNK	600	250	E				
VLEP	FRA	1210	500	2420	1000			
HTP	FIN	1200	500	1500	630			
TLV	GRC	1780	3560					

Suarez Company						Revision nr. 1
BLK0039-2 - SWEET HOME - PROFUMATORE AMBIENTE TALCO						Dated 05/12/2024
						First compilation
						Printed on 06/12/2024
						11/25
AK	HUN	1210				
GVI/KGVI	HRV	1210	500			
VLEP	ITA	1210	500			
TLV	NOR	295	125			
TGG	NLD	1210	2420			
VLE	PRT	1210	500			
NDS/NDSch	POL	600	1800			
TLV	ROU	1210	500			
NGV/KGV	SWE	600	250	1200 (C)	500 (C)	
NPEL	SVK	1210	500			
MV	SVN	1210	500	2420	1000	
WEL	GBR	1210	500	3620	1500	
OEL	EU	1210	500			
TLV-ACGIH			250		500	
toluene						
Threshold Limit Value						
Type	Country	TWA/8h	STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	150		300		
TLV	CZE	200		500		SKIN
AGW	DEU	190	50	760	200	SKIN
MAK	DEU	190	50	760	200	
TLV	DNK	94	25			SKIN
VLA	ESP	192	50	384	100	SKIN
VLEP	FRA	76,8	20	384	100	SKIN
HTP	FIN	81	25	380	100	SKIN
TLV	GRC	192	50	384	100	
AK	HUN	190		760		
GVI/KGVI	HRV	192	50	384	100	SKIN
VLEP	ITA	192	50			SKIN
TLV	NOR	94	25			SKIN
TGG	NLD	150		384		
VLE	PRT	192	50	384	100	SKIN
NDS/NDSch	POL	100		200		
TLV	ROU	192	50	384	100	SKIN
NGV/KGV	SWE	192	50	384	100	SKIN
NPEL	SVK	192	50	384		SKIN
MV	SVN	192	50	384	100	SKIN
WEL	GBR	191	50	384	100	SKIN
OEL	EU	192	50	384	100	SKIN
TLV-ACGIH		75,4	20			
Predicted no-effect concentration - PNEC						

Normal value in fresh water	0,68	mg/l						
Normal value in marine water	0,68	mg/l						
Normal value for fresh water sediment	16,39	mg/kg/d						
Normal value for marine water sediment	16,39	mg/kg/d						
Normal value for water, intermittent release	0,68	mg/l						
Normal value of STP microorganisms	13,61	mg/l						
Normal value for the food chain (secondary poisoning)	2,89	mg/kg soil dw						
Health - Derived no-effect level - DNEL / DMEL								
	Effects on consumers	Effects on workers						
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				8,13 mg/kg bw/d				
Inhalation	226 mg/m3	226 mg/m3	56,5 mg/m3	56,5 mg/m3	384 mg/m3	384 mg/m3	192 mg/m3	192 mg/m3
Skin				226 mg/kg bw/d				384 mg/kg bw/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear

open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS
The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	Method:internal Temperature: 20 °C
Colour	light blue	Remark:Visual Temperature: 20 °C
Odour	characteristic	Method:internal
Odour threshold	18,8	Method:internal Remark:mg/m3 Substance:ETHANOL Temperature: 20 °C
Melting point / freezing point	-114 °C	Method:HSDB 2015; INRS 2011 Substance:ETHANOL
Initial boiling point	78,5 °C	Method:HSDB 2015; INRS 2011 Substance:ETHANOL Initial boiling point: 78 °C
Flammability	Easily flammable liquid and vapors.	Method:ISO 3679:2023
Lower explosive limit	3,3 % (v/v)	Method:internal Remark:INAIL, 2018 Substance:ETHANOL
Upper explosive limit	19 % (v/v)	Method:internal Remark:INAIL, 2018 Substance:ETHANOL
Flash point	18 °C	Method:ISO 3679:2023
Auto-ignition temperature	363 °C	Method:internal Remark:1013 hPa Substance:ETHANOL
Decomposition temperature	not available	Reason for missing data:It only applies to authoritative substances and mixtures, organic peroxides and other substances and mixtures that they can decompose
pH	not available	Reason for missing data:not determined
Kinematic viscosity	not available	Reason for missing data:not determined
Solubility	soluble in water	Method:internal Temperature: 20 °C
Partition coefficient: n-octanol/water	-0,35	Method:internal Substance:ETHANOL Temperature: 20 °C
Vapour pressure	5,9 kPa	Method:INRS, 2011

Substance:ETHANOL
Vapour pressure: 45 mmHg
Temperature: 20 °C

Method:HSDB, 2015; INRS, 2011
Remark:(aria=1) HSDB, 2015; INRS, 2011
Substance:ETHANOL

Density and/or relative density not available
Relative vapour density 1,6

Particle characteristics
Median equivalent diameter
Remark: It only applies to solids
Size distribution
Remark: It only applies to solids
Dustiness
Remark: It only applies to solids
Specific surface area
Remark: It only applies to solids
Shape
Remark: It only applies to solids

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Explosive properties	not available	Reason for missing data:Absent chemical groups associated with explosive properties in accordance with the provisions of Annex I, Part 2, chap. 2.1.4.3 of Reg. (EC) 1272/2008 - CLP
Oxidising properties	not available	Reason for missing data:Absent requirements related to the presence of atoms or chemical bonds associated with oxidizing properties in the molecules of the components according to Annex I, Part 2, 2.13.4 Reg. (CE) 1272/2008

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

ACETONE

Decomposes under the effect of heat.

toluene

Avoid exposure to: light.

Suarez Company		Revision nr. 1
		Dated 05/12/2024
		First compilation
BLK0039-2 - SWEET HOME - PROFUMATORE AMBIENTE TALCO		Printed on 06/12/2024
		15/25
10.2. Chemical stability		
The product is stable in normal conditions of use and storage.		
10.3. Possibility of hazardous reactions		
The vapours may also form explosive mixtures with the air.		
ETHANOL		
Risk of explosion on contact with: alkaline metals,alkaline oxides,calcium hypochlorite,sulphur monofluoride,acetic anhydride,acids,concentrated hydrogen peroxide,perchlorates,perchloric acid,perchloronitrile,mercury nitrate,nitric acid,silver,silver nitrate,ammonia,silver oxide,ammonia,strong oxidising agents,nitrogen dioxide.May react dangerously with: bromoacetylene,chlorine acetylene,bromine trifluoride,chromium trioxide,chromyl chloride,fluorine,potassium tert-butoxide,lithium hydride,phosphorus trioxide,black platinum,zirconium (IV) chloride,zirconium (IV) iodide.Forms explosive mixtures with: air.		
ACETONE		
Risk of explosion on contact with: bromine trifluoride,fluorine dioxide,hydrogen peroxide,nitrosyl chloride,2-methyl-1,3 butadiene,nitromethane,nitrosyl perchlorate.May react dangerously with: potassium tert-butoxide,alkaline hydroxides,bromine,bromoform,isoprene,sodium,sulphur dioxide,chromium trioxide,chromyl chloride,nitric acid,chloroform,peroxymonosulphuric acid,phosphoryl oxychloride,chromosulphuric acid,fluorine,strong oxidising agents,strong reducing agents.Develops flammable gas on contact with: nitrosyl perchlorate.		
toluene		
Risk of explosion on contact with: fuming sulphuric acid,nitric acid,silver perchlorate,nitrogen dioxide,non-metal halogenates,acetic acid,organic nitrocompounds.May form explosive mixtures with: air.May react dangerously with: strong oxidising agents,strong acids,sulphur.		
10.4. Conditions to avoid		
Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.		
ETHANOL		
Avoid exposure to: sources of heat,naked flames.		
ACETONE		
Avoid exposure to: sources of heat,naked flames.		
10.5. Incompatible materials		
ACETONE		
Incompatible with: acids,oxidising substances.		
10.6. Hazardous decomposition products		
In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.		
ACETONE		
May develop: ketenes,irritant substances.		

BLK0039-2 - SWEET HOME - PROFUMATORE AMBIENTE TALCO

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

METHANOL

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

toluene

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

METHANOL

The minimum lethal dose for humans by ingestion is considered to be in the range from 300 to 1000 mg/kg. Ingestion of 4-10 ml of the substance may cause permanent blindness in adult humans (IPCS).

toluene

Toxic effect on the central and peripheral nervous system with encephalopathy and polyneuritis; irritating for the skin, conjunctiva, cornea and respiratory apparatus.

Interactive effects

toluene

Certain drugs and other industrial products can interfere with the metabolism of the toluene.

ACUTE TOXICITY

ATE (Inhalation) of the mixture:

Not classified (no significant component)

ATE (Oral) of the mixture:

Not classified (no significant component)

ATE (Dermal) of the mixture:

Not classified (no significant component)

ETHANOL

LD50 (Oral):

> 5000 mg/kg Rat

LC50 (Inhalation vapours):

120 mg/l/4h Pimephales promelas

benzyl salicylate

LD50 (Dermal):

> 2000 mg/kg bw rabbit

LD50 (Oral):

> 2000 mg/kg rat

galaxolide

LD50 (Dermal):

> 5000 mg/kg rabbit

LD50 (Oral):

> 4640 mg/kg rat

2H-CHROMEN-2-ONE

LD50 (Dermal):

293 mg/kg bw rat

Suarez Company		Revision nr. 1
		Dated 05/12/2024
		First compilation
BLK0039-2 - SWEET HOME - PROFUMATORE AMBIENTE TALCO		Printed on 06/12/2024
		17/25
LD50 (Oral): 290 mg/kg bw rat		
LC50 (Inhalation mists/powders): 293 mg/kg rat		
2,6-di-tert-butyl-p-cresol		
LD50 (Dermal): > 2000 mg/kg rat		
LD50 (Oral): 2930 mg/kg rat		
7-HYDROXYCITRONELLAL		
LD50 (Dermal): > 2000 mg/kg rabbit		
LD50 (Oral): > 5000 mg/kg rat		
METHANOL		
LD50 (Oral): > 1187 mg/kg Rat		
LC50 (Inhalation vapours): 43,68 mg/l/6h Rat		
toluene		
LD50 (Dermal): > 5000 mg/kg bw Rabbit		
LD50 (Oral): > 5000 mg/kg bw Rat		
LC50 (Inhalation vapours): 100 ppm human		
<u>SKIN CORROSION / IRRITATION</u>		
Does not meet the classification criteria for this hazard class		
<u>SERIOUS EYE DAMAGE / IRRITATION</u>		
Causes serious eye irritation		
<u>RESPIRATORY OR SKIN SENSITISATION</u>		
May produce an allergic reaction.		
Contains:		
7-HYDROXYCITRONELLAL		
2H-CHROMEN-2-ONE		
benzyl salicylate		
<u>GERM CELL MUTAGENICITY</u>		
Does not meet the classification criteria for this hazard class		
<u>CARCINOGENICITY</u>		
Does not meet the classification criteria for this hazard class		
toluene		
Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 1999).		
The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".		
<u>REPRODUCTIVE TOXICITY</u>		
Does not meet the classification criteria for this hazard class		
<u>STOT - SINGLE EXPOSURE</u>		
Does not meet the classification criteria for this hazard class		
<u>STOT - REPEATED EXPOSURE</u>		

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it has negative effects on the aquatic environment.

12.1. Toxicity

7-HYDROXYCITRONELLAL		
LC50 - for Fish		31,6 mg/l/96h
EC50 - for Crustacea		410 mg/l/48h
EC50 - for Algae / Aquatic Plants		123,32 mg/l/72h
toluene		
LC50 - for Fish		5,5 mg/l/96h Oncorhynchus kisutch
EC50 - for Crustacea		3,78 mg/l
EC50 - for Algae / Aquatic Plants		134 mg/l/3 h Chlorella vulgaris and Chlamydomonas angulosa
Chronic NOEC for Algae / Aquatic Plants		10 mg/l/72 h Skeletonema costatum
benzyl salicylate		
LC50 - for Fish		1,03 mg/l/96h Danio rerio
EC50 - for Crustacea		1,16 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants		1,29 mg/l/72h Pseudokirchneriella subcapitata
Chronic NOEC for Crustacea		0,894 mg/l Daphnia magna
Chronic NOEC for Algae / Aquatic Plants		0,502 mg/l Pseudokirchneriella subcapitata
galaxolide		
LC50 - for Fish		1,36 mg/l/96h Lepomis macrochirus
EC50 - for Crustacea		0,3 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants		0,723 mg/l/72h Pseudokirchneriella subcapitata
Chronic NOEC for Fish		0,093 mg/l/21 d Lepomis macrochirus
Chronic NOEC for Crustacea		0,038 mg/l Acartia tonsa
Chronic NOEC for Algae / Aquatic Plants		0,201 mg/l/72 h Pseudokirchneriella subcapitata
2,6-di-tert-butyl-p-cresol		
LC50 - for Fish		0,199 mg/l/96h
EC50 - for Crustacea		0,48 mg/l/48h
EC50 - for Algae / Aquatic Plants		> 0,4 mg/l/72h
Chronic NOEC for Fish		0,053 mg/l

Suarez Company		Revision nr. 1
		Dated 05/12/2024
		First compilation
BLK0039-2 - SWEET HOME - PROFUMATORE AMBIENTE TALCO		Printed on 06/12/2024
		19/25
Chronic NOEC for Crustacea		
		0,15 mg/l
ETHANOL		
LC50 - for Fish		14200 mg/l/96h
EC50 - for Crustacea		454 mg/l/48h
EC50 - for Algae / Aquatic Plants		275 mg/l/72h
Chronic NOEC for Fish		250 mg/l
Chronic NOEC for Crustacea		96 mg/l
Chronic NOEC for Algae / Aquatic Plants		11,5 mg/l
METHANOL		
LC50 - for Fish		15320 mg/l/96h <i>Leuciscus idus melanotus</i>
EC50 - for Crustacea		18260 mg/l/96 h <i>Daphnia magna</i>
EC50 - for Algae / Aquatic Plants		22000 mg/l/96 h <i>Pseudokirchneriella subcapitata</i>
Chronic NOEC for Fish		3950 mg/l/96 h <i>Danio rerio</i>
Chronic NOEC for Crustacea		7960 mg/l/96 h <i>Mytilus edulis</i>
2H-CHROMEN-2-ONE		
LC50 - for Fish		1,324 mg/l/96h
EC50 - for Crustacea		8,012 mg/l/48h
EC50 - for Algae / Aquatic Plants		1,452 mg/l/72h
Chronic NOEC for Fish		0,119 mg/l
Chronic NOEC for Crustacea		0,448 mg/l
Chronic NOEC for Algae / Aquatic Plants		0,408 mg/l
12.2. Persistence and degradability		
7-HYDROXYCITRONELLAL		
Rapidly degradable toluene		
Solubility in water		100 - 1000 mg/l
Rapidly degradable benzyl salicylate		
Rapidly degradable galaxolide		
Rapidly degradable 2,6-di-tert-butyl-p-cresol		
Rapidly degradable ETHANOL		
Solubility in water		1000 - 10000 mg/l
Rapidly degradable METHANOL		
Solubility in water		1000 - 10000 mg/l
Rapidly degradable ACETONE		
Rapidly degradable 2H-CHROMEN-2-ONE		
Rapidly degradable		
12.3. Bioaccumulative potential		

BLK0039-2 - SWEET HOME - PROFUMATORE AMBIENTE TALCO

toluene

Partition coefficient: n-octanol/water 2,73

BCF 90

galaxolide

Partition coefficient: n-octanol/water 5,3

BCF 498 5 d

2,6-di-tert-butyl-p-cresol

Partition coefficient: n-octanol/water 5,1

BCF 598,4 -

ETHANOL

Partition coefficient: n-octanol/water -0,35

METHANOL

Partition coefficient: n-octanol/water -0,77

BCF 0,2

ACETONE

Partition coefficient: n-octanol/water -0,23

BCF 3

12.4. Mobility in soil

7-HYDROXYCITRONELLAL

Partition coefficient: soil/water 1 a 25°C

toluene

Partition coefficient: soil/water 2,31

galaxolide

Partition coefficient: soil/water 4,39

2,6-di-tert-butyl-p-cresol

Partition coefficient: soil/water 4,2

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

BLK0039-2 - SWEET HOME - PROFUMATORE AMBIENTE TALCO**12.7. Other adverse effects**

Information not available

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information**14.1. UN number or ID number**

ADR / RID, IMDG, IATA: UN 1170

14.2. UN proper shipping name

ADR / RID: ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

IMDG: ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

IATA: ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3

IMDG: Class: 3 Label: 3

IATA: Class: 3 Label: 3

**14.4. Packing group**

ADR / RID, IMDG, IATA: II

14.5. Environmental hazards

ADR / RID: NO

IMDG: not marine pollutant

IATA: NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 33	Limited Quantities: 1 L	Tunnel restriction code: (D/E)
	Special provision: 144, 601		
IMDG:	EMS: F-E, S-D	Limited Quantities: 1 L	
IATA:	Cargo:	Maximum quantity: 60 L	Packaging instructions: 364
	Passengers:	Maximum quantity: 5 L	Packaging instructions: 353
	Special provision:	A3, A58, A180	

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product	
Point	3 - 40

Contained substance

Point	75
-------	----

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

BLK0039-2 - SWEET HOME - PROFUMATORE AMBIENTE TALCO

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 3: Severe hazard to waters

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Repr. 2	Reproductive toxicity, category 2
Acute Tox. 3	Acute toxicity, category 3
STOT SE 1	Specific target organ toxicity - single exposure, category 1
Acute Tox. 4	Acute toxicity, category 4
Asp. Tox. 1	Aspiration hazard, category 1
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
Skin Sens. 1	Skin sensitization, category 1
Skin Sens. 1B	Skin sensitization, category 1B
STOT SE 3	Specific target organ toxicity - single exposure, category 3
STOT SE 2	Specific target organ toxicity - single exposure, category 2
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H225	Highly flammable liquid and vapour.
H361d	Suspected of damaging the unborn child.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H331	Toxic if inhaled.

BLK0039-2 - SWEET HOME - PROFUMATORE AMBIENTE TALCO

H370	Causes damage to organs.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H371	May cause damage to organs.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament

BLK0039-2 - SWEET HOME - PROFUMATORE AMBIENTE TALCO

9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707
24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.