

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code:BLK0276-2

Product name:SWEET HOME - PROFUMATORE AMBIENTE SANDALO

UFI :U6KJ-F3SM-UX0Q-6532

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified Uses	Industrial	Professional	Consumer
Room deodorant	-	-	✓
Uses Advised Against			
Do not use for uses other than those indicated			

1.3. Details of the supplier of the safety data sheet

NameSuarez Company

Full addressVia Pergolesi , 1 ang. Via Monteverdi

District and Country20811 Cesano Maderno
Italia

Tel. +39 0362 659766

www.suarezcompany.it

e-mail address of the competent person
responsible for the Safety Data Sheet

info@suarezcompany.it

1.4. Emergency telephone number

For urgent inquiries refer to

Suarez Company

+39 0362 659766

(8:30 - 12:30 13:30-17:30)

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:		
Flammable liquid, category 2	H225	Highly flammable liquid and vapour.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin sensitization, category 1A	H317	May cause an allergic skin reaction.
Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.

BLK0276-2 - SWEET HOME - PROFUMATORE AMBIENTE SANDALO

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P302+P352 IF ON SKIN: Wash with plenty of water / . . .

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice / attention.

P337+P313 If eye irritation persists: Get medical advice / attention.

P501 Dispose of contents / container in accordance with current regulations.

Contains:

CINNAMALDEHYDE

(4-TERT-BUTYLCYCLOHEXYL) ACETATE

Reaction mass of 1-[(1R*,6S*)-2,2,6-trimethylcyclohexyl]hexan-3-ol and 1-[(1S*,6S*)-2,2,6-trimethylcyclohexyl]hexan-3-ol

CINEOLE

benzyl salicylate

linalool

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
ETHANOL		
INDEX 603-002-00-5	74 ≤ x < 78	Flam. Liq. 2 H225, Eye Irrit. 2 H319
EC 200-578-6		Eye Irrit. 2 H319: ≥ 50%
CAS 64-17-5		
REACH Reg. 01-2119457610-43		
(4-TERT-BUTYLCYCLOHEXYL) ACETATE		
INDEX -	7 ≤ x < 8	Skin Sens. 1B H317
EC 250-954-9		
CAS 32210-23-4		
REACH Reg. 01-2119976286-24		
DIPROPYLENE GLYCOL MONOMETHYL ETHER		
INDEX -	3,5 ≤ x < 4	Substance with a community workplace exposure limit.
EC 252-104-2		
CAS 34590-94-8		
REACH Reg. 01-2119450011-60		
2-ETHYL-4-(2,2,3-TRIMETHYL-3-CYCLOPENTEN-1-YL)-2-BUTEN-1-OL		
INDEX -	0,7 ≤ x < 0,8	Eye Irrit. 2 H319, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1
EC 248-908-8		
CAS 28219-61-6		
REACH Reg. 01-2119529224-45		
REACTION MASS OF 2-METHYLBUTYL SALICYLATE AND PENTYL SALICYLATE		
INDEX -	0,35 ≤ x < 0,4	Acute Tox. 4 H302, Aquatic Acute 1 H400 M=1, Aquatic Chronic 2 H411
EC 911-280-7		LD50 Oral: 2000 mg/kg
CAS -		
REACH Reg. 01-2119969444-27		
linalool		
INDEX 603-235-00-2	0,3 ≤ x < 0,35	Eye Irrit. 2 H319, Skin Irrit. 2 H315, Skin Sens. 1B H317
EC 201-134-4		

Suarez Company			Revision nr. 1
			Dated 03/12/2024
			First compilation
BLK0276-2 - SWEET HOME - PROFUMATORE AMBIENTE SANDALO			Printed on 03/12/2024
			4/35
CAS 78-70-6			
REACH Reg. 01-2119474016-42			
benzyl salicylate			
INDEX 607-754-00-5	0,2 ≤ x < 0,25	Eye Irrit. 2 H319, Skin Sens. 1B H317, Aquatic Chronic 3 H412	
EC 204-262-9			
CAS 118-58-1			
REACH Reg. 01-2119969442-31			
2,6-di-tert-butyl-p-cresol			
INDEX -	0,1 ≤ x < 0,15	Aquatic Chronic 1 H410 M=1	
EC 204-881-4			
CAS 128-37-0			
REACH Reg. 01-2119565113-46			
(±) trans—3,3-dimethyl-5-(2,2,3-trimethyl-cyclopent-3-en-1-yl)-pent-4-en-2-ol			
INDEX 603-150-00-0	0,1 ≤ x < 0,15	Skin Irrit. 2 H315, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1	
EC 411-580-3			
CAS 107898-54-4			
REACH Reg. 01-0000015895-58			
CINEOLE			
INDEX -	0,1 ≤ x < 0,15	Flam. Liq. 3 H226, Skin Sens. 1B H317	
EC 207-431-5			
CAS 470-82-6			
REACH Reg. 01-2119967772-24			
Reaction mass of 1-[(1R*,6S*)-2,2,6-trimethylcyclohexyl]hexan-3-ol and 1-[(1S*,6S*)-2,2,6-trimethylcyclohexyl]hexan-3-ol			
INDEX -	0,1 ≤ x < 0,15	Skin Sens. 1B H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1	
EC 947-716-8			
CAS -			
REACH Reg. 01-2120768938-30			
CINNAMALDEHYDE			
INDEX 606-155-00-6	0,05 ≤ x < 0,1	Skin Sens. 1A H317	
EC 203-213-9			
CAS 104-55-2			
REACH Reg. 01-2119935242-45			
ALPHA-CEDRENE			
INDEX -	0 < x < 0,025	Asp. Tox. 1 H304, Aquatic Acute 1 H400 M=10, Aquatic Chronic 1 H410 M=10	
EC 207-418-4			
CAS 469-61-4			
acetic acid ...%			
INDEX 607-002-00-6	0 < x < 0,05	Flam. Liq. 3 H226, Skin Corr. 1A H314, Eye Dam. 1 H318, Classification note according to Annex VI to the CLP Regulation: B	
EC 200-580-7			
CAS 64-19-7			

BLK0276-2 - SWEET HOME - PROFUMATORE AMBIENTE SANDALO

REACH Reg. 01-2119475328-30

METHANOL

INDEX 603-001-00-X 0 < x < 0,05 Flam. Liq. 2 H225, Acute Tox. 3 H301, Acute Tox. 3 H311, Acute Tox. 3 H331, STOT SE 1 H370

EC 200-659-6 STOT SE 2 H371: ≥ 3% - < 10%

CAS 67-56-1 ATE Oral: 100 mg/kg, ATE Dermal: 300 mg/kg, ATE Inhalation vapours: 3 mg/l

REACH Reg. 01-2119433307-44

HEPTANE

INDEX 601-008-00-2 0 < x < 0,05 Flam. Liq. 2 H225, Asp. Tox. 1 H304, Skin Irrit. 2 H315, STOT SE 3 H336, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1, Classification note according to Annex VI to the CLP Regulation: C

EC 205-563-8

CAS 142-82-5

REACH Reg. 01-2119457603-38

ACETONE

INDEX 606-001-00-8 0 < x < 0,05 Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066

EC 200-662-2

CAS 67-64-1

REACH Reg. 01-2119471330-49

toluene

INDEX 601-021-00-3 0 < x < 0,05 Flam. Liq. 2 H225, Repr. 2 H361d, Asp. Tox. 1 H304, STOT RE 2 H373, Skin Irrit. 2 H315, STOT SE 3 H336

EC 203-625-9

CAS 108-88-3

REACH Reg. 01-2119471310-51-

phenol

INDEX 604-001-00-2 0 < x < 0,05 Muta. 2 H341, Acute Tox. 3 H301, Acute Tox. 3 H311, Acute Tox. 3 H331, STOT RE 2 H373, Skin Corr. 1B H314, Eye Dam. 1 H318

EC 203-632-7 Skin Corr. 1B H314: ≥ 3%, Skin Irrit. 2 H315: ≥ 1% - < 3%

CAS 108-95-2 LD50 Oral: 282 mg/kg bw, LD50 Dermal: 525 mg/kg bw, ATE Inhalation mists/powders: 0,501 mg/l

REACH Reg. 01-2119471329-32

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures**4.1. Description of first aid measures**

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off immediately all contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice/attention. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the

Suarez Company	Revision nr. 1
	Dated 03/12/2024
BLK0276-2 - SWEET HOME - PROFUMATORE AMBIENTE SANDALO	First compilation
	Printed on 03/12/2024
	6/35

contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

If symptoms occur, whether acute or delayed, consult a doctor.

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT
Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.
UNSUITABLE EXTINGUISHING EQUIPMENT
Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE
Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION
Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.
SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS
Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.
Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

Suarez Company	Revision nr. 1
	Dated 03/12/2024
BLK0276-2 - SWEET HOME - PROFUMATORE AMBIENTE SANDALO	First compilation
	Printed on 03/12/2024
	7/35

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.
Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

Storage class TRGS 510 (Germany):
3

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
CZE	Česká Republika	NAŘÍZENÍ VLÁDY ze dne 10. května 2021, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci
DEU	Deutschland	Forschungsgemeinschaft MAK- und BAT-Werte-Liste 2022 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe Mitteilung 58
DNK	Danmark	Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019
ESP	España	Límites de exposición profesional para agentes químicos en España 2023
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en FranceDécret n° 2021-1849 du 28 décembre 2021
FIN	Suomi	HTP-VÄRDEN 2020. Koncentrationer som befunnits skadliga. SOCIAL - OCH HÄLSOVÄRDSMINISTERIETS PUBLIKATIONER 2020:25
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α΄ 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ για την τροποποίηση της οδηγίας 2004/37/ΕΚ ``σχετικά με

HUN	Magyarország	την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία`» Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnimkemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021) Decreto Legislativo 9 Aprile 2008, n.81 Forskrift om endring i forskrift om tiltaksverdi og grenseverdi for fysiske og kjemiske faktorer i arbeidsmiljøet samt smitterisikogrupper for biologiske faktorer (forskrift om tiltaks- og grenseverdi), 21. august 2018 nr. 1255 Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006 Hygieniska gränsvärden, Arbetsmiljöverkets föreskrifter och allmänna råd om hygieniska gränsvärden (AFS 2018:1) NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénym a mutagénym faktorom pri práci v znení neskorších predpisov Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19) EH40/2005 Workplace exposure limits (Fourth Edition 2020) Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC. ACGIH 2023
HRV	Hrvatska	
ITA	Italia	
NOR	Norge	
NLD	Nederland	
PRT	Portugal	
POL	Polska	
ROU	România	
SWE	Sverige	
SVK	Slovensko	
SVN	Slovenija	
GBR	United Kingdom	
EU	OEL EU	
	TLV-ACGIH	

ETHANOL					
Threshold Limit Value					
Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
TLV	BGR	1000			
TLV	CZE	1000		3000	
AGW	DEU	960	500	1920	1000
MAK	DEU	960	500	1920	1000
TLV	DNK	1900	1000		
VLA	ESP			1910	1000
VLEP	FRA	1900	1000	9500	5000
HTP	FIN	1900	1000	2500	1300
TLV	GRC	1900	1000		
AK	HUN	1900		7600	
GVI/KGVI	HRV	1900	1000		
TLV	NOR	950	500		
TGG	NLD	260		1900	
NDS/NDSch	POL	1900			
NGV/KGV	SWE	1000	500	1900	1000
NPEL	SVK	960	500	1920	
WEL	GBR	1920	1000		
TLV-ACGIH				1884	1000
Predicted no-effect concentration - PNEC					

Suarez Company						Revision nr. 1		
BLK0276-2 - SWEET HOME - PROFUMATORE AMBIENTE SANDALO						Dated 03/12/2024		
						First compilation		
						Printed on 03/12/2024		
						9/35		
Normal value in fresh water				0,96		mg/l		
Normal value in marine water				0,79		mg/l		
Normal value for fresh water sediment				3,6		mg/kg		
Normal value for marine water sediment				2,9		mg/kg		
Normal value for water, intermittent release				2,75		mg/l		
Normal value of STP microorganisms				580		mg/l		
Normal value for the food chain (secondary poisoning)				0,38		mg/kg		
Normal value for the terrestrial compartment				0,63		mg/kg		
Health - Derived no-effect level - DNEL / DMEL								
				Effects on consumers		Effects on workers		
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				87 mg/kg bw/d				
Inhalation				114 mg/m3				950 mg/m3
Skin				206 mg/kg bw/d				343 mg/kg bw/d
(4-TERT-BUTYLCYCLOHEXYL) ACETATE								
Predicted no-effect concentration - PNEC								
Normal value in fresh water				0,0053		mg/l		
Normal value in marine water				0,00053		mg/l		
Normal value for fresh water sediment				2,01		mg/kg		
Normal value for marine water sediment				0,21		mg/kg		
Normal value for water, intermittent release				0,053		mg/l		
Normal value of STP microorganisms				12,2		mg/l		
Normal value for the food chain (secondary poisoning)				66,67		mg/kg		
Normal value for the terrestrial compartment				0,42		mg/kg		
DIPROPYLENE GLYCOL MONOMETHYL ETHER								
Threshold Limit Value								
Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
TLV	BGR	308				SKIN		
TLV	CZE	270		550		SKIN		
AGW	DEU	310	50	310	50			
MAK	DEU	310	50	310	50			
TLV	DNK	300	50					
VLA	ESP	308	50			SKIN		
VLEP	FRA	308	50			SKIN		
HTP	FIN	310	50					
TLV	GRC	600	100	900	150			
AK	HUN	308		308				
VLEP	ITA	308	50			SKIN		
TLV	NOR	300	50			SKIN		
VLE	PRT	308	50			SKIN		

Suarez Company						Revision nr. 1			
BLK0276-2 - SWEET HOME - PROFUMATORE AMBIENTE SANDALO						Dated 03/12/2024			
						First compilation			
						Printed on 03/12/2024			
						10/35			
NDS/NDSch	POL	240		480					
NGV/KGV	SWE	300	50	450		75		SKIN	
NPEL	SVK	308	50					SKIN	
MV	SVN	308	50					SKIN	
WEL	GBR	308	50					SKIN	
OEL	EU	308	50					SKIN	
TLV-ACGIH		606	100	909		150		SKIN	
Predicted no-effect concentration - PNEC									
Normal value in fresh water				19		mg/l			
Normal value in marine water				1,9		mg/l			
Normal value for fresh water sediment				70,2		mg/kg			
Normal value for marine water sediment				7,02		mg/kg			
Normal value for water, intermittent release				190		mg/l			
Normal value of STP microorganisms				4168		mg/l			
Normal value for the terrestrial compartment				2,74		mg/kg			
Health - Derived no-effect level - DNEL / DMEL									
		Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic	
Oral				36 mg/kg bw/d					
Inhalation				37,2 mg/m3					308 mg/m3
Skin				121 mg/kg bw/d					283 mg/kg bw/d
REACTION MASS OF 2-METHYLBUTYL SALICYLATE AND PENTYL SALICYLATE									
Predicted no-effect concentration - PNEC									
Normal value in fresh water				0,00077		mg/l			
Normal value in marine water				0,000077		mg/l			
Normal value for fresh water sediment				0,389		mg/kg			
Normal value for marine water sediment				0,039		mg/kg			
Normal value for water, intermittent release				0,0077		mg/l			
Normal value of STP microorganisms				10		mg/l			
Normal value for the food chain (secondary poisoning)				80		mg/kg			
Normal value for the terrestrial compartment				1,786		mg/kg			
Health - Derived no-effect level - DNEL / DMEL									
		Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic	
Oral				0,45 mg/kg bw/d					
Inhalation				0,78 mg/m3					3,17 mg/m3
Skin				0,45 mg/kg bw/d					0,9 mg/kg bw/d
linalool									
Predicted no-effect concentration - PNEC									
Normal value in fresh water				0,2		mg/l			
Normal value in marine water				0,02		mg/l			

Suarez Company						Revision nr. 1 Dated 03/12/2024 First compilation		
BLK0276-2 - SWEET HOME - PROFUMATORE AMBIENTE SANDALO						Printed on 03/12/2024 11/35		
Normal value for fresh water sediment			2,22		mg/kg			
Normal value for marine water sediment			0,222		mg/kg			
Normal value for water, intermittent release			2		mg/l			
Normal value of STP microorganisms			10		mg/l			
Normal value for the food chain (secondary poisoning)			7,8		mg/kg food			
Normal value for the terrestrial compartment			0,327		mg/kg			
Health - Derived no-effect level - DNEL / DMEL								
Effects on consumers			Effects on workers					
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		1,2 mg/kg bw/d		0,2 mg/kg bw/d				
Inhalation		4,1 mg/m3		0,7 mg/m3		16,5 mg/m3		2,8 mg/m3
Skin	1,5 mg/cm2	2,5 mg/kg bw/d	1,5 mg/cm2	1,25 mg/kg bw/d	3 mg/cm2	5 mg/kg bw/d	3 mg/cm²	2,5 mg/kg bw/d
benzyl salicylate								
Predicted no-effect concentration - PNEC								
Normal value in fresh water			0,001		mg/l			
Normal value in marine water			0		mg/l			
Normal value for fresh water sediment			0,583		mg/kg			
Normal value for marine water sediment			0,058		mg/kg			
Normal value for water, intermittent release			0,01		mg/l			
Normal value of STP microorganisms			10		mg/l			
Normal value for the food chain (secondary poisoning)			80		mg/kg			
Normal value for the terrestrial compartment			1,41		mg/kg			
Health - Derived no-effect level - DNEL / DMEL								
Effects on consumers			Effects on workers					
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				0,45 mg/kg bw/d				
Inhalation				0,78 mg/m3				3,17 mg/m3
Skin				0,45 mg/kg bw/d				0,9 mg/kg bw/d
(±) trans—								
3,3-dimethyl-5-(2,2,3-trimethyl-cyclopent-3-en-1-yl)-pent-4-en-2-ol								
Predicted no-effect concentration - PNEC								
Normal value in fresh water			0,0012		mg/l			
Normal value in marine water			0,00012		mg/l			
Normal value for fresh water sediment			0,246		mg/kg/d			
Normal value for marine water sediment			0,025		mg/kg/d			
Normal value for water, intermittent release			0,012		mg/l			
Normal value of STP microorganisms			0,1		mg/l			
Normal value for the food chain (secondary poisoning)			222,2		mg/kg food			
Normal value for the terrestrial compartment			0,048		mg/kg			
Reaction mass of 1-[(1R*,6S*)-2,2,6-trimethylcyclohexyl]hexan-3-ol and 1-[(1S*,6S*)-2,2,6-trimethylcyclohexyl]hexan-3-ol								

Suarez Company					Revision nr. 1			
					Dated 03/12/2024			
					First compilation			
BLK0276-2 - SWEET HOME - PROFUMATORE AMBIENTE SANDALO					Printed on 03/12/2024			
					12/35			
Predicted no-effect concentration - PNEC								
Normal value in fresh water				0,001	mg/l			
Normal value in marine water				0	mg/l			
Normal value for fresh water sediment				0,5	mg/kg/d			
Normal value for marine water sediment				0,05	mg/kg/d			
Normal value of STP microorganisms				100	mg/l			
Normal value for the terrestrial compartment				0,396	mg/kg/d			
Health - Derived no-effect level - DNEL / DMEL								
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				0,5 mg/kg bw/d				
Inhalation				1,74 mg/m3	9.87 mg/m3			
Skin				1 mg/kg bw/d	2,8 mg/kg bw/d			
CINEOLE								
Predicted no-effect concentration - PNEC								
Normal value in fresh water				0,057	mg/l			
Normal value in marine water				0,0057	mg/l			
Normal value for fresh water sediment				1,425	mg/kg			
Normal value for marine water sediment				0,142	mg/kg			
Normal value for water, intermittent release				0,57	mg/l			
Normal value of STP microorganisms				10	mg/l			
Normal value for the food chain (secondary poisoning)				40	mg/kg			
Normal value for the terrestrial compartment				0,25	mg/kg			
Health - Derived no-effect level - DNEL / DMEL								
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				600 mg/kg bw/d				
Inhalation				1,74 mg/m3	7,05 mg/m3			
Skin				1 mg/kg bw/d	2 mg/kg bw/d			
2,6-di-tert-butyl-p-cresol								
Predicted no-effect concentration - PNEC								
Normal value in fresh water				0,000199	mg/l			
Normal value in marine water				0,02	µg/l			
Normal value for fresh water sediment				0,0996	mg/kg			
Normal value for marine water sediment				0,00996	mg/kg			
Normal value for water, intermittent release				0,00199	mg/l			
Normal value of STP microorganisms				0,17	mg/l			
Normal value for the food chain (secondary poisoning)				8,33	mg/kg			
Normal value for the terrestrial compartment				0,04769	mg/kg			
Health - Derived no-effect level - DNEL / DMEL								
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic	Acute local	Acute	Chronic local	Chronic

Suarez Company					Revision nr. 1			
BLK0276-2 - SWEET HOME - PROFUMATORE AMBIENTE SANDALO					Dated 03/12/2024			
					First compilation			
					Printed on 03/12/2024			
					13/35			

Suarez Company						Revision nr. 1		
BLK0276-2 - SWEET HOME - PROFUMATORE AMBIENTE SANDALO						Dated 03/12/2024		
						First compilation		
						Printed on 03/12/2024		
						14/35		
WEL	GBR	266	200	333	250	SKIN		
OEL	EU	260	200	SKIN				
TLV-ACGIH		262	200	328	250			
Predicted no-effect concentration - PNEC								
Normal value in fresh water				20,8	mg/l			
Normal value in marine water				2,08	mg/l			
Normal value for fresh water sediment				77	mg/kg			
Normal value for marine water sediment				7,7	mg/kg			
Normal value for water, intermittent release				1540	mg/l			
Normal value of STP microorganisms				100	mg/l			
Normal value for the terrestrial compartment				100	mg/kg			
Health - Derived no-effect level - DNEL / DMEL								
	Effects on consumers			Effects on workers				
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		4 mg/kg bw/d		4 mg/kg bw/d				
Inhalation	26 mg/m3	26 mg/m3	26 mg/m3	26 mg/m3	130 mg/m3	130 mg/m3	130 mg/m3	130 mg/m3
Skin		4 mg/kg bw/d		4 mg/kg bw/d		20 mg/kg bw/d		20 mg/kg bw/d
HEPTANE								
Threshold Limit Value								
Type	Country	TWA/8h	STEL/15min		Remarks / Observations			
		mg/m3	ppm	mg/m3	ppm			
TLV	BGR	1600						
TLV	CZE	1000	240	2000	480			
MAK	DEU	2100	500	2100	500			
TLV	DNK	820	200			E		
VLA	ESP	2085	500			Como n-Eptano		
VLEP	FRA	1668	400	2085	500			
TLV	GRC	2000	500	2000	500			
AK	HUN	2000						
GVI/KGVI	HRV	2085	500			SKIN		
VLEP	ITA	2085	500					
TLV	NOR	800	200					
TGG	NLD	1200		1600				
VLE	PRT	2085	500					
NDS/NDSch	POL	1200		2000				
TLV	ROU	2085	500					
NGV/KGV	SWE	800	200	1200 (C)	300 (C)			
NPEL	SVK	2085	500					
MV	SVN	2085	500	2085	500			
WEL	GBR	2085	500					
OEL	EU	2085	500					
TLV-ACGIH		1639	400	2049	500			

ACETONE						
Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	600		1400		
TLV	CZE	800	331,2	1500	621	
AGW	DEU	1200	500	2400 (C)	1000 (C)	
MAK	DEU	1200	500	2400	1000	
TLV	DNK	600	250			E
VLEP	FRA	1210	500	2420	1000	
HTP	FIN	1200	500	1500	630	
TLV	GRC	1780		3560		
AK	HUN	1210				
GVI/KGVI	HRV	1210	500			
VLEP	ITA	1210	500			
TLV	NOR	295	125			
TGG	NLD	1210		2420		
VLE	PRT	1210	500			
NDS/NDSch	POL	600		1800		
TLV	ROU	1210	500			
NGV/KGV	SWE	600	250	1200 (C)	500 (C)	
NPEL	SVK	1210	500			
MV	SVN	1210	500	2420	1000	
WEL	GBR	1210	500	3620	1500	
OEL	EU	1210	500			
TLV-ACGIH			250		500	
toluene						
Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	150		300		
TLV	CZE	200		500		SKIN
AGW	DEU	190	50	760	200	SKIN
MAK	DEU	190	50	760	200	
TLV	DNK	94	25			SKIN
VLA	ESP	192	50	384	100	SKIN
VLEP	FRA	76,8	20	384	100	SKIN
HTP	FIN	81	25	380	100	SKIN
TLV	GRC	192	50	384	100	
AK	HUN	190		760		
GVI/KGVI	HRV	192	50	384	100	SKIN
VLEP	ITA	192	50			SKIN

Suarez Company						Revision nr. 1 Dated 03/12/2024 First compilation		
BLK0276-2 - SWEET HOME - PROFUMATORE AMBIENTE SANDALO						Printed on 03/12/2024 16/35		
TLV	NOR	94	25	SKIN				
TGG	NLD	150	384					
VLE	PRT	192	50	384	100	SKIN		
NDS/NDSch	POL	100	200					
TLV	ROU	192	50	384	100	SKIN		
NGV/KGV	SWE	192	50	384	100	SKIN		
NPEL	SVK	192	50	384	SKIN			
MV	SVN	192	50	384	100	SKIN		
WEL	GBR	191	50	384	100	SKIN		
OEL	EU	192	50	384	100	SKIN		
TLV-ACGIH		75,4	20					
Predicted no-effect concentration - PNEC								
Normal value in fresh water				0,68	mg/l			
Normal value in marine water				0,68	mg/l			
Normal value for fresh water sediment				16,39	mg/kg/d			
Normal value for marine water sediment				16,39	mg/kg/d			
Normal value for water, intermittent release				0,68	mg/l			
Normal value of STP microorganisms				13,61	mg/l			
Normal value for the food chain (secondary poisoning)				2,89	mg/kg soil dw			
Health - Derived no-effect level - DNEL / DMEL								
		Effects on consumers			Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				8,13 mg/kg bw/d				
Inhalation	226 mg/m3	226 mg/m3	56,5 mg/m3	56,5 mg/m3	384 mg/m3	384 mg/m3	192 mg/m3	192 mg/m3
Skin				226 mg/kg bw/d				384 mg/kg bw/d
phenol								
Threshold Limit Value								
Type	Country	TWA/8h	STEL/15min			Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
TLV	BGR	7,8	SKIN					
TLV	CZE	7,5	15 SKIN					
AGW	DEU	8	2	16	4	SKIN		
TLV	DNK	4	1					
VLA	ESP	8	2	16	4	SKIN		
VLEP	FRA	7,8	2	15,6	4	SKIN		
HTP	FIN	8	2	16	4	SKIN		
TLV	GRC	8	2	16	4			
AK	HUN	7,8						
GVI/KGVI	HRV	7,8	2	SKIN				
VLEP	ITA	8	2	16	4	SKIN		
TLV	NOR	4	1	SKIN				
TGG	NLD	8	SKIN					

Suarez Company						Revision nr. 1			
BLK0276-2 - SWEET HOME - PROFUMATORE AMBIENTE SANDALO						Dated 03/12/2024			
						First compilation			
						Printed on 03/12/2024			
						17/35			
VLE	PRT	8	2	16	4	SKIN			
NDS/NDSch	POL	7,8		16					
TLV	ROU	8	2	16	4	SKIN			
NGV/KGV	SWE	4	1	8	2	SKIN			
NPEL	SVK	7,8	2						
MV	SVN	8	2	16	4	SKIN			
WEL	GBR	7,8	2	16	4	SKIN			
OEL	EU	8	2	16	4	SKIN			
TLV-ACGIH		19,2	5						
Predicted no-effect concentration - PNEC									
Normal value in fresh water				0,008	mg/l				
Normal value in marine water				0,001	mg/l				
Normal value for fresh water sediment				0,091	mg/kg/d				
Normal value for marine water sediment				0,009	mg/kg/d				
Normal value for water, intermittent release				0,031	mg/l				
Normal value of STP microorganisms				2,1	mg/l				
Normal value for the terrestrial compartment				0,136	mg/kg/d				
Health - Derived no-effect level - DNEL / DMEL									
		Effects on consumers			Effects on workers				
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic	
Oral				0,4 mg/kg bw/d					
Inhalation				1,32 mg/m3	16 mg/m3			8 mg/m3	
Skin				0,4 mg/kg bw/d				1,23 mg/kg bw/d	
acetic acid ...%									
Threshold Limit Value									
Type	Country	TWA/8h		STEL/15min		Remarks / Observations			
		mg/m3	ppm	mg/m3	ppm				
TLV	BGR	25		37					
TLV	CZE	25		35					
AGW	DEU	25	10	50	20				
MAK	DEU	25	10	50	20				
TLV	DNK	25	10						
VLA	ESP	25	10	37	15				
VLEP	FRA			25	10				
HTP	FIN	13	5	25	10				
TLV	GRC	25	10	37	15				
AK	HUN	25		25					
GVI/KGVI	HRV	25	10						
TLV	NOR	25	10						
VLE	PRT	25	10						
NDS/NDSch	POL	15		30					
NGV/KGV	SWE	13	5	25	10				

NPEL	SVK	25	10					
MV	SVN	25	10					
OEL	EU	25	10	50		20		
TLV-ACGIH		25	10	37		15		
Predicted no-effect concentration - PNEC								
Normal value in fresh water				3,058		mg/l		
Normal value in marine water				0,306		mg/l		
Normal value for fresh water sediment				11,36		mg/kg		
Normal value for marine water sediment				1,136		mg/kg		
Normal value for water, intermittent release				30,58		mg/l		
Normal value of STP microorganisms				85		mg/l		
Normal value for the terrestrial compartment				0,47		mg/kg		
Health - Derived no-effect level - DNEL / DMEL								
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation	25 mg/m3		25 mg/m3		25 mg/m3		25 mg/m3	

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	Method:internal Temperature: 20 °C
Colour	brown	Remark:Visual Temperature: 20 °C
Odour	characteristic	Method:internal
Odour threshold	18,8	Method:internal Remark:mg/m3 Substance:ETHANOL Temperature: 20 °C
Melting point / freezing point	-114 °C	Method:HSDB 2015; INRS 2011 Substance:ETHANOL
Initial boiling point	78,5 °C	Method:HSDB 2015; INRS 2011 Substance:ETHANOL Initial boiling point: 78 °C
Flammability	Easily flammable liquid and vapors.	Method:ISO 3679:2023
Lower explosive limit	3,3 % (v/v)	Method:internal Remark:INAIL, 2018 Substance:ETHANOL
Upper explosive limit	19 % (v/v)	Method:internal Remark:INAIL, 2018 Substance:ETHANOL
Flash point	18 °C	Method:ISO 3679:2023
Auto-ignition temperature	363 °C	Method:internal Remark:1013 hPa Substance:ETHANOL
Decomposition temperature	not available	Reason for missing data:It only applies to authoritative substances and mixtures, organic peroxides and other substances and mixtures that they can decompose
pH	not available	Reason for missing data:This property is not relevant to the safety and classification of this product.
Kinematic viscosity	not available	Reason for missing data:This property is not

BLK0276-2 - SWEET HOME - PROFUMATORE AMBIENTE SANDALO

Solubility	soluble in water	relevant to the safety and classification of this product. Method:internal Temperature: 20 °C
Partition coefficient: n-octanol/water	-0,35	Method:internal Substance:ETHANOL Temperature: 20 °C
Vapour pressure	5,9 kPa	Method:INRS, 2011 Substance:ETHANOL Vapour pressure: 45 mmHg Temperature: 20 °C
Density and/or relative density	not available	
Relative vapour density	1,6	Method:HSDB, 2015; INRS, 2011 Remark:(aria=1) HSDB, 2015; INRS, 2011 Substance:ETHANOL

Particle characteristics

Median equivalent diameter

Remark: It only applies to solids

Size distribution

Remark: It only applies to solids

Dustiness

Remark: It only applies to solids

Specific surface area

Remark: It only applies to solids

Shape

Remark: It only applies to solids

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Explosive properties	not available	Reason for missing data:Absent chemical groups associated with explosive properties in accordance with the provisions of Annex I, Part 2, chap. 2.1.4.3 of Reg. (EC) 1272/2008 - CLP
Oxidising properties	not available	Reason for missing data:Absent requirements related to the presence of atoms or chemical bonds associated with oxidizing properties in the molecules of the components according to Annex I, Part 2, 2.13.4 Reg. (CE) 1272/2008

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

Suarez Company		Revision nr. 1
		Dated 03/12/2024
		First compilation
BLK0276-2 - SWEET HOME - PROFUMATORE AMBIENTE SANDALO		Printed on 03/12/2024
		21/35
DIPROPYLENE GLYCOL MONOMETHYL ETHER		
May react with: oxidising substances.When heated to decomposition releases: harsh fumes,zinc alloys.		
ACETONE		
Decomposes under the effect of heat.		
toluene		
Avoid exposure to: light.		
10.2. Chemical stability		
The product is stable in normal conditions of use and storage.		
10.3. Possibility of hazardous reactions		
The vapours may also form explosive mixtures with the air.		
ETHANOL		
Risk of explosion on contact with: alkaline metals,alkaline oxides,calcium hypochlorite,sulphur monofluoride,acetic anhydride,acids,concentrated hydrogen peroxide,perchlorates,perchloric acid,perchloronitrile,mercury nitrate,nitric acid,silver,silver nitrate,ammonia,silver oxide,ammonia,strong oxidising agents,nitrogen dioxide.May react dangerously with: bromoacetylene,chlorine acetylene,bromine trifluoride,chromium trioxide,chromyl chloride,fluorine,potassium tert-butoxide,lithium hydride,phosphorus trioxide,black platinum,zirconium (IV) chloride,zirconium (IV) iodide.Forms explosive mixtures with: air.		
ACETONE		
Risk of explosion on contact with: bromine trifluoride,fluorine dioxide,hydrogen peroxide,nitrosyl chloride,2-methyl-1,3 butadiene,nitromethane,nitrosyl perchlorate.May react dangerously with: potassium tert-butoxide,alkaline hydroxides,bromine,bromoform,isoprene,sodium,sulphur dioxide,chromium trioxide,chromyl chloride,nitric acid,chloroform,peroxymonosulphuric acid,phosphoryl oxychloride,chromosulphuric acid,fluorine,strong oxidising agents,strong reducing agents.Develops flammable gas on contact with: nitrosyl perchlorate.		
toluene		
Risk of explosion on contact with: fuming sulphuric acid,nitric acid,silver perchlorate,nitrogen dioxide,non-metal halogenates,acetic acid,organic nitrocompounds.May form explosive mixtures with: air.May react dangerously with: strong oxidising agents,strong acids,sulphur.		
acetic acid ...%		
Risk of explosion on contact with: chromium (VI) oxide,potassium permanganate,sodium peroxide,perchloric acid,phosphorus chloride,hydrogen peroxide.May react dangerously with: alcohols,bromine pentafluoride,chlorosulphuric acid,dichromate-sulphuric acid,ethane diamine,ethylene glycol,potassium hydroxide,strong bases,sodium hydroxide,strong oxidising agents,nitric acid,ammonium nitrate,potassium tert-butoxide,oleum.Forms explosive mixtures with: air.		
10.4. Conditions to avoid		
Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.		
ETHANOL		
Avoid exposure to: sources of heat,naked flames.		

BLK0276-2 - SWEET HOME - PROFUMATORE AMBIENTE SANDALO

ACETONE

Avoid exposure to: sources of heat,naked flames.

acetic acid ...%

Avoid exposure to: sources of heat,naked flames.

10.5. Incompatible materials

ACETONE

Incompatible with: acids,oxidising substances.

acetic acid ...%

Incompatible with: carbonates,hydroxides,phosphates,oxidising substances,bases.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

ACETONE

May develop: ketenes,irritant substances.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.
It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

METHANOL

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

toluene

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

METHANOL

The minimum lethal dose for humans by ingestion is considered to be in the range from 300 to 1000 mg/kg. Ingestion of 4-10 ml of the substance may cause permanent blindness in adult humans (IPCS).

Suarez Company		Revision nr. 1
		Dated 03/12/2024
		First compilation
BLK0276-2 - SWEET HOME - PROFUMATORE AMBIENTE SANDALO		Printed on 03/12/2024
		23/35
toluene		
Toxic effect on the central and peripheral nervous system with encephalopathy and polyneuritis; irritating for the skin, conjunctiva, cornea and respiratory apparatus.		
Interactive effects		
toluene		
Certain drugs and other industrial products can interfere with the metabolism of the toluene.		
ACUTE TOXICITY		
ATE (Inhalation) of the mixture:		Not classified (no significant component)
ATE (Oral) of the mixture:		Not classified (no significant component)
ATE (Dermal) of the mixture:		Not classified (no significant component)
ETHANOL		
LD50 (Oral):		> 5000 mg/kg Rat
LC50 (Inhalation vapours):		120 mg/l/4h Pimephales promelas
(4-TERT-BUTYLCYCLOHEXYL) ACETATE		
LD50 (Dermal):		> 5000 mg/kg rabbit
LD50 (Oral):		3,6 mg/kg rat
DIPROPYLENE GLYCOL MONOMETHYL ETHER		
LD50 (Dermal):		10 mL/kg rabbit
LD50 (Oral):		> 5000 mg/kg rat
LC50 (Inhalation vapours):		3,35 mg/L 7h
REACTION MASS OF 2-METHYLBUTYL SALICYLATE AND PENTYL SALICYLATE		
LD50 (Dermal):		> 2000 mg/kg rabbit
LD50 (Oral):		2000 mg/kg rat
linalool		
LD50 (Dermal):		5610 mg/kg rabbit
LD50 (Oral):		2200 mg/kg mouse
LC50 (Inhalation vapours):		> 3,2 mg/l 90 min mouse
benzyl salicylate		
LD50 (Dermal):		> 2000 mg/kg bw rabbit
LD50 (Oral):		> 2000 mg/kg rat
(±) trans—		
3,3-dimethyl-5-(2,2,3-trimethyl-cyclopent-3-en-1-yl)-pent-4-en-2-ol		
LD50 (Dermal):		> 2000 mg/kg rat
LD50 (Oral):		> 5000 mg/kg rat
Reaction mass of 1-[(1R*,6S*)-2,2,6-trimethylcyclohexyl]hexan-3-ol and 1-[(1S*,6S*)-2,2,6-trimethylcyclohexyl]hexan-3-ol		
LD50 (Dermal):		> 2000 mg/kg rat
LD50 (Oral):		> 18000 mg/kg rat
CINEOLE		
LD50 (Dermal):		> 2 g/kg rat
LD50 (Oral):		4,3 g/kg rat
2,6-di-tert-butyl-p-cresol		
LD50 (Dermal):		> 2000 mg/kg rat
LD50 (Oral):		2930 mg/kg rat
CINNAMALDEHYDE		
LD50 (Dermal):		620 mg/kg rabbit

Suarez Company		Revision nr. 1
		Dated 03/12/2024
		First compilation
BLK0276-2 - SWEET HOME - PROFUMATORE AMBIENTE SANDALO		Printed on 03/12/2024
		24/35
LD50 (Oral):1160 mg/kg guinea pig LC50 (Inhalation vapours):68,889 mg/l/4h rat METHANOL LD50 (Oral):> 1187 mg/kg Rat LC50 (Inhalation vapours):43,68 mg/l/6h Rat toluene LD50 (Dermal):> 5000 mg/kg bw Rabbit LD50 (Oral):> 5000 mg/kg bw Rat LC50 (Inhalation vapours):100 ppm human phenol LD50 (Dermal):525 mg/kg bw Rat LD50 (Oral):282 mg/kg bw Mouse acetic acid ...% LD50 (Dermal):1060 mg/kg Rabbit LD50 (Oral):3310 mg/kg Rat LC50 (Inhalation vapours):11,4 mg/l/4h Rat SKIN CORROSION / IRRITATION Does not meet the classification criteria for this hazard class SERIOUS EYE DAMAGE / IRRITATION Causes serious eye irritation RESPIRATORY OR SKIN SENSITISATION Sensitising for the skin GERM CELL MUTAGENICITY Does not meet the classification criteria for this hazard class CARCINOGENICITY Does not meet the classification criteria for this hazard class toluene Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 1999). The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential". REPRODUCTIVE TOXICITY Does not meet the classification criteria for this hazard class STOT - SINGLE EXPOSURE Does not meet the classification criteria for this hazard class STOT - REPEATED EXPOSURE Does not meet the classification criteria for this hazard class		

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it has negative effects on the aquatic environment.

12.1. Toxicity

Reaction mass of 1-[(1R*,6S*)-2,2,6-trimethylcyclohexyl]hexan-3-ol and 1-[(1S*,6S*)-2,2,6-trimethylcyclohexyl]hexan-3-ol	
LC50 - for Fish	999 mg/l/96h
EC50 - for Crustacea	696 mg/l/48h
CINNAMALDEHYDE	
LC50 - for Fish	> 3,5 mg/l/96h
EC50 - for Crustacea	3,21 mg/l/48h
EC50 - for Algae / Aquatic Plants	16,09 mg/l/72h
Chronic NOEC for Crustacea	0,049 mg/l
(±) trans—3,3-dimethyl-5-(2,2,3-trimethyl-cyclopent-3-en-1-yl)-pent-4-en-2-ol	
LC50 - for Fish	1,2 mg/l/96h Oncorhynchus mykiss
EC50 - for Crustacea	1 mg/l/48h
EC50 - for Algae / Aquatic Plants	0,88 mg/l/72h
Chronic NOEC for Crustacea	0,56 mg/l
Chronic NOEC for Algae / Aquatic Plants	0,45 mg/l
toluene	
LC50 - for Fish	5,5 mg/l/96h Oncorhynchus kisutch
EC50 - for Crustacea	3,78 mg/l
EC50 - for Algae / Aquatic Plants	134 mg/l/3 h Chlorella vulgaris and Chlamydomonas angulosa
Chronic NOEC for Algae / Aquatic Plants	10 mg/l/72 h Skeletonema costatum
phenol	
LC50 - for Fish	21,93 mg/l/14 d Poecilia reticulata
EC50 - for Crustacea	3,1 mg/l/48h Ceriodaphnia dubia
EC50 - for Algae / Aquatic Plants	61,1 mg/l/96h 96 h EC50 (cell number increase): 61.1 mg phenol/L (95 % confidence limits: 37.1 - 84.5 mg/L)
Chronic NOEC for Fish	4 mg/l/14 d Poecilia reticulata
Chronic NOEC for Crustacea	0,16 mg/l

Suarez Company		Revision nr. 1
		Dated 03/12/2024
		First compilation
BLK0276-2 - SWEET HOME - PROFUMATORE AMBIENTE SANDALO		Printed on 03/12/2024
		26/35
benzyl salicylate		
LC50 - for Fish	1,03 mg/l/96h Danio rerio	
EC50 - for Crustacea	1,16 mg/l/48h Daphnia magna	
EC50 - for Algae / Aquatic Plants	1,29 mg/l/72h Pseudokirchneriella subcapitata	
Chronic NOEC for Crustacea	0,894 mg/l Daphnia magna	
Chronic NOEC for Algae / Aquatic Plants	0,502 mg/l Pseudokirchneriella subcapitata	
2,6-di-tert-butyl-p-cresol		
LC50 - for Fish	0,199 mg/l/96h	
EC50 - for Crustacea	0,48 mg/l/48h	
EC50 - for Algae / Aquatic Plants	> 0,4 mg/l/72h	
Chronic NOEC for Fish	0,053 mg/l	
Chronic NOEC for Crustacea	0,15 mg/l	
HEPTANE		
LC50 - for Fish	375 mg/l/96h Tilapia mossambica	
EC50 - for Crustacea	82,5 mg/l/48h Daphnia magna	
EC50 - for Algae / Aquatic Plants	1,5 mg/l/72h Algae	
(4-TERT-BUTYLCYCLOHEXYL) ACETATE		
LC50 - for Fish	8,6 mg/l/96h Cyprinus carpio	
EC50 - for Crustacea	5,3 mg/l/48h Daphnia magna	
EC50 - for Algae / Aquatic Plants	22 mg/l/72h Desmodesmus subspicatus	
Chronic NOEC for Algae / Aquatic Plants	6,8 mg/l Desmodesmus subspicatus	
DIPROPYLENE GLYCOL MONOMETHYL ETHER		
LC50 - for Fish	> 150 mg/l/96h	
EC50 - for Crustacea	> 1000 mg/l/48h	
EC50 - for Algae / Aquatic Plants	> 969 mg/l/72h	
Chronic NOEC for Crustacea	1000 mg/l 48h	
Chronic NOEC for Algae / Aquatic Plants	969 mg/l	
CINEOLE		
LC50 - for Fish	57 mg/l/96h Oncorhynchus mykiss	
EC50 - for Crustacea	> 100 mg/l/48h Daphnia magna	
EC50 - for Algae / Aquatic Plants	74 mg/l/72h	
Chronic NOEC for Fish	32 mg/l Oncorhynchus mykiss	
Chronic NOEC for Crustacea	100 mg/l Daphnia magna	
Chronic NOEC for Algae / Aquatic Plants	9,1 mg/l	
ETHANOL		
LC50 - for Fish	14200 mg/l/96h	
EC50 - for Crustacea	454 mg/l/48h	

Suarez Company		Revision nr. 1
		Dated 03/12/2024
		First compilation
BLK0276-2 - SWEET HOME - PROFUMATORE AMBIENTE SANDALO		Printed on 03/12/2024
		27/35
EC50 - for Algae / Aquatic Plants	275 mg/l/72h	
Chronic NOEC for Fish	250 mg/l	
Chronic NOEC for Crustacea	96 mg/l	
Chronic NOEC for Algae / Aquatic Plants	11,5 mg/l	
acetic acid ...%		
LC50 - for Fish	> 1000 mg/l/96h	
EC50 - for Crustacea	> 300,82 mg/l/48h	
EC50 - for Algae / Aquatic Plants	> 1000 mg/l/72h	
METHANOL		
LC50 - for Fish	15320 mg/l/96h	Leuciscus idus melanotus
EC50 - for Crustacea	18260 mg/l/96 h	Daphnia magna
EC50 - for Algae / Aquatic Plants	22000 mg/l/96 h	Pseudokirchneriella subcapitata
Chronic NOEC for Fish	3950 mg/l/96 h	Danio rerio
Chronic NOEC for Crustacea	7960 mg/l/96 h	Mytilus edulis
linalool		
LC50 - for Fish	27,8 mg/l/96h	Oncorhynchus mykiss
EC50 - for Crustacea	59 mg/l/48h	Daphnia magna
EC50 - for Algae / Aquatic Plants	88,3 mg/l/72h	Desmodesmus subspicatus
Chronic NOEC for Fish	< 3,5 mg/l	Oncorhynchus mykiss
REACTION MASS OF 2-METHYLBUTYL SALICYLATE AND PENTYL SALICYLATE		
LC50 - for Fish	1,34 mg/l/96h	
EC50 - for Crustacea	0,88 mg/l/48h	
EC50 - for Algae / Aquatic Plants	0,49 mg/l/72h	
Chronic NOEC for Algae / Aquatic Plants	0,2 mg/l	
12.2. Persistence and degradability		
Reaction mass of 1-[(1R*,6S*)-2,2,6-trimethylcyclohexyl]hexan-3-ol and 1-[(1S*,6S*)-2,2,6-trimethylcyclohexyl]hexan-3-ol		
NOT rapidly degradable		
CINNAMALDEHYDE		
Rapidly degradable		
(±) trans— 3,3-dimethyl-5-(2,2,3-trimethyl-cyclopent-3-en-1-yl)-pent-4-en-2-ol		
Rapidly degradable		
toluene		
Solubility in water	100 - 1000 mg/l	
Rapidly degradable		
phenol		
Rapidly degradable		
benzyl salicylate		
Rapidly degradable		

Suarez Company		Revision nr. 1
		Dated 03/12/2024
		First compilation
BLK0276-2 - SWEET HOME - PROFUMATORE AMBIENTE SANDALO		Printed on 03/12/2024
		28/35
2,6-di-tert-butyl-p-cresol		
Rapidly degradable		
HEPTANE		
Solubility in water	0,1 - 100 mg/l	
Rapidly degradable		
(4-TERT-BUTYLCYCLOHEXYL) ACETATE		
Rapidly degradable		
DIPROPYLENE GLYCOL MONOMETHYL ETHER		
Solubility in water	1000 - 10000 mg/l	
Rapidly degradable		
CINEOLE		
Rapidly degradable		
ETHANOL		
Solubility in water	1000 - 10000 mg/l	
Rapidly degradable		
acetic acid ...%		
Solubility in water	> 10000 mg/l	
Rapidly degradable		
METHANOL		
Solubility in water	1000 - 10000 mg/l	
Rapidly degradable		
ACETONE		
Rapidly degradable		
linalool		
Rapidly degradable		
REACTION MASS OF 2-METHYLBUTYL SALICYLATE AND PENTYL SALICYLATE		
Rapidly degradable		
12.3. Bioaccumulative potential		
CINNAMALDEHYDE		
BCF	147,91	
(±) trans—		
3,3-dimethyl-5-(2,2,3-trimethyl-cyclopent-3-en-1-yl)-pent-4-en-2-ol		
BCF	46	
toluene		
Partition coefficient: n-octanol/water	2,73	
BCF	90	
phenol		
Partition coefficient: n-octanol/water	1,47	
BCF	17,5	
2,6-di-tert-butyl-p-cresol		
Partition coefficient: n-octanol/water	5,1	
BCF	598,4 -	

Suarez Company		Revision nr. 1
		Dated 03/12/2024
		First compilation
BLK0276-2 - SWEET HOME - PROFUMATORE AMBIENTE SANDALO		Printed on 03/12/2024
		29/35
HEPTANE		
Partition coefficient: n-octanol/water	4,5	
BCF	552	
DIPROPYLENE GLYCOL MONOMETHYL ETHER		
Partition coefficient: n-octanol/water	0,0043	
CINEOLE		
BCF	155 l/kg	
ETHANOL		
Partition coefficient: n-octanol/water	-0,35	
acetic acid ...%		
Partition coefficient: n-octanol/water	-0,17	
METHANOL		
Partition coefficient: n-octanol/water	-0,77	
BCF	0,2	
ACETONE		
Partition coefficient: n-octanol/water	-0,23	
BCF	3	
REACTION MASS OF 2-METHYLBUTYL SALICYLATE AND PENTYL SALICYLATE		
BCF	1170	
12.4. Mobility in soil		
CINNAMALDEHYDE		
Partition coefficient: soil/water	1,958	
(±) trans— 3,3-dimethyl-5-(2,2,3-trimethyl-cyclopent-3- en-1-yl)-pent-4-en-2-ol		
Partition coefficient: soil/water	3,023	
toluene		
Partition coefficient: soil/water	2,31	
phenol		
Partition coefficient: soil/water	1,57 l/kg	
2,6-di-tert-butyl-p-cresol		
Partition coefficient: soil/water	4,2	

BLK0276-2 - SWEET HOME - PROFUMATORE AMBIENTE SANDALO

HEPTANE

Partition coefficient: soil/water 2,38

CINEOLE

Partition coefficient: soil/water 2,33

acetic acid ...%

Partition coefficient: soil/water 1,153

REACTION MASS OF 2-METHYLBUTYL
SALICYLATE AND PENTYL SALICYLATE

Partition coefficient: soil/water 37

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information**14.1. UN number or ID number**

ADR / RID, IMDG, IATA: UN 1170

14.2. UN proper shipping name

ADR / RID:ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

IMDG:ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

IATA:ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

14.3. Transport hazard class(es)

ADR / RID:

Class: 3

Label: 3

IMDG:

Class: 3

Label: 3

IATA:

Class: 3

Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA:

II

14.5. Environmental hazards

ADR / RID:NO

IMDG:not marine pollutant

IATA:NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 33	Limited Quantities: 1 L	Tunnel restriction code: (D/E)
	Special provision: 144, 601		
IMDG:	EMS: F-E, S-D	Limited Quantities: 1 L	
IATA:	Cargo:	Maximum quantity: 60 L	Packaging instructions: 364
	Passengers:	Maximum quantity: 5 L	Packaging instructions: 353
	Special provision:	A3, A58, A180	

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P5c

BLK0276-2 - SWEET HOME - PROFUMATORE AMBIENTE SANDALO

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage $\geq$ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 2: Hazard to waters

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

BLK0276-2 - SWEET HOME - PROFUMATORE AMBIENTE SANDALO

Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3
Muta. 2	Germ cell mutagenicity, category 2
Repr. 2	Reproductive toxicity, category 2
Acute Tox. 3	Acute toxicity, category 3
STOT SE 1	Specific target organ toxicity - single exposure, category 1
Acute Tox. 4	Acute toxicity, category 4
Asp. Tox. 1	Aspiration hazard, category 1
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Skin Corr. 1A	Skin corrosion, category 1A
Skin Corr. 1B	Skin corrosion, category 1B
Skin Corr. 1C	Skin corrosion, category 1C
Skin Corr. 1	Skin corrosion, category 1
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
Skin Sens. 1A	Skin sensitization, category 1A
Skin Sens. 1B	Skin sensitization, category 1B
STOT SE 3	Specific target organ toxicity - single exposure, category 3
STOT SE 2	Specific target organ toxicity - single exposure, category 2
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H341	Suspected of causing genetic defects.
H361d	Suspected of damaging the unborn child.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H331	Toxic if inhaled.
H370	Causes damage to organs.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H371	May cause damage to organs.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Suarez Company	Revision nr. 1
	Dated 03/12/2024
BLK0276-2 - SWEET HOME - PROFUMATORE AMBIENTE SANDALO	First compilation
	Printed on 03/12/2024
	34/35

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

- LEGEND:
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
 - ATE: Acute Toxicity Estimate
 - CAS: Chemical Abstract Service Number
 - CE50: Effective concentration (required to induce a 50% effect)
 - CE: Identifier in ESIS (European archive of existing substances)
 - CLP: Regulation (EC) 1272/2008
 - DNEL: Derived No Effect Level
 - EmS: Emergency Schedule
 - GHS: Globally Harmonized System of classification and labeling of chemicals
 - IATA DGR: International Air Transport Association Dangerous Goods Regulation
 - IC50: Immobilization Concentration 50%
 - IMDG: International Maritime Code for dangerous goods
 - IMO: International Maritime Organization
 - INDEX: Identifier in Annex VI of CLP
 - LC50: Lethal Concentration 50%
 - LD50: Lethal dose 50%
 - OEL: Occupational Exposure Level
 - PBT: Persistent, bioaccumulative and toxic
 - PEC: Predicted environmental Concentration
 - PEL: Predicted exposure level
 - PMT: Persistent, mobile and toxic
 - PNEC: Predicted no effect concentration
 - REACH: Regulation (EC) 1907/2006
 - RID: Regulation concerning the international transport of dangerous goods by train
 - TLV: Threshold Limit Value
 - TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
 - TWA: Time-weighted average exposure limit
 - TWA STEL: Short-term exposure limit
 - VOC: Volatile organic Compounds
 - vPvB: Very persistent and very bioaccumulative
 - vPvM: Very persistent and very mobile
 - WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707
24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)

BLK0276-2 - SWEET HOME - PROFUMATORE AMBIENTE SANDALO

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.