

¹ Chapter 1

² Introduction

³ The aim of the thesis is to present and discuss applications of diamond based particle
⁴ detectors.

⁵ The introductory chapter paints a picture of the current state of particle physics
⁶ research. It presents some of the research institutes that are active in this field,
⁷ pushing the boundaries of human knowledge further. It explains their goals and the
⁸ means with which they are achieving them. Next section describes particle detectors
⁹ in a broad sense – their history and the types existing now. One type in particular –
¹⁰ a diamond detector – is then described more in detail.

¹¹ Second chapter discusses the properties of diamond detectors. Dissecting the de-
¹² tector chain into individual parts and describing them in detail – sensors, amplifiers,
¹³ digitizers and data processors. We learn about energy resolution in diamond, analog
¹⁴ and digital noise contribution etc. Principles of signal formation are presented, start-
¹⁵ ing with the famous Shockley-Ramo theorem and building from there. We will see
¹⁶ that different types of radiation induce different electrical signals.

¹⁷ The base laid down in the second chapter is complemented in the third where the
¹⁸ measurements are presented and the results discussed. The focus is on diamond's
¹⁹ measurement stability with respect to irradiation damage. To carry out this study,
²⁰ two diamond sensors were irradiated to two different doses, with the measurements
²¹ carried out before and after irradiation.

²² Building on the understanding of the behaviour of the diamond, two applications
²³ were developed. The fourth chapter describes the Diamond Beam Monitor, a detec-
²⁴ tor that makes use of the diamond's charge measurement capabilities and its high
²⁵ radiation hardness. This detector has been installed in one of the largest particle
²⁶ physics experiments in the world and is currently taking data. Here, its development
²⁷ process is presented: the quality control procedures during assembly and installation,
²⁸ its performance in the test environment and some recent experimental data.

²⁹ The final and most important chapter describes the real-time application for par-
³⁰ ticle identification. Here the shape of the electrical signal of the diamond sensor is
³¹ used to discriminate different types of radiation in real time and dead time free. The
³² chapter includes the description of the device's logic and algorithms, lab test results
³³ and the application in neutron monitoring.




Figure 1.1: Standard model [8]

³⁴ 1.1 Fundamental research

³⁵ This section gives a short overview of the institutes and collaborations carrying out
³⁶ fundamental physics research. The facilities were used for the research carried out in
³⁷ this thesis.

³⁸ The aim of fundamental (even pure or basic) research is to improve the scientific
³⁹ theories and verify them to improve our understanding of the universe. It does not
⁴⁰ in itself focus on applying this research by developing products and is not meant to
⁴¹ create a direct return on investment. Instead, it expands the overall knowledge of the
⁴² human kind - by making the results freely available to the general public.

⁴³ Particle physics research peers into the smallest constituents of the universe, dis-
⁴⁴ secting the atoms into quarks and electrons, catching cosmic rays and figuring out
⁴⁵ what dark matter is made up of. Particle physicists want to explain the phenomena
⁴⁶ surrounding us by studying the fundamental particles and the mechanisms governing
⁴⁷ their interactions. By understanding this, we would be able to answer difficult ques-
⁴⁸ tions; How did the universe begin? What is the invisible force (dark matter, dark
⁴⁹ energy) pushing the galaxies apart from each other? Where does mass come from?
⁵⁰ Why is there almost no antimatter in the universe? In this effort, scientists have
⁵¹ formed several theories. One of them, the Standard Model of particles, is currently
⁵² the best theory to describe the visible universe.

⁵³ **The Standard Model** (SM) is a physics theory developed in the 1970's [12]. It
⁵⁴ was designed to explain the current experimental results. As such, it was also able to
⁵⁵ predict new discoveries and was a driving force for the scientists to invest time and
⁵⁶ money in developing new experiments. To date, it is by far the most established and
⁵⁷ verified physics theory. It explains how the basic building blocks of matter – *fermions*
⁵⁸ – interact with each other via mediators of interactions called *bosons*. There are two
⁵⁹ main families of fermions - *quarks* and *leptons*, as shown in diagram 1.1. Each group
⁶⁰ consists of six members divided into three *generations*, the first being the lightest and
⁶¹ most stable and the last the heaviest – unstable. The nature around us is made up
⁶² of the stable particles – those from the second or third generations can only be found

in cosmic rays or produced artificially using particle accelerators.

Quarks have a spin of 1/2 and a charge of either +2/3 (up, charm, top) or -1/3 (down, strange, bottom) while the leptons have a spin of 1/2 and a charge of either 1 (electron, muon, tau) or 0 (electron neutrino, muon neutrino, tau neutrino). Leptons only exist individually – they do not cluster. Quarks, however, immediately form a cluster of either two (unstable), three (more stable) or five (unstable). Two up and one down quark make up a proton whereas two down and one up quark make up a neutron.

In addition to fermions, each particle has a corresponding antiparticle – a particle with the same mass but the opposite charge. If an antiparticle hits a particle, they annihilate each other, producing energy in form of photons.

Bosons are the carriers of force, mediating weak (W^+ , W^- and Z bosons), strong (gluons) and electromagnetic (photons) interactions. The weak interaction is responsible for the radioactive decay of subatomic particles, thus playing an essential role in nuclear fission – a process taking place in the stars. The electromagnetic interaction works at a macroscopic level – it allows particles to interact via electric and magnetic fields. The strong interaction is effective at distances of a femtometer and it governs how quarks interact and bind with each other. An additional boson is the so-called Higgs boson and was discovered at CERN in 2012 []. It is a representation of the Higgs mechanism, which gives rise to the masses of all the particles in the Standard Model.

1.1.1 CERN

CERN (European Centre for Nuclear Research) [2] is a nuclear research institute housing the largest particle physics laboratory in the world. It straddles the Swiss-French border just outside Geneva. It was established in 1954 to bring the war-torn Europe together by means of fundamental scientific research. Today, it has 22 member state countries and several observer states. More than 10000 scientists, engineers, technicians, students and others from all around the globe work at CERN on many projects in research fields ranging from particle to nuclear physics. The scope is to probe the fundamental structure of the universe and to understand the mechanisms governing it. Therefore CERN's main function is to provide the infrastructure for high-energy physics experiments. These are carried out using large machines called particle accelerators. These instruments boost beams of particles to high energies before making them collide with each other or with stationary targets. The resulting collisions are recorded by particle detectors and later analysed by physicists. To carry out research on the smallest constituents of matter, their dynamics and structure, very high energies are needed. This is why the most powerful accelerators are used for fundamental research. The largest accelerators at CERN are the Proton Synchrotron [], the Super Proton Synchrotron [11] and the Large Hadron Collider [].




Figure 1.2: The Large Hadron Collider [7]

¹⁰² 1.1.2 Particle accelerators

¹⁰³ A particle accelerator is a machine that accelerates beams of charged particles like
¹⁰⁴ protons, electrons, ions etc. It generates electric fields that add kinetic energy to
¹⁰⁵ the particles, speeding them up. It then uses magnets to keep them within a defined
¹⁰⁶ trajectory. This can be either linear (linear accelerators) or circular (circular or cyclic
¹⁰⁷ accelerators). The advantage of the latter ones is that they can accelerate particles
¹⁰⁸ many times while keeping them in orbit.

¹⁰⁹ Particle accelerators are used in numerous fields ranging from fundamental and
¹¹⁰ material research, cancer treatment to industrial applications, such as biomedicine
¹¹¹ and material processing. There are several types of accelerators: electrostatic accelerators,
¹¹² linear accelerators (LINACs), cyclotrons, synrocyclotrons, synchrotrons, syn-
¹¹³ chrotron radiation sources and fixed-field alternating gradient accelerators (FFAGs).

¹¹⁴ **The Large Hadron Collider** (LHC, figure 1.2) at CERN is the largest particle
¹¹⁵ collider in the world. It is a 27 km long circular machine set up in a tunnel deep
¹¹⁶ under the surface (ranging from 50 to 175 m). It accelerates two proton beams to
¹¹⁷ the energy of 6.5 TeV per beam before it makes them to collide with each other at
¹¹⁸ four different points around its circumference. The LHC was build between 1998 and
¹¹⁹ 2008 and was first successfully started in 2010 and operated stably until 2013 when
¹²⁰ it underwent a two years long upgrade. They restarted it at the beginning of 2015.
¹²¹ The hair-thin particle beams travel inside two evacuated pipes with a \sim 5 cm radius.
¹²² Coils made up of a superconductive material are wound up around the pipes in special
¹²³ patterns. When they are cooled down to -271 °C using liquid helium, they become
¹²⁴ superconductive - the resistivity of the material drops significantly, minimising the
¹²⁵ heat dissipation despite high electric currents. These produce strong magnetic fields
¹²⁶ which bend the particles and keep them in a circular trajectory. The particles are
¹²⁷ accelerated when traversing the radiofrequency (RF) cavities with the RF frequency




Figure 1.3: The ATLAS Experiment [13]

of 400 MHz. This oscillating frequency creates so-called buckets of bunches which are 2.5 ns long. Only one out of ten buckets is being filled, so the bunches are spaced at 25 ns. This defines the machine's clock as well as the maximum rate of collisions - the bunches travelling in the opposite direction will cross at the intersections up to 40 million times per second. Currently around 20 collisions occur during every crossing, making the maximum collision rate of 10^9 per second. The number of collisions will further increase in the next years, when they will increase the number of particles in every bunch and decrease the transverse spread of the bunches – squeeze them, therefore increase their density and the collision probability.

1.1.3 The ATLAS experiment

ATLAS (short for A Toroidal Lhc ApparatuS, figure 1.3) [] is a particle physics experiment at CERN. Its purpose is to verify current theories and search for new discoveries by observing and analysing high energy proton-proton collisions produced by the LHC. It is the biggest experiment at CERN by dimensions (45 m in length and 26 m in height) and the number of people involved (more than 3000 physicists and engineers). The ATLAS detector consists of many detectors, each designed to measure a specific property of the particles and photons produced during the collision. The closest to the collision point is the Inner Detector (ID), which consists of several layers of highly spatially segmented semiconductor sensors. These can record the path of the individual particles and photons. In addition, a strong magnetic field of 2 T curves the paths of the charged particles, which in turn allows the ID to identify an individual particle's charge and momentum. The next two parts are the electromagnetic and tile calorimeter. These detectors weigh a few thousand tonnes and measure the energy of

151 the particles that are stopping in the bulk. The only particles that make it through
152 the calorimeters are muons. These are detected by the Muon Spectrometer, a set of
153 large plates placed all around the inner layers. Last is the superconductive magnet,
154 which provides the magnetic field through the whole of ATLAS except the ID, which
155 already has its own magnets. To sum up, the Inner Detector measures the charge and
156 momenta of the particles and photons, the calorimeters measure their energies, the
157 Muon Spectrometer measures muons and the magnets provide magnetic fields, which
158 curve the trajectories of the charged particles, facilitating the charge and momentum
159 measurements.

160 A complex Trigger and Data Acquisition system (TDAQ) is in place to distribute
161 the clock signal, configure the detectors, trigger them and handle the output data.

162 The ATLAS detector has been designed to measure every collision taking place in
163 its core. With 25 ns between collisions, this makes up 40 million collisions per second.
164 In reality, the maximum rate is about 300 kHz. The recorded collision is called an
165 event. Every event holds information from all the detector channels within ATLAS.
166 With $\sim 10^6$ channels, an event size is 10 MB. At the maximum achievable rate this
167 means a data rate of up to 3 TB/s. Unfortunately no supercomputer existing today is
168 capable of reading in and saving such a huge amount of data. This is where the trigger
169 logic comes into play. It is programmed to decide in the order of tens of nanoseconds
170 after an event whether this is a potentially interesting event or not. If so, it triggers
171 the readout of the whole detector. This way, the recorded event rate is reduced from
172 300 kHz to ~ 500 Hz, which is already within the limits of the computing centre's
173 capabilities.

174 1.1.4 Atominsttitut, Vienna

175 Atominsttitut (ATI) [1], an institute for atomic and subatomic physics, was estab-
176 lished in 1958 in Vienna as an inter-university institute. It currently houses around
177 200 people involved in a broad range of research fields: quantum, particle, neutron,
178 nuclear, radiation and reactor physics, quantum optics etc. Its central facility is a
179 TRIGA MARK II neutron reactor (described in detail below).

180 As of 2002 the ATI is part of the University of Technology in Vienna.

181 **TRIGA MARK II neutron reactor** [4] is a reactor of a swimming-pool type
182 used for training, research and isotope production. It is one of 40 such reactors
183 worldwide, produced by an californian company General Atomic in the early 60's. It
184 is capable of continuous operation at a maximum output power of 250 kW. The reactor
185 core consists of 3 kg of 20 % enriched uranium (^{235}U). The fuel moderator rods are
186 mostly made up of zirconium with low percentage of hydrogen and uranium. Both the
187 core and the rods are immersed in a pool of water as shown in figure 1.4 for the purpose
188 of cooling and radiation protection. The surrounding concrete walls are 2 m wide
189 with an added graphite layer for improved shielding. Four main experimental beam
190 holes are placed radially through the walls. All exits are heavily shielded to prevent
191 radiation damage to people, but still leaving enough space to set up experiments.




Figure 1.4: The TRIGA MARK II neutron reactor [5]

192 Apart from the beam holes, there are several other exits and components, e.g. a
193 thermal column for generation of thermal (low energetic) neutrons.

194 1.1.5 n-ToF, CERN

195 n-ToF (or neutron time-of-flight) [3] is a scientific collaboration with the aim of study-
196 ing neutron-nucleus interactions. Over 30 institutes and universities are currently
197 active members of this collaboration, among them Atominstutut in Vienna. n-ToF
198 is also a facility at CERN where the experiments are carried out in a 200 m long
199 experimental area. The knowledge stemming from the experimental results can then
200 be applied in various fields ranging from nuclear technology and cancer therapy to
201 astrophysics.

202 A pulsed beam of highly energetic protons (20 GeV/c) is produced by the Proton
203 Synchrotron (PS) and aimed at a fixed lead spallation target. Each proton hitting
204 the target produces around 300 neutrons of various energies. Initially highly energetic
205 neutrons are slowed down by the target and by a slab of water placed behind it. This
206 broadens their energy spectrum, which then ranges from meV (so-called thermal
207 neutrons) to GeV (so-called fast neutrons). The neutrons are then collimated and
208 sent through a 185 m long evacuated pipe to the experimental area, where they are
209 made to collide with another target or a sample. The radiation resulting from the
210 collisions is detected by a set of dedicated detectors around the interaction point (seen
211 in figure 1.5). Having different energies, neutrons travel with different speeds, highly
212 energetic ones reaching the target faster than those with low energies. Analysis of
213 the collisions with a precise timing allows us to determine the interaction probability
214 with sample material as a function of incident neutron energy.

215 1.2 Particle detectors

216 Particle detectors, or radiation detectors, have first come into use at the end of the
217 19th century. At that time Wilhelm Röntgen used a photographic plate onto which




Figure 1.5: The calorimeter in the n-ToF area [6]

he shone X-rays. Soon after, in 1912, Victor F. Hess discovered cosmic rays during a balloon flight. This paved way for development of particle detectors. A cloud chamber was designed – a chamber filled with a supersaturated vapour of water or alcohol. If a highly energetic particle traversed the chamber, the mixture ionised, creating condensation nuclei. These traces were visible and were photographed. All the subsequent particle detectors relied on the same principle of interaction between the particles – ionisation. The bubble chamber invented in 1952 used a superheated transparent liquid – a liquid heated just below its boiling point. A particle ionised the liquid, forming microscopic bubbles along its trajectory. Then followed the spark chamber and wire chamber where the particle ionised the gas, causing a spark between two parallel plates at a high potential difference. These are nowadays used in museums as showcases. Next were ionisation chambers, which measured the induced current of the free ionised charges moving in an externally applied electric field. Finally in the 1960s, semiconductor detectors were introduced. Their principle of operation is similar to that of an ionisation chamber, with the difference that a semi-conductive material is used as an ionisation medium instead of gas. Every technology has its advantages and disadvantages. Nowadays an ensemble of several types of detectors is used as a single detector system. There are many considerations that need to be taken into account when designing such a system: detector geometry, segmentation, event rate, efficiency, readout, support structures, cabling, cooling, cost etc.

On large, particle detectors can be divided in two groups: tracking detectors and calorimeters. The former are designed to measure trajectories (momentum) of particles and photons with a minimal impact on their flight path or energy. They must be built with a high spatial resolution and lightweight. Typically they are



Figure 1.6: The Insertable B-Layer – a silicon particle tracker installed in the ATLAS experiment in 2014 [10]

242 semiconductor detectors. The calorimeters, on the other hand, measure the energy
 243 of the particles/photons by stopping them. This means they need to be heavy and
 244 dense. A typical physics experiment nowadays would consist of a tracking detector
 245 enclosed by a calorimeter. This way both the momentum and energy are derived,
 246 measuring energy, charge and trajectory of every particle/photon.

247 1.2.1 Semiconductor detectors

248 Semiconductor particle detectors are devices that use a semiconductor for detecting
 249 radiation. They work on the principle of an ionisation chamber. An incident particle
 250 or a photon ionises the atoms in the crystal lattice. The freed charges start drift-
 251 ing in an externally applied electric field, inducing current on the electrodes. The
 252 charges are freed if the deposited energy is higher than the energy band gap. There
 253 are many semiconductor materials currently existing, each with a different band gap.
 254 Germanium (Ge), for instance, has a band gap of 0.67 eV, which means that most
 255 of the electrons at the room temperature will already be in an excited state. Di-
 256 amond's 5.5 eV band gap, on the other hand, is too high for the visible light to
 257 excite the electrons. However, silicon has been the material of choice for the majority
 258 of semiconductor applications, including radiation detectors. Semiconductor detec-
 259 tors are most widely used for tracking applications, like the Insertable B-Layer (see
 260 figure 1.6) [14], which was installed in ATLAS Experiment in 2014. They can be
 261 produced into light and thin sensors, they have a fast signal response, they are highly
 262 efficient and highly resistant to radiation damage. They also allow for a fine spatial
 263 segmentation to increase the tracking resolution. Semiconductor sensors come in sev-
 264 eral configurations. The simplest type is a pad – a single plate measuring 25 mm^2 .
 265 Pads are used for particle counting and radiation monitoring. Next is a strip detector,
 266 a more finely segmented detector made out of long parallel sensing areas or strips.
 267 Each strip has its own signal line for readout. Usually the strip detectors are used in




Figure 1.7: A pCVD diamond pad detector [9]

268 pairs – one detector is placed on top of the other at a 90° angle to increase spatial
 269 resolution in both axes. The third and the most finely segmented is a pixel detector,
 270 consisting of a 2D array of independent sensing areas. In tracking applications, pixel
 271 detectors are used where the detection resolution is the highest. Due to their high
 272 production cost and a high number of signal channels, they can only cover limited
 273 areas. Strip detectors are cheaper to produce and can be used to cover larger areas
 274 in several consecutive layers.

275 1.2.2 Diamond sensors

276 Diamond has been known for over two millennia, valued for its mechanical properties
 277 and its appearance. When we learnt how to synthesise it, diamond found its way to
 278 a broad range of industries which exploited its optical and electrical properties. The
 279 discovery of the Chemical Vapour Deposition (described below) as a new synthesis
 280 process gave rise to a range of new applications. From being used on machines
 281 for drilling tunnels it found its way to electronics, high-power switching devices,
 282 electrochemical systems, radiation sensors, quantum computing etc. Recently it was
 283 found that it also exhibits superconductivity. This thesis focuses on the use of diamond
 284 for radiation detection. Compared to a natural diamond, a detector-grade CVD
 285 diamond has almost no impurities (foreign atoms like nitrogen or boron). The carbon
 286 lattice is very uniform, which improves its electrical properties. It is an almost perfect
 287 insulator, but behaves as a semiconductor under certain conditions. Compared to
 288 silicon, the most widely used semiconductor material for radiation detection, it has
 289 many advantages, which are described in detail in chapter ???. Figure 1.7 shows a
 290 diamond pad detector produced by CVIDEC Instrumentation GmbH.

291 **Chemical vapour deposition** (CVD) is a process where a material is deposited
 292 from a gas onto a substrate, involving chemical reactions. It is often carried out
 293 under high pressure and high temperatures. It takes place in enclosed chambers

294 called furnaces with careful regulation of the temperature, pressure and gas mixture.
295 Synthetic diamond is grown at 700–900 °C with a mixture of hydrogen and methane
296 gas. At this temperature the molecules dissociate into carbon and hydrogen atoms.
297 The carbon atoms are the building blocks and are deposited on the surface of the
298 substrate. However, they would rather form graphitic bonds as they are more stable
299 than diamond bonds. Nevertheless, with high pressure, high temperature and with
300 the abrasive atomic hydrogen, the graphitic double bonds are broken up and converted
301 into diamond bonds. The speed of the growth can be anywhere between 0.1 and 10
302 micron per hour. The detector grade samples are grown at a rate of the order of
303 1 micron per hour. They can grow up to several millimetres in thickness. Their
304 width, however, depends entirely on the substrate used. Diamond can be deposited
305 on various materials: diamond, silicon, tungsten, quartz glass etc. The substrate
306 material must be able to withstand the high temperatures during the CVD process.
307 The diamond substrate does not need any surface pre-treatment. Carbon atoms form
308 bonds with atoms in the existing crystal structure. This is a so-called homoepitaxial
309 growth where the newly deposited atoms retain the orientation of the structure in the
310 substrate. Other non-diamond substrates, however, need to be pre-treated, usually by
311 being polished using diamond powder. Some powder particles remain on the surface,
312 acting as seeds for the growth of small crystals or grains. These grains grow and
313 at some point merge with the adjacent ones, making up a compact material. The
314 lower side is later polished away. These diamonds are called *polycrystalline* (pCVD)
315 whereas those grown on a diamond substrate are *single crystal* (sCVD) diamonds.
316 The area of the former can be large - up to 0.5 m² or more compact 15 cm² in the case
317 of detector grade diamonds. The sCVD diamonds, on the other hand, can currently
318 only measure up to 1.5 cm².

³¹⁹ Bibliography

- ³²⁰ [1] *Atominstytut, Technical University of Vienna, Austria.*
- ³²¹ [2] *European Centre for Nuclear Research, CERN.*
- ³²² [3] *Neutron Time-of-flight experiment.*
- ³²³ [4] *TRIGA MARK II neutron reactor.*
- ³²⁴ [5] General Atomics. *View of the TRIGA reactor.* 2015.
- ³²⁵ [6] Maximilien Brice. *View of the nTOF detector.* Oct 2010.
- ³²⁶ [7] Maximilien Brice. *LHC tunnel.* Jan 2011.
- ³²⁷ [8] Daniel Dominguez. *Standard Model. Le modele standard.* General Photo, Mar 2015.
- ³²⁸ [9] CIVIDEC Instrumentation GmbH. *sCVD diamond sensor.* 2015.
- ³³⁰ [10] Claudia Marcelloni De Oliveira. *IBL installation into the inner detector of the ATLAS Experiment side C.* General Photo, May 2014.
- ³³² [11] W P C Mills. *The present performance of the SPS.* *IEEE Trans. Nucl. Sci.*, 26(CERN-SPS-AOP-79-9):3176–3178. 3 p, Mar 1979.
- ³³⁴ [12] S. F. Novaes. *Standard model: An Introduction.* In *Particles and fields. Proceedings, 10th Jorge Andre Swieca Summer School, Sao Paulo, Brazil, February 6-12, 1999.* 1999.
- ³³⁷ [13] Joao Pequenao. *Computer generated image of the whole ATLAS detector.* Mar 2008.
- ³³⁹ [14] Heinz Pernegger. *The Pixel Detector of the ATLAS Experiment for LHC Run-2.* Technical Report ATL-INDET-PROC-2015-001, CERN, Geneva, Feb 2015.