

Ejecutar en terminal de linux aplicando modo “Sudo”

Al aplicar el comando [sudo nmap -F + ip red + mascara de subred] ---> sudo nmap -F 192.168.0.0/24

```
(mcface811@ DESKTOP-ATNISA0)~  
$ sudo nmap -F 192.168.0.0/24  
Starting Nmap 7.99 ( https://nmap.org ) at 2026-06-17 19:32 -0400  
Nmap scan report for 192.168.0.1  
Host is up (0.0076s latency).  
Not shown: 96 closed tcp ports (reset)  
PORT      STATE SERVICE  
80/tcp    open  http  
443/tcp   open  https  
1723/tcp  filtered pptp  
8080/tcp  open  http-proxy  
  
Nmap scan report for 192.168.0.5  
Host is up (0.045s latency).  
All 100 scanned ports on 192.168.0.5 are in ignored states.  
Not shown: 100 closed tcp ports (reset)  
  
Nmap scan report for 192.168.0.6  
Host is up (0.024s latency).  
Not shown: 95 filtered tcp ports (no-response)  
PORT      STATE SERVICE  
135/tcp   open  msrpc  
139/tcp   open  netbios-ssn  
445/tcp   open  microsoft-ds  
3306/tcp  open  mysql  
5357/tcp  open  wsddapi  
  
Nmap scan report for 192.168.0.8  
Host is up (0.012s latency).  
Not shown: 99 closed tcp ports (reset)  
PORT      STATE SERVICE  
7/tcp     filtered echo
```

```
Nmap scan report for 192.168.0.31  
Host is up (0.022s latency).  
Not shown: 99 closed tcp ports (reset)  
PORT      STATE SERVICE  
5060/tcp  filtered sip  
  
Nmap scan report for 192.168.0.32  
Host is up (0.018s latency).  
Not shown: 99 closed tcp ports (reset)  
PORT      STATE SERVICE  
49152/tcp open  unknown  
  
Nmap scan report for EPSON4B2F30 (192.168.0.44)  
Host is up (0.044s latency).  
Not shown: 95 closed tcp ports (reset)  
PORT      STATE SERVICE  
80/tcp    open  http  
443/tcp   open  https  
515/tcp   open  printer  
631/tcp   open  ipp  
9100/tcp  open  jetdirect  
  
Nmap scan report for 192.168.0.51  
Host is up (0.037s latency).  
Not shown: 99 filtered tcp ports (no-response)  
PORT      STATE SERVICE  
5357/tcp  open  wsddapi
```

Este comando se usa para realizar un escaneo de los 100 puertos mas utilizados a toda una subred. En este caso, se realiza el escaneo de toda la subred, desde la dirección ip 192.168.0.0 hasta 192.168.1.255 en busca equipos activos y servicios básicos abiertos. **Dato:** [-F] activa el modo rápido

Al aplicar el comando [sudo **nmap -sn ip red + mascara de subred**] ---> sudo nmap -sn 192.168.0.0/24

```
(mcface811@ DESKTOP-ATN15A0)-[~]  
$ sudo nmap -sn 192.168.0.0/24  
Starting Nmap 7.99 ( https://nmap.org ) at 2026-06-17 19:34 -0400  
Nmap scan report for 192.168.0.1  
Host is up (0.0032s latency).  
Nmap scan report for 192.168.0.5  
Host is up (0.11s latency).  
Nmap scan report for 192.168.0.6  
Host is up (0.0049s latency).  
Nmap scan report for 192.168.0.8  
Host is up (0.62s latency).  
Nmap scan report for 192.168.0.10  
Host is up (0.0033s latency).  
Nmap scan report for 192.168.0.31  
Host is up (0.079s latency).  
Nmap scan report for EPSON4B2F30 (192.168.0.44)  
Host is up (0.12s latency).  
Nmap scan report for 192.168.0.51  
Host is up (0.050s latency).  
Nmap scan report for 192.168.0.77  
Host is up (0.16s latency).  
Nmap scan report for 192.168.0.94  
Host is up (0.0050s latency).  
Nmap scan report for 192.168.0.95  
Host is up (0.0040s latency).  
Nmap scan report for 192.168.0.107  
Host is up (0.0056s latency).  
Nmap scan report for 192.168.0.109  
Host is up (0.075s latency).  
Nmap scan report for 192.168.0.135  
Host is up (0.0070s latency).  
Nmap scan report for 192.168.0.137  
Host is up (0.0018s latency).  
Nmap scan report for 192.168.0.142  
Host is up (0.0078s latency).  
Nmap scan report for 192.168.0.147
```

Este comando se conoce como un escaneo de ping; su objetivo es descubrir que dispositivos están encendidos y conectados a la red. Su acción es enviar paquete de ICMP y peticiones de ARP a cada dirección IP de la Red, esperando que los dispositivos respondan.

Al aplicar el comando [sudo **nmap** -p- --open -vvv + **ip red** + **mascara de subred**] ---> sudo nmap -p- --open -vvv 192.168.0.0/24

```
(mcfac811@ DESKTOP-ATNISA0)-[~]
$ sudo nmap -p- --open -vvv 192.168.0.0/24
Starting Nmap 7.99 ( https://nmap.org ) at 2026-06-17 19:38 -0400
Initiating Ping Scan at 19:38
Scanning 256 hosts [4 ports/host]
Completed Ping Scan at 19:38, 8.82s elapsed (256 total hosts)
Initiating Parallel DNS resolution of 20 hosts. at 19:38
Completed Parallel DNS resolution of 20 hosts. at 19:38, 7.50s elapsed
DNS resolution of 20 IPs took 7.50s. Mode: Async [#: 1, OK: 1, NX: 5, DR: 14, SF: 0, TR: 54, CN: 0]
Initiating SYN Stealth Scan at 19:38
Scanning 4 hosts [65535 ports/host]
Discovered open port 80/tcp on 192.168.0.1
Discovered open port 8080/tcp on 192.168.0.1
Discovered open port 443/tcp on 192.168.0.1
Discovered open port 139/tcp on 192.168.0.6
Discovered open port 135/tcp on 192.168.0.6
Discovered open port 445/tcp on 192.168.0.6
Discovered open port 3306/tcp on 192.168.0.6
Discovered open port 20002/tcp on 192.168.0.1
SYN Stealth Scan Timing: About 20.57% done; ETC: 19:41 (0:02:00 remaining)
Discovered open port 49671/tcp on 192.168.0.6
Discovered open port 5357/tcp on 192.168.0.6
SYN Stealth Scan Timing: About 42.12% done; ETC: 19:41 (0:01:24 remaining)
SYN Stealth Scan Timing: About 57.74% done; ETC: 19:41 (0:01:07 remaining)
SYN Stealth Scan Timing: About 70.59% done; ETC: 19:41 (0:00:52 remaining)
Discovered open port 5040/tcp on 192.168.0.6
SYN Stealth Scan Timing: About 82.66% done; ETC: 19:41 (0:00:32 remaining)
Completed SYN Stealth Scan against 192.168.0.1 in 170.47s (3 hosts left)
Completed SYN Stealth Scan against 192.168.0.8 in 170.92s (2 hosts left)
Completed SYN Stealth Scan against 192.168.0.5 in 170.97s (1 host left)
Discovered open port 33060/tcp on 192.168.0.6
```

Este comando se usa para asegurarse de que no haya ningún servicio oculto o backdoor corriendo en un puerto inusual (como los conocidos 45321 o 61234) cuando se esta realizando un auditoria de seguridad profunda (pentesting).

Al aplicar el comando [sudo **nmap** -p #puerto -vvv sCV + **ip del equipo objetivo**] ---> sudo nmap -p 445 -vvv -sCV 192.168.0.142

```
(mcface811@ DESKTOP-ATNISA0) ~  
$ sudo nmap -p 445 -vvv -sCV 192.168.0.142  
Starting Nmap 7.99 ( https://nmap.org ) at 2026-06-17 19:43 -0400  
Initiating Parallel DNS resolution of 1 host. at 19:43  
Completed Parallel DNS resolution of 1 host. at 19:43, 2.50s elapsed  
Initiating System DNS resolution of 1 host. at 19:43  
Completed System DNS resolution of 1 host. at 19:43, 3.65s elapsed  
DNS resolution of 2 IPs took 6.15s. Mode: Async [#: 1, OK: 0, NX: 0, DR: 0, SF: 0, TR: 4, CN: 0]  
Failed to resolve "sCV".  
Initiating Ping Scan at 19:43  
Scanning 192.168.0.142 [4 ports]  
Completed Ping Scan at 19:43, 0.05s elapsed (1 total hosts)  
Initiating Parallel DNS resolution of 1 host. at 19:43  
Completed Parallel DNS resolution of 1 host. at 19:43, 0.09s elapsed  
DNS resolution of 1 IPs took 0.09s. Mode: Async [#: 1, OK: 1, NX: 0, DR: 0, SF: 0, TR: 1, CN: 0]  
Initiating SYN Stealth Scan at 19:43  
Scanning DESKTOP-E11B7KB (192.168.0.142) [1 port]  
Completed SYN Stealth Scan at 19:43, 0.23s elapsed (1 total ports)  
Nmap scan report for DESKTOP-E11B7KB (192.168.0.142)  
Host is up, received echo-reply ttl 127 (0.015s latency).  
Scanned at 2026-06-17 19:43:50 -04 for 0s  
  
PORT      STATE      SERVICE      REASON  
445/tcp   filtered  microsoft-ds no-response  
  
Read data files from: /usr/share/nmap  
Nmap done: 1 IP address (1 host up) scanned in 6.60 seconds  
Raw packets sent: 6 (240B) | Rcvd: 1 (28B)
```

Este comando es utilizado en auditoria profunda y especifica. Se enfoca únicamente en el puerto que se desee consulta, en este caso el puerto 445, el cual es utilizado para compartir archivos e impresoras.

Al aplicar el comando [sudo **nmap** --script vult + **ip del equipo objetivo**] ---> sudo nmap --script vuln 192.168.0.142

```
(mcface811@ DESKTOP-ATNI5A0)-[~]  
$ sudo nmap --script vuln 192.168.0.142  
Starting Nmap 7.99 ( https://nmap.org ) at 2026-06-17 19:45 -0400  
Nmap scan report for DESKTOP-E11B7KB (192.168.0.142)  
Host is up (0.0093s latency).  
Not shown: 997 filtered tcp ports (no-response)  
PORT      STATE SERVICE  
3306/tcp  open  mysql  
5357/tcp  open  wsdaapi  
7070/tcp  open  realserver  
  
Nmap done: 1 IP address (1 host up) scanned in 17.62 seconds
```

Este comando es utilizado para realizar un análisis automático de vulnerabilidades sobre el objetivo específico.