

Ejecutar CMD en modo administrador

Al aplicar el comando [**nmap -F + ip red + mascara de subred**] ---> **nmap -F 192.168.0.0/24**

```
C:\Windows\system32>nmap -F 192.168.0.0/24
Starting Nmap 7.99 ( https://nmap.org ) at 2026-06-17 18:38 -0400
Nmap scan report for 192.168.0.1
Host is up (0.011s latency).
Not shown: 96 closed tcp ports (reset)
PORT      STATE      SERVICE
80/tcp    open      http
443/tcp   open      https
1723/tcp  filtered  pptp
8080/tcp  open      http-proxy
MAC Address: B0:BE:76:20:02:48 (TP-Link Technologies)

Nmap scan report for 192.168.0.5
Host is up (0.089s latency).
All 100 scanned ports on 192.168.0.5 are in ignored states.
Not shown: 100 closed tcp ports (reset)
MAC Address: 1C:CC:D6:0F:45:C4 (Xiaomi Communications)

Nmap scan report for 192.168.0.8
Host is up (0.70s latency).
Not shown: 99 closed tcp ports (reset)
PORT      STATE      SERVICE
7/tcp     filtered  echo
MAC Address: D2:5D:02:10:2F:BA (Unknown)
```

Este comando se usa para realizar un escaneo de los 100 puertos mas utilizados a toda una subred. En este caso, se realiza el escaneo de toda la subred, desde la dirección ip 192.168.0.0 hasta 192.168.1.255 en busca equipos activos y servicios básicos abiertos. **Dato: [-F]** activa el modo rápido

Al aplicar el comando [**nmap -sn ip red + mascara de subred**] ---> nmap -sn 192.168.0.0/24

```
C:\Windows\system32>nmap -sn 192.168.0.0/24
Starting Nmap 7.99 ( https://nmap.org ) at 2026-06-17 18:46 -0400
Nmap scan report for 192.168.0.1
Host is up (0.037s latency).
MAC Address: B0:BE:76:20:02:48 (TP-Link Technologies)
Nmap scan report for 192.168.0.5
Host is up (0.073s latency).
MAC Address: 1C:CC:D6:0F:45:C4 (Xiaomi Communications)
Nmap scan report for 192.168.0.8
Host is up (0.063s latency).
MAC Address: D2:5D:02:10:2F:BA (Unknown)
Nmap scan report for 192.168.0.10
Host is up (0.045s latency).
MAC Address: 00:0E:53:33:A8:6E (AV Tech)
Nmap scan report for 192.168.0.28
Host is up (0.19s latency).
MAC Address: 54:13:79:3B:EE:15 (Hon Hai Precision Ind.)
Nmap scan report for 192.168.0.44
Host is up (0.11s latency).
MAC Address: A4:D7:3C:4B:2F:30 (Seiko Epson)
Nmap scan report for 192.168.0.51
Host is up (0.16s latency).
MAC Address: 5C:EA:1D:91:C8:17 (Hon Hai Precision Ind.)
Nmap scan report for 192.168.0.55
Host is up (0.14s latency).
MAC Address: 54:13:79:3B:EE:15 (Hon Hai Precision Ind.)
Nmap scan report for 192.168.0.77
Host is up (0.15s latency).
MAC Address: 54:13:79:3B:EE:15 (Hon Hai Precision Ind.)
Nmap scan report for 192.168.0.82
Host is up (0.14s latency).
MAC Address: F8:59:71:05:12:BB (Intel Corporate)
Nmap scan report for 192.168.0.94
Host is up (0.046s latency).
MAC Address: F4:E2:C6:13:A9:1C (Ubiquiti)
Nmap scan report for 192.168.0.95
```

Este comando se conoce como un escaneo de ping; su objetivo es descubrir que dispositivos están encendidos y conectados a la red. Su acción es enviar paquete de ICMP y peticiones de ARP a cada dirección IP de la Red, esperando que los dispositivos respondan.

Al aplicar el comando [**nmap -p- --open -vvv + ip red + mascara de subred**] ---> **nmap -p- --open -vvv 192.168.0.0/24**

```
C:\Windows\system32>nmap -p- --open -vvv 192.168.0.0/24
Starting Nmap 7.99 ( https://nmap.org ) at 2026-06-17 18:49 -0400
Initiating ARP Ping Scan at 18:49
Scanning 255 hosts [1 port/host]
Completed ARP Ping Scan at 18:49, 3.30s elapsed (255 total hosts)
Initiating Parallel DNS resolution of 19 hosts. at 18:49
Completed Parallel DNS resolution of 19 hosts. at 18:49, 1.01s elapsed
DNS resolution of 19 IPs took 1.05s. Mode: Async [#: 1, OK: 0, NX: 19, DR: 0, SF: 0, TR: 19, CN: 0]
Initiating SYN Stealth Scan at 18:49
Scanning 4 hosts [65535 ports/host]
Discovered open port 80/tcp on 192.168.0.10
Discovered open port 80/tcp on 192.168.0.1
Discovered open port 8080/tcp on 192.168.0.1
Discovered open port 554/tcp on 192.168.0.10
Discovered open port 443/tcp on 192.168.0.1
Discovered open port 3389/tcp on 192.168.0.28
Discovered open port 135/tcp on 192.168.0.28
```

Este comando se usa para asegurarse de que no haya ningún servicio oculto o backdoor corriendo en un puerto inusual (como los conocidos 45321 o 61234) cuando se esta realizando un auditoria de seguridad profunda (pentesting).

Al aplicar el comando [**nmap -p #puerto -vvv sCV + ip del equipo objetivo**] ---> nmap -p 445 -vvv -sCV 192.168.0.142

```
C:\Windows\system32>nmap -p 445 -vvv sCV 192.168.0.142
Starting Nmap 7.99 ( https://nmap.org ) at 2026-06-17 18:53 -0400
Initiating Parallel DNS resolution of 1 host. at 18:53
Completed Parallel DNS resolution of 1 host. at 18:53, 0.51s elapsed
Initiating System DNS resolution of 1 host. at 18:53
Completed System DNS resolution of 1 host. at 18:53, 2.28s elapsed
DNS resolution of 2 IPs took 2.81s. Mode: Async [#: 1, OK: 0, NX: 0, DR: 0, SF: 0, TR: 2, CN: 0]
Failed to resolve "sCV".
Initiating ARP Ping Scan at 18:53
Scanning 192.168.0.142 [1 port]
Completed ARP Ping Scan at 18:53, 0.12s elapsed (1 total hosts)
Initiating Parallel DNS resolution of 1 host. at 18:53
Completed Parallel DNS resolution of 1 host. at 18:53, 0.51s elapsed
DNS resolution of 1 IPs took 0.52s. Mode: Async [#: 1, OK: 0, NX: 1, DR: 0, SF: 0, TR: 1, CN: 0]
Initiating SYN Stealth Scan at 18:53
Scanning 192.168.0.142 [1 port]
Completed SYN Stealth Scan at 18:53, 0.59s elapsed (1 total ports)
Nmap scan report for 192.168.0.142
Host is up, received arp-response (0.056s latency).
Scanned at 2026-06-17 18:53:56 Hora estándar oeste, Sudamérica for 0s

PORT      STATE      SERVICE      REASON
445/tcp   filtered  microsoft-ds no-response
MAC Address: 54:13:79:27:DE:33 (Hon Hai Precision Ind.)

Read data files from: C:\Program Files (x86)\Nmap
Nmap done: 1 IP address (1 host up) scanned in 4.52 seconds
Raw packets sent: 3 (116B) | Rcvd: 1 (28B)
```

Este comando es utilizado en auditoria profunda y especifica. Se enfoca únicamente en el puerto que se desee consulta, en este caso el puerto 445, el cual es utilizado para compartir archivos e impresoras.

Al aplicar el comando [**nmap --script vult + ip del equipo objetivo**] ---> nmap --script vuln 192.168.0.142

```
C:\Windows\system32>nmap --script vuln 192.168.0.142
Starting Nmap 7.99 ( https://nmap.org ) at 2026-06-17 18:55 -0400
Nmap scan report for 192.168.0.142
Host is up (0.054s latency).
Not shown: 997 filtered tcp ports (no-response)
PORT      STATE SERVICE
3306/tcp  open  mysql
5357/tcp  open  wsdaapi
7070/tcp  open  realserver
MAC Address: 54:13:79:27:DE:33 (Hon Hai Precision Ind.)

Nmap done: 1 IP address (1 host up) scanned in 35.74 seconds
```

Este comando es utilizado para realizar un análisis automático de vulnerabilidades sobre el objetivo específico.