
Starting models
Best starting model
Non-winning models (in the order tried)
Best discovered (±2 SE)
Run 1
Run 2
Run 3
Subjective randomness
Personal pattern-detection gain
+3,260
Edge-streak primacy/recency
+3,023
Streak-weary trick coin
+2,669
Non-winning models (238)
Local representativeness (Kahneman & Tversky, 1972)
Motif model (Griffiths et al., 2018)
Difficulty predictor (Falk & Konold, 1997)
Finite experience (Hahn & Warren, 2009)
−15,000
−10,000
Reference games
Avoidable-ambiguity listener
+198
Competition + endpoint binding
+61
Feature-surprisal ensemble
+8
Non-winning models (214)
RSA-2 + salience, distinctiveness
RSA-2 + salience, familiarity
RSA-2 + salience, valence
Surprisal + isolation (depth 4)
Familiarity + isolation (depth 2)
Isolation + costs (depth 3)
Confusion-averse speaker
Evaluative prominence
RSA, depth 2 (Frank & Goodman, 2012)
RSA, depth 1 (Frank & Goodman, 2012)
Perceptual-oddity heuristic
Lexical-preemption heuristic
−11,000
−10,000
ELPD (nats)
Number game
Digit similarity + even rule
+1,592
Non-winning models (85)
Learned rule prior (Bigelow & Piantadosi, 2016)
Learned rule and interval prior (Bigelow & Piantadosi, 2016)
Rules and similarity (Tenenbaum, 2000)
−6,000
−4,000