



Notes & General Fabrication Requirements:

1. Materials, manufacturing and certification:
DNV Standard for Certification
No 2.22, Lifting Appliances.
2. Material certification: EN 10 204,
type 3.1 required for items 1-4
3. Safe Working Load: 10T
- Load test: 2xSWL =20T .
- Design factor: 4.0
4. Calculated assembly weight: 24,7 kg

Itm.	Qty.	Description	Drg. / Spec.	Material
9	2	Ø8 Lock Washer	NL8ss / HLS-8s	A4-80
8	2	M8 x 20 Low Head Socket Screw	DIN 7984	A4
7	2	Tilt Stop	AF64-1018M16	AISI 316
6	1	Bear-ring	AF64-1018M15	POM-C
5	2	Locking Plate	AF64-1018M14	AISI 316
4	1	Swivel Body	AF64-1018M13	SI65M WL.4418
3	2	Pivot Bolt	AF64-1018M12	SI65M WL.4418
2	1	Swivel Fork	AF64-1018M11	SI65M WL.4418
1	1	ROV Bullet	AF64-1018M10	SI65M WL.4418

Rev.	Date	Description	Prep	Chk	App
3	04.02.2019	Mod. item 1	GOS	AHO	EKB
2	10.12.2015	Mod. Item 5+8+9. re-IFC	MT	AHO	EKB
1	07.07.2015	ISSUED FOR CONSTRUCTION	MT	AHO	EKB
A	08.05.2015	ISSUED FOR COMMENTS	MT	AHO	EKB



Drawing title		Size	
ROV BULLET JOINT GA, Assembly & Parts List		A3	
KYSTDESIGN AS www.kystdesign.no		Scale 1:4	Sheet 1
		File name AF64-1018M01	of 1