



B227512

NSX400N M.logic 2,3 400A 3P

Partnumber: LV432693

Wholesalernumber: 4393909

EAN 13 code: 3606480015137

circuit breaker Compact NSX400N - Micrologic 2.3 - 400 A - 3 poles 3d

Technical information

Usage / Application

circuit breaker application

distribution

Functional

control type

toggle

local signalling

LED 105 % Ir

LED 90 % Ir

LED ready

trip unit protection functions

LSol

protection type

instantaneous short-circuit protection

overload protection (long time)

short time short-circuit protection

adjustable 9 settings

long time pick-up adjustment type Ir

long time pick-up adjustment range

0.9...1 x Io

long time delay adjustment type

fixed

[tr] long-time delay adjustment

16 s 6 x Ir

thermal memory

20 minutes before and after tripping

short-time pick-up adjustment type Isd

adjustable 9 settings

[Isd] short-time pick-up adjustment range

1.5...10 x Ir

short-time delay adjustment type

fixed

instantaneous pick-up adjustment type Ii

fixed

instantaneous pick-up adjustment range

4800 A

Electrical

poles description

3P

protected poles description

3t

network type

AC

network frequency

50/60 Hz

[In] rated current

400 A (40 °C)

[U_i] rated insulation voltage

800 V AC 50/60 Hz

[U_{imp}] rated impulse withstand voltage

8 kV

[U_e] rated operational voltage

690 V AC 50/60 Hz

breaking capacity

20 kA at 600 V AC 50/60 Hz conforming to NEMA AB1

20 kA at 600 V AC 50/60 Hz conforming to UL 508

42 kA at 480 V AC 50/60 Hz conforming to NEMA AB1

50 kA at 480 V AC 50/60 Hz conforming to UL 508

85 kA at 240 V AC 50/60 Hz conforming to NEMA AB1

85 kA at 240 V AC 50/60 Hz conforming to UL 508

Icu 10 kA at 660/690 V AC 50/60 Hz conforming to IEC 60947-2

Icu 22 kA at 525 V AC 50/60 Hz conforming to IEC 60947-2

Icu 30 kA at 500 V AC 50/60 Hz conforming to IEC 60947-2

Icu 42 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2

Icu 50 kA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2

Icu 85 kA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2

utilisation category

category A

Performance

[Ics] rated service breaking capacity	Ics 10 kA 660/690 V AC 50/60 Hz conforming to IEC 60947-2 Ics 11 kA 525 V AC 50/60 Hz conforming to IEC 60947-2 Ics 30 kA 500 V AC 50/60 Hz conforming to IEC 60947-2 Ics 42 kA 440 V AC 50/60 Hz conforming to IEC 60947-2 Ics 50 kA 380/415 V AC 50/60 Hz conforming to IEC 60947-2 Ics 85 kA 220/240 V AC 50/60 Hz conforming to IEC 60947-2
mechanical durability	15000 cycles cycles
electrical durability	12000 cycles 440 V In/2 conforming to IEC 60947-2 3000 cycles 690 V In conforming to IEC 60947-2 6000 cycles 440 V In conforming to IEC 60947-2 6000 cycles 690 V In/2 conforming to IEC 60947-2
► Connections	
upside connection	front
downside connection	front
connection pitch	45 mm mm
► Installation	
mounting mode	fixed
mounting support	backplate
► Product identification	
range of product	NSX400...630
product or component type	circuit breaker
circuit breaker name	Compact NSX400N
device short name	Compact NSX400N
rating code	N
suitability for isolation	yes conforming to EN 60947-2 yes conforming to IEC 60947-2
trip unit name	Micrologic 2.3
trip unit technology	electronic
trip unit rating	400 A (40 °C)
► Physical characteristics	
height	255 mm mm
width	140 mm mm
depth	110 mm mm
product weight	6.05 kg kg
► Environment	
electrical shock protection class	class II
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 62262
pollution degree	3 conforming to IEC 60664-1
ambient air temperature for operation	-35...70 °C °C
ambient air temperature for storage	-55...85 °C °C
► Certifications and standards	
standards	EN 60947-2 IEC 60947-2 NEMA AB1 UL 508
product certifications	CSA UL

Supplier information

Supplier: Schneider Electric Norge AS
Address: Deliveien 10, 1540 Vestby

Fax: + 47 64 98 57 01
Phone: +47 64 98 56 00

Web: <http://www.schneider-electric.no>
e-Mail: kundesenter@no.schneider-electric.com