

Version Control with Git and GitHub

Winter Institute in Data Science

Ryan T. Moore

3 January 2020

Introducing Git + GitHub

Workflow and Git Commands

Branches

Merging and Rebasing

Pull Requests and Forks

Introducing Git + GitHub

“Git is a free and open source distributed version control system”

– *<https://git-scm.com/>*

“Git is a free and open source distributed version control system”

– <https://git-scm.com/>

- ▶ Set of command-line tools for *version control*: explicit management of file history

“Git is a free and open source distributed version control system”

– <https://git-scm.com/>

- ▶ Set of command-line tools for *version control*: explicit management of file history
- ▶ *Distributed*: full codebase (current and history) lives on every developer's machine

“Git is a free and open source distributed version control system”

– <https://git-scm.com/>

- ▶ Set of command-line tools for *version control*: explicit management of file history
- ▶ *Distributed*: full codebase (current and history) lives on every developer's machine
- ▶ Originally written by Linus Torvalds (Linux)

GitHub

- ▶ A web-based repository for code

GitHub

- ▶ A web-based repository for code
- ▶ Utilizes `git` version control system for careful tracking of how files change

GitHub

- ▶ A web-based repository for code
- ▶ Utilizes `git` version control system for careful tracking of how files change
- ▶ Facilitates collaboration by organizing simultaneous editing, issue tracking, merging, conflict management, ...

GitHub

- ▶ A web-based repository for code
- ▶ Utilizes `git` version control system for careful tracking of how files change
- ▶ Facilitates collaboration by organizing simultaneous editing, issue tracking, merging, conflict management, ...
- ▶ (“Collaboration” includes your future self)


GitHub

- ▶ A web-based repository for code
- ▶ Utilizes `git` version control system for careful tracking of how files change
- ▶ Facilitates collaboration by organizing simultaneous editing, issue tracking, merging, conflict management, ...
- ▶ (“Collaboration” includes your future self)
- ▶ Think Dropbox/GDrive, but better, more deliberate.

GitHub

- ▶ A web-based repository for code
- ▶ Utilizes `git` version control system for careful tracking of how files change
- ▶ Facilitates collaboration by organizing simultaneous editing, issue tracking, merging, conflict management, ...
- ▶ (“Collaboration” includes your future self)
- ▶ Think Dropbox/GDrive, but better, more deliberate.
- ▶ Next step: Docker

Examples

 [ryantmoore](#) / [r-data-science](#) Private

Unwatch ▾ 1


★ Star 0


🍴 Fork


[Code](#) [Issues 5](#) [Pull requests 0](#) [Projects 0](#) [Wiki](#) [Security](#) [Insights](#) [Settings](#)


Introductory R for Data Science


[Manage topics](#)

 **267** commits

 **1** branch


 **0** releases











 **3** contributors

 GPL-3.0


Branch: **master** ▾ [New pull request](#)


[Create new file](#) [Upload files](#) [Find file](#) [Clone or download](#)

 **ryantmoore** Update PS6 Latest commit fd1ff6d 6 days ago


 admin	Update PS6	6 days ago
 code	Update pkg tests and building	6 days ago
 data	Make laws data longer	last year
 notes	Update pkg tests and building	6 days ago
 ps_labs	ps05 Exam class	18 days ago
 quiz	Initialize quiz pkg2	6 days ago
 .gitignore	Create full gitignore	9 months ago
 LICENSE	Initial commit	2 years ago
 README.md	Fix typo	13 days ago
 r-data-science.Rproj	Add Rproj file	8 months ago


Examples


 [ryantmoore](#) / [blockTools](#) Private


 Unwatch ▾


10


 S


 Code

 Issues 16

 Pull requests 1

 Projects 0

 Insights


 Settings

Branch: master ▾












[blockTools](#) / [blockTools](#) /

Create new file

Upload file

 **ryantmoore** Add tarball 0.6-2. Update all /blockTools/ files. Latest commit

..

 R	Add tarball 0.6-2. Update all /blockTools/ files.
 data	Initial
 demo	Add tarball 0.6-2. Update all /blockTools/ files.
 inst	Copying directory blockTools/ from devel to master
 man	Add tarball 0.6-2. Update all /blockTools/ files.
 src	Add tarball 0.6-2. Update all /blockTools/ files.
 CHANGELOG	Add tarball 0.6-2. Update all /blockTools/ files.
 COPYING	Initial
 DESCRIPTION	Add tarball 0.6-2. Update all /blockTools/ files.
 LICENSE	Add tarball 0.6-2. Update all /blockTools/ files.
 NAMESPACE	Add tarball 0.6-2. Update all /blockTools/ files.

15 / 161

Examples

🔒 [ryantmoore / blockTools](#) Private

Unwatch ▼ 10 Star 0 Fork

Code Issues 16 Pull requests 1 Projects 0 Insights Settings

Optimal greedy randomly breaks ties. Can we set a seed to get same blocks? #57

[Edit](#) [New](#)

Open ryantmoore opened this issue on Jun 14, 2017 · 3 comments



ryantmoore commented on Jun 14, 2017

+

In `block()`, the optimal-greedy algorithm breaks ties randomly to create blocks. Can we set a seed so that we can replicate the blocks when a lot of ties exist? @keithschnak will this involve passing a new argument to `optgreedy()` in `block()` to influence the underlying C code?



ryantmoore added enhancement question labels on Jun 14, 2017



ryantmoore assigned keithschnak on Jun 14, 2017



keithschnak commented on Jun 14, 2017

+

I think I can make it pass the seed from R as an argument to the C function. I'll take a look this evening.

...

Assignees

keithschnak

Labels

enhancement

question

Projects

None yet

Milestone

No milestone

Notifications

Unsubscribe

16 / 161

Git + GitHub

The Motivation

- ▶ Web resources: page, README, issue tracking and assignment

The Motivation

- ▶ Web resources: page, README, issue tracking and assignment
- ▶ Work simultaneously, large group, without fear of conflicts

The Motivation

- ▶ Web resources: page, README, issue tracking and assignment
- ▶ Work simultaneously, large group, without fear of conflicts
- ▶ Package sharing w/o CRAN or `tar.gz`

The Motivation

- ▶ Web resources: page, `README`, issue tracking and assignment
- ▶ Work simultaneously, large group, without fear of conflicts
- ▶ Package sharing w/o CRAN or `tar.gz`
- ▶ Gists: small stand-alone functions/code (e.g., <http://j.mp/2djpFON>)

The Motivation

- ▶ Web resources: page, README, issue tracking and assignment
- ▶ Work simultaneously, large group, without fear of conflicts
- ▶ Package sharing w/o CRAN or `tar.gz`
- ▶ Gists: small stand-alone functions/code (e.g., <http://j.mp/2djpFON>)
- ▶ Data science jobs: provide GitHub ID

Alternatives

Git:

- ▶ Mercurial
- ▶ Concurrent Versions System (CVS)
- ▶ Subversion (SVN)
- ▶ ...

Alternatives

Git:

- ▶ Mercurial
- ▶ Concurrent Versions System (CVS)
- ▶ Subversion (SVN)
- ▶ ...

GitHub:

- ▶ Bitbucket
- ▶ GitLab
- ▶ GitKraken
- ▶ SourceForge
- ▶ ...

Workflow and Git Commands

Git + GitHub

The General Workflow:

- ▶ Create/designate/find *repository* to track

Git + GitHub

The General Workflow:

- ▶ Create/designate/find *repository* to track
- ▶ Make changes to code

The General Workflow:

- ▶ Create/designate/find *repository* to track
- ▶ Make changes to code
- ▶ *Commit* changes: declare “save this snapshot”

Git + GitHub

The General Workflow:

- ▶ Create/designate/find *repository* to track
- ▶ Make changes to code
- ▶ *Commit* changes: declare “save this snapshot”
- ▶ Send commits to GitHub (*push*)

Workflow and Product

- ▶ Include elements of the work product

Workflow and Product

- ▶ Include elements of the work product
 - ▶ Code files

Workflow and Product

- ▶ Include elements of the work product
 - ▶ Code files
 - ▶ Documentation (how to use your code)

Workflow and Product

- ▶ Include elements of the work product
 - ▶ Code files
 - ▶ Documentation (how to use your code)
 - ▶ Metadata

Workflow and Product

- ▶ Include elements of the work product
 - ▶ Code files
 - ▶ Documentation (how to use your code)
 - ▶ Metadata
 - ▶ Compiled files? (`.pdf`, `.tar.gz`, ...)

Workflow and Product

- ▶ Include elements of the work product
 - ▶ Code files
 - ▶ Documentation (how to use your code)
 - ▶ Metadata
 - ▶ Compiled files? (`.pdf`, `.tar.gz`, ...)
- ▶ Exclude elements of the workflow

Workflow and Product

- ▶ Include elements of the work product
 - ▶ Code files
 - ▶ Documentation (how to use your code)
 - ▶ Metadata
 - ▶ Compiled files? (`.pdf`, `.tar.gz`, ...)
- ▶ Exclude elements of the workflow
 - ▶ Directory setting

Workflow and Product

- ▶ Include elements of the work product
 - ▶ Code files
 - ▶ Documentation (how to use your code)
 - ▶ Metadata
 - ▶ Compiled files? (`.pdf`, `.tar.gz`, ...)
- ▶ Exclude elements of the workflow
 - ▶ Directory setting
 - ▶ Package installation


Workflow and Product

- ▶ Include elements of the work product
 - ▶ Code files
 - ▶ Documentation (how to use your code)
 - ▶ Metadata
 - ▶ Compiled files? (`.pdf`, `.tar.gz`, ...)
- ▶ Exclude elements of the workflow
 - ▶ Directory setting
 - ▶ Package installation
- ▶ Exclude sensitive files


Workflow and Product

- ▶ Include elements of the work product
 - ▶ Code files
 - ▶ Documentation (how to use your code)
 - ▶ Metadata
 - ▶ Compiled files? (`.pdf`, `.tar.gz`, ...)
- ▶ Exclude elements of the workflow
 - ▶ Directory setting
 - ▶ Package installation
- ▶ Exclude sensitive files
 - ▶ Seriously. This is hard to undo.

Work Product: Directory Structure




Work Product: Directory Structure




- Set up on your machine

Work Product: Directory Structure




- ▶ Set up on your machine
- ▶ But `git` won't track empty directories

Work Product: Directory Structure




- ▶ Set up on your machine
- ▶ But `git` won't track empty directories
- ▶ Add, track an empty file

Work Product: Directory Structure




- ▶ Set up on your machine
- ▶ But `git` won't track empty directories
- ▶ Add, track an empty file
 - ▶ (How I make `ps` directories)

Work Product: Sensitive Data




Work Product: Sensitive Data




- Store sensitive data in local `sample_project/data/`

Work Product: Sensitive Data




- ▶ Store sensitive data in local `sample_project/data/`
- ▶ But do not `git` track it

Work Product: Sensitive Data




- ▶ Store sensitive data in local `sample_project/data/`
- ▶ But do not `git` track it
- ▶ Assume everything in public, even if “private” repo

Work Product: Sensitive Data




- ▶ Store sensitive data in local `sample_project/data/`
- ▶ But do not `git` track it
- ▶ Assume everything in public, even if “private” repo
 - ▶ federal laws (HIPAA, FERPA, etc.)

Work Product: Sensitive Data




- ▶ Store sensitive data in local `sample_project/data/`
- ▶ But do not `git` track it
- ▶ Assume everything in public, even if “private” repo
 - ▶ federal laws (HIPAA, FERPA, etc.)
 - ▶ agreements with clients, employers, funders, partners, etc.

Work Product: Sensitive Data




- ▶ Store sensitive data in local `sample_project/data/`
- ▶ But do not `git` track it
- ▶ Assume everything in public, even if “private” repo
 - ▶ federal laws (HIPAA, FERPA, etc.)
 - ▶ agreements with clients, employers, funders, partners, etc.
- ▶ Difficult to remove (the point of version control...)

Work Product: Sensitive Data




- ▶ Store sensitive data in local `sample_project/data/`
- ▶ But do not `git` track it
- ▶ Assume everything in public, even if “private” repo
 - ▶ federal laws (HIPAA, FERPA, etc.)
 - ▶ agreements with clients, employers, funders, partners, etc.
- ▶ Difficult to remove (the point of version control...)
 - ▶ First add to `.gitignore` (avoid future problem)

Work Product: Sensitive Data




- ▶ Store sensitive data in local `sample_project/data/`
- ▶ But do not `git` track it
- ▶ Assume everything in public, even if “private” repo
 - ▶ federal laws (HIPAA, FERPA, etc.)
 - ▶ agreements with clients, employers, funders, partners, etc.
- ▶ Difficult to remove (the point of version control...)
 - ▶ First add to `.gitignore` (avoid future problem)
 - ▶ Then remove sensitive file from history's dirty commits

Work Product: Sensitive Data




- ▶ Store sensitive data in local `sample_project/data/`
- ▶ But do not `git` track it
- ▶ Assume everything in public, even if “private” repo
 - ▶ federal laws (HIPAA, FERPA, etc.)
 - ▶ agreements with clients, employers, funders, partners, etc.
- ▶ Difficult to remove (the point of version control...)
 - ▶ First add to `.gitignore` (avoid future problem)
 - ▶ Then remove sensitive file from history's dirty commits
 - ▶ `git-filter-branch`

Work Product: Sensitive Data



- ▶ Store sensitive data in local `sample_project/data/`
- ▶ But do not `git` track it
- ▶ Assume everything in public, even if “private” repo
 - ▶ federal laws (HIPAA, FERPA, etc.)
 - ▶ agreements with clients, employers, funders, partners, etc.
- ▶ Difficult to remove (the point of version control...)
 - ▶ First add to `.gitignore` (avoid future problem)
 - ▶ Then remove sensitive file from history's dirty commits
 - ▶ `git-filter-branch`
 - ▶ (Or `bfg` from BFG Repo Cleaner)

Work Product: Sensitive Data



- ▶ Store sensitive data in local `sample_project/data/`
- ▶ But do not `git` track it
- ▶ Assume everything in public, even if “private” repo
 - ▶ federal laws (HIPAA, FERPA, etc.)
 - ▶ agreements with clients, employers, funders, partners, etc.
- ▶ Difficult to remove (the point of version control...)
 - ▶ First add to `.gitignore` (avoid future problem)
 - ▶ Then remove sensitive file from history's dirty commits
 - ▶ `git-filter-branch`
 - ▶ (Or `bfg` from BFG Repo Cleaner)
 - ▶ Repeat for every branch

Work Product and .gitignore

To **not track**, list in .gitignore file.

You can gitignore

- ▶ a specific file

Work Product and .gitignore

To **not track**, list in .gitignore file.

You can gitignore

- ▶ a specific file
- ▶ an entire file type

Work Product and .gitignore

To **not track**, list in .gitignore file.

You can gitignore

- ▶ a specific file
- ▶ an entire file type
- ▶ an entire directory

Work Product and .gitignore

To **not track**, list in .gitignore file.

You can gitignore

- ▶ a specific file
- ▶ an entire file type
- ▶ an entire directory
- ▶ a file type within a directory

Work Product and .gitignore

To **not track**, list in .gitignore file.

You can gitignore

- ▶ a specific file
- ▶ an entire file type
- ▶ an entire directory
- ▶ a file type within a directory
- ▶ ...

Work Product and .gitignore

My .gitignore workflow:

- ▶ Initialize repo w/ .gitignore, choose R
- ▶ Immediately update via <https://www.gitignore.io>

Work Product and .gitignore

My .gitignore workflow:

- ▶ Initialize repo w/ .gitignore, choose R
- ▶ Immediately update via <https://www.gitignore.io>
- ▶ R
- ▶ L^AT_EX
- ▶ T_EX
- ▶ Python
- ▶ Data files, directories
- ▶ ...

How should I `git`?

There are many ways to `git`.

How should I `git`?

There are many ways to `git`.

Be familiar w/ command line `git`, even if you GUI.

How should I `git`?

There are many ways to `git`.

Be familiar w/ command line `git`, even if you GUI.

Each GUI defines its own “sync”, but `git` is more specific.

How should I `git`?

There are many ways to `git`.

Be familiar w/ command line `git`, even if you GUI.

Each GUI defines its own “sync”, but `git` is more specific.

If “sync” fails, was it `push`, `fetch`, `pull`, `merge`, ...?

How should I `git`?

There are many ways to `git`.

Be familiar w/ command line `git`, even if you GUI.

Each GUI defines its own “sync”, but `git` is more specific.

If “sync” fails, was it `push`, `fetch`, `pull`, `merge`, ...?

- ▶ GitHub's GUI
- ▶ GitKraken
- ▶ Tower
- ▶ RStudio?
- ▶ ...

Some Command Line basics

Where to find the command line?

- ▶ Stand-alone programs:
 - ▶ MacOS **iTerm2**, Terminal ...
 - ▶ Windows **Cmder**, Git BASH, PowerShell
- ▶ RStudio Terminal
 - ▶ (next to Console)
 - ▶ (why not? Workflow.)
 - ▶ (Multiple windows, Cmd-tab, file mngmnt w/o RStudio)

Some Command Line basics

- ▶ `ls`: list files/dirs
- ▶ `pwd`: print working dir
- ▶ `mkdir subdir`: make new subdir
- ▶ `cd subdir`: change working dir (to `subdir`)
- ▶ `cd ..`: change working dir (to one above)
- ▶ `cp file.R file_copy.R`: copy file
- ▶ `mv file.R subdir/file.R`: move file
- ▶ `rm file.R`: delete file
- ▶ `touch file.R`: create new file
- ▶ `open file.R`: open extant file
(Win: `file.R` + Enter)
- ▶ `cat file.R`: print contents of file
- ▶ `man ls`: help file for `ls` (e.g.)

Find a Friend

One	Two
Mark	Hubbert
Sophie	Carine
JessicaK	Kelly
Cameron	Kathleen
Ethan	Kate
AndrewZ	Olan
Bryce	Hannah
Zeinabou	Tanesia
Lauren	Jocelyn
LucasG	Marc
LucasA	Edward
Erin	Milika
JessieG	

Challenge: complete first 10, show me 11.

Let's Practice

Using only the command line,

1. Navigate to your Desktop
2. Make a directory called `cl_dir`
3. Navigate to `cl_dir`
4. Create an empty file here called `empty.txt`
5. Open `empty.txt`
6. Add a line of text; save the file
7. Change the filename to `notempty.txt`
8. Navigate up to the Desktop
9. Print contents of `notempty.txt`
10. List the files in `Desktop/cl_dir`
11. Delete `notempty.txt`

Some Command Line basics

This is how I navigate files/directories.

Some Command Line basics

This is how I navigate files/directories.

Git uses similar commands, prefaced with `git`.

Some Command Line intermediates

- ▶ `ps -u <username>`: view running processes
- ▶ `top`: view CPU hogs
- ▶ `kill <pid>`: kill process (given ID)
- ▶ `mail`
- ▶ `cal`

Some help

GitHub's Git Cheat Sheet:
<http://j.mp/2Y5HklD>

Creating a new repository

- ▶ On GitHub.com:
Profile > Repositories > New
- ▶ Name (**mytest**)
- ▶ Description (brief descr)
- ▶ README (yes, initialize it)
- ▶ **.gitignore**
(yes, choose R, then www.gitignore.io)
- ▶ license (yes, select one)

Contributing to a repository

On web directly:

- ▶ Click on README, pencil icon. Edit the .md file.

Contributing to a repository

On web directly:

- ▶ Click on README, pencil icon. Edit the .md file.
- ▶ Preview changes

Contributing to a repository

On web directly:

- ▶ Click on README, pencil icon. Edit the .md file.
- ▶ Preview changes
- ▶ Commit

Contributing to a repository

On web directly:

- ▶ Click on README, pencil icon. Edit the .md file.
- ▶ Preview changes
- ▶ Commit

Contributing to a repository

On web directly:

- ▶ Click on `README`, pencil icon. Edit the `.md` file.
- ▶ Preview changes
- ▶ Commit

`README.md` is “GitHub-flavored markdown”

Like `.Rmd`, but not identical.

Contributing to a repository

On web directly:

- ▶ Update `.gitignore`: Don't ignore `.Rproj` files

Contributing to a repository

On web directly:

- ▶ Update `.gitignore`: Don't ignore `.Rproj` files
- ▶ Edit file, Preview changes

Contributing to a repository

On web directly:

- ▶ Update `.gitignore`: Don't ignore `.Rproj` files
- ▶ Edit file, Preview changes
- ▶ Commit

Contributing to a repository

On web directly:

- ▶ Upload files
- ▶ Commit

Contributing to a repository

Note: each commit is *complete* and *minimal*.

- ▶ Solve a problem, make an addition
- ▶ Addresses a **single** issue

Contributing to a repository

Note: each commit is *complete* and *minimal*.

- ▶ Solve a problem, make an addition
- ▶ Addresses a **single** issue

Different problem? Different commit.

Contributing to a repository

Using local version:

- ▶ Clone repo

Contributing to a repository

Using local version:

- ▶ Clone repo
- ▶ Edit files directly

Contributing to a repository

Using local version:

- ▶ Clone repo
- ▶ Edit files directly
- ▶ Send changes to GitHub

Contributing to a repository

Using local version:

- ▶ Clone repo
- ▶ Edit files directly
- ▶ Send changes to GitHub

Contributing to a repository

Using local version:

- ▶ Clone repo
- ▶ Edit files directly
- ▶ Send changes to GitHub

```
git status
```

```
git add
```

```
git commit -m "Commit Msg"
```

```
git push
```

Contributing to a repository

Using local version:

- ▶ Clone repo
- ▶ Edit files directly
- ▶ Send changes to GitHub

```
git status
```

```
git add
```

```
git commit -m "Commit Msg"
```

```
git push
```

Workflow: commit, commit, commit, ..., push

In Case of Emergency

In Case of Emergency



Cloning extant repository

```
git clone git@github.com:<username>/<reponame>.git
```


Workflow Commands

```
git status
```

Workflow Commands

```
git status
```

Neurotically.

Workflow Commands

`git status`

Neurotically.

`git status` will suggest what to do next.

Workflow Commands

When I start,

```
git fetch
```

to bring pushed changes to my local version.

Workflow Commands

When I start,

```
git fetch
```

to bring pushed changes to my local version.

If needed,

```
git pull
```

to merge version on GitHub into mine.

Workflow Commands

Make changes.

Workflow Commands

Make changes. Then git:

```
git add <file>
```

```
git commit -m "Commit msg"
```

```
git push
```

Clone an extant repository

At terminal prompt, `pwd` and `cd` to a dir
(Desktop, e.g.).

Clone an extant repository

At terminal prompt, `pwd` and `cd` to a dir (Desktop, e.g.).

Then,

```
git clone git@github.com:<yourusername>/mytest.git
```

and `/mytest/` will appear in the dir.

Clone an extant repository

At terminal prompt, `pwd` and `cd` to a dir (Desktop, e.g.).

Then,

```
git clone git@github.com:<yourusername>/mytest.git
```

and `/mytest/` will appear in the dir.

Now, edit `README` a bit.

Clone an extant repository

At terminal prompt, `pwd` and `cd` to a dir (Desktop, e.g.).

Then,

```
git clone git@github.com:<yourusername>/mytest.git
```

and `/mytest/` will appear in the dir.

Now, edit `README` a bit.

Then, at terminal

```
git status
```

```
git commit -m "Commit Msg"
```

```
git push
```

Delete the local version

- ▶ Delete the local folders
- ▶ (Note: no `git` here, so truth unaffected.)
- ▶ Reclone

Remove a file from future commits

- ▶ `git rm ps06/rtm.R`

Remove a file from future commits

- ▶ `git rm ps06/rtm.R`

(Repeat: *future* commits)

Branches

Branches

During Git, you are always on *branch* of codebase.

Branches

During Git, you are always on *branch* of codebase.

By default, create and are on the **master** branch.

Branches

During Git, you are always on *branch* of codebase.

By default, create and are on the **master** branch.

Create other branches to make changes, commit them, etc., **without** touching the **master** branch.

Branches

During Git, you are always on *branch* of codebase.

By default, create and are on the **master** branch.

Create other branches to make changes, commit them, etc., **without** touching the **master** branch.

Then, recombine work on the branch back into **master** branch.

Branches

During Git, you are always on *branch* of codebase.

By default, create and are on the **master** branch.

Create other branches to make changes, commit them, etc., **without** touching the **master** branch.

Then, recombine work on the branch back into **master** branch.

Goal: **master** always works.

Branching Workflow

- ▶ Create branch

Branching Workflow

- ▶ Create branch
- ▶ Move to that branch

Branching Workflow

- ▶ Create branch
- ▶ Move to that branch
- ▶ Make edits to code

Branching Workflow

- ▶ Create branch
- ▶ Move to that branch
- ▶ Make edits to code
- ▶ Commit and push

Branching Workflow

- ▶ Create branch
- ▶ Move to that branch
- ▶ Make edits to code
- ▶ Commit and push
- ▶ Issue pull request at [GitHub.com](https://github.com)

Branching Workflow

- ▶ Create branch
- ▶ Move to that branch
- ▶ Make edits to code
- ▶ Commit and push
- ▶ Issue pull request at [GitHub.com](https://github.com)
- ▶ Someone reviews pull request, merges your branch in, deletes it

Branching Workflow

- ▶ `git branch bugFix`

Branching Workflow

- ▶ `git branch bugFix`
- ▶ `git checkout bugFix`

Branching Workflow

- ▶ `git branch bugFix`
- ▶ `git checkout bugFix`
- ▶ Make edits to code

Branching Workflow

- ▶ `git branch bugFix`
- ▶ `git checkout bugFix`
- ▶ Make edits to code
- ▶ `git add`, `git commit`, `git push`

Branching Workflow

- ▶ `git branch bugFix`
- ▶ `git checkout bugFix`
- ▶ Make edits to code
- ▶ `git add`, `git commit`, `git push`
- ▶ (`git status` keeps me on track)

Branching Workflow

- ▶ `git branch bugFix`
- ▶ `git checkout bugFix`
- ▶ Make edits to code
- ▶ `git add`, `git commit`, `git push`
- ▶ (`git status` keeps me on track)
- ▶ `git checkout master` to return

Branching Workflow

- ▶ `git branch bugFix`
- ▶ `git checkout bugFix`
- ▶ Make edits to code
- ▶ `git add`, `git commit`, `git push`
- ▶ (`git status` keeps me on track)
- ▶ `git checkout master` to return
- ▶ Eventually, `git merge bugFix`

Terminology for Branches, Forks, Commits

Recall: *distributed* version control.

Terminology for Branches, Forks, Commits

Recall: *distributed* version control.

- ▶ a *remote*: non-local version of repo

Terminology for Branches, Forks, Commits

Recall: *distributed* version control.

- ▶ a *remote*: non-local version of repo
- ▶ **origin**: standard name of your GitHub remote

Terminology for Branches, Forks, Commits

Recall: *distributed* version control.

- ▶ a *remote*: non-local version of repo
- ▶ **origin**: standard name of your GitHub remote
- ▶ **upstream**: source of your clone (usually **origin**)

Terminology for Branches, Forks, Commits

Recall: *distributed* version control.

- ▶ a *remote*: non-local version of repo
- ▶ **origin**: standard name of your GitHub remote
- ▶ **upstream**: source of your clone (usually **origin**)
- ▶ **master**: standard name of main branch


Terminology for Branches, Forks, Commits

Recall: *distributed* version control.


- ▶ a *remote*: non-local version of repo
- ▶ **origin**: standard name of your GitHub remote
- ▶ **upstream**: source of your clone (usually **origin**)
- ▶ **master**: standard name of main branch
- ▶ **HEAD**: most recent commit on **master** branch

Merging and Rebasing

Merging



Merging



Rebasing

Rebasing: another way to combine **master** and **subbranch**.

Rebase creates a linear (unbranched) history of commits.


Rebasing


Rebasing: another way to combine **master** and **subbranch**.


Rebase creates a linear (unbranched) history of commits.

This is a matter of some controversy.











How to Merge

From `master` branch,

```
git merge subbranch
```

will merge the work done on `subbranch` into the `master` branch.

How to Rebase

From subbranch,

```
git rebase master
```

will add work of subbranch as a downstream commit of master.

How to Rebase

From subbranch,

```
git rebase master
```

will add work of subbranch as a downstream commit of master.

But then, update master by moving to master, then rebasing:

```
git checkout master
```

```
git rebase subbranch
```

How to Rebase

From subbranch,

```
git rebase master
```

will add work of subbranch as a downstream commit of master.

But then, update master by moving to master, then rebasing:

```
git checkout master
```

```
git rebase subbranch
```

Now, branches are in sync, same commit.

To learn branching,

<https://learngitbranching.js.org>

- ▶ Complete Intro Sequence 1-3 (*Intro*, *Branching*, and *Merging*)
- ▶ (Bonus: Get through level 4, *Rebasing*)
- ▶ Read every message terminal, in terminal, and file list each step.

Pull Requests and Forks

Pull Requests

Issues, focused on branches and merging.

Pull Requests

Issues, focused on branches and merging.

Three components:

- ▶ Conversation
- ▶ Commits
- ▶ Diffs

Forking

Fork: your *copy* of a repo you don't control

Forking

Fork: your *copy* of a repo you don't control

- ▶ Clone repo

Forking

Fork: your *copy* of a repo you don't control

- ▶ Clone repo
- ▶ Stay current with canonical version

Forking

Fork: your *copy* of a repo you don't control

- ▶ Clone repo
- ▶ Stay current with canonical version
- ▶ Create branch

Forking

Fork: your *copy* of a repo you don't control

- ▶ Clone repo
- ▶ Stay current with canonical version
- ▶ Create branch
- ▶ Edit

Forking

Fork: your *copy* of a repo you don't control

- ▶ Clone repo
- ▶ Stay current with canonical version
- ▶ Create branch
- ▶ Edit
- ▶ Issue pull request

Forking

Fork: your *copy* of a repo you don't control

- ▶ Clone repo
- ▶ Stay current with canonical version
- ▶ Create branch
- ▶ Edit
- ▶ Issue pull request
- ▶ (Then, later pushes update pull request)

Find a Friend

One	Two
Bryce	Erin
JessieG	Kate
LucasA	Kelly
Milika	Mark
Olan	Cameron
Zeinabou	AndrewZ
Kathleen	Hannah
Edward	Hubbert
Jocelyn	JessicaK
Lauren	Ethan
LucasG	Sophie
Tanesia	Carine
Marc	