

CRAFT — Pitch Package

Audited retrieval-augmented AI assistant for CSA mission engineering and finance (bilingual EN/FR, cited answers, HITL-gated).

1. Containers (L2)

Figure 1 · L2 — Containers, Actors, External Systems




Figure 1 · Actors, routes, containers, data, external systems, audit perimeter.

Flask + Dash. Every route is role-checked; every step emits an AGENT_ACTION record (UMR-015/027). A LangGraph ReAct agent dispatches to the Tool and DataSource registries; responses carry citations (UMR-002/006) and a confidence score (UMR-007/010).

2. Internals (L3)

Figure 2 · L3 — Internal Clusters




Figure 2 · Agent loop with HITL branch, Tool registry, DataSource registry, auth cluster.

HITL (UMR-021–026/HITL-001–007) is a graph interrupt off `tool_node`, not middleware: the queue, timeout, reviewer UI, and decision log sit inside the same auth and audit perimeter as the agent. Self-correction / grounding loops (UMR-009/010) attach as graph nodes between retrieve and respond.

3. Use Cases

Figure 3 · Use-Case Lanes — E2 · F1 · F4




Figure 3 · UC-E2 risk + HITL · UC-F1 parametric cost + HITL · UC-F4 vendor cost roll-up (SAP).

4. Design Decisions

COMPONENT	WHY CHOSEN
Flask (server) + Dash (UI)	Routes are the integration contract — anything with a token (user, cron, agent, Teams bot) can call CRAFT. Dash shares the Flask process so the HITL reviewer UI inherits the same auth and audit.
LangGraph ReAct	First-class interrupt for HITL (UMR-021), bounded recursion (UMR-013/AAR-003 → <code>recursion_limit</code>), graph-level test anchors. Actively maintained by LangChain Inc.; standard pattern.
Protocol-typed registries (<code>Tool</code> , <code>DataSource</code> , <code>ChatProvider</code> , <code>WorkspaceStore</code> , <code>AgentActionLog</code>)	New capability or new backend = one class satisfying a protocol; no agent edit. Pyright-checked contracts (UMR-012/AAR-002).
Azure OpenAI / Azure AI Foundry (end state)	Canadian-region PBMM data residency; Foundry gives us model routing (UMR-028), rate limits (UMR-030/ASG-004), and content safety (UMR-020/ASG-001) under one procurement line.
Azure AI Search (end state)	Hybrid semantic + BM25 natively (UMR-005/ARR-002), top-K ranking at 0.72 cosine (UMR-004), managed vector store.
Azure Container Apps sandbox	Isolated per-request code exec for UMR-093 (code, inputs, outputs, exit status audited).
Entra ID + MSAL	CSA-standard identity; same token flow for human and agent callers (UMR-017/AAR-007).
Log Analytics (end state) / hash-chained JSONL (now)	Immutable audit per UMR-027/ASG-003; KQL-queryable at end state, grep-able today.
Postgres (HITL queue, 3-tier memory)	Durable approval state across restarts (UMR-025 TTL); same instance backs the episodic/semantic/procedural tiers (UMR-014/AAR-004).
SQLite (now) / managed DB (end state)	File-local for scratch + per-user data today; swap target already named behind <code>WorkspaceStore</code> .
pytest + pyright + ruff + bandit + pip-audit + detect-secrets	Architecture invariants ship as tests (route × role, protocol contracts, audit-envelope present). Industry-standard, maintained.

5. Solving the Problems — Today and at End State

The system is already running against stubs or local alternatives wired through the same registries that will carry the Azure services at end state. Cutover is a config change per row, not a rewrite.

PROBLEM (REQUIREMENT)	HOW THE ARCHITECTURE SOLVES IT TODAY	HOW IT SOLVES IT AT END STATE (AZURE-CONSOLIDATED)
Cited retrieval (UMR-002/005/006, ARR-002/003)	DocumentSearchTool + TextAnalysisTool over LocalFileSource; retrieval response schema carries document / page / section provenance.	Replace LocalFileSource with Azure AI Search backend (hybrid semantic + BM25); same DataSource call site, same citation schema.
Grounding + confidence (UMR-007/008/010)	Grounding node sits between retrieve and respond; emits confidence into AGENT_ACTION; escalates below 0.6.	Foundry evaluation + RAGAS-style scoring plugs into the same node; threshold remains code-side.
HITL approvals (UMR-021–026, HITL-001–007)	LangGraph interrupt → Postgres approval queue → Dash reviewer UI, same auth as routes; decisions logged immutably with reasoning chain, confidence, sources.	Content Safety + Foundry rate limits layer in front; approval queue and UI unchanged.
RBAC + data scope (UMR-012/017/058, AAR-002/007)	Route-gated _ROUTE_RULES + _ROLE_LEVEL; SqliteDataStore scoped by QueryTool.set_user; per-tool RBAC column staged.	Entra ID issues tokens; same role check in before_request; classification tags enforced at the data store.
Immutable audit (UMR-015/027/045, ASG-003)	AgentActionLog writes append-only JSONL with hash chain; daily rotation; covers every tool call and LLM turn.	Forward the same envelope to Log Analytics (immutability policy); KQL replaces grep.
Guardrails + sandbox (UMR-020/029/030/093, ASG-001/004/011)	Guardrail hook point in tool wrapper; code-exec slot reserved; rate limit at APIM-like proxy.	Content Safety on the hook; Azure Container Apps for code-exec; Foundry rate controls.
External data (UMR-051–054)	LocalFileSource reads mirrors / CSV fixtures of the CSA corpus and SAP line items; UC-E2 / F1 / F4 lanes run end-to-end.	SharePoint, SAP, STK, MATLAB each land as a DataSource class with MSAL / OAuth.
Multi-agent + memory (UMR-011/014/018/095, AAR-001/004)	Primary agent + tool registry + session workspace; agent_id in AGENT_ACTION already carries sub-task identity.	Add orchestrator + specialist nodes; Postgres holds the three memory tiers; per-session agent factory.
Bilingual reports (UMR-001/046/048)	Agent accepts EN/FR free text; report generator attaches citations and runs through HITL.	Azure Translator + Foundry NLG for narrative sections; same template + evidence pipeline.
Interoperability (UMR-055)	REST surface is the contract today; schema documented; external agents can trigger CRAFT with a token.	Same routes behind APIM + App Gateway (WAF, rate limit); GraphQL layer optional on top.
SLA + scale (UMR-056/057/059)	Single-instance App Service with health checks; load-test harness in place.	HA App Service + Azure Front Door; auto-scale; SSC LaunchPad for the landing zone.

6. Requirements Traceability

CAPABILITY	REQUIREMENTS	DESIGN
Primary agent	UMR-001/011/013/016/018/019/094/095, AAR-001/003/006, ASG-005	LangGraph ReAct · ChatProvider · bounded recursion
Retrieval + RAG	UMR-002/003/004/005/006/009/010/060/067, ARR-002–007	Hybrid search tool · DataSource · citation + grounding schema
Audit + traceability	UMR-015/027/045/061/062/093, AAR-005, ASG-003	AgentAction envelope · AgentActionLog · hash-chained JSONL → Log Analytics
HITL approvals	UMR-021–026/035/039/044/049, HITL-001–007, ASG-002	LangGraph interrupt · Postgres queue · Dash reviewer UI
RBAC + data scope	UMR-012/017/058/065/066, AAR-002/007	_ROUTE_RULES + _ROLE_LEVEL · SqliteDataStore · QueryTool.set_user
Session + workspace	UMR-014/092/095	WorkspaceStore → SqliteStore + SessionScratchStore; per-session agent factory
Guardrails + containment	UMR-020/029/030, ASG-001/004/011	Content Safety hook · APIM rate limit · Container Apps sandbox
Connectors + external	UMR-051–055	DataSource + MSAL · Flask REST · SAP / STK / MATLAB classes
Domain capabilities	UMR-007/008/031–050/075, ARR-001	New Tool classes over existing registries
Deployment + SLA	UMR-028/056/057/059/064/069/070/074/085, ASG-006	Azure App Service PBMM · APIM + WAF · SSC LaunchPad HA · git config

7. Blockages (End State / Current Alternative)

Each row is an Azure-consolidated end-state component wired through the registry the current alternative already runs against.

END-STATE COMPONENT	OWNER	CURRENT ALTERNATIVE
Azure AI Search (hybrid retrieval)	IT	LocalFileSource + file-name/path search
Azure Log Analytics + immutability	IT	Hash-chained append-only JSONL on disk
Azure Content Safety	Procurement	Guardrail hook off (config flag)
Azure Container Apps sandbox	Procurement	CodeExecTool registration slot reserved
Entra ID (app registration + MSAL)	IT	LocalAuthProvider stub, mocked tokens
SharePoint DataSource	IT + CSA	LocalFileSource reads a corpus mirror
SAP DataSource	Finance + Procurement	CSV fixtures via LocalFileSource (UC-F4 runs)
STK / MATLAB adapters	Procurement (licenses)	Tool slot reserved
Azure AI Foundry (model routing / rate limits)	IT	Azure OpenAI direct (Canadian region)
SSC LaunchPad HA	SSC	Single-region App Service
CSA risk taxonomy	CSA Domain	Stub taxonomy drives the classifier for tests
Historical mission DB	CSA Finance	CSV fixtures through LocalFileSource (UC-F1 runs)

8. System-Health Tooling

Runs on every commit and in CI; these are invariants, not blockages.

TOOL	ROLE
ruff	Lint (flake8 + isort + pyupgrade)
pyright (strict)	Type checking · protocol conformance
pytest + coverage	Route × role matrix · protocol contracts · audit-envelope invariants (156 tests, 91% cov)
bandit	Security scan
pip-audit	Dependency CVE audit
detect-secrets	No credentials in git