

Package ‘crestr’

February 17, 2023

Title A Probabilistic Approach to Reconstruct Past Climates Using Palaeoecological Datasets

Version 1.3.0.9000

Description Applies the CREST climate reconstruction method. It can be used using the calibration data that can be obtained through the package or by importing private data. An ensemble of graphical outputs were designed to facilitate the use of the package and the interpretation of the results. More information can be obtained from Chevalier (2022) <[doi:10.5194/cp-18-821-2022](https://doi.org/10.5194/cp-18-821-2022)>.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.3

Imports clipr,
DBI,
methods,
openxlsx,
plot3D,
plyr,
raster,
RPostgres,
RSQLite,
scales,
sp,
stringr,
viridis

Suggests knitr,
rmarkdown,
pals

Depends R (>= 2.10)

Language en-us

VignetteBuilder knitr

URL <https://github.com/mchevalier2/crestr>, <https://mchevalier2.github.io/crestr/index.html>

BugReports <https://github.com/mchevalier2/crestr/issues>

R topics documented:

accBasinNames	3
accClimateVariables	4
accCountryNames	4
accRealmNames	5
calib_clim_space	6
check_coordinates	6
cite_climate_data	7
cite_crest	7
cite_distrib_data	8
cite_method	8
climate_from_xy	9
close_db_connection	9
colour_theme	10
connect_local_sqlite3	11
connect_online	11
convert2percentages	12
convert2presenceAbsence	13
copy_crest	13
createPSE	14
crest	15
crest.calibrate	17
crest.get_modern_data	18
crest.reconstruct	21
crest.set_modern_data	22
crest.simplify	23
crest_ex	24
crest_ex_pse	25
crest_ex_selection	25
crestObj	26
crop	28
dbRequest	29
dbSubset	30
eqearth_get_ext	31
excludeTaxa	31
explore_calibration_dataset	32
export	33
export_pdfs	35
find.original.name	36
fit_pdfsp	36
fit_xrange	37
get_taxa_type	38
getClimateSpace	38
getDistribTaxa	40
getSpeciesdiversity	41
getTaxaTypeFromTaxID	42
getTaxonID	42
getTaxonomy	43
includeTaxa	44
is.crestObj	45
isColourStr	45

<i>accBasinNames</i>	3
loo	46
M1	46
makeTransparent	47
meanPositiveValues	47
normalise	48
pdf_ranges	48
plot.crestObj	49
plot_climateSpace	51
plot_combinedPDFs	52
plot_diagram	54
plot_loo	56
plot_map_eqearth	58
plot_scatterPDFs	59
plot_taxaCharacteristics	60
plot_violinPDFs	62
reconstr	63
taxonComposition	63
testConnection	64
Index	65

<code>accBasinNames</code>	<i>Return the list of oceans and seas.</i>
----------------------------	--

Description

Return the list of oceans and seas.

Usage

```
accBasinNames(basin = NA)
```

Arguments

`basin` A name of basin. Default is NA and returns a list of all the accepted names.

Value

A list of accepted names.

See Also

<https://www.marineregions.org/downloads.php>

Examples

```
accBasinNames()
accBasinNames('Indian Ocean')
```

accClimateVariables *Describes all the variables available in the database.*

Description

Provides the index and the short and full names of all the variables available in the database.

Usage

```
accClimateVariables(v = NA, domain = NA)
```

Arguments

v	The name of a variable to quickly access its description and ID (default NA returns all possible values).
domain	The domain ('Terrestrial' or 'Marine') of the variables. Default value is NA and both terrestrial and marine climate variable names are returned.

Value

A data frame descriptive of the climate variables available in the database (if v=NA) or the description of variable v.

See Also

<https://www.worldclim.org/data/bioclim.html> for details on the 'bio' data, <https://cgiarcsi.community/2019/01/24/global-aridity-index-and-potential-evapotranspiration-climate-database-v2/> for details on 'ai', <https://www.ncei.noaa.gov/products/world-ocean-atlas> for details on the sea surface temperature, sea surface salinity and nutrient Concentration data, or <https://psl.noaa.gov/data/gridded/data.noaa.oisst.v2.highres.html> for the sea ice concentration data.

Examples

```
## Not run:
  accClimateVariables()
  accClimateVariables(v='bio12')

## End(Not run)
```

accCountryNames *Return the list of the continents and associated countries.*

Description

Return the list of the continents and associated countries.

Usage

```
accCountryNames(continent = NA)
```

Arguments

continent A name of continent. Default is NA and returns a list of all the country names sorted by continent.

Value

A list where each element is a vector of corresponding country names.

See Also

<https://www.naturalearthdata.com/downloads/10m-cultural-vectors/10m-admin-0-countries/>

Examples

```
accCountryNames()
accCountryNames('Europe')
```

accRealmNames	<i>Return the list of the realms and associated biomes and ecoregions.</i>
---------------	--

Description

Return the list of the realms and associated biomes and ecoregions.

Usage

```
accRealmNames(realms = NA, ecoregion = TRUE)
```

Arguments

realms A name of accepted realm. Default is NA and returns a list of all the biome and ecoregion names sorted by realm.

ecoregion A boolean to choose whether to get the ecoregions names.

Value

A list with elements that correspond to the biomes (and possibly ecoregions) of each realm.

See Also

<https://www.worldwildlife.org/publications/terrestrial-ecoregions-of-the-world>

Examples

```
accRealmNames()
accRealmNames(realms='Africotropical')
accRealmNames(realms='Africotropical', ecoregion=FALSE)
```

calib_clim_space	<i>Calibrate the distribution of the modern climate space.</i>
------------------	--

Description

Calibrate the distribution of the modern climate space.

Usage

```
calib_clim_space(climate, bin_width)
```

Arguments

climate	A vector of climatic values where the species is present.
bin_width	The width of the bins used to correct for unbalanced climate state. Use values that split the studied climate gradient in 15-25 classes (e.g. 2°C for temperature variables). Default is 1.

Value

A ccs object that will be used by [fit_pdfsp](#).

Examples

```
calib_clim_space(sample(0:300 / 10, 4000, replace = TRUE), 2)
```

check_coordinates	<i>Check if the coordinates are correct.</i>
-------------------	--

Description

Check if the coordinates are correct.

Usage

```
check_coordinates(xmn, xmx, ymn, ymx)
```

Arguments

xmn, xmx, ymn, ymx	The coordinates defining the study area.
--------------------	--

Value

Return a set of valid coordinates.

Examples

```
check_coordinates(NA, NA, NA, NA)
check_coordinates(-200, 0, 0, 90)
check_coordinates(20, 0, 90, 0)
```

<code>cite_climate_data</code>	<i>Returns the references associated with the climate data used to fit the pdfs.</i>
--------------------------------	--

Description

Returns the references associated with the climate data used to fit the pdfs.

Usage

```
cite_climate_data(x, verbose = TRUE)
```

Arguments

<code>x</code>	A <code>crestObj</code> produced by one of the <code>crest</code> , <code>crest.get_modern_data</code> , <code>crest.calibrate</code> , <code>crest.reconstruct</code> or <code>loo</code> functions.
<code>verbose</code>	A boolean to print non-essential comments on the terminal (default TRUE).

Value

A list of references to add if the data generated by crestr are published.

<code>cite_crest</code>	<i>Returns the list of references associated to the reconstruction.</i>
-------------------------	---

Description

Returns the list of references associated to the reconstruction.

Usage

```
cite_crest(x, verbose = TRUE)
```

Arguments

<code>x</code>	A <code>crestObj</code> produced by one of the <code>crest</code> , <code>crest.get_modern_data</code> , <code>crest.calibrate</code> , <code>crest.reconstruct</code> or <code>loo</code> functions.
<code>verbose</code>	A boolean to print non-essential comments on the terminal (default TRUE).

Value

A list of references to add if the data generated by crestr are published.

cite_distrib_data	<i>Returns the references associated with the GBIF data used to fit the pdfs.</i>
-------------------	---

Description

Returns the references associated with the GBIF data used to fit the pdfs.

Usage

```
cite_distrib_data(x, verbose = TRUE)
```

Arguments

x	A <code>crestObj</code> produced by one of the <code>crest</code> , <code>crest.get_modern_data</code> , <code>crest.calibrate</code> , <code>crest.reconstruct</code> or <code>loo</code> functions.
verbose	A boolean to print non-essential comments on the terminal (default TRUE).

Value

A list of references to add if the data generated by crestr are published.

cite_method	<i>Returns the references associated with the development of CREST.</i>
-------------	---

Description

Returns the references associated with the development of CREST.

Usage

```
cite_method(x, verbose = TRUE)
```

Arguments

x	A <code>crestObj</code> produced by one of the <code>crest</code> , <code>crest.get_modern_data</code> , <code>crest.calibrate</code> , <code>crest.reconstruct</code> or <code>loo</code> functions.
verbose	A boolean to print non-essential comments on the terminal (default TRUE).

Value

A list of references to add if the data generated by crestr are published.

climate_from_xy	<i>Extract The climate values associated to a set of coordinates.</i>
-----------------	---

Description

Extract The climate values associated to a set of coordinates.

Usage

```
climate_from_xy(
  long,
  lat,
  climate = accClimateVariables()[, 2],
  resol = 0.25,
  dbname = "gbif4crest_02"
)
```

Arguments

long	The longitude of the site.
lat	The latitude of the site.
climate	The climate variables to extract the values from. Returns all possible values by default.
resol	The resolution of the target climatology (default 0.25 degrees).
dbname	The name of the data source database.

Value

A data frame containing the climate values.

Examples

```
## Not run:
climate_from_xy(50, 10, c('bio1', 'ai'))
climate_from_xy(50, 10)

## End(Not run)
```

close_db_connection	<i>Disconnect the database connection.</i>
---------------------	--

Description

Disconnect the database connection.

Usage

```
close_db_connection(db)
```

Arguments

db An active database connection

Value

No return value, function called to close the connection to the database.

Examples

```
## Not run:  
db <- connect_online()  
close_db_connection(db)  
  
## End(Not run)
```

colour_theme	<i>Returns a vector of colours</i>
--------------	------------------------------------

Description

Returns a vector of colours

Usage

```
colour_theme(n)
```

Arguments

n An index to select the colour theme

Value

A vector of colours.

Examples

```
colour_theme(1)
```

connect_local_sqlite3	<i>Connect to the gbif4crest calibration database</i>
-----------------------	---

Description

Connect to the gbif4crest_02 database using a local SQLite3 copy.

Usage

```
connect_local_sqlite3(dbname = "gbif4crest_02.sqlite3")
```

Arguments

dbname	The complete path to the SQLite3 file. The name should end by '.sqlite3'
--------	--

Value

An active connection to a database

See Also

The SQLite3 database can be downloaded from https://figshare.com/articles/dataset/GBIF_for_CREST_database/6743207.

Examples

```
## Not run:  
db <- connect_online()  
  
## End(Not run)
```

connect_online	<i>Connect to the gbif4crest calibration database</i>
----------------	---

Description

Connect to the gbif4crest_02 database by accessing the server on Amazon.

Usage

```
connect_online(  
  dbname = "gbif4crest_02",  
  port = 5432,  
  host = "gbif4crest.cvqgy2mnjwtg.eu-west-3.rds.amazonaws.com",  
  user = "guestuser",  
  password = "pwd12345"  
)
```

Arguments

dbname	The name of the database. Default is 'gbif4crest_02'.
port	The port to connect to the server. Default is 5432.
host	The host of the database server. Default is 'gbif4crest.cvqgy2mnjwgtg.eu-west-3.rds.amazonaws.com'.
user	The user name to use to connect. Default is 'guestuser'.
password	The password associated with the user name. Default is 'pwd12345'.

Value

An active connection to a database

Examples

```
## Not run:
db <- connect_online()

## End(Not run)
```

convert2percentages	<i>Convert abundance data into percentage data.</i>
---------------------	---

Description

Convert abundance data into percentage data.

Usage

```
convert2percentages(df, col2convert = 2:ncol(df))
```

Arguments

df	The dataframe containing the data to convert.
col2convert	A vector of the columns to convert. Default is all the columns but the first, which contains an age, a depth or a sampleID.

Value

A vector of unique taxonIDs.

Examples

```
df <- data.frame(matrix(1:25, ncol = 5))
colnames(df) <- paste(rep("col", 5), 1:5, sep = "")
convert2percentages(df)
convert2percentages(df, col2convert = 3:5)
```

 convert2presenceAbsence

Convert data into presence/absence data.

Description

Convert data into presence/absence data.

Usage

```
convert2presenceAbsence(df, threshold = 2, col2convert = 2:ncol(df))
```

Arguments

df	The dataframe containing the data to convert.
threshold	The threshold that defines presence (presence if \geq threshold)
col2convert	A vector of the columns to convert. Default is all the columns but the first, which contains an age, a depth or a sampleID.

Value

A vector of unique taxonIDs.

Examples

```
df <- data.frame(matrix(1:25, ncol = 5))
colnames(df) <- paste(rep("col", 5), 1:5, sep = "")
convert2presenceAbsence(df, threshold = 15)
convert2presenceAbsence(df, col2convert = 3:5)
```

 copy_crest

Copy crest data to the clipboard.

Description

Copy crest data to the clipboard for an easy extraction of the data from the R environment.

Usage

```
copy_crest(
  x,
  climate = x$parameters$climate,
  optima = TRUE,
  mean = FALSE,
  uncertainties = FALSE
)
```

Arguments

x	A <code>crestObj</code> produced by the <code>crest.reconstruct</code> or <code>crest</code> functions.
climate	A vector of the climate variables to extract. See <code>accClimateVariables</code> for the list of accepted values.
optima	A boolean value to indicate if the optima should be copied to the clipboard.
mean	A boolean value to indicate if the means should be copied to the clipboard.
uncertainties	A boolean value to indicate if the uncertainties should be copied to the clipboard.

Value

No return value. This function is called to copy the crest data to the clipboard.

Examples

```
## Not run:
if(requireNamespace('clipr', quietly=TRUE)) {
  reconstr <- crest(
    df = crest_ex, pse = crest_ex_pse, taxaType = 0,
    climate = c("bio1", "bio12"), bin_width = c(2, 20),
    shape = c("normal", "lognormal"),
    selectedTaxa = crest_ex_selection, dbname = "crest_example",
    leave_one_out = TRUE
  )
  copy_crest(reconstr, uncertainties=TRUE)
  ## You can now paste the values in a spreadsheet.
}

## End(Not run)
```

createPSE

Creates a spreadsheet with the format required for a PSE.

Description

Creates a spreadsheet with the format required for a PSE from a list of taxa.

Usage

```
createPSE(taxa, loc = "proxy_species_equivalency.xlsx")
```

Arguments

taxa	A list of taxa to include in the PSE file.
loc	An absolute or relative path that indicates where the spreadsheet should be saved. Also used to specify the name of the file. Default: the file is saved in the working directory under the name <code>proxy_species_equivalency.xlsx</code> .

Value

No return value, called to create a PSE file.

Examples

```
data(crest_ex)
createPSE(taxa = colnames(crest_ex)[-1],
          loc=file.path(tempdir(), 'pse.xlsx')
)
```

crest	<i>A wrapper for all the crest functions.</i>
-------	---

Description

Runs all the different steps of a CREST reconstruction in one function.

Usage

```
crest(
  df,
  climate,
  pse = NA,
  taxaType = 0,
  distributions = NA,
  site_info = rep(NA, length(climate)),
  site_name = NA,
  xmn = NA,
  xmx = NA,
  ymn = NA,
  ymx = NA,
  continents = NA,
  countries = NA,
  realms = NA,
  biomes = NA,
  ecoregions = NA,
  minGridCells = 20,
  selectedTaxa = NA,
  bin_width = rep(1, length(x$parameters$climate)),
  shape = rep("normal", length(x$parameters$climate)),
  npoints = 500,
  ai.sqrt = FALSE,
  geoWeighting = TRUE,
  climateSpaceWeighting = TRUE,
  presenceThreshold = 0,
  taxWeight = "normalisation",
  uncertainties = c(0.5, 0.95),
  leave_one_out = FALSE,
  verbose = TRUE,
  dbname = "gbif4crest_02"
)
```

Arguments

<code>df</code>	A data frame containing the data to reconstruct (counts, percentages or presence/absence data).
<code>climate</code>	A vector of the climate variables to extract. See accClimateVariables for the list of accepted values.
<code>pse</code>	A pollen-Species equivalency table. See createPSE for details.
<code>taxaType</code>	A numerical index (between 1 and 6) to define the type of palaeoproxy used: 1 for plants, 2 for beetles, 3 for chironomids, 4 for foraminifers, 5 for diatoms and 6 for rodents. The example dataset uses <code>taxaType=0</code> (pseudo-data). Default is 1.
<code>distributions</code>	A dataframe containing the presence records of the studied proxies and their associated climate values.
<code>site_info</code>	A vector containing the coordinates of the study site. Default <code>c(NA, NA)</code> .
<code>site_name</code>	The name of the dataset (default NA).
<code>xmn, xmx, ymn, ymx</code>	The coordinates defining the study area.
<code>continents</code>	A vector of the continent names defining the study area.
<code>countries</code>	A vector of the country names defining the study area.
<code>realms</code>	A vector of the studied botanical realms defining the study area.
<code>biomes</code>	A vector of the studied botanical biomes defining the study area.
<code>ecoregions</code>	A vector of the studied botanical ecoregions defining the study area.
<code>minGridCells</code>	The minimum number of unique presence data necessary to estimate a species' climate response. Default is 20.
<code>selectedTaxa</code>	A data frame assigns which taxa should be used for each variable (1 if the taxon should be used, 0 otherwise). The colnames should be the climate variables' names and the rownames the taxa names. Default is 1 for all taxa and all variables.
<code>bin_width</code>	The width of the bins used to correct for unbalanced climate state. Use values that split the studied climate gradient in 15-25 classes (e.g. 2°C for temperature variables). Default is 1.
<code>shape</code>	The imposed shape of the species pdfs. We recommend using 'normal' for temperature variables and 'lognormal' for the variables that can only take positive values, such as precipitation or aridity. Default is 'normal' for all.
<code>npoints</code>	The number of points to be used to fit the pdfs. Default 200.
<code>ai.sqrt</code>	A boolean to indicate whether ai values should be square-root transformed (default FALSE).
<code>geoWeighting</code>	A boolean to indicate if the species should be weighting by the square root of their extension when estimating a genus/family level taxon-climate relationships.
<code>climateSpaceWeighting</code>	A boolean to indicate if the species pdfs should be corrected for the modern distribution of the climate space (default TRUE).
<code>presenceThreshold</code>	All values above that threshold will be used in the reconstruction (e.g. if set at 1, all percentages below 1 will be set to 0 and the associated presences discarded). Default is 0.

taxWeight	One value among the following: 'originalData', 'presence/absence', 'percent-ages' or 'normalisation' (default).
uncertainties	A (vector of) threshold value(s) indicating the error bars that should be calculated (default both 50 and 95% ranges).
leave_one_out	A boolean to indicate whether the leave one out (loo) reconstructions should be computed (default FALSE).
verbose	A boolean to print non-essential comments on the terminal (default TRUE).
dbname	The name of the database. Default is 'gbif4crest_02'.

Value

A `crestObj` containing the reconstructions.

Examples

```
## Not run:
data(crest_ex)
data(crest_ex_pse)
data(crest_ex_selection)
reconstr <- crest(
  df = crest_ex, pse = crest_ex_pse, taxaType = 0,
  site_info = c(7.5, 7.5), site_name = 'crest_example',
  climate = c("bio1", "bio12"), bin_width = c(2, 50),
  shape = c("normal", "lognormal"),
  selectedTaxa = crest_ex_selection, dbname = "crest_example",
  leave_one_out = TRUE,
  verbose = FALSE
)
plot(reconstr)
plot_loo(reconstr)

## End(Not run)
```

crest.calibrate

Fit the species and proxy pdfs

Description

This function fits the climate response of the selected taxa to the selected climate variables.

Usage

```
crest.calibrate(
  x,
  bin_width = x$parameters$bin_width,
  shape = x$parameters$shape,
  npoints = x$parameters$npoints,
  geoWeighting = x$parameters$geoWeighting,
  climateSpaceWeighting = x$parameters$climateSpaceWeighting,
  verbose = TRUE
)
```

Arguments

x	A <code>crestObj</code> produced by the <code>crest.get_modern_data</code> function.
bin_width	The width of the bins used to correct for unbalanced climate state. Use values that split the studied climate gradient in 15-25 classes (e.g. 2°C for temperature variables). Default is 1.
shape	The imposed shape of the species pdfs. We recommend using 'normal' for temperature variables and 'lognormal' for the variables that can only take positive values, such as precipitation or aridity. Default is 'normal' for all.
npoints	The number of points to be used to fit the pdfs. Default 200.
geoWeighting	A boolean to indicate if the species should be weighting by the square root of their extension when estimating a genus/family level taxon-climate relationships.
climateSpaceWeighting	A boolean to indicate if the species pdfs should be corrected for the modern distribution of the climate space (default TRUE).
verbose	A boolean to print non-essential comments on the terminal (default TRUE).

Value

A `crestObj` object containing the spatial distributions and the climate space.

Examples

```
## Not run:
data(crest_ex_pse)
data(crest_ex_selection)
data(crest_ex)
x <- crest.get_modern_data( df = crest_ex,
  pse = crest_ex_pse, taxaType = 0,
  climate = c("bio1", "bio12"),
  selectedTaxa = crest_ex_selection, dbname = "crest_example",
  verbose = FALSE
)
x <- crest.calibrate(x,
  geoWeighting = TRUE, climateSpaceWeighting = TRUE,
  bin_width = c(2, 50), shape = c("normal", "lognormal"),
  verbose = FALSE
)

## End(Not run)
```

`crest.get_modern_data` *Extract distributions from the database*

Description

This function will extract the distributions of all the species composing each taxon and return them as a list.

Usage

```
crest.get_modern_data(
  pse,
  taxaType,
  climate,
  df = NA,
  ai.sqrt = FALSE,
  xmn = NA,
  xmx = NA,
  ymn = NA,
  ymx = NA,
  continents = NA,
  countries = NA,
  basins = NA,
  sectors = NA,
  realms = NA,
  biomes = NA,
  ecoregions = NA,
  minGridCells = 20,
  elev_min = NA,
  elev_max = NA,
  elev_range = NA,
  year_min = 1900,
  year_max = 2021,
  nodate = TRUE,
  type_of_obs = c(1, 2, 3, 8, 9),
  selectedTaxa = NA,
  site_info = c(NA, NA),
  site_name = NA,
  dbname = "gbif4crest_02",
  verbose = TRUE
)
```

Arguments

pse	A pollen-Species equivalency table. See createPSE for details.
taxaType	A numerical index (between 1 and 6) to define the type of palaeoproxy used: 1 for plants, 2 for beetles, 3 for chironomids, 4 for foraminifers, 5 for diatoms and 6 for rodents. The example dataset uses taxaType=0 (pseudo-data). Default is 1.
climate	A vector of the climate variables to extract. See accClimateVariables for the list of accepted values.
df	A data frame containing the data to reconstruct (counts, percentages or presence/absence data).
ai.sqrt	A boolean to indicate whether ai values should be square-root transformed (default FALSE).
xmn, xmx, ymn, ymx	The coordinates defining the study area.
continents	A vector of the continent names defining the study area.
countries	A vector of the country names defining the study area.
basins	A vector of the ocean names defining the study area.

sectors	A vector of the marine sector names defining the study area.
realms	A vector of the studied botanical realms defining the study area.
biomes	A vector of the studied botanical biomes defining the study area.
ecoregions	A vector of the studied botanical ecoregions defining the study area.
minGridCells	The minimum number of unique presence data necessary to estimate a species' climate response. Default is 20.
elev_min, elev_max	Parameters to only selected grid cells with an elevation higher than elev_min or lower than elev_max (default is 'NA').
elev_range	Parameters discard the grid cell with a high elevation range (default is NA).
year_min, year_max	The oldest and youngest occurrences accepted (default is 1900-2021).
nodate	A boolean to accept occurrences without a date (can overlap with occurrences with a date; default TRUE).
type_of_obs	The type of observation to use in the study. 1: human observation, 2: observation, 3: preserved specimen, 4: living specimen, 5: fossil specimen, 6: material sample, 7: machine observation, 8: literature, 9: unknown (Default c(1, 2, 3, 8, 9))
selectedTaxa	A data frame assigns which taxa should be used for each variable (1 if the taxon should be used, 0 otherwise). The colnames should be the climate variables' names and the rownames the taxa names. Default is 1 for all taxa and all variables.
site_info	A vector containing the coordinates of the study site. Default c(NA, NA).
site_name	The name of the dataset (default NA).
dbname	The name of the database. Default is 'gbif4crest_02' and data will be extracted from the online database. The SQLite3 version of the database can also be used here by providing the complete path to a file ending by .sqlite3, e.g. /path/to/file/gbif4crest_02.sqlite3
verbose	A boolean to print non-essential comments on the terminal (default TRUE).

Value

A `crestObj` object containing the spatial distributions.

See Also

The SQLite3 database can be downloaded from https://figshare.com/articles/dataset/GBIF_for_CREST_database/6743207.

Examples

```
## Not run:
data(crest_ex_pse)
data(crest_ex_selection)
data(crest_ex)
x <- crest.get_modern_data( df = crest_ex,
  pse = crest_ex_pse, taxaType = 0,
  climate = c("bio1", "bio12"),
  selectedTaxa = crest_ex_selection, dbname = "crest_example",
  verbose = FALSE
```

```

    )
  x
  lapply(x$modelling$distributions, head)

## End(Not run)

```

crest.reconstruct	<i>Reconstruct climate from fossil data</i>
-------------------	---

Description

This function fits the climate response of the selected taxa to the selected climate variables.

Usage

```

crest.reconstruct(
  x,
  presenceThreshold = 0,
  taxWeight = "normalisation",
  uncertainties = c(0.5, 0.95),
  skip_for_loo = FALSE,
  verbose = TRUE
)

```

Arguments

x	A crestObj produced by the crest.calibrate function.
presenceThreshold	All values above that threshold will be used in the reconstruction (e.g. if set at 1, all percentages below 1 will be set to 0 and the associated presences discarded). Default is 0.
taxWeight	One value among the following: 'originalData', 'presence/absence', 'percentages' or 'normalisation' (default).
uncertainties	A (vector of) threshold value(s) indicating the error bars that should be calculated (default both 50 and 95% ranges).
skip_for_loo	A boolean that tells the loo function to skip parts and fasten the process. Not for users, always leave to FALSE.
verbose	A boolean to print non-essential comments on the terminal (default TRUE).

Value

A [crestObj](#) object containing the reconstructions and all the associated data.

Examples

```

data(crest_ex_pse)
data(crest_ex_selection)
data(crest_ex)
## Not run:
x <- crest.get_modern_data( df = crest_ex,

```

```

pse = crest_ex_pse, taxaType = 0,
climate = c("bio1", "bio12"),
selectedTaxa = crest_ex_selection, dbname = "crest_example",
verbose = FALSE
)
x <- crest.calibrate(x,
  geoWeighting = TRUE, climateSpaceWeighting = TRUE,
  bin_width = c(2, 50), shape = c("normal", "lognormal"),
  verbose = FALSE
)
x <- crest.reconstruct(x,
  verbose = FALSE)
plot(x)

## End(Not run)

```

crest.set_modern_data *Format a crestObj with private data.*

Description

Format a crestObj with private data.

Usage

```

crest.set_modern_data(
  distributions,
  climate,
  df = NA,
  climate_space = NA,
  weight = FALSE,
  minGridCells = 0,
  selectedTaxa = NA,
  site_info = c(NA, NA),
  site_name = NA,
  site_climate = rep(NA, length(climate)),
  verbose = TRUE
)

```

Arguments

distributions	A dataframe containing the presence records of the studied proxies and their associated climate values.
climate	A vector of the climate variables to extract. See accClimateVariables for the list of accepted values.
df	A data frame containing the data to reconstruct (counts, percentages or presence/absence data).
climate_space	A dataframe of climate values across the study area useful to correct for the imbalance of the sampling data (see ' crest.calibrate ' for more details). Default is NA.

weight	The records in the distributions can be weighted using the percentages by setting weight=TRUE. Include a column called 'weight' in the distributions table.
minGridCells	The minimum number of unique presence data necessary to estimate a species' climate response. Default is 20.
selectedTaxa	A data frame assigns which taxa should be used for each variable (1 if the taxon should be used, 0 otherwise). The colnames should be the climate variables' names and the rownames the taxa names. Default is 1 for all taxa and all variables.
site_info	A vector containing the coordinates of the study site. Default c(NA, NA).
site_name	The name of the dataset (default NA).
site_climate	The climate values at the location of the dataset '(default NA).
verbose	A boolean to print non-essential comments on the terminal (default TRUE).

Value

A `crestObj` object containing the spatial distributions.

Examples

```
#> Reformating the example dataset to fit this function
distributions <- cbind('ProxyName'= rep('Taxon1', nrow(reconstr$modelling$distributions[[1]])),
                      reconstr$modelling$distributions[[1]],
                      stringsAsFactors = FALSE)
for(tax in names(reconstr$modelling$distributions)[-1]) {
  distributions <- rbind(distributions,
                        cbind('ProxyName'= rep(tax, nrow(reconstr$modelling$distributions[[tax]])),
                              reconstr$modelling$distributions[[tax]],
                              stringsAsFactors = FALSE)
                        )
}
distributions <- distributions[, c(2,1,3:6)]
print(head(distributions))

climate_space <- reconstr$modelling$climate_space
print(head(climate_space))

x <- crest.set_modern_data(distributions, df=crest_ex,
                          climate = c("bio1", "bio12"))
x <- crest.set_modern_data(distributions, df=crest_ex,
                          climate_space=climate_space,
                          climate = c("bio1", "bio12"))
```

```
crest.simplify
```

Simplify a crestObj into a dataframe.

Description

Simplify a `crestObj` with reconstructed values into a dataframe.

Usage

```
crest.simplify(x, optima = TRUE)
```

Arguments

x A `crestObj` produced by the `crest`, `crest.reconstruct` or `loo` functions.

optima A boolean to indicate whether to plot the optimum (TRUE) or the mean (FALSE) estimates.

Value

A dataframe with the age/depth of each sample and all the best reconstructed values.

Examples

```
head(crest.simplify(reconstr))
```

crest_ex	<i>Example dataset to run the CREST method for the first time.</i>
----------	--

Description

A dataset containing 20 randomly generated pollen samples for 7 pollen taxa.

Usage

```
crest_ex
```

Format

A data frame with 20 rows (samples) and 8 columns (1 column for the age and one for each of the 7 taxa):

Age: Age of each sample

Taxon1: Percentage of Taxon1 in each sample.

Taxon2: Percentage of Taxon2 in each sample.

Taxon3: Percentage of Taxon3 in each sample.

Taxon4: Percentage of Taxon4 in each sample.

Taxon5: Percentage of Taxon5 in each sample.

Taxon6: Percentage of Taxon6 in each sample.

Taxon7: Percentage of Taxon7 in each sample.

`crest_ex_pse`*Example dataset to Extract data from the example database.*

Description

A database indicating the taxonomy of the example proxies.

Usage`crest_ex_pse`**Format**

A data frame with 7 rows (taxa) and 5 columns (taxonomy description):

Level: An integer indicating the taxonomic resolution (1 family, 2 genus, 3 species, 4 or higher ignore taxon)

Family: The family corresponding to the ProxyName

Genus: The genus corresponding to the ProxyName

Species: The species corresponding to the ProxyName

ProxyName: The names of the observed proxies, as reported in the main data file

`crest_ex_selection`*Example dataset to associate taxa with climate variables.*

Description

A data frame indicating the taxa that should be used to reconstruct each climate variable (1s in the matrix) and those who should be excluded (0s).

Usage`crest_ex_selection`**Format**

A data frame with 7 rows (taxa) and 2 columns (climate variables):

bio1: The first variable to reconstruct (mean annual temperature)

bio12: The second variable to reconstruct (annual precipitation)

crestObj	Create a crestObj object.
----------	---------------------------

Description

Creates a crestObj object with all default parameters.

Usage

```
crestObj(
  taxa.name,
  taxaType,
  climate,
  pse = NA,
  dbname = NA,
  continents = NA,
  countries = NA,
  basins = NA,
  sectors = NA,
  realms = NA,
  biomes = NA,
  ecoregions = NA,
  xmn = NA,
  xmx = NA,
  ymn = NA,
  ymx = NA,
  elev_min = NA,
  elev_max = NA,
  elev_range = NA,
  year_min = 1900,
  year_max = 2021,
  nodate = TRUE,
  type_of_obs = c(1, 2, 3, 8, 9),
  df = NA,
  x = NA,
  x.name = "",
  minGridCells = 20,
  weightedPresences = FALSE,
  bin_width = NA,
  shape = NA,
  npoints = 200,
  geoWeighting = TRUE,
  climateSpaceWeighting = TRUE,
  selectedTaxa = NA,
  distributions = NA,
  presenceThreshold = 0,
  taxWeight = "normalisation",
  uncertainties = c(0.5, 0.95)
)
```

Arguments

taxa.name	A vector that contains the names of the taxa to study.
taxaType	A numerical index (between 1 and 6) to define the type of palaeoproxy used: 1 for plants, 2 for beetles, 3 for chironomids, 4 for foraminifers, 5 for diatoms and 6 for rodents. The example dataset uses taxaType=0 (pseudo-data). Default is 1.
climate	A vector of the climate variables to extract. See accClimateVariables for the list of accepted values.
pse	A pollen-Species equivalency table. See createPSE for details.
dbname	The name of the data source database.
continents	A vector of the continent names defining the study area.
countries	A vector of the country names defining the study area.
basins	A vector of the ocean names defining the study area.
sectors	A vector of the marine sector names defining the study area.
realms	A vector of the studied botanical realms defining the study area.
biomes	A vector of the studied botanical biomes defining the study area.
ecoregions	A vector of the studied botanical ecoregions defining the study area.
xmn, xmx, ymn, ymx	The coordinates defining the study area.
elev_min, elev_max	Parameters to only selected grid cells with an elevation higher than elev_min or lower than elev_max (default is 'NA').
elev_range	Parameters discard the grid cell with a high elevation range (default is NA).
year_min, year_max	The oldest and youngest occurrences accepted (default is 1900-2021).
nodate	A boolean to accept occurrences without a date (can overlap with occurrences with a date; default TRUE).
type_of_obs	The type of observation to use in the study. 1: human observation, 2: observation, 3: preserved specimen, 4: living specimen, 5: fossil specimen, 6: material sample, 7: machine observation, 8: literature, 9: unknown (Default c(1, 2, 3, 8, 9))
df	A data frame containing the data to reconstruct (counts, percentages or presence/absence data).
x	The name, age or depth of the rows of df (the samples).
x.name	A string describing the x axis (e.g. 'Sample Name', 'Age', 'Depth').
minGridCells	The minimum number of unique presence data necessary to estimate a species' climate response. Default is 20.
weightedPresences	A boolean to indicate whether the presence records should be weighted. Default is FALSE.
bin_width	The width of the bins used to correct for unbalanced climate state. Use values that split the studied climate gradient in 15-25 classes (e.g. 2°C for temperature variables). Default is 1.
shape	The imposed shape of the species pdfs. We recommend using 'normal' for temperature variables and 'lognormal' for the variables that can only take positive values, such as precipitation or aridity. Default is 'normal' for all.

<code>npoints</code>	The number of points to be used to fit the pdfs. Default 200.
<code>geoWeighting</code>	A boolean to indicate if the species should be weighting by the square root of their extension when estimating a genus/family level taxon-climate relationships.
<code>climateSpaceWeighting</code>	A boolean to indicate if the species pdfs should be corrected for the modern distribution of the climate space (default TRUE).
<code>selectedTaxa</code>	A data frame assigns which taxa should be used for each variable (1 if the taxon should be used, 0 otherwise). The colnames should be the climate variables' names and the rownames the taxa names. Default is 1 for all taxa and all variables.
<code>distributions</code>	A dataframe containing the presence records of the studied proxies and their associated climate values.
<code>presenceThreshold</code>	All values above that threshold will be used in the reconstruction (e.g. if set at 1, all percentages below 1 will be set to 0 and the associated presences discarded). Default is 0.
<code>taxWeight</code>	One value among the following: 'originalData', 'presence/absence', 'percentages' or 'normalisation' (default).
<code>uncertainties</code>	A (vector of) threshold value(s) indicating the error bars that should be calculated (default both 50 and 95% ranges).

Value

A `crestObj` object that is used to store data and information for reconstructing climate

See Also

See `vignette('technicalities')` for details about the structure of the object. See also <https://gbif.github.io/parsers/apidocs/org/gbif/api/vocabulary/BasisOfRecord.html> for a detailed explanation of the types of observation.

`crop`

Crop the dataset obtained from `crest.get_modern_data`

Description

Crop the dataset obtained from `crest.get_modern_data` according to an object of the class `SpatialPolygonsDataFrame`

Usage

```
crop(x, shp)
```

Arguments

<code>x</code>	A <code>crestObj</code> produced by the <code>crest.get_modern_data</code> function.
<code>shp</code>	A shapefile to crop the data. Data points will be kept if their centroid is within the shape.

Value

An updated version of the `crest.get_modern_data`.

Examples

```
## Not run:
data(M1)
## We want only the data covering Nigeria
M2 <- M1[M1$COUNTRY == 'Nigeria', ]
data(reconstr)
reconstr.cropped <- crop(reconstr, M2)
data1 <- raster::rasterFromXYZ(reconstr$modelling$climate_space[, 1:3],
                              crs=raster::crs(M1))
data2 <- raster::rasterFromXYZ(reconstr.cropped$modelling$climate_space[, 1:3],
                              crs=raster::crs(M1))
layout(matrix(c(1,2,3,4), byrow=FALSE, ncol=2), width=1, height=c(0.2, 0.8))
plot_map_eqearth(data1, brks.pos=seq(13,29,2), colour_scale=TRUE,
                 title='Full dataset', zlim=c(13, 29))
plot_map_eqearth(data2, brks.pos=seq(13,29,2), colour_scale=TRUE,
                 title='Cropped dataset', zlim=c(13, 29))

## End(Not run)
```

dbRequest

Connect to the gbif4crest database

Description

Connect to the gbif4crest_02 database by accessing the server on Amazon.

Usage

```
dbRequest(request, dbname = "gbif4crest_02")
```

Arguments

request	A SQL request to be executed.
dbname	The name of the data source database.

Value

The result of the request.

Examples

```
## Not run:
# Extracting the number of taxa recorded in the database
dbRequest("SELECT count(*) FROM taxa")

# Extracting all the taxa that have at least one occurrence in South Africa.
southAfricaTaxa <- dbRequest(paste0(
  "SELECT DISTINCT taxa.* ",
```

```

"FROM taxa, distrib_qdgc, geo_qdgc ",
"WHERE taxa.taxonid=distrib_qdgc.taxonid ",
"AND   distrib_qdgc.latitude=geo_qdgc.latitude ",
"AND   distrib_qdgc.longitude=geo_qdgc.longitude ",
"AND   geo_qdgc.countryname='South Africa'"
))
head(southAfricaTaxa)

## End(Not run)

```

dbSubset

Create a subset of the global calibration dataset

Description

Create a subset of the global calibration dataset

Usage

```

dbSubset(
  taxaType,
  xmn = NA,
  xmx = NA,
  ymn = NA,
  ymx = NA,
  dbname = "gbif4crest_02",
  out = "gbif4crest_reduced",
  verbose = TRUE
)

```

Arguments

taxaType	A numerical index (between 1 and 6) to define the type of palaeoproxy used: 1 for plants, 2 for beetles, 3 for chironomids, 4 for foraminifers, 5 for diatoms and 6 for rodents. The example dataset uses taxaType=0 (pseudo-data). Default is 1.
xmn, xmx, ymn, ymx	The coordinates defining the study area.
dbname	The name of the database. Default is 'gbif4crest_02' and data will be extracted from the online database. The SQLite3 version of the database can also be used here by providing the complete path to a file ending by .sqlite3, e.g. /path/to/file/gbif4crest_02.sqlite3
out	The name or path of the new dataset
verbose	A boolean to print non-essential comments on the terminal (default TRUE).

See Also

The full SQLite3 database can be downloaded from https://figshare.com/articles/dataset/GBIF_for_CREST_database/6743207.

Examples

```
## Not run:
  dbSubset(2, xmn=0, xmx=15, ymn=0, ymx=15, out='example.sqlite3')

## End(Not run)
```

eqearth_get_ext	<i>Calculates the extent of the plot in the equal earth projection.</i>
-----------------	---

Description

Calculates the extent of the plot in the equal earth projection.

Usage

```
eqearth_get_ext(ext, npoints = 15)
```

Arguments

ext	A set of coordinates.
npoints	The number of points used to draw the polygon along each dimension.

Value

The set of coordinates ext projected in equal earth.

Examples

```
## Not run:
  eqearth_get_ext(c(-15, 50, 30, 70))

## End(Not run)
```

excludeTaxa	<i>Excludes the list of taxa from the reconstructions.</i>
-------------	--

Description

Excludes the list of taxa from the reconstructions.

Usage

```
excludeTaxa(x, taxa, climate)
```

Arguments

x	A <code>crestObj</code> produced by one of the <code>crest</code> , <code>crest.get_modern_data</code> , <code>crest.calibrate</code> , <code>crest.reconstruct</code> or <code>loo</code> functions.
taxa	A vector of taxa to exclude.
climate	A vector of climate variables to unlink the taxa with.

Value

Return the updated `crestObj`.

Examples

```
data(reconstr)
print(reconstr$inputs$selectedTaxa)
reconstr <- excludeTaxa(reconstr, 'Taxon3', 'bio1')
## 'Taxon3' is now excluded from the reconstruction of 'bio1'.
print(reconstr$inputs$selectedTaxa)
```

explore_calibration_dataset

Extract distributions from the database

Description

This function will extract the distributions of all the studied climate proxy and plot the data on a map.

Usage

```
explore_calibration_dataset(
  taxaType,
  save = FALSE,
  filename = "calibrationDataset.pdf",
  col = viridis::viridis(22)[3:22],
  width = 7.48,
  height = 7.48,
  as.png = FALSE,
  png.res = 300,
  xmn = NA,
  xmx = NA,
  ymn = NA,
  ymx = NA,
  continents = NA,
  countries = NA,
  realms = NA,
  biomes = NA,
  ecoregions = NA,
  dbname = "gbif4crest_02"
)
```


Arguments

taxaType	A numerical index (between 1 and 6) to define the type of palaeoproxy used: 1 for plants, 2 for beetles, 3 for chironomids, 4 for foraminifers, 5 for diatoms and 6 for rodents. The example dataset uses taxaType=0 (pseudo-data). Default is 1.
save	A boolean to indicate if the diagram should be saved as a pdf file. Default is FALSE.
filename	An absolute or relative path that indicates where the diagram should be saved. Also used to specify the name of the file. Default: the file is saved in the working directory under the name 'Reconstruction_climate.pdf'.
col	A colour gradient.
width, height	The dimensions of the pdf file (default 7.48in ~19cm).
as.png	A boolean to indicate if the output should be saved as a png. Default is FALSE and the figure is saved as a pdf file.
png.res	The resolution of the png file (default 300 pixels per inch).
xmn, xmx, ymn, ymx	The coordinates defining the study area.
continents	A vector of the continent names defining the study area.
countries	A vector of the country names defining the study area.
realms	A vector of the studied botanical realms defining the study area.
biomes	A vector of the studied botanical biomes defining the study area.
ecoregions	A vector of the studied botanical ecoregions defining the study area.
dbname	The name of the database. Default is 'gbif4crest_02'.

Value

The distribution data

Examples

```
## Not run:
#> Replace 'tempdir()' by the location where to save the sample (e.g. 'getwd()')
d = explore_calibration_dataset(2, xmn=-85, xmx=-30, ymn=-60, ymx=15,
                               save=TRUE, width = 4, height = 7.5,
                               filename=file.path(tempdir(), 'calibrationDataset.pdf'))
)
head(d)

## End(Not run)
```

export

Export the results

Description

Export the results generated by the reconstruction

Usage

```
export(
  x,
  dataname = x$misc$site_info$site_name,
  climate = x$parameters$climate,
  loc = getwd(),
  as.csv = FALSE,
  fullUncertainties = FALSE,
  loo = FALSE,
  weights = FALSE,
  pdfs = FALSE
)
```

Arguments

<code>x</code>	The name, age or depth of the rows of <code>df</code> (the samples).
<code>dataname</code>	The name of the site (default: <code>x\$misc\$site_info\$site_name</code>)
<code>climate</code>	The climate data to export. Data for all climate variables are saved by default.
<code>loc</code>	The path where to export the data (default: working directory)
<code>as.csv</code>	Boolean to indicate if the data should be exported as csv (TRUE) or xlsx (FALSE, default)
<code>fullUncertainties</code>	A boolean to export the full climate uncertainty distribution (default FALSE)
<code>loo</code>	A boolean to export the leave-one-out data if they exist (default FALSE)
<code>weights</code>	A boolean to export the weights derived from the percentages (default FALSE)
<code>pdfs</code>	A boolean to export the taxa's pdfs (default FALSE)

Value

No return value, function called to export the results.

Examples

```
## Not run:
data(crest_ex)
data(crest_ex_pse)
data(crest_ex_selection)
reconstr <- crest(
  df = crest_ex, pse = crest_ex_pse, taxaType = 0,
  site_info = c(7.5, 7.5),
  climate = c("bio1", "bio12"), bin_width = c(2, 20),
  shape = c("normal", "lognormal"),
  selectedTaxa = crest_ex_selection, dbname = "crest_example",
  leave_one_out = TRUE
)
#> Replace 'tempdir()' by the location where the sample should be saved (e.g. 'getwd()')
export(reconstr, dataname='crest_example',
  fullUncertainties=TRUE, weights=TRUE, loo=TRUE, pdfs=TRUE,
  loc=tempdir())

## End(Not run)
```

export_pdfs	<i>Export the pdfs fitted for the different taxa.</i>
-------------	---

Description

Export the pdfs fitted for the different taxa.

Usage

```
export_pdfs(
  x,
  dataname = x$misc$site_info$site_name,
  climate = x$parameters$climate,
  taxa = x$inputs$taxa.name,
  loc = getwd(),
  as.csv = FALSE
)
```

Arguments

x	The name, age or depth of the rows of df (the samples).
dataname	The name of the site (default: x\$misc\$site_info\$site_name)
climate	A vector of the climate variables to extract. See accClimateVariables for the list of accepted values.
taxa	The names of the taxa of interest. All the pdfs are saved by default.
loc	The path where to export the data (default: working directory)
as.csv	Boolean to indicate if the data should be exported as csv (TRUE) or xlsx (FALSE, default)

Value

No return value, function called to export the PDFs as files.

Examples

```
## Not run:
data(crest_ex)
data(crest_ex_pse)
data(crest_ex_selection)
reconstr <- crest(
  df = crest_ex, pse = crest_ex_pse, taxaType = 0,
  site_info = c(7.5, 7.5),
  climate = c("bio1", "bio12"), bin_width = c(2, 20),
  shape = c("normal", "lognormal"),
  selectedTaxa = crest_ex_selection, dbname = "crest_example",
  leave_one_out = TRUE
)
#> Replace 'tempdir()' by the location where the sample should be saved (e.g. 'getwd()')
export_pdfs(reconstr,
  dataname='crest_example',
  loc=tempdir())
```

```
)
## End(Not run)
```

find.original.name	Returns the name of the function argument in the global environment
--------------------	---

Description

Returns the name of the function argument in the global environment

Usage

```
find.original.name(x)
```

Arguments

x	The function argument
---	-----------------------

Value

The name of the function argument in the global environment.

fit_pdfsp	Fit the species pdfs.
-----------	-----------------------

Description

Fit the species pdfs.

Usage

```
fit_pdfsp(climate, ccs, bin_width, shape, xrange, use_ccs = TRUE)
```

Arguments

climate	A vector of climatic values where the species is present.
ccs	A ccs object returned by calib_clim_space .
bin_width	The width of the bins used to correct for unbalanced climate state. Use values that split the studied climate gradient in 15-25 classes (e.g. 2°C for temperature variables). Default is 1.
shape	The imposed shape of the species pdfs. We recommend using 'normal' for temperature variables and 'lognormal' for the variables that can only take positive values, such as precipitation or aridity. Default is 'normal' for all.
xrange	The climate gradient upon which the pdf will be defined.
use_ccs	Boolean to indicate if the pdfsp should be corrected by the distribution of the modern climate space

Value

The pdf of the species.

Examples

```
# Creating one randomised species
climate_species <- round(stats::rnorm(50, 15, 2), 1)

# Creating one randomised climate space
climate_space <- base::sample(0:300 / 10, 4000, replace = TRUE)

ccs <- calib_clim_space(climate_space, 2)
xrange <- fit_xrange(ccs, "normal", 2)
pdfsp <- fit_pdfsp(climate_species, ccs, 2, "normal", xrange)
plot(xrange, pdfsp, type = "l")

# Testing that the area under the curve is equal to 1.
all.equal(sum(pdfsp * (xrange[2] - xrange[1])), 1)
```

fit_xrange

Define the climate gradient to fit the pdfs.

Description

Define the climate gradient to fit the pdfs.

Usage

```
fit_xrange(ccs, shape, bin_width, npoints = 500)
```

Arguments

ccs	A ccs object returned by calib_clim_space .
shape	The imposed shape of the species pdfs. We recommend using 'normal' for temperature variables and 'lognormal' for the variables that can only take positive values, such as precipitation or aridity. Default is 'normal' for all.
bin_width	The width of the bins used to correct for unbalanced climate state. Use values that split the studied climate gradient in 15-25 classes (e.g. 2°C for temperature variables). Default is 1.
npoints	The number of points to be used to fit the pdfs. Default 200.

Value

A regularly spaced climate gradient with npoints points.

Examples

```
# Creating one randomised climate space
climate_space <- sample(0:300 / 10, 4000, replace = TRUE)
ccs <- calib_clim_space(climate_space, 2)
xrange <- fit_xrange(ccs, "normal", 2)
head(xrange)
```

get_taxa_type	<i>Returns the taxa type corresponding to the index.</i>
---------------	--

Description

Returns the taxa type corresponding to the index.

Usage

```
get_taxa_type(taxaType)
```

Arguments

taxaType	An integer between 0 and 6
----------	----------------------------

Value

Returns the taxa type corresponding to the index.

getClimateSpace	<i>Extract the distribution of the studied climate gradient(s) across the study area.</i>
-----------------	---

Description

Extract the distribution of the studied climate gradient(s) across the study area.

Usage

```
getClimateSpace(
  climate,
  xmn = NA,
  xmx = NA,
  ymn = NA,
  ymx = NA,
  continents = NA,
  countries = NA,
  basins = NA,
  sectors = NA,
  realms = NA,
  biomes = NA,
  ecoregions = NA,
  elev_min = NA,
  elev_max = NA,
  elev_range = NA,
  dbname = "gbif4crest_02"
)
```

Arguments

climate	A vector of the climate variables to extract. See accClimateVariables for the list of accepted values.
xmn, xmx, ymn, ymx	The coordinates defining the study area.
continents	A vector of the continent names defining the study area.
countries	A vector of the country names defining the study area.
basins	A vector of the ocean names defining the study area.
sectors	A vector of the marine sector names defining the study area.
realms	A vector of the studied botanical realms defining the study area.
biomes	A vector of the studied botanical biomes defining the study area.
ecoregions	A vector of the studied botanical ecoregions defining the study area.
elev_min, elev_max	Parameters to only selected grid cells with an elevation higher than elev_min or lower than elev_max (default is 'NA').
elev_range	Parameters discard the grid cell with a high elevation range (default is NA).
dbname	The name of the data source database.

Value

A matrix of occurrence records with the associated climate.

See Also

[accClimateVariables](#) for a list of accepted climate variable names, [accCountryNames](#) for a list of accepted continent and country names, [accBasinNames](#) for a list of accepted basin and sector names, [accRealmNames](#) for a list of accepted realm, biome and ecoregion names.

Examples

```
## Not run:
climate <- getClimateSpace("bio1", -90, 90, -90, 90,
  continents = "Europe",
  countries = c("Germany", "Netherlands", "Sweden"),
  realms = "Palearctic"
)
head(climate)
raster::plot(raster::rasterFromXYZ(climate), asp=1)

## End(Not run)
```

getDistribTaxa

*Extract taxonID(s) corresponding to the taxonomic description***Description**

Extract all possible TaxonIDs corresponding to the provided taxonomical description, which can be at the family, the genus or the species levels.

Usage

```
getDistribTaxa(
  taxIDs,
  climate = NA,
  xmn = NA,
  xmx = NA,
  ymn = NA,
  ymx = NA,
  continents = NA,
  countries = NA,
  basins = NA,
  sectors = NA,
  realms = NA,
  biomes = NA,
  ecoregions = NA,
  elev_min = NA,
  elev_max = NA,
  elev_range = NA,
  year_min = 1900,
  year_max = 2021,
  nodate = TRUE,
  type_of_obs = c(1, 2, 3, 8, 9),
  dbname = "gbif4crest_02"
)
```

Arguments

taxIDs	A vector of accepted Taxa IDs (as returned by getTaxonID).
climate	A vector of the climate variables to extract. See accClimateVariables for the list of accepted values.
xmn, xmx, ymn, ymx	The coordinates defining the study area.
continents	A vector of the continent names defining the study area.
countries	A vector of the country names defining the study area.
basins	A vector of the ocean names defining the study area.
sectors	A vector of the marine sector names defining the study area.
realms	A vector of the studied botanical realms defining the study area.
biomes	A vector of the studied botanical biomes defining the study area.
ecoregions	A vector of the studied botanical ecoregions defining the study area.

elev_min, elev_max	Parameters to only selected grid cells with an elevation higher than elev_min or lower than elev_max (default is 'NA').
elev_range	Parameters discard the grid cell with a high elevation range (default is NA).
year_min, year_max	The oldest and youngest occurrences accepted (default is 1900-2021).
nodate	A boolean to accept occurrences without a date (can overlap with occurrences with a date; default TRUE).
type_of_obs	The type of observation to use in the study. 1: human observation, 2: observation, 3: preserved specimen, 4: living specimen, 5: fossil specimen, 6: material sample, 7: machine observation, 8: literature, 9: unknown (Default c(1, 2, 3, 8, 9))
dbname	The name of the data source database.

Value

A matrix of occurrence records with the associated climate.

See Also

[getTaxonID](#) for taxIDs, [accClimateVariables](#) for a list of accepted climate variable names, [accCountryNames](#) for a list of accepted continent and country names, [accRealmNames](#) for a list of accepted realm, biome and ecoregion names.

Examples

```
## Not run:
taxIDs <- getTaxonID("Zamiaceae", "Ceratozamia")
distrib <- getDistribTaxa(taxIDs, "bio1", -90, 90, -90, 90,
  continents = "Europe",
  countries = c("Germany", "Netherlands", "Sweden"),
  realms = "Palearctic"
)
distrib

## End(Not run)
```

getSpeciesdiversity	<i>Calculates how many species compose the response of each taxon.</i>
---------------------	--

Description

Calculates how many species compose the response of each taxon.

Usage

```
getSpeciesdiversity(x)
```

Arguments

x A [crestObj](#) generated by the [crest.reconstruct](#), [loo](#) or [crest](#) functions.

Value

Return the number of composing species of each taxon.

Examples

```
data(reconstr)
getSpeciesdiversity(reconstr)
```

getTaxaTypeFromTaxID	<i>Returns the taxa type corresponding to the taxID.</i>
----------------------	--

Description

Returns the taxa type corresponding to the taxID.

Usage

```
getTaxaTypeFromTaxID(taxID)
```

Arguments

taxID	An integer between 0 and 6
-------	----------------------------

Value

Returns the taxa type ID corresponding to the taxon ID.

getTaxonID	<i>Extract taxonID(s) corresponding to the taxonomic description</i>
------------	--

Description

Extract all possible TaxonIDs corresponding to the provided taxonomical description, which can be at the family, the genus or the species levels.

Usage

```
getTaxonID(
  family = "",
  genus = "",
  species = "",
  taxaType = 1,
  dbname = "gbif4crest_02"
)
```

Arguments

family	The name of the family.
genus	The name of the genus.
species	The name of the species.
taxaType	A numerical index (between 1 and 6) to define the type of palaeoproxy used: 1 for plants, 2 for beetles, 3 for chironomids, 4 for foraminifers, 5 for diatoms and 6 for rodents. The example dataset uses taxaType=0 (pseudo-data). Default is 1.
dbname	The name of the data source database.

Value

A vector of unique taxonIDs.

Examples

```
## Not run:
  getTaxonID("Zamiaceae")
  getTaxonID("Zamiaceae", "Ceratozamia")
  ## \code{taxaType = 2} searches for beetles and not plants, so the next line returns nothing.
  getTaxonID("Zamiaceae", "Ceratozamia", taxaType = 2)

## End(Not run)
```

getTaxonomy

Extract taxonID(s) corresponding to the taxonomic description

Description

Extract all possible TaxonIDs corresponding to the provided taxonomical description, which can be at the family, the genus or the species levels.

Usage

```
getTaxonomy(
  family = "",
  genus = "",
  species = "",
  taxaType = 1,
  depth.out = 8,
  dbname = "gbif4crest_02"
)
```

Arguments

family	The name of the family.
genus	The name of the genus.
species	The name of the species.

taxaType	A numerical index (between 1 and 5) to define the type of palaeoproxy used: 1 for plants, 2 for beetles, 3 for chironomids, 4 for foraminifers, 5 for diatoms and 6 for rodents.
depth.out	The taxonomic resolution of the output table. 1 for Kingdom, 2 for phylum, 3 for class_name, 4 for order_name, 5 for family, 6 for genus, 7 for species and 8 to also include the taxonID.
dbname	The name of the data source database.

Value

A vector of unique taxonIDs.

Examples

```
## Not run:
getTaxonomy("Zamiaceae")
getTaxonomy(genus="Ceratozamia", depth.out=6)
## \code{taxaType = 2} searches for beetles and not plants, so the next line returns nothing.
getTaxonomy("Zamiaceae", "Ceratozamia", taxaType = 2)

## End(Not run)
```

includeTaxa	<i>Includes the list of taxa into the reconstructions.</i>
-------------	--

Description

Includes the list of taxa into the reconstructions.

Usage

```
includeTaxa(x, taxa, climate)
```

Arguments

x	A crestObj produced by one of the crest , crest.get_modern_data , crest.calibrate , crest.reconstruct or loo functions.
taxa	A vector of taxa to include.
climate	A vector of climate variables to link the taxa with.

Value

Return the updated [crestObj](#).

Examples

```
data(reconstr)
print(reconstr$inputs$selectedTaxa)
reconstr <- includeTaxa(reconstr, reconstr$inputs$taxa.name, 'bio12')
## All the taxa are not selected for 'bio12', except for 'Taxon7' for which
## data are unavailable.
print(reconstr$inputs$selectedTaxa)
```

is.crestObj	<i>Test if x is a crestObj.</i>
-------------	---------------------------------

Description

Test if x is a crestObj.

Usage

```
is.crestObj(x)
```

Arguments

x	The object to be tested
---	-------------------------

Value

TRUE (x is a crestObj) or FALSE (not a crestObj).

isColourStr	<i>Test if R can interpret a string as a colour</i>
-------------	---

Description

Test if R can interpret a string as a colour

Usage

```
isColourStr(col)
```

Arguments

col	The string to be tested.
-----	--------------------------

Value

A boolean value, TRUE if col is a valid colour, FALSE otherwise

Examples

```
isColourStr('black')  
isColourStr('blakc')
```

loo	<i>Performs the leave-one-out analysis</i>
-----	--

Description

Repeat the reconstructions by removing one taxon at a time.

Usage

```
loo(x, verbose = TRUE)
```

Arguments

x	a crestObj produced by the crest.reconstruct or crest functions.
verbose	A boolean to print non-essential comments on the terminal (default TRUE).

Value

A [crestObj](#) object containing the reconstructions and all the associated data.

Examples

```
## Not run:
data(crest_ex)
data(crest_ex_pse)
data(crest_ex_selection)
reconstr <- crest(
  df = crest_ex, pse = crest_ex_pse, taxaType = 0,
  climate = c("bio1", "bio12"), bin_width = c(2, 20),
  shape = c("normal", "lognormal"),
  selectedTaxa = crest_ex_selection, dbname = "crest_example"
)
reconstr <- loo(reconstr)

## End(Not run)
## example using pre-saved reconstruction obtained with the previous command.
data(reconstr)
lapply(reconstr$reconstructions$bio12$loo, head)
plot_loo(reconstr)
```

M1	<i>A shapefile of the world's country borders.</i>
----	--

Description

A shapefile of the world's country borders.

Usage

```
M1
```

Format

An object of class SpatialPolygonsDataFrame with 252 rows and 1 columns.

makeTransparent	<i>Wrapper function of to add transparency to a colour.</i>
-----------------	---

Description

Add transparency to the selected colours.

Usage

```
makeTransparent(colour, alpha)
```

Arguments

colour	A R colour
alpha	A value between 0 and 1 that defines the transparency 0 for full transparency and 1 for no transparency

Value

Return a colour with the provided level of transparency.

Examples

```
makeTransparent('black', 0.5)
makeTransparent('black', 1:10/10)
makeTransparent(rainbow(10), 1:10/10)
```

meanPositiveValues	<i>Calculate the mean of all strictly positive values.</i>
--------------------	--

Description

Calculate the mean of all strictly positive values.

Usage

```
meanPositiveValues(x)
```

Arguments

x	A vector of values.
---	---------------------

Value

The average of all the positive values. Returns NaN is no strictly positive values are found.

Examples

```
meanPositiveValues(-10:10)
```

normalise	<i>Normalises the percentages</i>
-----------	-----------------------------------

Description

Normalises the percentages

Usage

```
normalise(df, col2convert = 2:ncol(df))
```

Arguments

df	The dataframe containing the data to convert.
col2convert	A vector of the columns to convert. Default is all the columns but the first, which contains an age, a depth or a sampleID.

Value

A vector of unique taxonIDs.

Examples

```
df <- data.frame(matrix(1:25, ncol = 5))
colnames(df) <- paste(rep("col", 5), 1:5, sep = "")
normalise(df)
normalise(df, col2convert = 3:5)
```

pdf_ranges	<i>Calculate the climate tolerance of the taxa from their pdfs.</i>
------------	---

Description

Calculate the climate tolerance of the taxa from their pdfs.

Usage

```
pdf_ranges(
  x,
  climate = x$parameters$climate,
  taxanames = x$input$taxa.name,
  uncertainties = x$parameters$uncertainties,
  orderby = NA
)
```


Arguments

x	A <code>crestObj</code> generated by either the <code>crest.calibrate</code> , <code>crest.reconstruct</code> or <code>crest</code> functions.
climate	Climate variables to be used to generate the plot. By default all the variables are included.
taxanames	A list of taxa to use for the plot (default is all the recorded taxa).
uncertainties	A (vector of) threshold value(s) indicating the error bars that should be calculated (default are the values stored in x).
orderby	A string ('name', or one of the climate variables) to sort the output table

Value

The set of coordinates ext projected in equal earth.

Examples

```
data(reconstr)
pdf_ranges(reconstr, climate='bio1')
pdf_ranges(reconstr, climate='bio12', orderby='bio1', uncertainties=c(0.2, 0.6, 0.95))
```

plot.crestObj	<i>Plot the reconstructions.</i>
---------------	----------------------------------

Description

Plot the reconstructions and their uncertainties if they exist.

Usage

```
## S3 method for class 'crestObj'
plot(
  x,
  climate = x$parameters$climate,
  uncertainties = x$parameters$uncertainties,
  optima = TRUE,
  add_modern = FALSE,
  simplify = FALSE,
  as.anomaly = FALSE,
  anomaly.base = x$misc$site_info$climate[climate],
  xlim = NA,
  ylim = NA,
  pt.cex = 0.8,
  pt.lwd = 0.8,
  pt.col = ifelse(simplify, "black", "white"),
  col.hiatus = "white",
  save = FALSE,
  width = 5.51,
  height = 5.51,
```

```

as.png = FALSE,
png.res = 300,
filename = "Reconstruction.pdf",
col = viridis::viridis(125)[26:125],
...
)

```

Arguments

x	A crestObj produced by the crest , crest.reconstruct or loo functions.
climate	The climate variables to plot (default is all the reconstructed variables from x)
uncertainties	A (vector of) threshold value(s) indicating the error bars that should be calculated (default are the values stored in x).
optima	A boolean to indicate whether to plot the optimum (TRUE) or the mean (FALSE) estimates.
add_modern	Adds the modern climate values to the plot.
simplify	A boolean to indicate if the full distribution of uncertainties should be plotted (FALSE, default) or if they should be simplified to the uncertainty range(s).
as.anomaly	A boolean to indicate if the reconstructions should be plotted as absolute values (Default, FALSE) or anomalies '(TRUE).
anomaly.base	The anomaly value. Should be a vector with the same length as climate. Default values are the climate values corresponding to the location of the record (site_info in <code>crest.get_modern_data</code>).
xlim	the x limits (x1, x2) of the plot. Note that x1 > x2 is allowed and leads to a 'reversed axis'. The default value, NULL, indicates that the range of the finite values to be plotted should be used.
ylim	the y limits of the plot.
pt.cex	The size of the points (default 0.8).
pt.lwd	The thickness of the lines (default 0.8).
pt.col	The colour of the points and lines.
col.hiatus	A colour for the hiatus(es) of the record (default white)
save	A boolean to indicate if the diagram should be saved as a pdf file. Default is FALSE.
width, height	The dimensions of the pdf file (default 5.51in ~14cm).
as.png	A boolean to indicate if the output should be saved as a png. Default is FALSE and the figure is saved as a pdf file.
png.res	The resolution of the png file (default 300 pixels per inch).
filename	An absolute or relative path that indicates where the diagram should be saved. Also used to specify the name of the file. Default: the file is saved in the working directory under the name 'Reconstruction_climate.pdf'.
col	A colour gradient.
...	other graphical parameters (see par and section 'Details' below).

Value

No return value, this function is used to plot.

Examples

```
## Not run:
data(crest_ex)
data(crest_ex_pse)
data(crest_ex_selection)
reconstr <- crest(
  df = crest_ex, pse = crest_ex_pse, taxaType = 0,
  climate = c("bio1", "bio12"), bin_width = c(2, 20),
  shape = c("normal", "lognormal"),
  selectedTaxa = crest_ex_selection, dbname = "crest_example"
)
reconstr <- loo(reconstr)

## End(Not run)
## example using pre-saved reconstruction obtained with the previous command.
data(reconstr)
plot(reconstr)
plot(reconstr, climate='bio1', simplify = TRUE, as.anomaly=TRUE)
```

plot_climateSpace	<i>Plot the studied climate space.</i>
-------------------	--

Description

Plot the studied climate space.

Usage

```
plot_climateSpace(
  x,
  climate = x$parameters$climate,
  save = FALSE,
  filename = "Climate_space.pdf",
  as.png = FALSE,
  png.res = 300,
  width = 7.48,
  height = min(9, 3.5 * length(climate)),
  y0 = 0.5,
  add_modern = FALSE,
  resol = 0.25
)
```

Arguments

x	A crestObj generated by either the crest.calibrate , crest.reconstruct or crest functions.
climate	Climate variables to be used to generate the plot. By default all the variables are included.
save	A boolean to indicate if the diagram should be saved as a pdf file. Default is FALSE.

filename	An absolute or relative path that indicates where the diagram should be saved. Also used to specify the name of the file. Default: the file is saved in the working directory under the name 'Climate_space.pdf'.
as.png	A boolean to indicate if the output should be saved as a png. Default is FALSE and the figure is saved as a pdf file.
png.res	The resolution of the png file (default 300 pixels per inch).
width	The width of the output file in inches (default 7.48in ~ 19cm).
height	The height of the output file in inches (default 3in ~ 7.6cm per variables).
y0	The space to allocate to each title (default 0.3in ~ 0.76 cm).
add_modern	A boolean to add the location and the modern climate values to the plot (default FALSE).
resol	For advanced users only: if higher resolution data are used to estimate the pdfs, use this parameter to define the resolution of the maps maps on the figures. (default is 0.25 degrees to match with the default database).

Value

No return value, this function is used to plot.

Examples

```
## Not run:
data(crest_ex_pse)
data(crest_ex_selection)
reconstr <- crest.get_modern_data(
  pse = crest_ex_pse, taxaType = 0,
  climate = c("bio1", "bio12"),
  selectedTaxa = crest_ex_selection, dbname = "crest_example"
)
reconstr <- crest.calibrate(reconstr,
  geoWeighting = TRUE, climateSpaceWeighting = TRUE,
  bin_width = c(2, 20), shape = c("normal", "lognormal")
)
plot_climateSpace(reconstr)

## End(Not run)
```

plot_combinedPDFs	<i>Plot representing how the pdfs combine to produce the reconstruction.</i>
-------------------	--

Description

Plot representing how the pdfs combine to produce the reconstruction.

Usage

```
plot_combinedPDFs(
  x,
  samples = 1:length(x$inputs$x),
  climate = x$parameters$climate[1],
  optima = TRUE,
  xlim = NA,
  only.present = FALSE,
  only.selected = FALSE,
  col = crestr::colour_theme(1),
  save = FALSE,
  filename = "samplePDFs.pdf",
  as.png = FALSE,
  png.res = 300,
  width = 7.48,
  height = 5
)
```

Arguments

x	A <code>crestObj</code> generated by the <code>crest.reconstruct</code> or <code>crest</code> functions.
samples	The list of samples for which the plot should be plotted. All samples will be plotted by default.
climate	The climate variable to use to plot the variable. Default is first variable (<code>x\$parameters\$climate[1]</code>).
optima	A boolean to indicate whether to plot the optimum (TRUE) or the mean (FALSE) estimates.
xlim	The climate range to plot the pdfs on. Default is the full range used to fit the pdfs (<code>x\$modelling\$xrange</code>).
only.present	A boolean to only add the names of the taxa recorded in the sample (default FALSE).
only.selected	A boolean to only add the names of the selected taxa (default FALSE).
col	A range of colour values to colour the pdfs. Colours will be recycled to match the number of taxa.
save	A boolean to indicate if the diagram should be saved as a pdf file. Default is FALSE.
filename	An absolute or relative path that indicates where the diagram should be saved. Also used to specify the name of the file. Default: the file is saved in the working directory under the name 'samplePDFs.pdf'.
as.png	A boolean to indicate if the output should be saved as a png. Default is FALSE and the figure is saved as a pdf file.
png.res	The resolution of the png file (default 300 pixels per inch).
width	The width of the output file in inches (default 7.48in ~ 19cm).
height	The height of the output file in inches (default 5in ~ 12.7cm).

Value

No return value, this function is used to plot.

Examples

```
## Not run:
data(crest_ex)
data(crest_ex_pse)
data(crest_ex_selection)
reconstr <- crest(
  df = crest_ex, pse = crest_ex_pse, taxaType = 0,
  climate = c("bio1", "bio12"), bin_width = c(2, 20),
  shape = c("normal", "lognormal"),
  selectedTaxa = crest_ex_selection, dbname = "crest_example",
  leave_one_out = FALSE
)

## End(Not run)
## example using pre-saved reconstruction obtained with the previous command.
data(reconstr)
plot_combinedPDFs(reconstr, samples=1:4, climate='bio12')
```

plot_diagram

Plot stratigraphic data as polygons or barplots.

Description

This function plots stratigraphic data either as polygons or bars.

Usage

```
plot_diagram(
  x,
  bars = FALSE,
  col = "black",
  amplif = 5,
  save = FALSE,
  filename = "Diagram.pdf",
  width = 3.54,
  height = 9,
  as.png = FALSE,
  png.res = 300,
  yax_incr = 5,
  bar_width = diff(range(x$inputs$x))/50,
  xlim = NA,
  tickAtSample = TRUE,
  col_pos = "black",
  col_neg = "grey80",
  title = NA,
  src = NA
)
```

Arguments

x	A data frame of the data to plot (first column with age or depth) and the taxa in the following columns. x can also be a <code>crestObj</code> .
bars	A boolean that indicates if the data should be plotted as polygons (default: bars=FALSE) or vertical bars (bars=TRUE).
col	Colours to be used for the polygons. If the number of colours does not match the number of taxa, colors will be recycled.
amplif	A factor the show exaggeration on the diagram. Only for polygon plot. Default 5.
save	A boolean to indicate if the diagram should be saved as a pdf file. Default is FALSE.
filename	An absolute or relative path that indicates where the diagram should be saved. Also used to specify the name of the file. Default: the file is saved in the working directory under the name 'Diagram.pdf'.
width	The width of the output file in inches (default 3.54in ~ 9cm).
height	The height of the output file in inches (default 9in ~ 23cm).
as.png	A boolean to indicate if the output should be saved as a png. Default is FALSE and the figure is saved as a pdf file.
png.res	The resolution of the png file (default 300 pixels per inch).
yax_incr	Graphical parameters describing the increment size on the y-axis (default 5).
bar_width	Width of the bars of the barplot (default 1/50th of the x range).
xlim	The range covered by the x-axis. Can be adjusted to get round numbers on the x-axis. If smaller than the range covered by the data, the data will be truncated (default: range of the data).
tickAtSample	Boolean that indicates whether a tick mark should be added on the x-axis at the location of each sample (default TRUE).
col_pos	Graphical parameter for the barplot. Colour of all the positive values (default black).
col_neg	Graphical parameter for the barplot. Colour of all the negative values (default light grey).
title	Name to be added on top of the plot (default NA).
src	A graphical parameter used by the <code>plot_loo()</code> function.

Value

No return value, this function is used to plot.

Examples

```
data(crest_ex)
plot_diagram(crest_ex, bars=TRUE, col='black', bar_width=0.8)
plot_diagram(crest_ex, col=1:7, tickAtSample=FALSE)
#> Replace 'tempdir()' by the location where the sample should be saved (e.g. 'getwd()')
plot_diagram(crest_ex, save=TRUE,
             filename=file.path(tempdir(), 'testDiagram.pdf'),
             bars=TRUE, col_pos='cornflowerblue', col_neg='darkgreen',
             bar_width=0.8, xlim=c(3,15))
```

plot_loo

*Plot the results of the leave-one-out analysis.***Description**

Plot the results of the leave-one-out analysis.

Usage

```
plot_loo(
  x,
  optima = TRUE,
  climate = x$parameters$climate,
  taxanames = x$inputs$taxa.name,
  save = FALSE,
  filename = "Diagram_loo.pdf",
  as.png = FALSE,
  png.res = 300,
  width = 3.54,
  height = 9,
  yax_incr = NA,
  bar_width = diff(range(x$inputs$x))/50,
  xlim = NA,
  tickAtSample = FALSE,
  sort = NA,
  filter = 0,
  col_pos = "black",
  col_neg = "grey80",
  title = NA
)
```

Arguments

x	A data frame of the data to plot (first column with age or depth) and the taxa in the following columns. x can also be a crestObj .
optima	A boolean to indicate whether to plot the optimum (TRUE) or the mean (FALSE) estimates.
climate	Climate variables to be used to generate the plot. By default all the variables are included.
taxanames	A list of taxa to use for the plot (default is all the recorded taxa).
save	A boolean to indicate if the diagram should be saved as a pdf file. Default is FALSE.
filename	An absolute or relative path that indicates where the diagram should be saved. Also used to specify the name of the file. Default: the file is saved in the working directory under the name 'Diagram_loo_climate.pdf'.
as.png	A boolean to indicate if the output should be saved as a png. Default is FALSE and the figure is saved as a pdf file.
png.res	The resolution of the png file (default 300 pixels per inch).
width	The width of the output file in inches (default 3.54in ~ 9cm).

height	The height of the output file in inches (default 9in ~ 23cm).
yax_incr	Graphical parameters describing the increment size on the y-axis (default 5).
bar_width	Width of the bars of the barplot (default 1).
xlim	The range covered by the x-axis. Can be adjusted to get round numbers on the x-axis. If smaller than the range covered by the data, the data will be truncated (default: range of the data).
tickAtSample	Boolean that indicates whether a tick mark should be added on the x-axis at the location of each sample (default TRUE).
sort	A string to sort the order of the taxa from the highest to lowest anomalies (sort='incr') or from the lowest to highest (sort='decr'). Use the default value NA to keep the taxa unsorted.
filter	A threshold value that determines the mean absolute anomaly value required for the taxon to be plotted (default 0 means that all taxa are plotted)
col_pos	Graphical parameter for the barplot. Colour of all the positive values (default black).
col_neg	Graphical parameter for the barplot. Colour of all the negative values (default grey80).
title	Name to be added on top of the plot (default NA).

Value

When used with a crestObj, it returns the average leave-one-out values for each selected taxa

Examples

```
## Not run:
data(crest_ex)
data(crest_ex_pse)
data(crest_ex_selection)
reconstr <- crest(
  df = crest_ex, pse = crest_ex_pse, taxaType = 0,
  climate = c("bio1", "bio12"), bin_width = c(2, 20),
  shape = c("normal", "lognormal"),
  selectedTaxa = crest_ex_selection, dbname = "crest_example"
)
reconstr <- loo(reconstr)

## End(Not run)
## example using pre-saved reconstruction obtained with the previous command.
data(reconstr)
loo_vals <- plot_loo(reconstr, yax_incr=c(0.5, 50), bar_width=0.8,
  col_pos=c('blue', 'cornflowerblue'),
  col_neg=c('red', 'goldenrod3'))
```

plot_map_eqearth	<i>Plots raster data in equal earth projection.</i>
------------------	---

Description

Plots raster data in equal earth projection.

Usage

```
plot_map_eqearth(
  dat,
  ext = raster::extent(dat),
  zlim = range(raster::values(dat), na.rm = TRUE),
  col = viridis::viridis(20),
  brks.pos = c(0, 1),
  brks.lab = brks.pos,
  npoints = 15,
  nlines = 9,
  title = "",
  colour_scale = TRUE,
  top_layer = NA,
  top_layer.col = "ghostwhite",
  site_xy = NA,
  dim = NA
)
```

Arguments

dat	The raster data to plot.
ext	The extent to use to plot the data. (default is extent of dat)
zlim	The range of the values to plot. (default is estimated from dat)
col	The color gradient to use. (default is viridis)
brks.pos	The position where to draw tick marks on the legend
brks.lab	The labels to add where the tickmarks are draw (default is tickmarks position)
npoints	The number of points used to draw the polygons and lines along each dimension. (default is 15 for a smooth result)
nlines	The number of coordinate lines to add in the background (default is 9)
title	A description title (default is empty).
colour_scale	A boolean to add the colour scale to the plot (default TRUE).
top_layer	A raster to overlay on top of the map (e.g. a distribution).
top_layer.col	A colour for plotting top_layer (default 'ghostwhite').
site_xy	Coordinates of a location to add to the plot.
dim	The dimension of the plotting window in inches (default dev.size()).

Value

The set of coordinates ext projected in equal earth.

plot_scatterPDFs

*Plot the pdf optima and uncertainty ranges in a climate biplot***Description**

Plot the pdf optima and uncertainty ranges in a climate biplot

Usage

```
plot_scatterPDFs(
  x,
  climate = x$parameters$climate[1:2],
  taxanames = x$input$taxa.name,
  uncertainties = x$parameters$uncertainties,
  xlim = range(x$modelling$climate_space[, climate[1]]),
  ylim = range(x$modelling$climate_space[, climate[2]]),
  save = FALSE,
  filename = "scatterPDFs.pdf",
  width = 5.51,
  height = 5.51,
  as.png = FALSE,
  png.res = 300
)
```

Arguments

x	A crestObj generated by either the crest.calibrate , crest.reconstruct or crest functions.
climate	Names of the two climate variables to be used to generate the plot. By default plot. By default the first two variables are included.
taxanames	A list of taxa to use for the plot (default is all the recorded taxa).
uncertainties	A (vector of) threshold value(s) indicating the error bars that should be calculated (default are the values stored in x).
xlim,	ylim The climate range to plot the data. Default is the full range of the observed climate space.
ylim	the y limits of the plot.
save	A boolean to indicate if the diagram should be saved as a pdf file. Default is FALSE.
filename	An absolute or relative path that indicates where the diagram should be saved. Also used to specify the name of the file. Default: the file is saved in the working directory under the name 'violinPDFs.pdf'.
width	The width of the output file in inches (default 7.48in ~ 19cm).
height	The height of the output file in inches (default 3in ~ 7.6cm per variables).
as.png	A boolean to indicate if the output should be saved as a png. Default is FALSE and the figure is saved as a pdf file.
png.res	The resolution of the png file (default 300 pixels per inch).

Value

A table with the climate tolerances of all the taxa

Examples

```
## Not run:
data(crest_ex_pse)
data(crest_ex_selection)
reconstr <- crest.get_modern_data(
  pse = crest_ex_pse, taxaType = 0,
  climate = c("bio1", "bio12"),
  selectedTaxa = crest_ex_selection, dbname = "crest_example"
)
reconstr <- crest.calibrate(reconstr,
  geoWeighting = TRUE, climateSpaceWeighting = TRUE,
  bin_width = c(2, 20), shape = c("normal", "lognormal")
)

## End(Not run)
## example using pre-saved reconstruction obtained with the previous command.
data(reconstr)
dat <- plot_scatterPDFs(reconstr, save=FALSE,
  taxanames=c(reconstr$inputs$taxa.name[c(2,4,5,1)], 'Taxon'))
dat
```

plot_taxaCharacteristics

Plot the distribution and responses of the studied taxa

Description

Plot the distribution and responses of the studied taxa

Usage

```
plot_taxaCharacteristics(
  x,
  taxanames = x$inputs$taxa.name,
  climate = x$parameters$climate,
  col.density = viridis::plasma(20),
  col.climate = viridis::viridis(22)[3:20],
  save = FALSE,
  filename = "taxaCharacteristics.pdf",
  as.png = FALSE,
  png.res = 300,
  width = 7.48,
  w0 = 0.3,
  height = 3 * length(climate),
  h0 = 0.4,
  add_modern = FALSE,
  resol = 0.25
)
```

Arguments

x	A <code>crestObj</code> generated by either the <code>crest.calibrate</code> , <code>crest.reconstruct</code> , <code>loo</code> or <code>crest</code> functions.
taxanames	A list of taxa to use for the plot (default is all the recorded taxa).
climate	Climate variables to be used to generate the plot. By default all the variables are included.
col.density	The colour gradient to use to map the density of species (top left map).
col.climate	The colour gradient to use to map the climate gradients (left column).
save	A boolean to indicate if the diagram should be saved as a pdf file. Default is FALSE.
filename	An absolute or relative path that indicates where the diagram should be saved. Also used to specify the name of the file. Default: the file is saved in the working directory under the name 'taxaCharacteristics.pdf'.
as.png	A boolean to indicate if the output should be saved as a png. Default is FALSE and the figure is saved as a pdf file.
png.res	The resolution of the png file (default 300 pixels per inch).
width	The width of the output file in inches (default 7.48in ~ 19cm).
w0	The width of the left column with the names.
height	The height of the output file in inches (default 3in ~ 7.6cm per variables).
h0	The vertical space used for the x-axes.
add_modern	A boolean to add the location and the modern climate values to the plot (default FALSE).
resol	For advanced users only: if higher resolution data are used to estimate the pdfs, use this parameter to define the resolution of the maps on the figures. (default is 0.25 degrees to match with the default database)

Value

No return value, this function is used to plot.

Examples

```
## Not run:
data(crest_ex_pse)
data(crest_ex_selection)
reconstr <- crest.get_modern_data(
  pse = crest_ex_pse, taxaType = 0, df = crest_ex,
  climate = c("bio1", "bio12"),
  selectedTaxa = crest_ex_selection, dbname = "crest_example"
)
reconstr <- crest.calibrate(reconstr,
  geoWeighting = TRUE, climateSpaceWeighting = TRUE,
  bin_width = c(2, 20), shape = c("normal", "lognormal")
)
plot_taxaCharacteristics(reconstr, taxanames='Taxon1')

## End(Not run)
```

plot_violinPDFs	<i>Plot the pdfs as violins</i>
-----------------	---------------------------------

Description

Plot the pdfs as violins

Usage

```
plot_violinPDFs(
  x,
  climate = x$parameters$climate[1],
  taxanames = x$input$taxa.name,
  col = viridis::viridis(20),
  ylim = range(x$modelling$xrange[[climate]]),
  save = FALSE,
  filename = "violinPDFs.pdf",
  width = 7.48,
  height = 5,
  as.png = FALSE,
  png.res = 300
)
```

Arguments

x	A crestObj generated by either the crest.calibrate , crest.reconstruct or crest functions.
climate	Climate variables to be used to generate the plot. By default all the variables are included.
taxanames	A list of taxa to use for the plot (default is all the recorded taxa).
col	A vector of colours that will be linearly interpolated to give a unique colour to each taxon.
ylim	The climate range to plot the pdfs on. Default is the full range used to fit the pdfs (x\$modelling\$xrange)
save	A boolean to indicate if the diagram should be saved as a pdf file. Default is FALSE.
filename	An absolute or relative path that indicates where the diagram should be saved. Also used to specify the name of the file. Default: the file is saved in the working directory under the name 'violinPDFs.pdf'.
width	The width of the output file in inches (default 7.48in ~ 19cm).
height	The height of the output file in inches (default 3in ~ 7.6cm per variables).
as.png	A boolean to indicate if the output should be saved as a png. Default is FALSE and the figure is saved as a pdf file.
png.res	The resolution of the png file (default 300 pixels per inch).

Value

A table with the climate tolerances of all the taxa

Examples

```
## Not run:
data(crest_ex_pse)
data(crest_ex_selection)
reconstr <- crest.get_modern_data(
  pse = crest_ex_pse, taxaType = 0,
  climate = c("bio1", "bio12"),
  selectedTaxa = crest_ex_selection, dbname = "crest_example"
)
reconstr <- crest.calibrate(reconstr,
  geoWeighting = TRUE, climateSpaceWeighting = TRUE,
  bin_width = c(2, 20), shape = c("normal", "lognormal")
)

## End(Not run)
## example using pre-saved reconstruction obtained with the previous command.
data(reconstr)
ranges <- plot_violinPDFs(reconstr, save=FALSE, ylim=c(5,35),
  taxanames=c(reconstr$inputs$taxa.name[c(2,4,5,1)], 'Taxon'),
  col=c('darkblue', 'firebrick3'))
lapply(ranges, head)
```

reconstr	A crestObj ran with the example dataset.
----------	--

Description

A [crestObj](#) ran with the example dataset. Useful to illustrate many functions of the package.

Usage

```
reconstr
```

Format

An object of class `crestObj` of length 5.

taxonComposition	<i>Return the size of the distribution of each composing species of each taxon</i>
------------------	--

Description

Return the size of the distribution of each composing species of each taxon

Usage

```
taxonComposition(x, taxanames = x$input$taxa.name)
```

Arguments

- x A `crestObj` generated by either the `crest.calibrate`, `crest.reconstruct` or `crest` functions.
- taxanames A list of taxa to use (default is all the recorded taxa).

Value

A list with the number of unique occurrences for each composing species

Examples

```
## Not run:
  data(reconstr)
  taxonComposition(reconstr)

## End(Not run)
```

testConnection	<i>Test if a connection can be established with the calibration data</i>
----------------	--

Description

Test if a connection can be established with the calibration data

Usage

```
testConnection(dbname = "gbif4crest_02")
```

Arguments

- dbname The name of the data source database.

Value

TRUE if the connection can be established, else FALSE.

Index

* datasets

- crest_ex, [24](#)
- crest_ex_pse, [25](#)
- crest_ex_selection, [25](#)
- M1, [46](#)
- reconstr, [63](#)
- accBasinNames, [3, 39](#)
- accClimateVariables, [4, 14, 16, 19, 22, 27, 35, 39–41](#)
- accCountryNames, [4, 39, 41](#)
- accRealmNames, [5, 39, 41](#)
- calib_clim_space, [6, 36, 37](#)
- check_coordinates, [6](#)
- cite_climate_data, [7](#)
- cite_crest, [7](#)
- cite_distrib_data, [8](#)
- cite_method, [8](#)
- climate_from_xy, [9](#)
- close_db_connection, [9](#)
- colour_theme, [10](#)
- connect_local_sqlite3, [11](#)
- connect_online, [11](#)
- convert2percentages, [12](#)
- convert2presenceAbsence, [13](#)
- copy_crest, [13](#)
- createPSE, [14, 16, 19, 27](#)
- crest, [7, 8, 14, 15, 24, 32, 41, 44, 46, 49–51, 53, 59, 61, 62, 64](#)
- crest.calibrate, [7, 8, 17, 21, 22, 32, 44, 49, 51, 59, 61, 62, 64](#)
- crest.get_modern_data, [7, 8, 18, 18, 28, 29, 32, 44](#)
- crest.reconstruct, [7, 8, 14, 21, 24, 32, 41, 44, 46, 49–51, 53, 59, 61, 62, 64](#)
- crest.set_modern_data, [22](#)
- crest.simplify, [23](#)
- crest_ex, [24](#)
- crest_ex_pse, [25](#)
- crest_ex_selection, [25](#)
- crestObj, [7, 8, 14, 17, 18, 20, 21, 23, 24, 26, 28, 32, 41, 44, 46, 49–51, 53, 55, 56, 59, 61–64](#)
- crop, [28](#)
- dbRequest, [29](#)
- dbSubset, [30](#)
- eqearth_get_ext, [31](#)
- excludeTaxa, [31](#)
- explore_calibration_dataset, [32](#)
- export, [33](#)
- export_pdfs, [35](#)
- find.original.name, [36](#)
- finite, [50](#)
- fit_pdfsp, [6, 36](#)
- fit_xrange, [37](#)
- get_taxa_type, [38](#)
- getClimateSpace, [38](#)
- getDistribTaxa, [40](#)
- getSpeciesdiversity, [41](#)
- getTaxaTypeFromTaxID, [42](#)
- getTaxonID, [40, 41, 42](#)
- getTaxonomy, [43](#)
- graphical parameters, [50](#)
- includeTaxa, [44](#)
- is.crestObj, [45](#)
- isColourStr, [45](#)
- loo, [7, 8, 21, 24, 32, 41, 44, 46, 50, 61](#)
- M1, [46](#)
- makeTransparent, [47](#)
- meanPositiveValues, [47](#)
- normalise, [48](#)
- par, [50](#)
- pdf_ranges, [48](#)
- plot.crestObj, [49](#)
- plot_climateSpace, [51](#)
- plot_combinedPDFs, [52](#)
- plot_diagram, [54](#)
- plot_loo, [56](#)
- plot_map_eqearth, [58](#)

`plot_scatterPDFs`, [59](#)
`plot_taxaCharacteristics`, [60](#)
`plot_violinPDFs`, [62](#)

`reconstr`, [63](#)

`taxonComposition`, [63](#)

`testConnection`, [64](#)