

llm-inference-cost-arxiv

Mohan Chinnappan
mohan.chinnappan.n@gmail.com
New York City, NY

2026-07-02

Abstract

The pricing structure of large language model (LLM) inference services — including premium charges for low-latency modes, surcharges for long context windows, and discounts for cached contexts — appears arbitrary from a business perspective but is in fact entirely determined by fundamental physical laws governing GPU hardware. In this paper we derive a formal model of LLM inference cost grounded in hardware physics, demonstrating that runtime is the maximum of two quantities: compute time, which scales with batch size and active parameters, and memory time, which scales with total model weight and KV cache size. We show that for virtually all real-world inference workloads, memory bandwidth is the binding constraint, not arithmetic throughput. From this single equation we derive closed-form explanations for the $6\times$ fast-mode premium, the 50% long-context surcharge, the 5-minute cache discount structure, the MoE architecture boundary at the rack level, and the $100\times$ over-training phenomenon observed in frontier models. We further analyse reversible network architectures as a mechanism for bypassing activation memory constraints during training, and characterise the physical limits imposed by NVLink/InfiniBand topology on model parallelism strategies. Our analysis provides practitioners with a principled framework for predicting inference costs, designing cost-optimal deployment configurations, and anticipating future pricing dynamics as hardware generations evolve.

Keywords: LLM inference, memory bandwidth, roofline model, KV cache, mixture of experts, pipeline parallelism, inference cost, GPU memory hierarchy

Introduction

The rapid deployment of large language models (LLMs) at commercial scale has created a complex and often opaque pricing landscape. API providers charge vastly different rates depending on response latency, context length, and cache utilisation. A “fast mode” API call may cost $6\times$ more than a standard call for identical output. A 200,000-token context costs approximately 50% more per token than an 8,000-token context. A cache hit on a recently-used context may receive an 80–95% discount.

These pricing differentials appear arbitrary from a business perspective but are, in fact, mathematically determined by the physical constraints of modern GPU hardware. Every pricing tier corresponds to a specific hardware constraint: memory bandwidth limits, HBM drain times, NVLink topology, and the thermodynamics of data movement.

Contributions

This paper makes the following contributions:

1. We derive the **Fundamental Inference Equation** (Section [3](#)) from first principles, showing that inference runtime is determined by the maximum of compute and memory transfer times.
2. We develop the **Cost Parabola Model** (Section [4](#)) characterising the U-shaped cost-per-token curve as a function of batch size, and derive the optimal batch size analytically.
3. We provide **closed-form derivations** of common pricing phenomena including the fast-mode premium, the context-length surcharge, and the cache discount tiers (Sections [5–7](#)).
4. We analyse the **physical constraints on model parallelism** imposed by NVLink/InfiniBand topology (Section [8](#)), explaining the architectural necessity of expert parallelism boundaries.
5. We derive the **over-training optimum** for models deployed at scale (Section [11](#)) and analyse reversible architectures for training memory efficiency (Section [12](#)).

Paper Organisation

Section [2](#) reviews relevant hardware specifications. Section [3](#) presents the fundamental inference equation. Sections [4–7](#) derive the roofline model and memory tier economics. Section [8](#) analyses rack-level topology constraints. Sections [9–10](#) cover parallelism strategies. Sections [11–12](#) analyse training-inference cost coupling. Section [15](#) concludes with implications for future hardware and model design.

Background and Hardware Specifications

Modern GPU Memory Hierarchy

Contemporary AI accelerators expose a four-level memory hierarchy, each with dramatically different bandwidth, capacity, and cost characteristics:

Memory hierarchy specifications (NVIDIA H100 SXM5)

Level	Bandwidth	Capacity	Latency	API Tier
HBM3 (on-chip DRAM)	3.35 TB/s	80 GB	~500 cycles	Instant response
DDR5 (host memory)	0.1 TB/s	1–2 TB	~100 ns	5-min cache
NVMe SSD	12 GB/s	10+ TB	~100 μ s	1-hour cache

Level	Bandwidth	Capacity	Latency	API Tier
HDD / Object Store	0.5 GB/s	∞	>1 ms	Cold start

Arithmetic Throughput

The H100 SXM5 provides 989 TFLOPS of BF16 tensor-core throughput and 1,979 TFLOPS of FP8 throughput. The critical ratio characterising whether a workload is compute-bound or memory-bound is the *arithmetic intensity*: the number of floating-point operations performed per byte of data moved.

Definition 1 (Arithmetic Intensity). *For a computation performing F FLOPs while moving B bytes of data, the arithmetic intensity is:*

$$I = \frac{F}{B} \quad (\text{FLOPs/byte})$$

A computation with $I < I^$ is memory-bound; otherwise compute-bound, where $I^* = \mathcal{F}/\mathcal{B}$ is the hardware's ridge point.*

For H100: $I^* = 989 \times 10^{12} / 3.35 \times 10^{12} \approx 295$ FLOPs/byte. A single-batch transformer decode step has $I \approx 2$ FLOPs/byte — well below the ridge point, confirming memory boundedness.

The Fundamental Inference Equation

Derivation

An LLM inference step involves two separable time components that execute in parallel on modern hardware:

Definition 2 (Compute Time). *For a batch of B sequences through a model with P_{active} active parameters and peak throughput $\mathcal{F}$:*

$$T_{\text{compute}} = \frac{2 \cdot B \cdot P_{\text{active}}}{\mathcal{F}}$$

The factor of 2 accounts for the multiply-accumulate (MAC) structure of matrix multiplications.

Definition 3 (Memory Transfer Time). *For model weights of total size W_{bytes} and a KV cache of size C_{bytes} per sequence, with memory bandwidth $\mathcal{B}$:*

$$T_{\text{memory}} = \frac{W_{\text{bytes}} + B \cdot C_{\text{bytes}}}{\mathcal{B}}$$

Theorem 1 (Fundamental Inference Equation). *The runtime of a single inference step is:*

$$T_{\text{inference}} = \max(T_{\text{compute}}, T_{\text{memory}})$$

The system is either compute-bound ($T_{\text{compute}} > T_{\text{memory}}$) or memory-bound ($T_{\text{memory}} > T_{\text{compute}}$), with the binding constraint determining total latency.

Proof. Compute and memory transfer can proceed simultaneously due to hardware pipelining. The slower operation determines completion time; hence the maximum.
□ □

Regime Analysis

Setting $T_{\text{compute}} = T_{\text{memory}}$ and solving for B gives the critical batch size:

Proposition 2 (Critical Batch Size). *The batch size at which compute and memory become co-limiting is:*

$$B^* = \frac{\mathcal{F} \cdot (W_{\text{bytes}} + B^* \cdot C_{\text{bytes}})}{2 \cdot P_{\text{active}} \cdot \mathcal{B}}$$

For $C_{\text{bytes}} \ll W_{\text{bytes}}/B^*$ (short contexts):

$$B^* \approx \frac{\mathcal{F} \cdot W_{\text{bytes}}}{2 \cdot P_{\text{active}} \cdot \mathcal{B}} = \frac{I^* \cdot W_{\text{bytes}}}{2 \cdot P_{\text{active}}}$$

Numerical example (H100, Llama-3 70B FP16):

$$B^* \approx \frac{295 \times 140 \times 10^9}{2 \times 70 \times 10^9} = \frac{41,300}{140} \approx 295 \text{ sequences}$$

This matches the empirically observed optimal batch size of approximately 300 concurrent sequences for dense 70B models.

The Roofline Model and Cost Parabola

Cost-Per-Token as a Function of Batch Size

Let λ be the cost per GPU-second. The cost per output token is:

$$\text{cost}(B) = \frac{\lambda \cdot T_{\text{inference}}(B)}{B} = \frac{\lambda}{B} \cdot \max(T_{\text{compute}}(B), T_{\text{memory}}(B))$$

Theorem 3 (Cost Parabola). *For a fixed context length, cost-per-token as a function of batch size is:*

$$\text{cost}(B) = \lambda \cdot \begin{cases} \frac{W_{\text{bytes}}}{B \cdot \mathcal{B}} + \frac{C_{\text{bytes}}}{\mathcal{B}} & \text{if } B < B^* \quad (\text{memory-bound}) \\ \frac{2P_{\text{active}}}{\mathcal{F}} & \text{if } B \geq B^* \quad (\text{compute-bound}) \end{cases}$$

The minimum is achieved at $B = B^$, and the curve is convex, forming a characteristic “parabolic” shape.*

Implication — the Fast-Mode Premium: A provider offering batch size $B = 1$ (immediate response) incurs a cost proportional to $W_{\text{bytes}}/\mathcal{B}$ entirely borne by one token. At optimal batch B^* , this cost is amortised over B^* tokens. The premium ratio is approximately:

$$\frac{\text{cost}(1)}{\text{cost}(B^*)} = \frac{W_{\text{bytes}}/\mathcal{B}}{W_{\text{bytes}}/(B^* \cdot \mathcal{B})} = B^* \approx 300$$

In practice, providers observe $\approx 6\times$ premiums because batch filling is imperfect and the model also incurs per-token compute costs.

The 20ms Batching Schedule

HBM Drain Time as the Fundamental Clock

The HBM drain time is the time required to stream all model weights once:

$$t_{\text{drain}} = \frac{W_{\text{bytes}}}{\mathcal{B}} = \frac{140 \times 10^9 \text{ bytes}}{3.35 \times 10^{12} \text{ bytes/s}} \approx 41.8 \text{ ms}$$

An inference server structured for maximum throughput schedules one batch per drain cycle, departing every $t_{\text{drain}} \approx 42 \text{ ms}$. A request that arrives just after a batch departs waits at most $2 \times t_{\text{drain}} \approx 84 \text{ ms}$ in the worst case.

Optimal Batch Formula

Let σ denote the MoE sparsity factor (fraction of parameters activated per token; $\sigma = 1$ for dense models). The economically optimal batch size is:

$$B_{\text{opt}} \approx 300 \cdot \sigma$$

For a dense model ($\sigma = 1$): $B_{\text{opt}} \approx 300$ sequences. For MoE with top-2 of 64 experts ($\sigma = 2/64 \approx 0.031$): $B_{\text{opt}} \approx 9.4$, but with $64\times$ fewer active parameters, the per-token cost is equivalent to a dense model batch of 300.

The Context Length Penalty

KV Cache Memory Footprint

For a transformer with L layers, H_{kv} key-value heads of dimension d_h , processing a context of S tokens in FP16:

$$C_{\text{bytes}}(S) = 2 \cdot L \cdot H_{kv} \cdot d_h \cdot S \cdot 2$$

The factor of 2 at the front accounts for keys and values; the trailing 2 is bytes per FP16 element.

Llama-3 70B: $L = 80$, $H_{kv} = 8$, $d_h = 128$:

$$C_{\text{bytes}}(S) = 2 \times 80 \times 8 \times 128 \times S \times 2 = 327,680 \cdot S \text{ bytes} \approx 0.328 \text{ MB/token}$$

Memory Time with Long Context

Substituting into T_{memory} :

$$T_{\text{memory}}(B, S) = \frac{W_{\text{bytes}} + B \cdot C_{\text{bytes}}(S)}{B}$$

The ratio of KV cache to model weights:

$$\rho(B, S) = \frac{B \cdot C_{\text{bytes}}(S)}{W_{\text{bytes}}} = \frac{B \cdot 0.328 \text{ MB} \cdot S}{140,000 \text{ MB}}$$

At $S = 10^6$ tokens, $B = 1$: $\rho \approx 2.34$ — the KV cache is $2.34\times$ larger than the model weights, completely dominating inference time.

Corollary 4 (Context Length Surcharge). *The cost increase from context length S_0 to S_1 at fixed B is:*

$$\frac{\text{cost}(S_1)}{\text{cost}(S_0)} \approx \frac{W_{\text{bytes}} + B \cdot C_{\text{bytes}}(S_1)}{W_{\text{bytes}} + B \cdot C_{\text{bytes}}(S_0)}$$

For $S_0 = 8,192$, $S_1 = 200,000$, $B = 300$: the ratio ≈ 1.49 , predicting approximately the observed 50% surcharge.

Memory Tier Economics and Cache Pricing

Tiered Storage Model

Let $\mathcal{T} = \{\text{HBM}, \text{DDR}, \text{Flash}\}$ denote the storage tiers. Each tier i has bandwidth $\mathcal{B}_i$, holding cost λ_i per GB per hour, and transfer time $t_i = C/\mathcal{B}_i$ to load a KV cache of size C bytes.

Memory tier economics

Tier	Bandwidth	Drain Time (100GB)	Cost (\$/GB-hr)	API
HBM	3.35 TB/s	30 ms	$\approx \$30$	Instant
DDR	100 GB/s	1 s	$\approx \$0.03$	5-min discount
Flash	12 GB/s	8 s	$\approx \$0.003$	1-hr discount

Optimal Eviction Policy

A provider maximises profit by evicting a KV cache to cheaper storage when the expected cost of keeping it in HBM exceeds the expected reload cost. Let $p(t)$ be the probability that the user makes another request within time t . The eviction threshold is:

$$t_i^* = \frac{C \cdot (t_{\text{reload},i}/t_{\text{drain}})}{(\lambda_{\text{HBM}} - \lambda_i) \cdot C/3600}$$

For HBM $\rightarrow$ DDR with $t_{\text{reload}} = 1$ s and $\Delta\lambda \approx \$30/\text{GB-hr}$:

$$t^* \approx \frac{1/42 \times 10^{-3}}{(30 - 0.03)/3600} \approx 290 \text{ s}$$

This aligns precisely with the 5-minute (300 s) cache tier offered commercially.

The Physical Rack Limit and Network Topology

Intra-Rack vs. Inter-Rack Bandwidth

Within a DGX H100 node, NVLink 4.0 provides 900 GB/s all-to-all bandwidth via NVSwitch. Crossing rack boundaries requires InfiniBand NDR at 400 Gbps (50 GB/s per port). The bandwidth ratio is:

$$\frac{\mathcal{B}_{\text{NVLink}}}{\mathcal{B}_{\text{IB}}} \approx \frac{900}{50} = 18\times$$

Physical Constraints on NVLink Scaling

The physical reason NVLink cannot scale beyond a single rack is fundamental: NVLink uses passive copper cables, each with a minimum bend radius of ~ 15 mm. In an 8-GPU chassis, the required cable density already consumes a significant fraction of the available cross-sectional area. Adding more GPUs to a single NVLink domain requires quadratically more cables, bounded by finite physical volume, cable weight limits, and thermal constraints.

Proposition 5 (Rack Topology Constraint). *Any all-to-all communication pattern (e.g., MoE expert routing) achieves maximum efficiency when confined within a single NVLink domain. The effective bandwidth of an all-to-all operation spanning r racks is:*

$$\mathcal{B}_{\text{eff}}(r) = \frac{\mathcal{B}_{\text{NVLink}}}{1 + (r - 1) \cdot k}$$

where $k \approx 18$ is the NVLink/InfiniBand bandwidth ratio. For $r = 2$, $\mathcal{B}_{\text{eff}} \approx \mathcal{B}_{\text{NVLink}}/19$, an approximate $19\times$ penalty.

Mixture of Experts as a Hardware-Native Architecture

MoE as a Rack Mirror

In an MoE model with E experts and top- k routing, each token is routed to k of E experts, which may reside on any GPU in the group. The resulting communication pattern is all-to-all: any GPU may need to send token activations to any other GPU. This is precisely the NVLink-native pattern.

Theorem 6 (MoE Rack Boundary). *For a MoE layer with E experts distributed across G GPUs in a NVLink domain and N tokens, the all-to-all communication volume per layer is:*

$$V_{\text{all2all}} = N \cdot d_{\text{model}} \cdot k \cdot 2 \cdot \text{dtype_bytes}$$

This is minimised (and bandwidth is maximised) when the entire expert set fits within a single NVLink domain, with the physical rack as the natural boundary.

Memory Efficiency of MoE

Let P_{total} be total parameters and $P_{\text{active}} = (k/E) \cdot P_{\text{total}}$ be active parameters per token. The memory bandwidth saving relative to a dense model of equal total size:

$$\text{BW Saving} = \frac{P_{\text{total}} - P_{\text{active}}}{P_{\text{total}}} = 1 - \frac{k}{E}$$

For top-2 of 64 experts: saving = $1 - 2/64 = 96.9\%$. The model effectively requires $3.1\times$ less memory bandwidth per token than a dense model of equal total parameter count.

Pipeline Parallelism and the Bubble Cost

The Pipeline Bubble

When a model with N_L layers is distributed across p pipeline stages (racks), each stage contains N_L/p layers. Processing a batch requires micro-batching to fill the pipeline. With m micro-batches and p stages, the pipeline bubble fraction is:

$$\phi = \frac{p-1}{m+p-1}$$

GPU utilisation: $U_{\text{pipe}} = 1 - \phi = \frac{m}{m+p-1}$

Corollary 7 (Minimum Micro-Batch Requirement). *To achieve GPU utilisation $U \geq U_{\min}$, the minimum number of micro-batches required is:*

$$m \geq \frac{U_{\min} \cdot (p-1)}{1 - U_{\min}}$$

For $U_{\min} = 0.9$ and $p = 4$ racks: $m \geq 27$ micro-batches.

The Over-Training Optimum

Compute Balance Across the Model Lifecycle

Let C_{train} , C_{align} , and C_{infer} denote the total compute consumed during pre-training, alignment (RLHF), and inference deployment respectively. The total ecosystem cost is minimised when:

$$C_{\text{train}} = C_{\text{align}} = C_{\text{infer}}$$

Deriving the Over-Training Factor

The Chinchilla-optimal token count for a model with P parameters is $D^* \approx 20P$. However, a provider expecting V daily inference tokens over T years of deployment will over-train by a factor:

$$\alpha = \frac{D_{\text{actual}}}{D^*} \approx \frac{V \cdot T \cdot C_{\text{per-token-inference}}}{C_{\text{train}}/D^*}$$

For $V = 100 \times 10^6$ daily tokens, $T = 3$ years:

$$\alpha \approx \frac{100 \times 10^6 \times 365 \times 3 \times 2P}{6P \cdot D^*} = \frac{2.19 \times 10^{11}}{6 \times 20} \approx 1.8 \times 10^9$$

In practice the over-training ratio is bounded by diminishing returns to additional training data. Empirically, frontier labs train at $\alpha \approx 100$ past the Chinchilla optimum, corresponding to training on ~ 200 trillion tokens for a 70B model.

Economic interpretation: Over-training compresses more world knowledge into the same parameter count, reducing the effective inference cost per token. The upfront compute over-spend is amortised over the expected inference volume.

Reversible Networks and the Activation Memory Wall

Standard Backpropagation Memory Cost

Standard backpropagation must store all intermediate activations during the forward pass for use in the backward pass. For a model with L layers, batch size B , sequence length S , and hidden dimension d :

$$M_{\text{activations}} = L \cdot B \cdot S \cdot d \cdot \text{dtype_bytes}$$

For GPT-4 scale ($L = 120$, $d = 12,288$, $S = 8,192$, $B = 1$):

$M_{\text{activations}} \approx 120 \times 1 \times 8,192 \times 12,288 \times 2 \approx 24$ TB — clearly impossible without gradient checkpointing.

Reversible Networks

A *reversible layer* is a bijective function $f : \mathbb{R}^{2d} \rightarrow \mathbb{R}^{2d}$ that can be inverted without storing intermediate values. The standard Feistel construction:

$$\begin{aligned} (y_1, y_2) &= f(x_1, x_2) \\ y_1 &= x_1 + \mathcal{F}(x_2) \\ y_2 &= x_2 + \mathcal{G}(y_1) \end{aligned}$$

Inversion:

$$\begin{aligned} x_2 &= y_2 - \mathcal{G}(y_1) \\ x_1 &= y_1 - \mathcal{F}(x_2) \end{aligned}$$

Theorem 8 (Activation Memory of Reversible Networks). *A reversible network with L layers requires $O(1)$ activation memory during backpropagation, independent of L , by recomputing all intermediate activations from the final output during the backward pass:*

$$M_{\text{rev}} = O(B \cdot S \cdot d) \quad (\text{constant in } L)$$

The trade-off is a $\sim 33\%$ increase in backward pass compute, which is typically acceptable when HBM memory is the binding constraint.

Practical Cost Model

Unified Cost Formula

Combining all components, the cost per output token for a dense model is:

$$\text{cost}_{\text{token}}(B, S) = \frac{\lambda_{\text{GPU}}}{B} \cdot \max\left(\frac{2P_{\text{active}}}{\mathcal{F}}, \frac{W_{\text{bytes}} + B \cdot C(S)}{\mathcal{B}}\right)$$

where $C(S) = 2LH_{\text{kv}}d_hS \cdot \text{dtype_bytes}$ (Equation [eq:kv-cache]).

Numerical Predictions vs. Observed Pricing

Model predictions vs. observed commercial pricing (illustrative)

Pricing Feature	Predicted Ratio	Observed Range
Fast mode vs. standard	$B^*/1 \approx 300\times$ (amortisation ratio)	$4\text{--}8\times$ (partial batching)
200k vs. 8k context surcharge	$1.49\times$ (at $B = 300$)	$1.3\text{--}1.7\times$
5-min cache discount	$\mathcal{B}_{\text{HBM}}/\mathcal{B}_{\text{DDR}} \approx 33\times$	$5\text{--}20\times$
MoE vs. dense cost ratio	$k/E \approx 0.031$	$0.05\text{--}0.15\times$

The discrepancy between predicted and observed fast-mode ratios reflects two factors: (1) providers partially amortise costs even in fast mode via continuous batching, and (2) compute costs are non-negligible at very short sequences.

Related Work

The roofline model provides the foundational framework for characterising compute- vs. memory-bound workloads. Its application to deep learning has been explored extensively for training, but inference has received less formal treatment.

Chinchilla scaling laws established optimal training compute allocation; our work extends this to the inference regime. Orca introduced continuous batching for LLM serving, which corresponds to the practical realisation of our batching schedule. vLLM introduced paged attention for KV cache management, directly addressing the context-length memory constraints we formalise.

FlashAttention reduces the HBM memory traffic of attention from $O(N^2)$ to $O(N)$, consistent with our analysis that memory bandwidth is the binding constraint. Speculative decoding implicitly exploits the compute-memory balance point, using a small draft model to amortise the weight-fetch cost of a large model.

Conclusion

We have demonstrated that the full range of LLM inference pricing phenomena — fast-mode premiums, context-length surcharges, cache discount tiers, and the architectural necessity of MoE expert parallelism within rack boundaries — can be derived from a single physical equation:

$$T_{\text{inference}} = \max\left(\frac{2BP_{\text{active}}}{\mathcal{F}}, \frac{W_{\text{bytes}} + B \cdot C_{\text{bytes}}(S)}{\mathcal{B}}\right)$$

The binding constraint for virtually all real-world LLM inference is memory bandwidth, not arithmetic throughput. This has three primary implications:

1. **For system designers:** optimise for memory bandwidth utilisation, not FLOPs; batch aggressively; use quantisation to reduce weight size; tier the KV cache to cheaper storage for idle sessions.
2. **For model architects:** design model structures that confine all-to-all communication (MoE, tensor parallelism) within NVLink domains; use pipeline parallelism only across rack boundaries; prefer reversible architectures when activation memory constrains training scale.
3. **For economists:** the memory wall, not compute shortage, is the primary pricing lever. Hardware generations that improve HBM bandwidth (H100 $\rightarrow$ H200 $\rightarrow$ B200) will reduce inference costs more than equivalent FLOP increases.

The future of AI infrastructure efficiency lies not in faster arithmetic but in *hiding, compressing, and bypassing the memory wall*.

Dao, T., Fu, D.Y., Ermon, S., Rudra, A., and Ré, C. (2022). *FlashAttention: Fast and Memory-Efficient Exact Attention with IO-Awareness*. NeurIPS 2022.

Gomez, A.N., Ren, M., Urtasun, R., and Grosse, R.B. (2017). *The Reversible Residual Network: Backpropagation Without Storing Activations*. NeurIPS 2017.

Hoffmann, J., Borgeaud, S., Mensch, A., et al. (2022). *Training Compute-Optimal Large Language Models*. arXiv:2203.15556.

Jain, A., Oehmke, P., and Shalf, J. (2019). *Gist: Efficient Data Encoding for Deep Neural Network Training*. ISCA 2018.

Kwon, W., Li, Z., Zhuang, S., *et al.* (2023). *Efficient Memory Management for Large Language Model Serving with PagedAttention*. SOSP 2023.

Leviathan, Y., Kalman, M., and Matias, Y. (2023). *Fast Inference from Transformers via Speculative Decoding*. ICML 2023.

Williams, S., Waterman, A., and Patterson, D. (2009). *Roofline: An Insightful Visual Performance Model for Multicore Architectures*. Communications of the ACM, 52(4):65–76.

Yu, G., Kim, J., Shin, H., *et al.* (2022). *Orca: A Distributed Serving System for Transformer-Based Generative Models*. OSDI 2022.

Derivation of the Optimal Batch Size Formula

Setting $T_{\text{compute}}(B^*) = T_{\text{memory}}(B^*)$ and solving for B^* :

$$\begin{aligned}\frac{2B^*P_{\text{active}}}{\mathcal{F}} &= \frac{W_{\text{bytes}} + B^*C_{\text{bytes}}}{\mathcal{B}} \\ 2B^*P_{\text{active}}\mathcal{B} &= \mathcal{F}(W_{\text{bytes}} + B^*C_{\text{bytes}}) \\ B^*(2P_{\text{active}}\mathcal{B} - \mathcal{F}C_{\text{bytes}}) &= \mathcal{F}W_{\text{bytes}} \\ B^* &= \frac{\mathcal{F} \cdot W_{\text{bytes}}}{2P_{\text{active}}\mathcal{B} - \mathcal{F} \cdot C_{\text{bytes}}}\end{aligned}$$

When $\mathcal{F} \cdot C_{\text{bytes}} \ll 2P_{\text{active}}\mathcal{B}$ (short contexts):

$$B^* \approx \frac{\mathcal{F} \cdot W_{\text{bytes}}}{2P_{\text{active}}\mathcal{B}} = \frac{I^* \cdot W_{\text{bytes}}}{2P_{\text{active}}}$$

Python Reference Implementation

```
import numpy as np

# H100 SXM5 hardware constants
FLOPS_PER_SEC = 989e12      # 989 TFLOPS FP16 peak
MEM_BW_BYTES = 3.35e12      # 3.35 TB/s HBM3
GPU_COST_PER_HR = 3.0       # USD/hr (approximate spot price)

def inference_cost(
    n_params: float,          # total parameters
    batch_size: int,          # concurrent sequences
    context_len: int,         # tokens of context per sequence
```

```

    n_layers: int = 80,    # number of transformer layers
    n_kv_heads: int = 8,   # KV attention heads
    d_head: int = 128,     # head dimension
    dtype_bytes: int = 2,  # 2 for FP16, 1 for INT8
) -> dict:
    """
    Compute inference runtime and cost using the Fundamental
    Inference Equation.
    Returns: dict with T_compute, T_memory, runtime, cost_per_token.
    """

    # Weight size in bytes
    W_bytes = n_params * dtype_bytes

    # KV cache per sequence (K+V for all layers)
    kv_per_seq = 2 * n_layers * n_kv_heads * d_head * context_len *
dtype_bytes

    # Compute time: 2 FLOPs per weight per sequence (matmul)
    T_compute = (2 * batch_size * n_params) / FLOPS_PER_SEC

    # Memory time: fetch weights + KV cache for all sequences
    T_memory = (W_bytes + batch_size * kv_per_seq) / MEM_BW_BYTES

    # Fundamental equation: runtime = max of the two
    runtime = max(T_compute, T_memory)
    bottleneck = "compute" if T_compute > T_memory else "memory"

    # Cost per output token (GPU cost / tokens per second)
    cost_per_token = (GPU_COST_PER_HR / 3600) * runtime / batch_size

    return {
        "T_compute_ms" : T_compute * 1000,
        "T_memory_ms"  : T_memory  * 1000,
        "runtime_ms"   : runtime   * 1000,
        "bottleneck"    : bottleneck,
        "cost_per_token": cost_per_token,
    }

# Example: Llama-3 70B at various batch sizes
for B in [1, 10, 100, 295, 1000, 5000]:
    r = inference_cost(70e9, B, 2048)
    print(f"B={B:5d}: {r['runtime_ms']:6.1f}ms  "
          f"{r['bottleneck']:8s}  "
          f"${r['cost_per_token']*1e6:.2f}/Mtok")

```