

# Open Source Intelligence - Development of a Trend Radar utilizing a Systematic Literature Review

Franz Kayser  
ESG  
[franz.kayser@esg.de](mailto:franz.kayser@esg.de)

Thomas Mayer  
ESG  
[thomas3.mayer@esg.de](mailto:thomas3.mayer@esg.de)

Michael Buecker  
FH Münster – University of Applied Sciences  
[michael.buecker@fh-muenster.de](mailto:michael.buecker@fh-muenster.de)

## Abstract

*Open Source Intelligence (OSINT) is currently experiencing an intensive discourse, heightened since the Russian invasion of Ukraine. However, despite numerous attempts at standardized definitions, the intelligence discipline remains ambiguous. This paper introduces a practice-validated OSINT trend radar, categorizing technologies by maturity, intelligence cycle phase, and use case. Serving as a profound knowledge base and tool for identifying research gaps, the radar emerges from a structured design process. Sixty studies underwent categorization and validation through expert interviews, revealing the absence of a comprehensive, autonomous third-generation OSINT system in Germany. Technological gaps, especially in the planning and direction and dissemination and integration phases, are evident. Although intelligent support technologies were identified, practical implementation lags behind theory. The human factor therefore remains central to the OSINT process. Future research should thus prioritize developing applications for underserved phases, probing reasons for limited widespread implementation of proven applications, with emphasis on legal, ethical, political, and social parameters.*

## 1. Introduction

OSINT is a currently more debated research field than ever before. Obtaining intelligence from publicly available data [1] has become undeniably important since the Russian invasion of Ukraine in 2022. The real-time analysis of social media in particular has brought highly relevant insights to light [2, 3]. However, despite numerous attempts to define OSINT (e.g. [4, 5, 6]), the concept remains controversial to this day [7, 8, 9]. This is not least because every definition of OSINT is subject to the advances in computer and data sciences, which continuously produce improvements in (intelligent) collection and analysis possibilities [7,

9]. This is accompanied by numerous new open means of communication, which have caused a veritable "information explosion" [1, 4, 6]. Data sources that were originally reserved for the defense and intelligence services are now publicly accessible [4, 9]. The understanding of intelligence thus changed completely [10].

To date, there has been a lack of fundamental scientific publications to penetrate the subject area [11] and address its rapid developments [7, 9]. In particular, there is a shortage of studies that identify the technologies behind OSINT and determine their characteristics. The question of whether autonomous third-generation OSINT systems [12, 5] exist has not yet been clarified [7, 5, 6]. Moreover, the majority of studies focus exclusively on the OSINT trend area "cyber security" [4, 12, 6]. The literature thus failed to cover the topic in its entirety. Important use cases of OSINT have therefore not yet been researched [13, 10, 7]. In addition, supplementary qualitative field research is absent to contrast theory with the corresponding practical implementation. Although OSINT has a major impact on topics such as security and defense, there is a lack of insight into these sectors [11, 12]. This paper is hence dedicated to answering the research question: *How can the current trends in OSINT in the form of the technologies used and their characteristics, in particular the maturity level and the use case, be presented in a trend radar and validated by experts within the security sector?*

The thereby aim is to identify the technologies used in OSINT applications and to present them systematically in a trend radar, according to their characteristics. In this way, a well-founded knowledge base will be compiled, and practice-relevant research gaps will be identified for a coordinated examination of the research field. The study follows the "Design Science Research Model" (DSRM) [14]. First, the relevant literature on OSINT will be analyzed and classified through a systematic literature review [15]. Second, the OSINT technologies and their

characteristics identified will be visualized in the form of a trend radar. The radar will then be validated using systematizing interviews [16] conducted with experts in the security sector. Finally, the interviews will be evaluated using a qualitative content analysis [17].

## 2. Theoretical Background

The domain of OSINT is continuously expanding due to the ongoing improvements of collecting and analysis possibilities [13, 7, 9]. In addition, the new means and methods of communication associated with advances in information and communication technology have turned OSINT into a complex discipline [13, 18, 19, 9].

### 2.1. Open Source Intelligence (OSINT) and its Components

One of the earliest and still frequently referenced definitions [1] was published by NATO in 2001. OSINT according to this definition is information that has been deliberately discovered, discriminated, distilled, and disseminated to a select audience, [...], in order to address a specific question. OSINT, [...] thus applies the proven process of intelligence to the broad diversity of open sources [...] and creates intelligence [23]. However, today the discipline is no longer seen as a purely governmental matter. Private research institutions and organizations [20, 21] are also massively driving the development of such systems, e.g. for competitive analyses or marketing activities [13, 10, 7]. The focus is thereby shifting to developing OSINT into a robust, autonomous solution (referred to as third-generation) [17, 12, 22]. The starting point for all OSINT activities thereby lies in data. Data forms the basis of the analysis and the conclusions derived from it [23]. In this context, Open Source Data (OSD) refers to non-processed [1], general raw data that is openly available [24] as well as legally and ethically accessible [22, 25]. Before intelligence can be obtained from OSD, they must undergo a preparation process that includes filtering, validation and summarization [1, 25]. The result of this data organization [22] is referred to as Open Source Information (OSINF). It provides the basis for the resulting intelligence creation [1, 22].

### 2.2. Intelligence and Intelligence Cycle

The core task of OSINT is to generate intelligence [4, 10] in terms of a profound basis for decision-making [26, 27]. The generation process of such an intelligence product is also referred to as the intelligence cycle [11, 28]. It represents the central element of every

intelligence discipline [29, 10]. The link between the phases is that the result of the preceding phase serves as input for the subsequent phase [30, 31]. Furthermore, the individual phases are also continuously iterated due to the fulfillment of previous requirements and new demands[23]. Today, to represent external influences or the assignment of responsibilities [32, 33, 34], numerous variations can be found [20, 29]. The Intelligence Cycle should therefore be seen less as a guideline and more as an informal coordination element[4]. In 2013, the JCS segmented the cycle into 6 phases [32] (see Fig 1).




Figure 1. Intelligence Cycle, according to [30]

The planning and direction phase combines the identification, definition and prioritization of the requirements for the cycle. It is also responsible for developing and monitoring the activities required to achieve these [35, 30, 35]. The collection phase refers to the gathering of raw data [28]. The core of this phase consists of the iterative repetition of research [25] to make the query more precise with each run [5]. The processing and utilization phase involves condensing these data volumes into action-relevant information [36, 30, 5]. Analysis and production refers to the synthesis of the information obtained into a user-oriented, timely and accurate intelligence product [35, 4, 25]. The final phase consists of handing over the finished product to the "customer" in a usable form [37, 35, 9]. Evaluation and feedback are not to be regarded as individual phases but take place continuously throughout the entire cycle. The aim is to achieve progressive optimization [36, 30, 25].

## 2.3. Previous Studies

Eight previous, publicly accessible literature reviews can be identified concerning OSINT. In 2017, Dos Passos [1] showed how big data and data science can make the decision-making process more useful and effective. Pastor-Galindo et al. then described the current state of OSINT in 2019 [12] and 2020 [5] focusing on services and techniques to improve cybersecurity. Moreover, they are responsible for the first and only rudimentary mapping of OSINT trends. They observed that OSINT is used in social opinion and sentiment analysis, cybercrime and organized crime, as well as cybersecurity and cyberdefence. Two further literature reviews were published in 2020. García Lozano et al. [38] identified methods for computer-assisted veracity assessment of public information. Herrera-Cubides et al. [11] investigated how the production of research and educational materials has developed. They concluded that the number of OSINT publications is lower compared to other trending topics. In 2021, Yogish and Krishna [6] explored the state of implementation and use of Artificial Intelligence (AI) technologies in the context of cybersecurity. The result of this study showed that Machine Learning (ML), pattern recognition and Natural Language Processing (NLP) can simplify OSINT given increasing data volumes. In the following year, Hwang et al. [4] investigated security threats and cybercriminality in the context of OSINT misuse. In 2023, Ghioni et al. [7] then examined the political, ethical, legal and social implications of OSINT in conjunction with AI. They discovered that there is still no framework for addressing these. They also found that third-generation OSINT is still in its early stages and that human components cannot yet be replaced.

## 3. Research Methodology

The structure of the study is based on the iterative DSRM [14]. It is a theory-based research paradigm for developing an explicitly applicable solution, in the form of an innovative artifact, [39], solving a (practical) problem [14, 40]. The model is therefore ideally suited to create the trend radar. It consists of six successive activities (see Fig. 2) [14]. Moreover, the first three evaluation steps according to Sonnenberg and vom Brocke [41] were applied to continuously evaluate the design process.

### 3.1. Problem Identification and Motivation

First, the research problem must be defined and the benefits of the solution explained (see chapter

Introduction).

### 3.2. Design Objectives of the Solution

The next step is to define the design objectives of the solution. The objectives can be divided into two content-related objectives (CO) and two formal objectives (FO). CO1 requires the trend radar to follow a procedural structure that reflects the process of generating intelligence. This will allow a structured mapping of the identified technologies according to their use. In doing so, any research gaps that become apparent can be directly assigned to the respective phase. It will thus be possible to verify if a third-generation OSINT system exists. As CO2, it was defined that the key characteristics, in particular the maturity level of the technologies and their use cases, must be taken into account. The maturity level of the technologies makes it possible to determine the respective research status. Through the use cases, the research directions can be revealed. As FO1, it was determined that the trend radar must follow a simple structure to enable the immediate identification of research gaps. In addition, the radar should have a high degree of standardization to be transferable to other intelligence gathering disciplines in later studies. As FO2, it was decided that the trend radar should be continuously expandable to capture the high field dynamics.

### 3.3. Evaluation of the Problem Statement and Design Objectives

In the theoretical background section, the main definitions, in particular, the intelligence cycle, which serves as a basis for the development of the trend radar ("suitability"), were presented. Moreover, the presentation of previous research work showed that there is still a lack of broad-based studies examining OSINT. Both the relevance of the research question and the suitability of the design objectives are thus underpinned [41].

### 3.4. Design and Development

The third activity involves the creation of the artifact. For this purpose, the relevant literature on OSINT was analyzed through a systematic literature review [42]. To clearly define the scope of the literature review, Cooper's taxonomy [43] was used. Subsequently, classification categories were defined to establish concept matrices [15], to systematically analyze the researched literature. To achieve a high degree of standardization, general categories were defined for each phase of the intelligence cycle. The evaluation




Figure 2. Design Science Research Model (DSRM)

and feedback phase was not treated separately due to its iterative nature.

The following six categories were defined for the collection phase: "use case", "data", "process", "technology", "technology complexity" and "maturity level". First, the area of application of the technologies was recorded under the use case. The category data reveals the composition of the data foundation. It is further subdivided into the data type to record the formats and the source to show the origin of the data. The category process is used to determine the degree of automation of the technologies. For this purpose, the following four levels were defined: manual, semi-automated, automated, [44] fully automated/autonomous [17, 45]. To improve categorization, the ten levels of automation [46, 47] were used. The fourth category serves to capture the technologies, defined as "the totality of material and immaterial means available for the input, output, conversion, transmission and storage of information" [48]. The fifth category evaluates the complexity of the technologies examined. The three subcategories "Volume" [49], "Variety" and "Velocity" were used [50, 51, 52]. Variety is further subdivided according to the data structure (structured [53], semi-structured and unstructured [54, 55]) [49]. Velocity, is further subdivided into the levels "Batch" [56], "Near Real-Time" [57, 58] and "Real-Time" [57]. The sixth category reflects the maturity level of the technologies used, based on the three macro-maturity phases of the German Federal Trend Radar: innovation phase, prototype phase and market establishment phase [59].

For the remaining phases the categories use case, process, technology, technology complexity and

	Databases	Web of Science	IEEE Xplore	ACM Digital Library	arXiv
Step 1	Search string	("OSINT" OR "Open Source Intelligence" OR "Open-Source Intelligence" OR "open source intelligence" OR "open-source intelligence")			
	Delimitation	German and English sources, full access			
	Result	89	207	145	25
Step 2	Delimitation	Time period from 2020 to 2023			
	Result	65	83	83	14
Step 3	Delimitation	Reading the title, the abstract, the chapter headings and the conclusion of the studies			
	Result	13	39	12	7
Step 4	Delimitation	Systematic reading and recapitulation of the study as a whole			
	Result	11	32	12	5

Figure 3. Literature review

maturity level were likewise defined. However, the complexity within the remaining phases is measured based on the underlying analysis, in ascending order: descriptive analysis, diagnostic analysis, predictive analysis, prescriptive analysis [60, 61].

After defining the classification criteria, the literature research was carried out (Fig. 3). A search string based on general terms for the highest possible number of hits was determined. Only studies with full access were considered. As the number of publications increased significantly between 2020 and 2023, the period was reduced to these years to ensure the most up-to-date coverage possible. The studies were downloaded on 05.06.2023. The SQR3 method [62] was applied for the systematic analysis and further delimitation. Altogether 60 studies were categorized.

For categorization, a dedicated Excel spreadsheet was created per Intelligence Cycle phase and the OSINT

technologies and their characteristics were methodically recorded [42, 15]. The identified technologies were then grouped according to relations in an additional column (see Repository X). Afterward, the categorization was verified using a "Python" script (see Appendix A). This queries the occurrence of predefined keywords in the included papers. Afterward, the trend radar was created based on the verified concept matrices.

### 3.5. Evaluation of the Design Specifications

The intelligence cycle as the basis of the trend radar provides a structured overview ("clarity") [26]. This fulfills the requirement of an intuitively understandable illustration ("understandability") for ensuring a simple extraction ("simplicity") of technologies and research gaps. Furthermore, the other intelligence disciplines are also derived from the cycle, which enables a later application to these ("applicability"). By aligning the architecture of the radar with the federal government's trend radar [59], a proven, robust, user-friendly design ("user-friendliness") with an appropriate level of detail ("level of detail") is used. Only the categories use case, technology and degree of maturity were therefore illustrated. Moreover, with the concept matrices, a template is used to constantly update the radar. Particular attention was paid to the general validity of the categories to achieve the highest possible degree of standardization ("generality"). Furthermore, a verification of the categorization was carried out ("internal consistency"). The decisive evaluation criteria [39] are thus fulfilled.

### 3.6. Demonstration

Next, the trend radar was demonstrated via guideline-based, systematizing expert interviews [16, 63, 64]. Especially in less structured and sparsely linked subject areas, the method enables dense data collection [16, 64]. Additionally, it is suitable in cases where access to the social field is limited [65, 63].

The experts (Tab. 1) were selected according to the method of theoretical sampling [66, 67]. It was specified that only experts in Germany should be interviewed to validate the trends in this country. It was also determined that at least one expert each from a security authority, the security industry and a start-up would be selected to capture different points of view. A "prestigious" company position is seen as a reliable guarantee that the respondents possess research-relevant knowledge [68].

The qualitative data collection that followed was carried out using semi-structured interviews. These are particularly suitable for revealing the underlying

**Table 1. Interviewed experts**

Organization	Position	ID
Industry/ Authority	Senior Intelligence Consultant	E1
Industry/ Authority	Referent Corporate Security	E2
Authority	In-House Senior Consultant	E3
Start-up	Co-Founder, Managing Director of a German start-up, for an OSINT platform	E4

relationships of a theory [16]. The questionnaire used is based on the structure of the Intelligence Cycle. At the beginning of the interview, the trend radar was presented. To compare it with the respondents' practical experience, first, open questions were asked for each phase. These reduce the influence of subjectivity [69]. Exploratory questions were added to direct the flow of conversation [69]. Thirs, specific closed questions for targeted follow-up queries were asked [69]. The interviews lasted up to one hour, with a maximum of three main questions for each phase [16] (see Respository X). The questionnaire was pilot-tested with a domain expert. The interviews were conducted online.

### 3.7. Evaluation of the First Instance of the Trend Radar

The demonstration of the trend radar confirmed its intuitive comprehensibility ("ease of use"). It was also perceived by the practitioners as a useful tool for providing an overview of OSINT technologies ("effectiveness"). In addition, they confirmed its completeness ("completeness") and internal consistency ("consistency") (cf. expert E1, 14.08.2023; expert E3, 28.07.2023; expert E4, 02.08.2023). The trend radar thus proved to be a suitable instrument for identifying research gaps and for serving as a guideline to practitioners ("fidelity with real world phenomenon"). The essential evaluation criteria [41] are thus demonstrably fulfilled.

### 3.8. Evaluation

The evaluation was carried out using a qualitative data analysis [63]. It extracts, synthesizes and structures the information contained in the interviews using a predefined search grid. This enables the targeted extraction and summarization of relevant, cross-interview information according to a "top-down approach" [16, 63].

First, the recorded interviews were transcribed. Second, the software MAXQDA [70] was used for

the subsequent analysis. The categorization system was therefore established as grid within MAXQDA (see repository X). The categories of the first level correspond to the individual phases of the intelligence cycle. The categories of the second level allow a classification of whether the experts express themselves in support of or in contradiction to the theory. The categories of the third level reflect the identified use cases. As many of the experts' statements were general, the category "general statements" was added. The categories of the fourth level reflect the individual technologies classified under them. Altogether, 257 statements were categorized in this way. Examples of the coding procedure can be found in Tab. 2.

### **3.9. Communication**

The research results are communicated in the form of this study. A new iteration, proceeding from this chapter, is therefore not carried out.

## **4. Results**

The trend radar (4, 5) is read from the outermost to the innermost. Each fifth of the cycle represents an Intelligence Cycle phase. Subdivisions indicate phase-specific use cases, while color gradations show maturity levels. Numbered black and white dots denote grouped technologies, presented in a boxplot-like format reflecting varying maturity levels.

### **4.1. Intelligence Cycle in Theory-Practice Comparison**

Studies could be attributed to each of the Intelligence Cycle phases. However, none of the applications identified covers all phases in the sense of a third-generation OSINT tool. Literature primarily focuses on the collection phase, followed by the analysis and production phase and the processing and exploitation phase. The dissemination and integration phase is covered by far the least after the planning and direction phase.

These findings align with the experts' practical experiences. They regard the Intelligence Cycle as "state of the art" (cf. E3, 28.12.2023), but note different manifestations of the phases in praxis (cf. E4, 02.08.2023). The planning and direction phase is often neglected, despite its crucial importance, leading to wasteful production (cf. E3, 28.07.2023). Conversely, OSINT is frequently associated solely with the collection phase, resulting in subpar outcomes due to high volumes of low-quality data (cf. E1, 14.07.2023; E2, 19.07.2023; E3, 28.07.2023). The main reason for

this is, that the Intelligence Cycle is operated by at least three groups of people. Firstly, the customers, usually located at the "decision-maker level", with a primarily legal professional background (cf. E2, 19.07.2023). The second is the technician who carries out the data collection and processing (cf. E2, 19.07.2023; E3, 28.07.2023). Lastly, the analyst evaluates the data and creates the intelligence product (cf. E1, 14.07.2023). The process thereby is rarely transparent between the parties (cf. E1, 14.07.2023; E2, 19.07.2023) and is rarely anchored at the organizational level (cf. E4, 02.08.2023). According to the experts, there is thus no third-generation OSINT tool in use, at least not in German authorities. In addition, the collection focus is driven by concerns about missing vital information, which could later be revealed as publicly available (cf. E1, 14.07.2023).

### **4.2. Use Cases in Theory-Practice Comparison**

Five main use cases emerged from the research: Cyber Security, Health, Security, Journalism, and Competition Analysis. Cyber Security studies primarily focus on Open Source Cyber Threat Intelligence (OSCTI), which involves collecting, monitoring, and analyzing publicly available data to detect potential cyber threats [71, 72]. Health applications mainly pertain to COVID-19, such as investigating the epidemic outbreak [73, 74]. The security use case includes applications such as analyzing violent behavior in public transport [75]. The identified Journalism study examines the Twitter activities of the OSINT journalists' association "Bellingcat" [76]. Competitive analysis involves for example the performance classification of Chinese logistics companies [77]. Additionally, two studies could be identified on general approaches to creating knowledge graphs on OSINF [78, 79].

According to the experts, OSINT is applied in all authorities and has proven itself in numerous use cases, even if not always explicitly labeled as such (cf. E2, 19.07.2023). Most common cases are in cyber security/CTI (cf. E1, 14.07.2023; E2, 19.07.2023), as well as general security, particularly with regard to the German Armed Forces, the (Federal) Intelligence Service, the German domestic intelligence services and the police.

### **4.3. Technologies and Maturity Levels in Theory-Practice Comparison**

Except for the initial phase, automated technologies are utilized across all subsequent phases and use cases. These technologies demonstrate considerable market

Table 2. Coding examples

Level 1	Level 2	Level 3	Level 4	Transcript example
Collection phase	Theory-supporting	General statement	"web crawler" and/or "web scraper"	And precisely because there are so many, so simple ways to create web crawlers and web scrapers, [...]"(Cf. expert E1, 14.07.2023)
Analysis and production phase	Theory-contradictory	Security	AI, ML, DL	"Deep learning, machine learning, artificial intelligence, in some places, I don't know anyone who has built in a random forest anywhere [...]" (cf. E3, 02.08.2023)




Figure 4. Trend radar

maturity, yet manual activities remain prevalent. The highest level of automation is observed in the CTI use case.

The most advanced automated technology in the collection phase is web crawlers and/or web scrapers. Established technologies include "off the shelf" tools (cf. [80]) and open source solutions like "Tweepy," a Python library for Twitter crawlers (cf. [81, 82]). More advanced prototypes involve combining parallelized, recursive, source-specific web crawlers and scrapers for improved data collection (cf. [83, 84]). Another method in the prototype phase is "focused crawling", adapting the crawling path dynamically using a content-driven ML algorithm, BERT ("Bidirectional Encoder Representation from Transformers") (cf. [85]). Technologies for crawling/scraping the dark web, like

"Torsion" (cf. [86]), were assigned to the innovation phase. The experts also note the increasing use of open source tools alongside manual work (cf. E1, 14.07.2023; E3, 28.07.2023; E1, 14.07.2023). However, they consider traditional web crawling and scraping outdated due to errors, implementation difficulties, and website resistance. Screenshot-based "web shooting" with subsequent OCR (Optical Character Recognition) extraction is seen as more modern and robust (cf. E3, 28.07.2023).

NLP applications/methods such as "Topic Classifying," "Part-of-Speech Tagging", "Entity and Relation Annotation", and "Named Entity Recognition" demonstrate high automation levels in the processing and utilization phase. Technologies commonly used include the "Python NLTK Toolkit" [87] and the

”Stanford CoreNLP Toolkit” [80]. Additionally, deep learning, particularly through ”word embedding” using the ”word2vec” algorithm, is prominent [88, 89, 90]. However, the experts note that this phase within authorities predominantly involves manual work due to the irreplaceable domain knowledge of experts (cf. E1, 14.07.2023; E2, 19.07.2023; E3, 28.07.2023). The degree of automation of technologies thus depends on the abstraction level. Operational tasks, which often require specific individual information, show lower automation levels compared to long-term general strategic analyses requiring extensive data (cf. E3, 28.07.2023).

The highest automation level is observed in the analysis and production phase, where AI, ML, and DL technologies are prevalent. Under DL, vectorization algorithms can also be found. Particularly BERT algorithms in different versions are commonly utilized (cf. [79, 91]). Furthermore, even under ML vectorization models such as BERT or ”Supervised Support Vector Machines” (SVM) (see e.g.: [92]) are listed. In addition, the algorithms ”Random Forest”, XGBoost (”eXtreme Gradient Boosting”), lightGBM (”light Gradient Boosting Machine”), ”Naive Bayes” and ”logistic regressions” are particularly common. Publications thereby often utilize multiple algorithms concurrently for performance comparison (e.g. [77]) or for layered analysis (e.g. [93]). AI technologies are generally less specified, except for Dale et al. [94], who developed a bidirectional recurrent neural network with BiGur (”Bidirectional Gated Recurrent Unit”) layers. Due to the modular use of publicly available models, the technologies are mostly classified as market-ready. Despite the potential, practical work in this phase largely relies on manual content analysis due to a lack of technological understanding and acceptance, especially at the contractor/provider level in Germany (cf. E2, 19.07.2023; E3, 28.07.2023; E4, 02.08.2023). Furthermore, ethical and legal barriers, such as GDPR (General Data Protection Regulation), hinder technology adoption (cf. E2, 19.07.2023; E4, 02.08.2023). Additionally, security concerns in German authorities favor standalone systems (cf. E2, 19.07.2023). If smart technologies are used, it is often only unofficially (cf. E4, 02.08.2023). However, there’s a need for modular, dynamically expandable systems to keep pace with rapid advancements (cf. E1, 14.07.2023; E3, 28.07.2023; E4, 02.08.2023). Nevertheless, human experience and specialization should not be outweighed, but rather a certain product quality be ensured in a supportive manner. Yet, the revolutionary potential of large language models (LLM) cannot be estimated (cf. expert E4, 02.08.2023).

In the dissemination and integration phase, tools like ”Power BI” [77] are utilized to create dashboards and visualization maps. Furthermore, user interfaces, web applications, and online platforms are developed, including Python GUIs, specific browser applications [95], improved user interfaces and input masks for entire tool stacks [96]. Additionally, Technologies for generating automated alerts, particularly for cyber security risk assessments, are prevalent [71]. Graph-based visualizations are also common, utilizing tools /libraries like ”Matplot,” ”Networkx,” ”Pygraphistry,” or the ”Neo4j-Browser” [80]. Except from the alerts, the retrieval of results is largely semi-automated and the technologies are in the market establishment phase. No information on targeted user tests or a new development run involving user feedback could thereby be found in any of the studies. The experts state that there is still very little automation within the authorities during this phase. The final product is often only a PDF document, an email or a verbal report (cf. E1, 14.07.2023), although in many cases no more is required (cf. E3, 28.07.2023). However, outside of the OSINT topic, there are several automated tools, that could be transferred to the authorities in this context (cf. E4 02.08.2023). Moreover, in practice, there is also a lack of necessary feedback for product improvement (cf. E3, 28.07.2023).

## 5. Discussion

### 5.1. Contributions and Implications

The investigation into the existence of a robust, automated third-generation OSINT system (cf. e.g: [7, 5, 6]) leads to a negative conclusion, at least for Germany. Identified applications fall short of fully covering the intelligence cycle, with significant gaps in the planning and direction phase, followed by the dissemination and integration phase. Humans therefore remain the driving (analysis) component. However, the finding by Pastor-Galindo et al. [5] that intelligent OSINT concepts are not yet widespread cannot be confirmed either. Numerous intelligent tools available on the market were identified in the other phases. Nevertheless, practical integration has so far fallen short of the (theoretical) possibilities. Yet this finding likewise does not confirm the thesis of Yogish et al. [6] that automated, AI-driven solutions, largely eliminating the human component, are inevitably required in every area of OSINT. Rather, the key research question should be why proven, available applications whose support is needed have not yet found widespread use, especially in intelligence authorities. In addition, the question of



how the first and last Intelligent Cycle phases, alongside the others, can be better supported technically should be investigated.

Addressing these research questions entails resolving numerous underlying research gaps (RGs), directly corresponding to the three key groups involved in the intelligence cycle. Primary among these are the product customers. (RG1) Technologically, there's a deficiency in tools covering the initial phase of the intelligence cycle, particularly in frameworks and tools for targeted requirements definition and communication, which could alleviate the overemphasis on the collection phase [32]. (RG2) Moreover, concerning the final phase, there's a dearth of dissemination and integration mechanisms tailored to authorities, largely due to insufficient user testing and iterative feedback incorporation. However, established frameworks and the Intelligence Cycle itself underscore the indispensability of consumer feedback for value-generating products [36, 30, 25] as it can significantly reduce data overload [23] and enhance product credibility and quality [97]. (RG3) Furthermore, the future of OSINT systems hinges on modular concepts, yet only two studies have been found on this (cf. [96, 98]). (RG4) Accordingly, it's imperative to revamp procurement procedures moving away from monolithic stand-alone setups. (RG5) Ensuring compliance with ethical and legal principles at the client and customer level is vital for product adoption, necessitating robust legislative updates to establish appropriate frameworks [7, 99]. This involves not only national but also international-level considerations, such as GDPR regulations [100, 101], taking into account not solely individual but societal impacts [7]. To date, these topics remain underexplored [7, 99]. (RG6) Addressing these challenges necessitates a foundational level of technical understanding at decision-maker levels, fostering openness to technology, and cultivating an information-sharing mindset, leveraging the public availability of information to transcend bureaucratic barriers [25].

The analysts, comprising the second group, create the final product and, at present, cannot be replaced by AI systems due to their extensive domain knowledge [102, 5]. (RG7) However, LLMs show promise in this realm, potentially becoming vital tools given their versatility [103, 104]. Yet, the use of such models in application development could not be found. For the time being, cross-use case task transferability can only be mapped to a limited extent with current learning algorithms and is currently still subject to human cognition (cf. [105, 7]). Until then, the pursuit of the ideal symbiosis between humans and machines

to bolster analysts amid the deluge of data remains paramount [102].

The third group, comprised of technicians, often handles the second and third phases of the intelligence cycle independently (RG8). Technologically, there's a notable absence of robust collection tools at this level to match the rapidly evolving media landscape (RG9). Process-wise, coordination gaps with analysts pose a risk of excessive data collection. Lowenthal [32] suggests that data collection biases may stem from emotional or lobby-driven factors, as it's seen as more enticing than its maintenance. Additionally, the fear of overlooking pertinent information underscores the necessity for technological tools to enhance transparency.

## 5.2. Limitations and Future Research

The first limitation relates to the fact that, due to a lack of clarity about the legal and ethical basis [7, 106, 99], it could not be verified whether only public sources [107] were used in the analyzed studies. It was also not verified whether the technologies meet the legal and ethical requirements for the use of the information obtained [5, 99]. The second limitation stems from classification categories not fully aligning with the MECE (Mutually-Exclusive-and-Collectively-Exhaustive) principle [108, 109], particularly evident in the hierarchical dependency of AI, ML, and DL technologies. In addition, the wording of the authors was followed for objective reproduction when identifying the technologies, but the accuracy of the information was not reviewed in detail. Moreover, no fixed limits could be defined for the volume category, as these were not recorded in uniform dimensions in the studies. The third limitation concerns the limited sample size in expert interviews. Due to the extremely difficult-to-access target group, the active user level and the decision-maker level within the authorities were not interviewed. For improved intercoder reliability, independent verification of the coding carried out by at least a second researcher is also recommended [65, 63, 110]. Lastly, the research structure, following the DSRM process, was executed linearly rather than iteratively as recommended [14].

Nevertheless, the study furnishes future researchers with a robust knowledge base on OSINT through a practice-validated trend radar. This facilitates an updated assessment of OSINT trends and underscores the current research landscape. The study reveals two crucial unanswered research questions and offers nine detailed research gaps for further exploration in the field.

Before addressing these questions, future researchers are advised to validate them further. Utilizing the presented tools to reevaluate literature categorization and update identified technologies is recommended. In addition, semantic control and indexing methods (e.g. LLM) should be included. Due to the high dynamic of the research field, it is also recommended to integrate news articles and scientific journals with shorter publication cycles. Reassessing categories based on MECE criteria and conducting further interviews, including internationally and with active authority members, is advisable. Employing methods like the Delphi technique to evaluate trends and establish consensus is suggested [111]. Subsequent iterations of the design process and adjustments to the trend radar, if necessary, should follow based on these results [14, 41].

## 6. Conclusion

In this paper, a practice-validated trend radar was developed that depicts current trends in the field of OSINT through applied technologies. It serves as a comprehensive knowledge base, allowing for contemporary evaluation and analysis of OSINT technologies as well as identifying research gaps for future studies, penetrating the complex research field. Moreover, it serves as a guideline for practitioners. The radar is adaptable to the evolving subject area and transferable to other intelligence disciplines. Results reveal the absence of an automated third-generation OSINT system in Germany, highlighting the need for technological support in the planning and direction as well as the dissemination and integration phases. The research questions identified for future studies are therefore, why proven, available applications, have not yet found widespread use, especially in the security authorities. In addition, the question of how the first and last Intelligent Cycle phases, alongside the others, can be better supported technically is to be investigated. The research gaps identified extend not only to technology but in particular to the legal, administrative, political and social sciences, necessitating interdisciplinary collaboration. Above all, a need to catch up is seen in the non-technical research fields, responsible for creating the decisive prerequisites for technology implementation.

## 7. References

### References

- [1] D. S. Dos Passos, "Big data, data science and their contributions to the development of the use of open source intelligence," *Sistemas & Gestão*, vol. 11, no. 4, pp. 392–396, 2017.

- [2] J. M. Hatfield, "There is no such thing as open source intelligence," *International Journal of Intelligence and CounterIntelligence*, pp. 1–22, 2023.
- [3] V. Smith-Boyle, "How osint has shaped the war in ukraine," 24.07.2023.
- [4] Y.-W. Hwang, I.-Y. Lee, H. Kim, H. Lee, and D. Kim, "Current status and security trend of osint," *Wireless Communications and Mobile Computing*, vol. 2022, pp. 1–14, 2022.
- [5] J. Pastor-Galindo, P. Nespoli, F. Gomez Marmol, and G. Martinez Perez, "The not yet exploited goldmine of osint: Opportunities, open challenges and future trends," *IEEE Access*, vol. 8, pp. 10282–10304, 2020.
- [6] P. U. Yogish and P. K. Krishna, "Open source intelligence and its applications in next generation cyber security - a literature review," 2021.
- [7] R. Ghioni, M. Taddeo, and L. Floridi, "Open source intelligence and ai: a systematic review of the gelsi literature," *AI & society*, pp. 1–16, 2023.
- [8] D. Ish, J. Ettinger, and C. Ferris, *Evaluating the Effectiveness of Artificial Intelligence Systems in Intelligence Analysis*, vol. RR-A464-1 of *Research reports*. Santa Monica, Calif.: RAND Corporation, 2022.
- [9] H. J. Williams and I. Blum, *Defining Second Generation Open Source Intelligence (OSINT) for the Defense Enterprise*, vol. RR-1964-OSD of *Research reports*. Santa Monica, Calif.: RAND Corporation, 2018.
- [10] T. Dokman and T. Ivanjko, "Open source intelligence (osint): issues and trends," in *INFuture2019: Knowledge in the Digital Age*, International Conference The Future of Information Sciences INFuture, Faculty of Humanities and Social Sciences, University of Zagreb Department of Information and Communication Sciences, FF press, 2020.
- [11] J. F. Herrera-Cubides, P. A. Gaona-García, and S. Sánchez-Alonso, "Open-source intelligence educational resources: A visual perspective analysis," *Applied Sciences*, vol. 10, no. 21, p. 7617, 2020.
- [12] J. Pastor-Galindo, P. Nespoli, F. Gomez Marmol, and G. Martinez Perez, "Osint is the next internet goldmine: Spain as an unexplored territory."
- [13] H. AlKilani and A. Qusef, "Osint techniques integration with risk assessment iso/iec 27001," in *International Conference on Data Science, E-learning and Information Systems 2021* (J. A. Lara Torralbo, S. A. Aljawarneh, V. Radhakrishna, and A. N., eds.), (New York, NY, USA), pp. 82–86, ACM, 2021.
- [14] K. Peffers, T. Tuunanen, M. A. Rothenberger, and S. Chatterjee, "A design science research methodology for information systems research," *Journal of Management Information Systems*, vol. 24, no. 3, pp. 45–77, 2007.
- [15] J. Webster, Watson, and T. Richard, "Analyzing the past to prepare for the future: Writing a literature review," *MIS Quarterly*, vol. 26, pp. xiii–xxiii, 2002.
- [16] A. Bogner, B. Littig, and W. Menz, *Interviews mit Experten: Eine praxisorientierte Einführung*. Wiesbaden: Springer Fachmedien Wiesbaden, 2014.
- [17] C. E. Billings, *Aviation automation: The search for a human-centered approach*. Human factors in transportation, Mahwah, N.J: Lawrence Erlbaum Associates Publishers, 1997.

- [18] L. Benes, "Osint, new technologies, education: Expanding opportunities and threats. a new paradigm," *Journal of Strategic Security*, vol. 6, no. 3Suppl, pp. 22–37, 2013.
- [19] Chen, Chiang, and Storey, "Business intelligence and analytics: From big data to big impact," *MIS Quarterly*, vol. 36, no. 4, p. 1165, 2012.
- [20] I. Böhm and S. Lolagar, "Open source intelligence," *International Cybersecurity Law Review*, vol. 2, no. 2, pp. 317–337, 2021.
- [21] S. C. Mercado, "Reexamining the distinction between open information and secrets," *Studies in Intelligence*, vol. 49, no. 2, 2005.
- [22] F. Schaurer and J. Störger, "The evolution of open source intelligence."
- [23] H. Gibson, "Acquisition and preparation of data for osint investigations," in *Open Source Intelligence Investigation* (B. Akhgar, P. S. Bayerl, and F. Sampson, eds.), Advanced Sciences and Technologies for Security Applications, pp. 69–93, Cham: Springer International Publishing, 2016.
- [24] C. Burke, "Freeing knowledge, telling secrets: Open sourceintelligence and development," *Research paper series: Centre for East-West Cultural & Economic Studies*, no. 13, 2007.
- [25] "Nato open source intelligence handbook."
- [26] A. Breakspear, "A new definition of intelligence," *Intelligence and National Security*, vol. 28, no. 5, pp. 678–693, 2013.
- [27] "The security intelligence handbook: Third edition: How to disrupt adversaries and reduce risk with security intelligence."
- [28] "Factbook on intelligence."
- [29] A. Reuser, "The ris open source intelligence cycle," *Journal of Mediterranean and Balkan Intelligence*, vol. 10, no. 2, 2017.
- [30] "Joint intelligence."
- [31] R. Pellissier and T. E. Nenzhelele, "Towards a universal competitive intelligence process model," *SA Journal of Information Management*, vol. 15, no. 2, 2013.
- [32] M. M. Lowenthal, *Intelligence: From secrets to policy*. Thousand Oaks, Calif.: SAGE/CQ Press, eighth edition ed., 2020.
- [33] M. Phythian, ed., *Understanding the intelligence cycle*. Studies in intelligence, London: Routledge, 2013.
- [34] R. Johnston, *Analytic culture in the US intelligence community: An ethnographic study*. Washington, DC: Central Intelligence Agency (CIA), 2005.
- [35] "Open-source intelligence."
- [36] "U.s. national intelligence: An overview 2011."
- [37] "The intelligence cycle: Briefing."
- [38] M. García Lozano, J. Brynielsson, U. Franke, M. Rosell, E. Tjörnhammar, S. Varga, and V. Vlassov, "Veracity assessment of online data," *Decision Support Systems*, vol. 129, p. 113132, 2020.
- [39] J. vom Brocke, A. Hevner, and A. Maedche, "Introduction to design science research," in *Design Science Research. Cases* (J. vom Brocke, A. Hevner, and A. Maedche, eds.), Progress in IS, pp. 1–13, Cham: Springer International Publishing, 2020.
- [40] Hevner, March, Park, and Ram, "Design science in information systems research," *MIS Quarterly*, vol. 28, no. 1, pp. 75–105, 2004.
- [41] C. Sonnenberg and J. vom Brocke, "Evaluations in the science of the artificial – reconsidering the build-evaluate pattern in design science research," in *Design Science Research in Information*, vol. 7286, pp. 381–397, 2012.
- [42] A. Cleven, B. Niehaves, R. Plattfaut, K. Riemer, A. Simons, and vom Brocke, Jan, Martin Hilti, "Reconstructing the giant: On the importance of rigour in documenting the literature search process."
- [43] H. M. Cooper, "Organizing knowledge syntheses: A taxonomy of literature reviews," *Knowledge in Society*, vol. 1, no. 1, pp. 104–126, 1988.
- [44] C. Duncheon, "Product miniaturization requires automation – but with a strategy," *Assembly Automation*, vol. 22, no. 1, pp. 16–20, 2002.
- [45] M. R. Endsley and D. B. Kaber, "Level of automation effects on performance, situation awareness and workload in a dynamic control task," *Ergonomics*, vol. 42, no. 3, pp. 462–492, 1999.
- [46] T. B. Sheridan and W. L. Verplank, "Human and computer control of undersea teleoperators."
- [47] R. Parasuraman, T. B. Sheridan, and C. D. Wickens, "A model for types and levels of human interaction with automation," *IEEE transactions on systems, man, and cybernetics. Part A, Systems and humans : a publication of the IEEE Systems, Man, and Cybernetics Society*, vol. 30, no. 3, pp. 286–297, 2000.
- [48] S. Bleck, *Entwicklung einer Methodik zur integrierten Planung von Informationstechnologie-Einsatz und intermediären Informationsdienstleistungen im elektronischen Geschäftsverkehr: Zugl.: Aachen, Techn. Hochsch., Diss., 2004*, vol. 72 of *Schriftenreihe Rationalisierung und Humanisierung*. Aachen: Shaker, 2004.
- [49] D. E. O’Leary, "Artificial intelligence and big data," *IEEE INTELLIGENT SYSTEMS*, 2012.
- [50] N. Elgendy and A. Elragal, "Big data analytics: A literature review paper," in *Advances in Data Mining*, vol. 8557, pp. 214–227, 2014.
- [51] P. Russom, "Big data analytics."
- [52] S. Singh and N. Singh, "Big data analytics."
- [53] Y. Lin, Z. Jun, M. Hongyan, Z. Zhongwei, and F. Zhanfang, "A method of extracting the semi-structured data implication rules," *Procedia Computer Science*, vol. 131, pp. 706–716, 2018.
- [54] A. Katal, M. Wazid, and R. H. Goudar, "Big data: Issues, challenges, tools and good practices," in *2013 Sixth International Conference on Contemporary Computing (IC3)*, pp. 404–409, IEEE, 2013.
- [55] S. Praveen and U. Chandra, "Influence of structured, semi- structured, unstructured data on various data models," *International Journal of Scientific and Engineering Research*, vol. 12, no. 8, pp. 67–69, 2020.
- [56] P. Carbone, S. Ewen, S. Haridi, A. Katsifodimos, V. Markl, and K. Tzoumas, "Apache flink: Stream and batch processing in a single engine," *Bulletin of the IEEE Computer Society Technical Committee on Data Engineering*, vol. 36, no. 4, 2015.

- [57] J. A. Stankovic and K. Ramamritham, "What is predictability for real-time systems?," *Real-Time Systems*, vol. 2, no. 4, pp. 247–254, 1990.
- [58] E. Gomes, F. Costa, C. de Rolt, P. Plentz, and M. Dantas, "A survey from real-time to near real-time applications in fog computing environments," *Telecom*, vol. 2, no. 4, pp. 489–517, 2021.
- [59] V. Stich, M.-F. Stroh, M. Abbas, K. Frings, and S. Kremer, "Digitalisierung der wirtschaft in deutschland: Technologie- und trendradar 2022."
- [60] D. Delen and H. Demirkan, "Data, information and analytics as services," *Decision Support Systems*, vol. 55, no. 1, pp. 359–363, 2013.
- [61] "Magic quadrant for bi platforms: Analytics value escalator."
- [62] F. P. Robinson, *Effective study*. New York: Harper & Row, 4th ed. ed., 1970.
- [63] J. Gläser and G. Laudel, *Experteninterviews und qualitative Inhaltsanalyse als Instrumente rekonstruierender Untersuchungen*. Lehrbuch, Wiesbaden: VS Verlag für Sozialwissenschaften, 3., überarb. aufl. ed., 2009.
- [64] M. Meuser and U. Nagel, "Expertinneninterviews - vielfach erprobt, wenig bedacht: ein beitrag zur qualitativen methodendiskussion," pp. 441–471, 1991.
- [65] A. Bogner, B. Littig, and W. Menz, *Das Experteninterview*. Wiesbaden: VS Verlag für Sozialwissenschaften, 2002.
- [66] B. G. Glaser and A. L. Strauss, *The discovery of grounded theory: Strategies for qualitative research*. Observations, New York, NY: Aldine, 1967.
- [67] K. M. Eisenhardt, "Building theories from case study research," *The Academy of Management Review*, vol. 14, no. 4, p. 532, 1989.
- [68] A. Bogner and W. Menz, "Das theoriegenerierende experteninterview," in *Das Experteninterview* (A. Bogner, B. Littig, and W. Menz, eds.), pp. 33–70, Wiesbaden: VS Verlag für Sozialwissenschaften, 2002.
- [69] M. Saunders, P. Lewis, and A. Thornhill, *Research methods for business students*. Always learning, Harlow and Munich: Pearson, 6. ed. ed., 2012.
- [70] "Maxqda - software für qualitative & mixed-methods-forschung," 19.07.2023.
- [71] K. Ahuja, Khushi, Dipali, and N. Sharma, "Cyber security threats and their connection with twitter," in *2022 Second International Conference on Artificial Intelligence and Smart Energy (ICAIS)*, pp. 1458–1463, IEEE, 2022.
- [72] N. A. Al-Dmour, M. Kamrul Hasan, M. Ajmal, M. Ali, I. Naseer, A. Ali, H. A. Hamadi, and N. Ali, "An automated platform for gathering and managing open-source cyber threat intelligence," in *2023 International Conference on Business Analytics for Technology and Security (ICBATS)*, pp. 1–7, IEEE, 2023.
- [73] E. B. Kpozehouen, X. Chen, M. Zhu, and C. R. Macintyre, "Using open-source intelligence to detect early signals of covid-19 in china: Descriptive study," *JMIR public health and surveillance*, vol. 6, no. 3, p. e18939, 2020.
- [74] Y. Thamtono, A. Moa, and C. R. MacIntyre, "Using open-source intelligence to identify early signals of covid-19 in indonesia," *Western Pacific surveillance and response journal : WPSAR*, vol. 12, no. 1, pp. 40–45, 2021.
- [75] M. Nobili, L. Faramondi, R. Setola, M. Ghelli, B. Persechino, and M. Lombardi, "An osint platform to analyse violence against workers in public trasportation," in *2021 International Conference on Cyber-Physical Social Intelligence (ICCSI)*, pp. 1–6, IEEE, 2021.
- [76] D. Bär, F. Calderon, M. Lawlor, S. Lickleder, M. Totzauer, and S. Feuerriegel, "Analyzing social media activities at bellingcat," in *Proceedings of the 15th ACM Web Science Conference 2023*, (New York, NY, USA), pp. 163–173, ACM, 2023.
- [77] Z. Tao, P. Charoenkwan, B. Paphawasit, and N. Rujeerapaiboon, "Machine learning-based classification of competitors performance: evidence from chinese logistics companies," in *2023 Joint International Conference on Digital Arts, Media and Technology with ECTI Northern Section Conference on Electrical, Electronics, Computer and Telecommunications Engineering (ECTI DAMT & NCON)*, pp. 131–137, IEEE, 2023.
- [78] Y. Hu, L. He, X. Tang, G. Luo, S. He, and Q. Fang, "Construction of domain knowledge graph based on open source intelligence," in *2023 IEEE 2nd International Conference on Electrical Engineering, Big Data and Algorithms (EEBDA)*, pp. 1378–1382, IEEE, 2023.
- [79] H. Ma, X. Liu, and W. Zhao, "Research on domain-specific knowledge graph based on the roberta-wwm-ext pretraining model," *Computational intelligence and neuroscience*, vol. 2022, p. 8656013, 2022.
- [80] S. Middleton, A. Lavorgna, G. Neumann, and D. Whitehead, "Information extraction from the long tail," in *12th ACM Conference on Web Science Companion*, (New York, NY, USA), pp. 82–88, ACM, 2020.
- [81] V. Adewopo, B. Gonen, and F. Adewopo, "Exploring open source information for cyber threat intelligence," in *2020 IEEE International Conference on Big Data (Big Data)*, pp. 2232–2241, IEEE, 2020.
- [82] U. Tekin and E. N. Yilmaz, "Obtaining cyber threat intelligence data from twitter with deep learning methods," in *2021 5th International Symposium on Multidisciplinary Studies and Innovative Technologies (ISMSIT)*, pp. 82–86, IEEE, 2021.
- [83] D. Jenkins, L. M. Liebrock, and V. Urias, "Designing a modular and distributed web crawler focused on unstructured cybersecurity intelligence," in *2021 International Carnahan Conference on Security Technology (ICCST)*, pp. 1–6, IEEE, 2021.
- [84] G. Rajendran, V. KS, P. S. AU, and P. Poornachandran, "Covid-19 relief measures assimilating open source intelligence," in *2022 International Conference on Connected Systems & Intelligence (CSI)*, pp. 1–7, IEEE, 2022.
- [85] P. Kuehn, M. Schmidt, M. Bayer, and C. Reuter, "Threatcrawl: A bert-based focused crawler for the cybersecurity domain."

- [86] H. S. Sonawane, S. Deshmukh, V. Joy, and D. Hadsul, "Torsion: Web reconnaissance using open source intelligence," in *2022 2nd International Conference on Intelligent Technologies (CONIT)*, pp. 1–4, IEEE, 2022.
- [87] J. Hubbard, G. Bendiab, and S. Shiaeles, "Ipass: A novel open-source intelligence password scoring system," in *2022 IEEE International Conference on Cyber Security and Resilience (CSR)*, pp. 90–95, IEEE, 2022.
- [88] C. Bai, A. Li, Z. Gao, and X. Cui, "Research on anti-terrorism intelligence mining method based on attention neural networks," in *2020 IEEE 2nd International Conference on Civil Aviation Safety and Information Technology (ICCASIT)*, pp. 458–464, IEEE, 2020.
- [89] A. Pingle, A. Piplai, S. Mittal, A. Joshi, J. Holt, and R. Zak, "Relxst: Relation extraction using deep learning approaches for cybersecurity knowledge graph improvement," *Association for Computing Machinery*, pp. 897–886, 2020.
- [90] A. Shen and K. P. Chow, "Time and location topic model for analyzing lihgk forum data," in *2020 13th International Conference on Systematic Approaches to Digital Forensic Engineering (SADFE)*, pp. 32–37, IEEE, 2020.
- [91] C.-M. Chen, F.-H. Hsu, and J.-N. Hwang, "Useful cyber threat intelligence relation retrieval using transfer learning," in *European Interdisciplinary Cybersecurity Conference* (A. Mileva, S. Wendzel, and V. Franqueira, eds.), (New York, NY, USA), pp. 42–46, ACM, 2023.
- [92] D. Iorga, D. Corlatescu, O. Grigorescu, C. Sandescu, M. Dascalu, and R. Rughinis, "Early detection of vulnerabilities from news websites using machine learning models," in *2020 19th RoEduNet Conference: Networking in Education and Research (RoEduNet)*, pp. 1–6, IEEE, 2020.
- [93] J.-Z. Yang, F. Liu, Y.-J. Zhao, L.-L. Liang, and J.-Y. Qi, "Ninsrapm: An ensemble learning based non-intrusive network security risk assessment prediction model," in *2022 7th IEEE International Conference on Data Science in Cyberspace (DSC)*, pp. 17–23, IEEE, 2022.
- [94] D. Dale, K. McClanahan, and Q. Li, "Ai-based cyber event osint via twitter data," in *2023 International Conference on Computing, Networking and Communications (ICNC)*, pp. 436–442, IEEE, 2023.
- [95] T. Elmas, T. R. Ibanez, A. Hutter, R. Overdorf, and K. Aberer, "Waypop machine: A wayback machine to investigate popularity and root out trolls," in *2022 IEEE/ACM International Conference on Advances in Social Networks Analysis and Mining (ASONAM)*, pp. 391–395, IEEE, 2022.
- [96] A. V. Arjun, A. K. Buvanasi, R. Meenakshi, S. Karthika, and K. M. Ashok, "Peoplexploit: A hybrid tool to collect public data," in *2020 4th International Conference on Computer, Communication and Signal Processing (ICCCSP)*, pp. 1–6, IEEE, 2020.
- [97] T. Day, H. Gibson, and S. Ramwell, "Fusion of osint and non-osint data," in *Open Source Intelligence Investigation* (B. Akhgar, P. S. Bayerl, and F. Sampson, eds.), Advanced Sciences and Technologies for Security Applications, pp. 133–152, Cham: Springer International Publishing, 2016.
- [98] T. Wright, S. Whitfield, S. Cahill, and J. Duffy, "Project umbra," in *2020 IEEE/ACM International Conference on Advances in Social Networks Analysis and Mining (ASONAM)*, pp. 748–751, IEEE, 2020.
- [99] S. Wittmer and F. Platzer, "Zulässigkeit von open source-ermittlungen zur strafverfolgung im darknet."
- [100] "Document 32016r0679: Regulation (eu) 2016/679 of the european parliament and of the council of 27 april 2016 on the protection of natural persons with regard to the processing of personal data and on the free movement of such data, and repealing directive 95/46/ec (general data protection regulation)," 2016.
- [101] "Enforcement and sanctions: What happens if my company processes data in different eu member states?," 18.08.2023.
- [102] C. Eldridge, C. Hobbs, and M. Moran, "Fusing algorithms and analysts: open-source intelligence in the age of 'big data'," *Intelligence and National Security*, vol. 33, no. 3, pp. 391–406, 2018.
- [103] A. Radford, J. Wu, R. Child, D. Luan, D. Amodei, and I. Sutskever, "Language models are unsupervised multitask learners."
- [104] W. X. Zhao, K. Zhou, J. Li, T. Tang, X. Wang, Y. Hou, Y. Min, B. Zhang, J. Zhang, Z. Dong, Du Yifan, C. Yang, Y. Chen, Z. Chen, J. Jiang, R. Ren, Y. Li, X. Tang, Z. Liu, P. Liu, J.-Y. Nie, and J.-R. Wen, "A survey of large language models."
- [105] M. Schilling, H. Ritter, and F. W. Ohl, "From crystallized adaptivity to fluid adaptivity in deep reinforcement learning — insights from biological systems on adaptive flexibility."
- [106] H. A. Ünver, "Digital open source intelligence and international security: A primer."
- [107] "Nato open source intelligence reader."
- [108] C.-Y. Lee and B.-S. Chen, "Mutually-exclusive-and-collectively-exhaustive feature selection scheme," *Applied Soft Computing*, vol. 68, pp. 961–971, 2018.
- [109] E. M. Rasiel, *The McKinsey way: Using the techniques of the world's top strategic consultants to help you and your business*. New York: McGraw-Hill, 1999.
- [110] "Intercoder-übereinstimmung," 16.03.2020.
- [111] M. Häder and S. Häder, eds., *Die Delphi-Technik in den Sozialwissenschaften: Methodische Forschungen und innovative Anwendungen*. ZUMA-Publikationen, Wiesbaden: Westdt. Verl., 2000.

1	Planning and Direction	2.3.3	Web crawler and/or web scraper	3.3.4	Statistical methods (e.g. aggregation via mean value, first-difference estimator)	4.3.4	Machine Learning (esp. Random Forest and Naive Bayes algorithms)
1.1	Cyber Security	2.3.4	Other open source tools (e.g. Impala shell tool)	3.3.5	Deep learning (text vectorization, e.g. using the word2vec algorithm)	4.4	Journalism, competitive analysis, general approach
1.1.1	Manual (e.g. manual definition of objectives and requirements)	2.4	Journalism, competitive analysis, general approach	3.4	Journalism, competitive analysis, general approach	4.4.1	Manual (expert analysis)
1.2	Health	2.4.1	Manually (e.g. via databases)	3.4.1	Manual (manual cleanup, labeling)	4.4.2	Deep learning (especially word embedding, for semantic analysis using different versions of the BERT algorithm)
1.2.1	Manual (e.g. manual requirements definition)	2.4.2	API Interface	3.4.2	Standardized methods/algorithms/tools (e.g. parser and other word segmentation tools, for lemmatization, word/character filtering)	4.4.3	Machine Learning (in particular Support Vector Machines or Random Forest and XGBoost algorithms)
1.3	Security	2.4.3	Web crawler and/or web scraper	3.4.3	Natural language processing (films and labeling methods/tools (e.g. using similarity algorithms and classification algorithms))	4.3.4	Machine Learning (esp. Random Forest and Naive Bayes algorithms)
1.3.1	Manual (e.g. manual hypothesis formulation)	3	Processing and Exploitation	4	Analysis and Production	5	Dissemination and Integration
2	Collection	3.1	Cyber Security	4.1	Cyber Security	5.1	Cyber Security
2.1	Cyber Security	3.1.1	Manual (e.g. labeling/review/verification/grouping via experts, search parameters in databases/search engines, manual cleansing)	4.1.1	Manual (content analysis)	5.1.1	Files/reports (e.g. CSV file, PDF dossier)
2.1.1	Manually (e.g. via databases and search engines)	3.1.2	Keyword/dictionary/hashtag filter (usually in combination with web crawler and web scraper)	4.1.2	Standardized methods/algorithms and tools (image hashing, open source tools, lexical approaches)	5.1.2	Dashboard/visualization map
2.1.2	API interface	3.1.3	Standardized methods/algorithms/tools (e.g. parser and other word segmentation tools, for normalization, lemmatization, word/character filtering, lowercase conversion and duplicate removal)	4.1.3	Tool stack	5.1.3	Web interface/web application/online platform
2.1.3	Web crawler and/or web scraper	3.1.4	Statistical methods (e.g. oversampling methods, N-gram algorithms, pattern matching)	4.1.4	Deep learning (especially word embedding, for semantic analysis using different versions of the BERT algorithm)	5.1.4	Automated alerts
2.1.4	Other open source tools (e.g. Python tools, data pipelines, stream listeners and lookup features)	3.1.5	Natural Language Processing filters and labeling methods/tools (e.g. heuristic methods, topic classification, part-of-speech tagging, entity and relation annotation, named entity recognition, e.g. using the CoreNLP toolkit or Python NLTK toolkit)	4.1.5	Machine learning (in particular Support Vector Machines or Random Forest, XGBoost, lightGBM, Naive Bayes and logistic regression algorithm)	5.1.5	Graph creation (e.g. using Matplotlib, Networkx, Pygraphistry or the Neo4j browser)
2.1.5	Web application (e.g. for the parallelization of searches in IoT search engines)	3.1.6	Deep learning (text vectorization, e.g. using the word2vec algorithm)	4.1.6	Artificial intelligence (e.g. neural network using BIGRU layers)	5.2	Health
2.2	Health	3.2	Health	4.2	Health	5.2.3	Web interface/web application/online platform
2.2.1	Manual (e.g. via databases, search engines and surveys)	3.2.1	Manual (e.g. selection by experts, expert interviews, search parameters in databases/search engines, manual cleansing)	4.2.1	Manual (content analysis)	5.3	Security
2.2.2	API interface	3.2.2	Keyword/dictionary/hashtag filter (usually in combination with web crawler and web scraper)	4.2.2	Statistical methods (meta-analysis)	5.3.1	Dashboard/visualization map
2.2.3	Web crawler and web scraper	3.2.3	Standardized methods/algorithms/tools (e.g. parsers and other word segmentation tools, for word and character filtering and file conversion tools)	4.2.3	Machine learning (in particular Support Vector Machines or XGBoost and Naive Bayes algorithms as well as Open Source tools)	5.4	Competitive analysis, general approach
2.2.4	Other open source tools (e.g. social media analysis tool and command line tool)	3.3	Security	4.3	Security	5.4.1	Dashboard/visualization map (e.g. using Power BI)
2.3	Security	3.3.1	Manual (e.g. verification via experts, search parameters in databases/search engines)	4.3.1	Standardized methods/algorithms and tools (e.g. dictionary comparison)		
2.3.1	Manual (e.g. via databases, search engines and surveys)	3.3.2	Keyword/dictionary/hashtag filter (usually in combination with web crawler and web scraper)	4.3.2	Statistical methods (correlation analysis, time series analysis, panel regression models)		
2.3.2	API interface	3.3.3	Standardized methods/algorithms/tools (e.g. parser)	4.3.3	Deep Learning (in particular vectorization algorithms)		

Figure 5. Trend radar explanation