RISING CIES



SAFE
Pack Level + Cabinet Level Fire Extinguisher

RUGGED
IP54 to Withstand Harsh Conditions

SUPERIOR
Proprietary Active Balance

SCALABLE
Scalable From 140 to 3900 kWh

RELIABLE
Compatible with Major PCS Brand

SMART
Remote Access Via Your Phone

RISING CIES

Model	CIES-140K-392	CIES-160K-392	CIES-180K-392	CIES-200K-392	CIES-220K-392	CIES-240K-392	CIES-260K-392
Performance							
Nominal Voltage (Vdc)	358.4	409.6	460.8	512	563.2	614.4	665.6
Operating Voltage (Vdc)	291.2 ~ 397.6	332.8 ~ 454.4	374.4 ~ 511.2	416 ~ 568	457.6 ~ 624.8	499.2 ~ 681.6	540.8 ~ 738.4
Nominal Capacity (Ah)	392						
Battery Energy (kWh)	140	160	180	200	220	240	260
Charge Current (A)	200						
Charge Power (kW)	71.68	81.92	92.16	102.4	112.64	122.88	133.12
Discharge Current (A)	250						
Discharge Power (kW)	89.6	102.4	115.2	128	140.8	153.6	166.4
Communication							
Display	7 inch(16:9)Touch Screen						
Communication	CAN						
General Specification							
Dimension (W x D x H mm)	1260 x 1160 x 2221						
Weight (kg)	1550	1690	1830	1970	2110	2250	2390
Installation	Floor Stand						
Operating Temperature	Charge: 0 ~ 55°C / Discharge -20°C ~ 55°C						
Operating Humidity	⩽ 95% RH						
Max Operating Altitude	⩽ 2000 m						
IP Rating	IP54						
Safe	Pack Level + Cabinet Level Fire Extinguisher, Smoke Detection, Audible + Visual Alarm						
Cell Technology	LiFePO4, Lithium Iron Phosphate						
Cycle Life	8000 Cycles @ 80% DoD / 25°C / 0.5C, 60% EOL						
Scalability	Max 15 CIES in Parallel						
Standard Compliance (more available upon request)							
Certificates	CE，UN38.3						
Ordering and Deliverable Part							
Product Ordering Part	CIES-140K-392 / CIES-160K-392 / CIES-180K-392 / CIES-200K-392 CIES-220K-392 / CIES-240K-392 / CIES-260K-392						