

glasstech, inc.

Service Bulletin

Customer Service Department

TELEPHONE: 419-661-9000 FAX: 419-661-9639

COLLOIDAL SILICA

Reference 012

Colloidal Alumina, the adhesive used for attaching the paper to the flat ceramic mold, will no longer be available through Glasstech.

Collidal Silica, an adhesive that has produced excellent results, will be the replacement available through the Glasstech Spare Parts Department. Order by part number: **S-CER8CS01G0001** (1 gallon container).

To ensure superior performance of colloidal silica, the recommendation is to transport and store this material within a normal "room temperature" range, typically 20 -25 degrees Celsius (68 - 77 degrees Fahrenheit), which will allow for a useful storage "shelf life" of up to 1 year. This material is sensitive to temperature extremes but does not normally require re-suspension/mixing prior to use. The pails can be re-sealed between use as well, but be aware this will reduce the shelf life.

Colloidal silica is subject to damage if exposed to freezing temperatures. The primary constituent is water (H₂O) with no chemical protection. If the material has been frozen, there will be a sediment of crystalline particles in the bottom of the container and the remaining liquid will not be as sticky to the touch as would normally be observed. In this case the material needs to be replaced.

If stored or subjected to temperatures above room temperature, the material will degrade and bacterial growth can occur. This bacterial pollution can be detected immediately by a strong sulphur odor when the container is opened. Also, as the bacterial growth continues the material will gel and begin to turn black in color. In this condition the colloidal silica is unusable as well.