



Service Bulletin

Customer Service Department

TELEPHONE: 419-661-9000 FAX: 419-661-9639

INTERNET: <http://www.glasstech.com>

Glasstech Flat Ceramic Mold Paper

Reference #048

Glasstech Flat Roll Paper – Part Numbers S-CER4RC031F801 & S-CER4RC1254801

The flat mold paper as supplied by Glasstech and used on the flat ceramic mold/pickup platen on Glasstech's side-exit quick-sag process is designed by the manufacturer for a multitude of high temperature applications. This paper is required to provide a buffer between the hot glass and fused silica pickup platen to prevent marring of the glass, and was originally chosen by Glasstech for use on flat molds for its relative thin material characteristics and high temperature [1260°C (2300°F)] service temperature rating.

This paper (supplied in bulk rolls) is manufactured for insulating applications and not necessarily for specific use in the Glasstech application. The manufacturing process does not allow for completely uniform material/surface consistency and therefore, this product will typically contain a certain number of imperfections that may need to be removed, resulting in a certain amount of scrap paper to be discarded. Although inspections of random samples are conducted prior to shipment, it is not possible for Glasstech to 100% inspect an entire roll of paper. Glasstech recommends that prior to installing the paper on the mold, the paper should be closely inspected for imperfections and defects that may lead to marking of the glass. Imperfections such as glass beads in the paper can be crushed or removed without affecting the overall quality of the paper. Other imperfections may require discarding of portions of the paper. **These imperfections are not considered warranty defects by the paper manufacturer or by Glasstech.**

NOTE: It's also important to follow the recommended procedures for handling, preparing and application of this paper to the mold per the Glasstech Manuals.