

Submittal Review Response

		Project Name:	Hilo WWTP Rehabilitation and Replacement Project Phase 01756-002.0			
		Date:	8/14/2025		_	
Client: C	ounty of	Hawai'i	Carollo Projec	t No.:	203975	
Contractor: N	an, Inc.					
Submittal Name:T	raining C	oordinator				
Reviewed By: G	avin Goo					
SUB	MITTAL	REVIEW				
quantities, dimensions comments. Refer to S	s, and def ection 01	tails. No deviation or variation is	responsibility is assumed by Caro approved unless specifically addr. The Contractor shall assume full requirements.	essed in	these review	
□ No Exceptions		No Exceptions				
Approved		Make Corrections Noted - See	Comments			
		Make Corrections Noted - Cor	firm			
Not Approved		Correct and Resubmit				
Not Approved		Rejected - See Remarks	ed - See Remarks			
Pagaint Aaknawladaa	d 🗵	Filed for Record				
Receipt Acknowledge	u 🗆	With Comments - Resubmit				

Review Comments:

- 1. Not a required submittal for EOR review per Section 1.05. or Section 1.06.D
- 1. Shows no history of similar role in past projects.
- 2. Name and qualification of manufacturer's trainers must be submitted for County approval at least 30 days prior to scheduled training per Section 3.13.D.

CONTRACTOR SUBMITTAL TRANSMITTAL FORM

Owner:	County of Hawaii	Date:	5/28/2025	
Contractor:	Nan, Inc.	Project No.:	WW-4705R	
Project Name:	Hilo WWTP Phase 1	Submittal Number:	01756-002.0	
Submittal Title:	Owner Provided Training Coor	dinator		
To:	Owner			
From:	Nan Inc.			
	Specification No.	. and Subject of Submittal / Equipment Suppl	ier	
Spec ##:	01756 Subject:	Owner Provided Training	ng Coordinator	
Authored By:	Matthew Ch	un Date Submitted:	5/28/2025	
	(P)	Submittal Certification		
Check Either (A) or	(B):			
X (A)		ment or material contained in this submittal meet	s all the requirements specified in the	
	project manual of shown on the	contract drawings with no exceptions.		
(B)	We have verified that the equip	ment or material contained in this submittal meet	s all the requirements specified in the	
		contract drawings except for the deviations lister		
	, , ,	present that I have determined and verified all fiel	f .	
	ngs and all Contract requirements	milar data, and I have checked and coordinated e	ach hem with other applicable	
General Contractor	's Reviewer's Signature:	Maulen Um		
Printed Name and T	Title: M. Ch	nun, QC		
	=	se does or will cause a change to the requirements	s of the Contract, Contractor shall	
immediately give wri	tten notice stating that Contractor	considers the response to be a Change Order.		
F1	G* ·	D (D (
Firm:	Signature:	Date Returned:		
		DM/CM Office Use		
Date Received GC to	DM/CM·	PM/CM Office Use		
Date Received PM/C				
Date Received Review				
Date Sent PM/CM to				
Date Sellt I W/CW to	GC.			
	N	an, Inc		
		VTP REHABILITATION		
		T PROJECT - PHASE 1		
JOB NO. WW-4705R				

THIS SUBMITTAL HAS BEEN CHECKED BY THIS CONTRACTOR. IT IS CERTIFIED CORRECT, COMPLETE, AND IN COMPLIANCE WITH CONTRACT DRAWINGS AND SPECIFICATIONS. ALL AFFECTED CONTRACTORS AND SUPPLIERS ARE AWARE OF, AND WILL INTEGRATE THIS SUBMITTAL (UPON APPROVAL) INTO THEIR OWN WORK.

	E /00 /0E
DATE RECEIVED	5/28/25
SPECIFICATION SEC	CTION #01756
SPECIFICATION	
PARAGRAPH3.	13-B
DRAWINGN/A	
SUBCONTRACTOR_	N/A
SUPPLIER	N/A
MANUFACTURER	N/A
CERTIFIED BY:	M. Chun

SECTION 01756

COMMISSIONING

PART 1 GENERAL

1.01 SUMMARY

- A. Section includes: Requirements for equipment and system testing and facility start-up and commissioning, including the following:
 - 1. Testing and Start-Up Plan.
 - 2. Testing and Start-Up Coordinator (TSC).
 - 3. Performance Testing.
 - 4. General Start-Up and Testing Requirements.
 - 5. Pre-Start-Up Tests and Checks.
 - 6. Operational Readiness Tests (ORTs).
 - 7. Functional Tests (FTs).
 - 8. Reliability Acceptance Tests (RATs).
 - 9. Operation Acceptance Testing.
 - 10. Certificate of Proper Installation.
 - 11. Services of manufacturer's representatives.
 - 12. Training of Owner's personnel.
- B. Apply the requirements of this Section to the various work restrictions and completion milestones defined in Section 01140 Work Restrictions.

1.02 DEFINITIONS

- A. System: A system means the collection of devices, equipment, pipes, tanks, channels, instruments, electrical systems, control systems, and other items that perform a specific function.
- B. Pre-Start-Up Tests: Pre-start-up tests are preliminary checks and tests, prior to starting Operational Readiness Tests (ORTs), as described in Article 3.08.
- C. Start-Up Tests: Start-up tests include all ORTs, Functional Tests (FTs), and Reliability Acceptance Tests (RATs).
- D. Functional Tests: Also referred to as Performance Tests (field).
- E. Factory Acceptance Testing: Also referred to as Factory Testing and Source Testing.

1.03 GENERAL TESTING, TRAINING, AND START-UP REQUIREMENTS

- A. Contract Requirements: Testing, training, and start-up are requisite to the satisfactory completion of the Contract.
- B. Complete testing, training, and start-up within the Contract Times.

- C. Allow realistic durations in the Progress Schedule for testing, training, and start-up activities.
- D. Furnish labor, power, chemicals, tools, equipment, instruments, and services required for and incidental to completing FTs, performance tests, and RATs.
- E. Provide competent, experienced technical representatives of equipment manufacturers for assembly, installation and testing guidance, and operator training.
- F. General Training Requirements:
 - 1. Training is requisite to the satisfactory completion of the Contract.
 - 2. Complete training within the time of completion set forth in the Contract.
 - 3. Allow realistic durations in the project schedule for training activities.
 - 4. Furnish all training materials (books, handouts, visual aids) and services required for and incidental to completing training.
 - 5. Owner will provide location for training at or near project site.

1.04 TESTING AND START-UP COORDINATOR

- A. The Contractor shall designate and provide an Equipment and Systems Testing and Start-up Coordinator (TSC) for this project.
 - 1. The TSC must be regularly engaged and experienced in all aspects of pre-start-up, start-up, and testing of wastewater pumping and treatment facilities, electrical switchgear, and treatment plant controls of similar size, type, and capacity as this project. This must be demonstrated with reference project descriptions and reference contact information.
 - 2. The TSC shall provide technical instruction for the start-up and start-up testing, and shall direct the actual facility operation during pre-start-up testing, start-up, start-up testing, and performance testing.
 - 3. The TSC shall lead all of the Contractor's efforts relating to testing and start-up of project facilities and shall be the primary interface with the Engineer and Owner for these activities.
 - 4. The specified testing and start-up activities will require a variety of expertise and the effort of several individuals working under the TSC. The TSC shall be supplemented by similarly experienced assistants as required.
- B. All facility operation and tests shall be performed in the presence of the Engineer unless such presence is expressly waived in writing.
- C. Submit qualification of the TSC for review and Owner approval.
- D. The TSC shall carefully review the additional testing requirements in other specification sections.

1.05 SUBMITTALS

- A. General:
 - 1. Organization chart for conducting start-up and testing.
 - 2. Description of previous experience on similar projects for the designated TSC. Include list of references complete with phone numbers.

- 3. Detailed start-up and testing plan with schedule signed by the TSC, for each equipment item and system. Submit schedules showing testing work not less than 120 days in advance of first scheduled tests. Schedules shall list each piece of equipment or component to be tested. Schedules shall include sequence and duration for all testing required including pre-start-up testing, ORTs, FTs, 7-day RATs, and Operation Acceptance Testing.
- 4. An overall schedule and subsequent updates, presenting the Contractor's plan for testing the equipment and systems installed under this contract.
- 5. A detailed schedule establishing the expected time period (calendar dates) when the Contractor plans to commence testing of the completed systems, along with a description of the temporary systems and installations planned to allow testing to take place.
- 6. A summary of the Quality Assurance Manager's qualifications.
- 7. The original and 3 copies of all records produced during the testing program.
- 8. Acceptance criteria required to release equipment and systems for start-up.
- 9. Manufacturer's certification of proper installation of equipment before testing begins.
- 10. Operation and maintenance instruction manual for each equipment item and system to be tested as specified in Section 01782 Operation and Maintenance Manuals.
- 11. Refer to Article 1.06, Manufacturer's Field Services, for additional requirements.
- 12. Refer to other specification sections for additional requirements.

B. Test Procedures and Forms:

- 1. The Contractor, through the services of the TSC, shall prepare and submit for review.
 - a. All testing procedures.
 - b. All testing forms.
 - c. Required information on all testing equipment.
- 2. Written testing procedures shall be submitted for initial review at least 90 days prior to the test for which the procedures have been prepared. Failure to submit complete test forms and procedures at least 90 days prior to the subject test shall result in rescheduling of the test, and any resulting delay shall be solely the responsibility of the Contractor.
- Detailed testing procedures setting forth step-by-step descriptions of the procedures proposed by the Contractor for the systematic testing of all equipment and systems installed under this contract.
 - a. Procedures shall include statement indicating test objective, test descriptions, forms, and checklists to be used to control and document the required tests.
 - b. Once the detailed Test Procedures Submittals have been reviewed by the Engineer and returned stamped either "no exceptions noted" or "make corrections noted," the tests may be scheduled.
 - c. Upon completion of each required test, a copy of the signed-off test procedures shall be submitted as test documentation.
- 4. The Contractor shall develop test plans detailing the coordinated, sequential testing of each item of equipment and system installed under this contract. Each test procedure shall be specific to the item of equipment or system to be tested. Generic or general test forms and procedures shall not be acceptable. Test procedures shall identify by specific equipment of tag number each

- device or control station to be manipulated or observed during the test procedures and the specific results to be observed or obtained. Test procedures shall also be specific as to support systems required to complete the test work, temporary systems required during the test work, Subcontractors' and Manufacturers' Representatives to be present, and expected test duration.
- 5. Test forms shall include, among other items, tag and name of equipment or device to be tested, date, names of persons conducting and witnessing (where applicable) the tests, blanks for entry of test data, description of each data item, check offs for each completed test or test step, and place for signature of person conducting tests and for the witnessing person (as applicable).
- 6. Test procedures and forms shall be subject to Engineer's approval.
- 7. Once the Engineer has reviewed and taken no exception to the Contractor's test plans, the Contractor shall reproduce the plans in sufficient number for the Contractor's purposes and an additional 6 copies for delivery to the Engineer. No test work shall begin until the Contractor has delivered the specified number of final test plans to the Engineer.

C. Test Reports:

- 1. Submit preliminary copies of test data in field report form within 2 days after completion of each test.
- 2. Submit 5 bound copies of field test reports of checkout and testing of all equipment within 30 days after completion of testing.
- 3. Test Reports for each phase of testing for each equipment system, shall be submitted and approved prior to start of next test or start-up phase.

D. Operation and Maintenance (O&M) Manuals:

- 1. In accordance with Section 01782 Operation and Maintenance Manuals.
- 2. The O&M manual shall be submitted by the Contractor and reviewed/accepted by the Owner prior to RAT testing and required training. The Owner reserves the right to delay the RAT test for a particular equipment item if the manuals for that equipment submitted by the Contractor are incomplete, inaccurate, or otherwise unsuitable for use by Owner's O&M staff. No contract extensions or extra costs will be allowed for delays due to O&M Manual submittal delays.

1.06 MANUFACTURER'S FIELD SERVICES

A. General:

1. Where manufacturer's services are specified, Contractor shall furnish a qualified Manufacturer's Representative to provide these services.

B. Definitions:

- 1. For purposes of furnishing Manufacturers' Representative services, the following definitions shall apply:
 - Manufacturer's Representative: Authorized employee of manufacturer who is factory trained and knowledgeable in technical aspects of their products and systems.

b. Workday or Instructor-Day: Eight hours straight time on the jobsite between 6:00 a.m. and 6:00 p.m., exclusive of Saturdays, Sundays, or holidays; does not include travel time. Size of manufacturer's field services team shall not be used to reduce the specified number of days on the jobsite.

C. Field Services:

- 1. Contractor shall coordinate all field services with the manufacturer, the Manufacturer's Representative, and Owner. Coordination shall begin during the preparation of equipment bids so that manufacturer can adequately determine the number of trips and Workdays that Contractor will require based on Contractor's sequence for testing, start-up, and training. Contractor's sequence will require staged testing and start-up for some equipment and systems as required in this Section and Section 01140 Work Restrictions.
- 2. Manufacturer's Representative shall perform the following services in separate trips to the project site. Number of trips and level of effort is the minimum requirement and applies to each type of equipment furnished by manufacturer. Also, the Contractor and manufacturer shall provide additional trips and effort as needed to meet required quality of Work:
 - a. Installation Assistance: As required.
 - b. Installation Inspection: One trip after installation for a duration as needed but not less than 1 Workday, unless specified otherwise.
 - c. Start-Up/Testing Assistance: One trip at start-up for a duration as needed but not less than 2 Workdays, unless specified otherwise. The equipment shall be ready for testing prior to manufacturer representative's arrival on the job site for testing.
 - d. Training: As specified in this Section and in the equipment specification sections
 - e. Final Acceptance Checkout: One trip for 1 Workday, unless specified otherwise.

D. Submittals:

- 1. Contractor shall submit the following in accordance with General Requirements, Section 01330 Submittal Procedures:
 - a. Qualifications and experience records of each proposed Manufacturer's Representative who will provide field services.
 - b. After installation inspection, each Manufacturer's Representative shall submit to Engineer a written report (using the form prepared by the TSC) certifying that the equipment is installed properly, in accordance with the manufacturer's installation instructions.
 - c. After start-up/testing, each Manufacturer's Representative shall submit to Engineer a written report (using the form prepared by the TSC) verifying that the equipment has been properly installed and lubricated and that it operated satisfactorily.
 - d. After final checkout, each Manufacturer's Representative shall submit to Engineer a written report (using the form prepared by the TSC) verifying that the equipment is in proper condition for regular continuous operation.
 - e. After post-start-up, each Manufacturer's Representative shall submit to Engineer a written report (using the form prepared by the TSC) verifying that this service has been performed and that the equipment Manufacturer's Representative and the Contractor have inspected all

- equipment under this contract as installed, the appropriate adjustments have been made, and the complete system is operating in conformance with the design, specifications, and manufacturer's requirements. Notation of improper operation shall be detailed, and recommendations made and attached to the report.
- f. In addition to the requirements indicated in the TSC form, each Manufacturer's Representative report shall include purpose of visit, work performed, findings, and corrective actions required. Reports shall be on the manufacturer's letterhead and shall be signed by the representative. Submit each report within 10 days of visit.

E. Scheduling of Manufacturer's Field Services:

- 1. The scheduling of all visits to the site by the Manufacturer's Representative shall be determined by Contractor and approved by Engineer. The Manufacturers' Representatives' visits specified herein are for the purpose of making equipment inspections and normal adjustments.
- 2. After complete installation but prior to operating or testing equipment, Manufacturer's Representative of each item of equipment for which field services are indicated in the individual sections of the Technical Specifications shall visit the site of the Work and inspect, check, adjust if necessary, and approve the equipment installation.
- 3. The Manufacturer's Representative shall be present when the equipment is being tested and placed in operation to verify that the equipment has been properly installed and lubricated, is in accurate alignment, is free from any undue stress imposed by connecting piping or anchor bolts, and has been operated under full load conditions and that it operated satisfactorily. During the testing, the Manufacturer's Representative shall assist the Contractor, as applicable for the type of equipment, with equipment and system adjustments and calibrations.
- 4. The Manufacturer's Representative shall revisit the jobsite as often as necessary until any and all problems are corrected and the equipment installation and operation are satisfactory to Owner.
- 5. Manufacturer's Representatives shall resolve assembly or installation problems attributable to or associated with, their products and equipment.
- 6. After all acceptance tests have been completed, but prior to final acceptance, Contractor shall recheck all equipment for proper alignment and adjustment, check oil levels, re-lubricate all bearing and wearing points, and, in general, assure that all equipment is in proper condition for regular continuous operation. Manufacturer's Representative shall re-inspect the installation and operation to verify this condition.

PART 2 PRODUCTS (NOT USED)

PART 3 EXECUTION

3.01 GENERAL

- A. General testing requirements are specified in this Section. The Contractor shall develop a specific test plan and sequence based on requirements in this Section, requirements in Section 01140 Work Restrictions requirements in the detailed equipment control strategies (Section 17100 Control Strategies and Sections 17101A through 17101W) and requirements in other Contract Documents. This shall be incorporated into the Contractor's construction schedule specified in Section 01321 Schedules and Reports.
- B. In general, testing of electrical equipment and building support systems must be completed prior to start-up and testing of the main process equipment. Refer to Section 01140 Work Restrictions for additional specific requirements. Complete testing as described below is required for all equipment and systems, including electrical equipment, ventilation systems, and building utility systems.
- C. All testing and related activities shall be the sole responsibility of the Contractor, except where explicitly specified otherwise. As specified below, the Owner will assist with some test activities, and shall have the right to direct or perform additional testing where deemed necessary to completely test an item or system of equipment, instrumentation, or other work.
- D. Written notification of scheduled tests must be delivered to the Engineer at least 21 days prior to the start of each test. Witnessed tests and tests requiring Owner assistance shall be scheduled and performed in accordance with applicable Owner staff working days and hours. Testing shall be performed during normal working hours, which shall be from 7:30 a.m. to 3:00 p.m., with a 45-minute lunch break and two 15-minute breaks each day.
- E. Completion of all test activities shall be documented by a certified report, including all test forms with test data entered, delivered to the Engineer with a clear and unequivocal statement that all test requirements have been satisfied.
- F. Contractor shall participate in, and cooperate with, a Start-Up Team consisting of Owner operations staff, Owner Engineering staff, Owner maintenance staff, consulting design engineer, Owner construction management staff, Contractor staff, TSC, and Training Coordinator. This team will meet regularly, generally weekly prior to and whenever testing and start-up activities are being performed. The meetings will be used to coordinate start-up and testing activities; schedule and plan training activities; familiarize and inform Owner staff on construction, start-up and testing activities and to plan and discuss testing activities. Contractor, through the TSC, shall prepare addenda and meeting minutes.
- G. The Owner reserves the right to waive or terminate any test, in whole or in part, for its convenience, at its sole discretion.

3.02 WORKSHOP

The Contractor shall plan and arrange for an 8-hour workshop and a follow-up 4-hour workshop. The purpose of the workshop shall be to work with appropriate Owner staff and to receive their input on a project-specific testing plan and testing schedule. The Owner will provide a meeting room to be coordinated by the Contractor and the Engineer. The workshop will be attended by 8 to 10 Owner staff. The following from the Contractor's team shall attend: Project Manager, On-Site Superintendent, TSC, Project Manager for the Instrumentation Subcontractor, the Contractor's Quality Assurance Manager, and appropriate tradesmen, subcontractors, vendors, and others, as deemed appropriate by the Contractor. The workshop is intended to provide brainstorming and discussion of the development of the test plan and test schedule. However, it is the Contractor's sole responsibility to develop the products defined in the Specifications, and as required by other Contract Documents. The Contractor shall provide all computers, projection, or other equipment that may be required to assist progress in the workshop. The equipment used within Owner meeting rooms should be coordinated with Owner through the Engineer. Hold the workshop within 550 days of Notice to Proceed.

3.03 SEQUENCING OF START-UP AND TESTING

A. The Summary of Field Testing Steps table summarizes the general test sequence and steps to be followed.

3.04 COORDINATION WITH OWNER OPERATIONS

- A. In addition to other notification requirements, Contractor shall notify Owner's operations staff not less than 72 hours in advance of the planned start of each equipment or system testing in order to coordinate project test with plant operations.
- B. Testing and start-up activities shall be designed and conducted to minimize impacts to ongoing treatment plant operations. No Contractor activity shall interfere with the Owner's ability to properly and safely treat wastewater.

3.05 MATERIALS AND EQUIPMENT

- A. Provide all testing and recording devices required for specified tests. The TSC shall determine or approve the type, number, and quality of all such devices. Obtain Engineer's acceptance of such equipment including oscillograph and test equipment calibration certification.
- B. Provide all lubricating oil, hydraulic oil, grease, packing, and insulating and lubricating fluids and filters required to clean, blow out, flush, and initially charge equipment and systems.

			Summary o	f Field Testing S	Steps
Test Step	Lead Responsible Entity	Owner Witnessing Required	Owner Assistance Required	Sewage and/or Sludge Available	Typical Test Summary
Pre-Start-Up Tests and Checks	Contractor	Some Tests	No	No	Mechanical: Leak test, equipment powered, clean and lubricate, ready to start, etc.
					Electrical: Wire tests, circuit tests, termination, power systems ready, etc.
					I&C: Calibration, initial checkout, etc.
Operational	Contractor	No	No	No	Loop checks.
Readiness Tests 1					Test hardwired logic.
					Test equipment in Local Manual mode.
Operational Readiness Tests 2	Contractor	Yes	No	No	Repeat ORT-1, witnessed.
Operational	Contractor	Yes	Yes	No	PLC software loaded and available.
Readiness Tests 3					End-to-end tests of signal from field to PLCs.
					Test equipment in Remote Manual.
					Test simple software logic.
Functional Tests	Contractor	Yes	Yes	Yes	Equipment wet tests, performance tests.
					Operate equipment for continuous periods through full range of operation.
					Test all Automatic logic; tune feedback loops.
					Test functionality of equipment systems.
Reliability Acceptance Tests	Contractor	Yes	No	Yes	Continuous operation of collections of equipment systems for minimum of 7 days.
(7-day)					Test reliability of Contractor-provided work.
Operation Acceptance Test	Owner	n/a	n/a	Yes	Continuous operation of collections of equipment systems by Owner staff for 30 days.
					Test reliability of Contractor-provided work.

3.06 TESTING AND START-UP RESPONSIBILITIES

- A. Owner's Responsibilities:
 - 1. Observe tests for compliance with the contract requirements.
- B. Contractor's Responsibilities:
 - Furnish labor and materials, tools, instruments, process control software, and services for checking, testing, and pre-start-up for each equipment item, except as specified. This includes such services as Manufacturers' Representatives, subcontractors, electricians, instrumentation technicians, and pipe fitters.
 - 2. Be responsible for and prepare testing schedule and incorporate testing and start-up activities in the progress schedule for the work, in accordance with Section 01321 Schedules and Reports.
 - 3. Obtain and furnish qualified Manufacturer's Representative to assist with testing of equipment.
 - 4. No required test shall be performed without prior written notice to the Engineer, which has the right to witness any test. Notify Engineer and all respective equipment manufacturers, in writing, at least 21 days prior to the date when each equipment system is scheduled to be tested or initially started.
 - 5. Submit testing plan, including schedule and quantity and source of utilities and other materials needed.
 - 6. Perform all testing specified herein.
 - 7. Review and become thoroughly familiar with the Process Control Strategies, Sections 17101A through 17101V.
 - 8. Prepare the submittals required for the work of this Section.
 - 9. Develop and implement test procedures.
 - 10. Develop a standard testing log to be used as a record of testing of each equipment item. This log shall:
 - a. Be subject to approval of Owner.
 - b. Include equipment name.
 - Have provisions for recording dates of completion for checking, inspection by manufacturer, verification of instrumentation and controls, and completion of tests.
 - d. Provide space for problems remaining with equipment and for signature of Engineer, TSC, Instrumentation Subcontractor (where applicable), and Manufacturer's Representatives (where applicable) indicating acceptance.
 - 11. Perform the actual pre-start-up tests and/or supervise the performance of pre-start-up tests for various pieces of equipment.
 - 12. Operate equipment during start-up and testing.
 - 13. Perform the ORTs.
 - 14. Perform the FTs.
 - 15. Perform the 7-Day RATs.
 - 16. Assist plant staff with the Operation Acceptance Test.
 - 17. Provide technical instruction during training.
 - 18. Prepare the test reports.

3.07 PERFORMANCE TESTING

- A. Test equipment for proper performance at point of manufacture or assembly when specified.
- B. When source quality control testing is specified:
 - 1. Demonstrate equipment meets specified performance requirements.
 - 2. Provide certified copies of test results.
 - 3. Do not ship equipment until certified copies have received written acceptance from Engineer. Written acceptance does not constitute final acceptance.
 - 4. Perform testing as specified in the equipment specification sections.
- C. Include costs associated with witnessing performance tests as specified in Section 01450 Quality Control.

3.08 FIELD TESTS

- A. Pre-Start-Up Test and Checks.
 - 1. Cleaning and Checking: Prior to testing of all equipment:
 - a. Inspect and clean equipment, devices, and connected piping so they are free of foreign material.
 - b. Lubricate equipment in accordance with manufacturer's instructions.
 - c. Turn rotating equipment by hand and check motor-driven equipment for correct rotation.
 - d. Open and close valves by hand and operate other devices to check for binding, interference, or improper functioning.
 - e. Check power supply to electric-powered equipment for correct voltage.
 - f. Check for proper equipment alignment.
 - g. Obtain manufacturer's certification of proper installation.
 - h. Complete all conductor tests specified in Divisions 16 and 17, including meggar, continuity, and resistance tests.
 - 2. Mechanical Systems: As specified in the individual equipment specification sections and Section 15050 Common Work Results for Mechanical Equipment, Section 15954 Testing, Adjusting, and Balancing for HVAC, and Section 15958 Mechanical Equipment Testing:
 - a. Remove rust preventatives and oils applied to protect equipment during construction.
 - b. Flush lubrication systems and dispose of flushing oils. Recharge lubrication system with lubricant recommended by manufacturer.
 - c. Flush fuel system and provide fuel for testing and start-up.
 - Install and adjust packing, mechanical seals, O-rings, and other seals.
 Replace defective seals.
 - e. Remove temporary supports, bracing, or other foreign objects installed to prevent damage during shipment, storage, and erection.
 - f. Check rotating machinery for correct direction of rotation and for freedom of moving parts before connecting driver.
 - g. Perform cold alignment and hot alignment to manufacturer's tolerances.
 - h. Adjust V-belt tension and variable pitch sheaves.
 - i. Inspect hand and motorized valves for proper adjustment. Tighten packing glands to ensure no leakage, but permit valve stems to rotate without galling. Verify valve seats are positioned for proper flow direction.

- j. Tighten leaking flanges or replace flange gasket. Inspect screwed joints for leakage.
- k. Install gratings, safety chains, handrails, shaft guards, and sidewalks prior to testing.
- 3. Ready-To-Test Determination: All equipment shall be determined by the Engineer ready to test based on the following:
 - a. Notification in writing by the TSC of equipment and system readiness for testing.
 - b. Submittal and approval of detailed start-up and testing plan, including detailed procedures and test forms.
 - c. Receipt of approved O&M manuals as specified in Section 01782 Operation and Maintenance Manuals.
 - d. Cleanliness of equipment, devices, and connected work.
 - e. Adequate completion of work adjacent to, or interfacing with, equipment to be tested.
 - f. Availability and acceptability of Manufacturer's Representative to assist testing of respective equipment and satisfactory fulfillment of other specified manufacturer's responsibilities.
- 4. After Ready-To-Test Determination, perform pre-start-up tests and make adjustments as needed. Pre-start-up tests shall include, but not be limited to, the following:
 - a. Check for correct operation and perform calibration tests of position, pressure, level, flow, speed, temperature, and all other monitoring instruments in accordance with Division 17.
 - b. Perform pre-start-up testing and conduct operating tests for all electrical equipment systems and subsystems as specified in Division 17 and Division 16 technical specification sections.
 - c. Perform pre-start-up testing for all mechanical equipment, systems and accessories specified in Divisions 11, 14, 15, and 17 technical specification sections. Inspect, adjust, and operate the equipment and systems:
 - Test gates and valves under dry conditions using local manual controls. Repeat operation and adjust as necessary until proper operation is obtained. Place gates and valves in their normal position.
 - 2) Operate pump and motor auxiliary systems (e.g., motor cooling, seal water, lubrication, etc.) to verify proper operation.
 - B) Operate all mechanical building systems to verify proper operation:
 - a) Plumbing and drainage systems.
 - b) Ventilation systems.
 - c) W1, W2, W3, potable water, and plant air systems.
 - d. Check and operate pipeline accessories such as air valves and blowoffs.
 - e. Inspect and verify proper anchorage and grounding of equipment.
 - f. Perform leak tests of pipe, fittings, gaskets, and seals.
- 5. Perform all pre-start-up tests specified in other sections of the technical specifications.
- 6. Perform tests recommended by the manufacturer's field service representatives and/or as required by manufacturer's catalogs or specifications.

- 7. A label shall be attached to all devices to indicate that pre-start-up testing has been performed, indicating the date that tests were completed and initialed by the person conducting the tests.
- 8. Obtain approval from Engineer to proceed with ORTs.
- B. Operational Readiness Test 1 (ORT-1):
 - The purpose of each ORT-1 is to verify that the equipment or other item being tested is properly installed and adjusted, has been properly wired, is ready for the next phase of testing, and is ready for operation in the Local mode. The Contractor shall fully document all ORT-1 test results; the test will not be witnessed. The Contractor, without Owner's assistance, shall perform these tests
 - 2. Perform ORTs with power applied to the equipment.
 - 3. Test each and every control circuit and signal circuit. Test each control loop from the primary element in the field, through all cabling and junction boxes, to the PLC registers. Verify each command signal, from PLC output registers to final control elements and equipment.
 - 4. Configure PLC software to support testing.
 - 5. Coordinate with the Owner staff before testing any equipment not supplied by the Contractor.
 - 6. Exercise equipment in Local-Manual mode:
 - a. Stroke all valves between ends of travel limits.
 - b. Bump all pumps and motors.
 - c. Prove all hardwired interlocks with equipment energized.
 - 7. Verify electrical operation of auxiliaries including:
 - a. Solenoids.
 - b. Limit switches.
 - c. Remote indicating devices.
 - d. Position, pressure, and level transmitters.
 - 8. Perform tests of on-off controls, limit switches, and indicating lamps.
 - 9. Perform tests of alarms, signals, and fail-safe or system shutdown controls.
 - 10. The proper operation of all final control element, control panels, and instrumentation furnished under this Contract shall be verified by tests. Final control elements, control panels, and ancillary equipment shall be tested to verify proper operation using motor control center and local field mounted control circuits. All control circuit interlocks and alarms shall be operational. The control of final control elements and ancillary equipment shall be tested using both manual and automatic (where provided external to the PLC) control circuits.
 - 11. Measured final control element variable position/speed setpoint settings shall be compared to measured final control element position/speed values at 0 percent, 25 percent, 50 percent, 75 percent, and 100 percent of span and the results checked against specified accuracy tolerances. Specified accuracy tolerances are defined as the root-men-square-summation of individual component accuracy requirements. Individual component accuracy requirements shall be as specified in the Contract Documents or as specified by published manufacturer accuracy specification whenever Contract Documents accuracy requirements are not specified.

- 12. Demonstrate all Hardwired Control Logic: For each control schematic in the electrical drawings perform a test to verify all logic works are shown. Test, on a line-by-line basis, each logical input and logical state. Verify that when an input signal or switch position changes state, all required outputs (relays, lights, solenoids, PLC inputs, etc.) are properly activated or deactivated. Also perform these tests for vendor package equipment and all other equipment that has logic not detailed in the Contract Documents control schematics.
- C. Operational Readiness Test 2 (ORT-2):
 - 1. Repeat ORT-1, witnessed.
- D. Operational Readiness Test 3 (ORT-3):
 - 1. The purpose of ORT-3 shall be to demonstrate that equipment and other items under test are properly wired and that equipment is ready for operation in the Remote Manual mode.
 - 2. Software will be loaded into PLC, as applicable, and each signal shall be tested end-to-end.
 - 3. The Contractor shall be responsible for all aspects of conducting the test and resolving deficiencies. Contractor shall schedule and direct the tests. Contractor shall enter test data and results on test forms. Contractor shall be responsible for all equipment operation, field support, injection of signals to simulate instrument operation, measurement of PLC output signals at final control elements, test equipment, test fluids, etc.
 - 4. For each PLC input signal, the Contractor shall actuate the signal at the primary field device, either by causing the sensor to output signals throughout its output range, or by injecting signals into the field wires at the primary device. Each analog input shall be field generated at 0, 50, and 100 percent of span. Each discrete signal shall be generated both "off" and "on. "Proper receipt of each signal shall be confirmed at a PLC.
 - 5. The Contractor shall verify proper receipt of each signal in the field by observing final control element (i.e., equipment) operation in the field.
 - 6. Any deficiencies in Contractor work discovered during the ORT shall be resolved and retested prior to completion of the test.
- E. Function Tests (FTs):
 - 1. The Contractor shall not schedule or perform any FT testing until a complete test plan for the entire project has been submitted to Engineer and approved.
 - 2. Contractor shall not begin FT for a complete equipment system until after completion of the ORT Part 3 for the complete equipment system, and acceptance of the test results submittal.
 - 3. A complete equipment system is a collection of related equipment, such as a Raw Sewage Pump and auxiliaries, all equipment and instrument items in a bar screen channel, etc. The Contractor shall identify each equipment system to be FT tested collectively in the Testing Plan submittal, which shall be subject to Owner approval.
 - 4. Regardless of how equipment systems are grouped for testing, all equipment control interactions and dependencies must be completely and thoroughly demonstrated and tested.

- 5. The purpose of FT shall be to thoroughly test each item of equipment, equipment system, or process system under test, and demonstrate its proper operation under actual operating conditions. The purpose of the test is also to ensure that PLC software is working in conjunction with the hardware and plant as specified. Equipment and process systems shall be tested using the actual fluid or medium that it handles during normal operation, such as water, sewerage, and other fluids and solids to demonstrate and test operation under actual operating condition. The Contractor shall perform all tests, using the actual fluid, medium, or solids that the equipment handles during normal operation, including functionality of all aspects of the software.
- 6. Equipment shall be operated by qualified Contractor personnel under the supervision of a Contractor provided Grade 4 licensed wastewater treatment plant operator. At the sole discretion of the Owner, some or all equipment will be operated by, or under the direction of, Owner staff. ADB
- 6.7. Perform a FT on each item of equipment and its related auxiliary systems and controls. Perform a FT on each process system and related controls. Test combined equipment and processes as systems, as required to thoroughly and completely test all Process Control Strategies in Sections 17101A through 17101V.
- 7.8. Each FT test shall include tests to verify equipment operation and performance in the Manual mode (Local and Remote), and shall include tests to verify and demonstrate proper equipment and process system operation (manual and automatic) modes using the software and hardwired controls.
- 8.9. For all equipment, perform equipment tests to verify proper operation under actual operating conditions with the use of the PLC software logic. Refer to Division 17 for additional requirements.
- 9.10. Where specified in the equipment specifications, perform additional tests to demonstrate proper equipment performance, alignment, installation, or other operational characteristic.
- the control of field-mounted automatic analog controllers or software-based controllers shall be assured by adjusting the controllers, as required, to eliminate oscillatory final control element operation. Transient stability shall be verified by applying control signal disturbances, monitoring the amplitude and decay rate of control parameter oscillations (if any), and making necessary controller adjustments, as required, to eliminate excessive oscillatory amplitudes and decay rates. All electronic control stations incorporating proportional, integral, and/or differential control circuits shall be optimally tuned, experimentally, by applying control signal disturbances and adjusting the gain, reset, and/or rate setting as required to achieve a proper response.
- 41.12. Pump and Motor Testing: Start-Up tests of pumps, motors, and VFDs shall be performed to verify pump performance and operation over the full operating range from minimum head/low flow up to maximum head/maximum capacity.
- 12.13. Contractor shall perform complete and comprehensive testing of the PLC software. Contractor shall troubleshoot and confirm software errors and will fix same when practical.
- 43.14. Contractor shall be responsible for all aspects of conducting the FT and resolving deficiencies. Contractor shall schedule and direct the tests. Contractor shall enter test data and results on test forms. Contractor shall be responsible for all equipment operation, test equipment, test fluids, etc.

- 14.15. The Process Control Strategies provided in the Contract Documents in Sections 17101A through 17101V shall be tested during the FT. The test shall demonstrate, on a sentence-by-sentence basis, that each and every function (both hardware and software specified in the Control Strategies operates as described. Each function shall be tested on each and every piece of equipment to which it applies, or a representative subset, at the Owner's sole discretion.
- 45.16. Any deficiencies in the work discovered during the test shall be resolved and retested prior to completion of the FT.
- F. Seven-Day Start-Up Reliability Acceptance Tests (RATs):
 - 1. Seven-Day RATs shall be performed by the Contractor after the FTs for each stage of construction are completed and accepted.
 - 2. Each 7-Day RAT shall be considered complete when, in the opinion of the Owner, the portion of the project under test has operated properly for 7 continuous days without significant interruption.
 - Equipment shall be operated by qualified Contractor personnel. At the sole
 discretion of the Owner, some or all equipment will be operated by, or under
 the direction of, Owner staff. Equipment shall be operated by qualified
 Contractor personnel under the supervision of a Contractor provided Grade 4
 licensed wastewater treatment plant operator. At the sole discretion of the
 Owner, some or all equipment will be operated by, or under the direction of,
 Owner staff. AD8
 - 4. Subject to Owner approval, the 7-Day RAT for each stage of construction shall begin as soon as possible after completion of the FTs.
 - 5. "Significant interruption" during a 7-Day RAT may include any of the following events:
 - a. Failure of a system (process, controls, etc.) that is not permanently corrected within 6 hours after such failure occurs.
 - b. Failure of a process equipment unit (mechanical, electrical, instruments, etc.) that is not permanently corrected within 8 hours after such failure occurs.
 - 6. "Permanently corrected" means without a repeat failure during the remaining duration of start-up and shall consist of all of the following:
 - a. Work repaired and replaced to conform with specified requirements.
 - b. Parts and components replaced as recommended by original manufacturer, without impacting the warranty, and conforming with reviewed submittals.
 - c. Piping and valves properly installed and connected.
 - d. Wiring properly terminated.
 - e. Accessories, including spare parts and lubricants, furnished as specified.
 - f. The facility is back on line and operating within normal operating parameters.
 - 7. Occurrence of a significant interruption shall require testing then in-progress to be stopped and restarted at time equals zero (begin at Day 1 again) after permanent corrections are made.
 - 8. During a 7-Day RAT, any condition which affects the ability of the project equipment to operate as specified, or which would significantly increase operating or maintenance costs shall be considered unsatisfactory. It is the intent to confirm that each part of the project is capable of performing

- satisfactorily. The performance of all other elements of the project necessary for this test shall also be considered.
- 9. Any malfunction of project equipment observed during the test shall be corrected when observed, unless otherwise directed by the Owner.
 - a. Where the malfunction is of a minor nature, as determined by the Owner, and any plant shutdown necessary for the repair can be scheduled and approved by the Owner, the test may be interrupted for a short period to correct the malfunction. The period of the test will then be increased by the duration of the actual period or periods of such shutdowns or for any shutdown requested by the Owner.
 - b. Where the malfunction is of a major nature and results in an unscheduled shutdown (of the process or equipment being tested), or a shutdown for an extended period or is considered unsatisfactory as defined above, all as determined by the Owner, the test will be deemed to have failed. After the malfunction has been corrected, the test shall be restarted and repeated until successfully performed.
- 10. Each RAT shall include a collection of equipment suitable to operate and demonstrate reliability of a related portion of the work.
 - a. Limited sewage flow rate will be available at the time of RAT testing. Therefore, multiple RAT tests will be required in order to test all facilities and equipment over the full range of operation. For process equipment, perform a minimum of two separate 7-day RATs for the Base Bid scope and one 7-day RAT for Additive Alternate No. 1 (if the County elects to include this additive alternate in the Contract). Equipment to be tested in each of these RATs are listed in the table below. Where more than one equipment is associated with a listed item in the table below (e.g. there are 2 return secondary sludge pumps are associated with each secondary clarifier), divide the RAT testing time equally between these equipment.
 - Additional RAT tests (at no additional cost to the Owner) shall be conducted if partial use or occupancy is sought for a portion of the Work. Partial use or occupancy shall comply with the restrictions and requirements specified in Section 01110 Summary of Work and the RAT testing for the associated portion of Work shall be in accordance with the table below. RAT testing shall be conducted for every portion of the Work for which partial use or occupancy is sought.

	RAT Testing	
RAT 1	RAT 2	RAT 3 (Additive Alternate No. 1)
Bar Screen 1	Bar Screen 2	
Screenings Conveyor	Screenings Conveyor	
Screenings Compactor 1	Screenings Compactor 2	
Influent Sampler	Influent Sampler	
Grit Basin 1, Grit Pump 1, Grit Washer 1	Grit Basin 2, Grit Pump 2, Grit Washer 2	
Primary Sedimentation Tanks 1 & 2	Primary Sedimentation Tanks 2 & 3	

	RAT Testing	
RAT 1	RAT 2	RAT 3 (Additive Alternate No. 1)
Primary Scum Pump 1	Primary Scum Pump 2	
Headworks Odor Control Scrubbers	Headworks Odor Control Scrubbers	
Secondary Clarifiers 1 & 2	Secondary Clarifiers 2 & 3	
WSS Pump 1	WSS Pump 2	
Sodium Hypo Metering Pump 1	Sodium Hypo Metering Pump 2	
Blend Tank 1, BS Mixing Pump 1, Thickener Feed Pump 1	Blend Tank 2, BS Mixing Pump 2, Thickener Feed Pump 2	
Blend Tanks Odor Control Scrubber	Blend Tanks Odor Control Scrubber	
Rotary Drum Thickeners 1 & 2	Rotary Drum Thickeners 2 & 3	
Digesters 1 and 2	Digesters 1 and 2	Digester 3
Digester Gas Conditioning System	Digester Gas Conditioning System	Digester Gas Conditioning System
Digester Gas Flare	Digester Gas Flare	Digester Gas Flare
Centrifuge 1	Centrifuge 2	
Cake Conveyor 1	Cake Conveyor 2	
Cake Hopper 1	Cake Hopper 2	
Solids Odor Control System	Solids Odor Control System	
Return Flow Pump 1 (Lead)	Return Flow Pump 2 (Lead)	
2W Booster Pump 1 (Lead)	2W Booster Pump 2 (Lead)	
3W Pump 1 (Lead)	3W Pump 2 (Lead)	
All associated equipment, instrumentation, and accessories	All associated equipment, instrumentation, and accessories	All associated equipment, instrumentation, and accessories

- b. In addition, all facilities, including buildings and support systems shall undergo RAT testing.
- c. TSC shall develop a RAT test plan to incorporate every item of equipment provided under this contract.
- d. If any item of equipment fails during a RAT, the test shall be stopped, the equipment repaired, and the test restarted.
- 11. The Owner, at its sole discretion, may alter, suspend, or terminate all, or part of, a 7-day RAT test if needed to maintain continuous, safe, and proper

- treatment and disposal of wastewater and byproducts. A suspended test shall be continued at Owner direction. If a portion of a test is terminated, in writing, the portion of equipment under test shall be considered to have completed its 7-day RAT, or at the Owner's discretion, shall be retested.
- 12. At its sole discretion, the Owner reserves the right to terminate any 7-day test and take beneficial occupancy of equipment, for its convenience.
- G. Operation Acceptance Testing: After satisfactory completion of all Reliability Acceptance Tests (RATs), the treatment plant (or portion thereof for which partial use or occupancy is sought) shall be placed into normal operation with wastewater for 30 calendar days to demonstrate fault-free operation while being operated by Owner staff, except that the sludge blending, digestion, and all solids handling facilities shall be placed into normal operation with sludge for 60 calendar days to demonstrate fault-free operation while being operated by Owner staff. Contractor staff shall be available to assist plant staff and to immediately address any failures and make corrections.
 - Occurrence of a significant interruption shall require testing then in progress to be stopped and restarted at time equals zero (begin at Day 1 again) after permanent corrections are made.

3.09 RETESTING OF EQUIPMENT

- A. When testing or operation of the equipment demonstrates that the equipment does not meet the specified requirements, Contractor shall repeat or perform all additional tests as necessary and required by Owner.
- B. When the re-testing is caused by failure of Contractor to perform the Work satisfactorily, as a required procedure, or for minor changes to the equipment,
- C. Contractor will not be granted an increase in the Contract Price, nor an extension of Contract Time.

3.10 OWNER OPERATION

A. After successful testing of a particular equipment type or system, Owner may elect to operate a portion of the equipment or system for continuous operation. Such operation will not interfere with testing of other equipment and systems that may still be underway, and shall not preclude the need to start up the portion operated in combination with the rest of the facility when all testing is completed.

3.11 TEST REPORTS

- A. TSC shall prepare the test reports.
- B. The report shall be comprehensive and contain all test data obtained during testing and shall include any data previously submitted in preliminary form, including but not limited to, the following:
 - 1. Manufacturer's Equipment Data:
 - a. Field-recorded dimensional measurements and clearances.
 - b. Pressure, pressure differential, level, flow, and other field settings.
 - c. All electrical devices field settings.

- d. Operational pressure tests, control system timing tests, settings, and other test data specified.
- e. Field wiring changes made, including marked-up drawings.
- 2. Test results, including completed test forms, test logs, test equipment printouts, and other documentation of test results.
- 3. Test equipment calibration certifications and calibration reports.

3.12 SCHEDULING OF TESTS AND TIME ALLOWANCES

A. All testing activities shall be clearly shown on the Contractor's CPM Schedule specified in Section 01321 - Schedules and Reports. Allow sufficient time periods for testing.

3.13 TRAINING OF OWNER'S PERSONNEL

- A. Provide site-specific operations and maintenance training for items of mechanical, electrical, and instrumentation equipment when specified in specifications for the equipment. Generally, all training will include a process overview component, operational process, maintenance, troubleshooting, and rebuilding. The Owner may provide a summary of training requirements.
- B. Contractor shall designate and provide a training coordinator responsible for coordinating, scheduling, and expediting training. The coordinator shall be present at all training coordination meetings with the Owner's staff, including representatives from the Owner's Operation and Maintenance Division.
 - C. The Contractor and coordinator shall organize and coordinate the training periods with Owner's personnel and manufacturer's representatives and shall submit a training schedule for each piece of equipment or system for which training is to be provided. Training schedules shall be submitted not less than 60 calendar days prior to the time that the associated training is to be provided.
 - D. The Contractor shall use only qualified manufacturer's representatives to conduct training sessions. Submit name and qualifications of trainer not less than 30 days before scheduled training. Approval of manufacturer's trainer by Owner is required.
 - E. Training sessions shall not overlap. The Contractor shall schedule classes so that each individual operator and maintenance technician does not attend more than 16 hours of training per week and that the total amount of training in any 2-week period does not exceed 32 hours. Training hours in excess of these amounts are at the discretion of the Owner.
 - F. Submit Operation and Maintenance Manual (in accordance with Section 01782 Operation and Maintenance Manuals) for specific equipment or systems not less than 30 days prior to training session for that equipment or system.
 - G. Training shall be satisfactorily completed after successful completion of FTs and before beginning the RAT for associated equipment.
 - 1. Training on some minor and incidental equipment and instruments may be allowed before FT or after RAT, but only if specifically accepted in writing by the Owner.

- H. Provide separate training sessions for plant operators, mechanical maintenance technicians, and electrical/instrumentation/controls maintenance technicians.
- I. Each training session for plant operators shall be repeated on 2 separate days to allow half the operators to attend the first session and the other half the second (repeat) session.
 - 1. Allowable training times for operations personnel: 7:30 a.m. - 2:30 p.m.
 - Maximum number of training sessions (separate equipment) per day: 2.
- J. Each maintenance training topic will be no more than 3 hours in duration per training day.
 - Allowable training times for maintenance personnel: 7:30 a.m. 2:30 p.m. 1.
 - 2. Maximum number of training sessions per week: 2 mechanical and 2 electrical/instrumentation.
- Training Sessions: Provide training sessions for equipment as specified in the individual equipment specification sections under Manufacturer's Field Services and in this Section.
- For systems with multiple components, the manufacturer that has primary responsibility for the overall system shall coordinate and schedule the training for the various components. The manufacturer that has primary responsibility for the system shall provide training on the overall system, as well as the component(s) manufactured by him. In addition, training shall be furnished for each component by the component's manufacturer.
- Training sessions shall be conducted according to the lesson plan approved by the Owner, and shall include hands-on activities, demonstration, and discussion. Simply reviewing the equipment manual does not fulfill the training requirements.
- N. Training Materials:
 - All training requires specific, customized and itemized class plans. A draft of the training lesson plan and any books, handouts, etc. to be used for the training shall be submitted not less than 30 days before the training.
 - 2. A complete set of any books, handouts, etc. shall be provided for each person to be trained. Each training session may have up to 10 Owner personnel.
 - 3. Two additional copies of any books, handouts, etc. shall be provided.
- O. Record Keeping:
 - Contractor shall videotape and transfer onto DVD-R, all training sessions and provide three copies to the Owner.
 - 2. Three electronic copies of any handouts, slides, pictures, or other visual aids (i.e., Microsoft PowerPoint®, etc.), shall be provided to the Owner.
 - Electronic training data shall comply with the labeling, formats, file saving, and 3. file naming conventions and requirements for electronic Operation and Maintenance data as specified in Section 01782 - Operation and Maintenance Manuals.

END OF SECTION

AD8 Addendum No. 8 - August 2024

Training Coordinator Qualifications

Training Coordinator

Per Specification Section 01756 - Commissioning

Project Name: 24-077 WWTP Rehabilitation and Replacement PH1

Contractor: Nan, Inc.

Date: 05/27/2025

Spec Section: 01756 - Commissioning

1. Designation of Training Coordinator

This letter serves as formal notification that the following individual is designated as the Training Coordinator for this project:

Name: Makoa Ng

Title: Project Engineer / Quality Control Representative

Phone: (808)640-7308

Email: Mng@nanhawaii.com

2. Responsibilities

- Coordinate, schedule, and expedite all training efforts for Owner's staff
- Ensure training content aligns with specifications and vendor documentation
- Maintain communication with the Engineer and Owner regarding training logistics
- Ensure lesson plans and training materials are submitted on schedule
- Collect training attendance and submit required documentation

3. Qualifications Resume

Project Engineer/Quality Control Representative - Hilo Wastewater Treatment Plant

Nan Inc. - Hilo, Hawaii

2025 - Present

- Assist and report to the QC manager and may perform production related duties
- Attend the Coordination Meeting and QC meetings and be physically present at the construction site to perform inspections or testing and prepare documentation for each definable feature of work in their area of responsibility.

Engineering & Technical Operations

Malama One - Hilo, Hawaii

2023 - 2025

- Developing 3D models to serve as investors' first sight and a mechanical maintenance guide for future operations.
- Developing relationships with partners and investors such as Hawaii Pacific University and Hawaii Army National Guard; improving the conceptual image of our company, facility, and goals.
- Managed the handling and storage of equipment by working with engineers, VPs, and cofounders to efficiently prioritize future installation maneuvers.

Pallet Production & Refabrication Manager

Waiakea Hawaiian Volcanic - Hilo, Hawaii

2023 - 2025

- Created a cost-effective pallet Production & Refabrication facility which included; ROIs, Safety Training, R&D, Budget Planning, and SOP development.
- Managed day-to-day operations which includes; Inventory management, Property Management, Production Scheduling, Maintenance Scheduling, Quality Control, Safety Compliance, and Vendor/Partner relations.
- Process improvement; Increased our production rate for finished products by up to 250% while only increasing our overall cost by 75%.

Service Ng LLC.

3D Model Design - Hilo, Hawaii

2021 - Present

- Develop models for such as Buildings, Rooms, Furniture, and Accessories.
- Develop models that can be Rigged, Rendered, Automated, Colored, and Textured to photo-realistic standards.
- Optimize models and files for the best user experience across multiple devices and platforms.
- Continuous software research to shorten lead times while maintaining high-quality projects.

UH-60 Blackhawk Repairman (15T)

Army National Guard - State of Hawaii

2021 - Present

- Experience in Maui Fire and other Emergency Relief Orders for maintenance support.
- High level of experience with technical manuals (IETMS) and Log Books (ULLS_A) of MIL aircrafts.
- Technical experience with Hydraulic, Pneumatic, Fuel, Drive, Engines, Rotor, and Flight Control Systems.
- Training Technicians on Outer Island Travel, Annual Certifications, and Advanced Troubleshooting Techniques.

Prepared by: Matt Chun
Title: Project Engineer / Quality Control Representative
Signature:
Date: